

HOMEWORK 4

Read the data

We will read dataset that is about the stores. The data contains following information.

- 1.UserID: Id of a user.
- 2.Gender: Gender of the customer.
- 3.Age: Age of customer is years
- 4.EstimatedSalary: Yearly estimated salary of the customer.
- 5.Purchased: Binary value with value 1 if the customer purchased the item, 0 otherwise.

```
In [103]... options(warn=-1)
library(ggplot2)
storeData <- read.csv('social.csv')
```

Inspect the data read

```
In [104]... head(storeData)
```

| User.ID | Gender | Age | EstimatedSalary | Purchased |
|----------|--------|-----|-----------------|-----------|
| 15624510 | Male | 19 | 19000 | 0 |
| 15810944 | Male | 35 | 20000 | 0 |
| 15668575 | Female | 26 | 43000 | 0 |
| 15603246 | Female | 27 | 57000 | 0 |
| 15804002 | Male | 19 | 76000 | 0 |
| 15728773 | Male | 27 | 58000 | 0 |

Spends are already reduced in given data.

```
In [105]... cat("Size of Store data",dim.data.frame(storeData))
Size of Store data 400 5
```

Aim is to train a support vector machine(SVM) that will predict whether a customer will purchase or not.

Splitting the data as training and testing data

```
In [106]... # sampling data to generate 75% training data and 25% test data
sdata <- sample(nrow(storeData), nrow(storeData)*0.75)
sampledata <- sort(sample(nrow(storeData), nrow(storeData)*0.75))
trainingData<-storeData[sampledata,]
testingData<-storeData[-sampledata,]
```

```
In [107]... cat("Training Data :: ", "Size :: ", dim.data.frame(trainingData))
head(trainingData)
cat("Testing Data :: ", "Size :: ", dim.data.frame(testingData))
head(testingData)
```

Trainig Data :: Size :: 300 5

```
# converting dataframe into matrix with required columns
ytrain <- as.matrix(trainingData$Purchased)
# creating y for computation assigning +1 for purchased and 0 for not purchased
ytrain <- matrix(apply(ytrain, 1, function(x){
  colnames(ytrain) <- c("Purchased")
  ones <- matrix(rep(1,nrow(ytrain)), nrow = 1,
  # Adding ones in first column of data for b
  xtrain <- cbind(ones,trainingData$Age,trainingData$EstimatedSalary)
  colnames(xtrain) <- c("ones","Age","EstimatedSalary")
  head("Training Data: Input and Output" )
  head(ytrain)
  head(ytrain)
  ytest <- as.matrix(testingData$Purchased)
  # creating y for computation assigning +1 for purchased and 0 for not purchased
  ytest <- matrix(apply(ytest, 1, function(x){
    colnames(ytest) <- c("Purchased")
    ones <- matrix(rep(1,nrow(ytest)), nrow = 1,
    # Adding ones in first column of data for b
    xtest <- cbind(ones,testingData$Age,testingData$EstimatedSalary)
    colnames(xtest) <- c("ones","Age","EstimatedSalary")
    head("Testing Data: Input and Output" )
    head(ytest)
    head(ytest)
    ytrain <- as.matrix(trainingData$Purchased)
    # creating y for computation assigning +1 for purchased and 0 for not purchased
    ytrain <- matrix(apply(ytrain, 1, function(x){
      colnames(ytrain) <- c("Purchased")
      ones <- matrix(rep(1,nrow(ytrain)), nrow = 1,
      # Adding ones in first column of data for b
      xtrain <- cbind(ones,trainingData$Age,trainingData$EstimatedSalary)
      colnames(xtrain) <- c("ones","Age","EstimatedSalary")
      head("Training Data: Input and Output" )
      head(ytrain)
      head(ytrain)
      ytest <- as.matrix(testingData$Purchased)
      # creating y for computation assigning +1 for purchased and 0 for not purchased
      ytest <- matrix(apply(ytest, 1, function(x){
        colnames(ytest) <- c("Purchased")
        ones <- matrix(rep(1,nrow(ytest)), nrow = 1,
        # Adding ones in first column of data for b
        xtest <- cbind(ones,testingData$Age,testingData$EstimatedSalary)
        colnames(xtest) <- c("ones","Age","EstimatedSalary")
        head("Testing Data: Input and Output" )
        head(ytest)
        head(ytest)
        ytrain <- as.matrix(trainingData$Purchased)
        # creating y for computation assigning +1 for purchased and 0 for not purchased
        ytrain <- matrix(apply(ytrain, 1, function(x){
          colnames(ytrain) <- c("Purchased")
          ones <- matrix(rep(1,nrow(ytrain)), nrow = 1,
          # Adding ones in first column of data for b
          xtrain <- cbind(ones,trainingData$Age,trainingData$EstimatedSalary)
          colnames(xtrain) <- c("ones","Age","EstimatedSalary")
          head("Training Data: Input and Output" )
          head(ytrain)
          head(ytrain)
          ytest <- as.matrix(testingData$Purchased)
          # creating y for computation assigning +1 for purchased and 0 for not purchased
          ytest <- matrix(apply(ytest, 1, function(x){
            colnames(ytest) <- c("Purchased")
            ones <- matrix(rep(1,nrow(ytest)), nrow = 1,
            # Adding ones in first column of data for b
            xtest <- cbind(ones,testingData$Age,testingData$EstimatedSalary)
            colnames(xtest) <- c("ones","Age","EstimatedSalary")
            head("Testing Data: Input and Output" )
            head(ytest)
            head(ytest)
            ytrain <- as.matrix(trainingData$Purchased)
            # creating y for computation assigning +1 for purchased and 0 for not purchased
            ytrain <- matrix(apply(ytrain, 1, function(x){
              colnames(ytrain) <- c("Purchased")
              ones <- matrix(rep(1,nrow(ytrain)), nrow = 1,
              # Adding ones in first column of data for b
              xtrain <- cbind(ones,trainingData$Age,trainingData$EstimatedSalary)
              colnames(xtrain) <- c("ones","Age","EstimatedSalary")
              head("Training Data: Input and Output" )
              head(ytrain)
              head(ytrain)
              ytest <- as.matrix(testingData$Purchased)
              # creating y for computation assigning +1 for purchased and 0 for not purchased
              ytest <- matrix(apply(ytest, 1, function(x){
                colnames(ytest) <- c("Purchased")
                ones <- matrix(rep(1,nrow(ytest)), nrow = 1,
                # Adding ones in first column of data for b
                xtest <- cbind(ones,testingData$Age,testingData$EstimatedSalary)
                colnames(xtest) <- c("ones","Age","EstimatedSalary")
                head("Testing Data: Input and Output" )
                head(ytest)
                head(ytest)
                ytrain <- as.matrix(trainingData$Purchased)
                # creating y for computation assigning +1 for purchased and 0 for not purchased
                ytrain <- matrix(apply(ytrain, 1, function(x){
                  colnames(ytrain) <- c("Purchased")
                  ones <- matrix(rep(1,nrow(ytrain)), nrow = 1,
                  # Adding ones in first column of data for b
                  xtrain <- cbind(ones,trainingData$Age,trainingData$EstimatedSalary)
                  colnames(xtrain) <- c("ones","Age","EstimatedSalary")
                  head("Training Data: Input and Output" )
                  head(ytrain)
                  head(ytrain)
                  ytest <- as.matrix(testingData$Purchased)
                  # creating y for computation assigning +1 for purchased and 0 for not purchased
                  ytest <- matrix(apply(ytest, 1, function(x){
                    colnames(ytest) <- c("Purchased")
                    ones <- matrix(rep(1,nrow(ytest)), nrow = 1,
                    # Adding ones in first column of data for b
                    xtest <- cbind(ones,testingData$Age,testingData$EstimatedSalary)
                    colnames(xtest) <- c("ones","Age","EstimatedSalary")
                    head("Testing Data: Input and Output" )
                    head(ytest)
                    head(ytest)
                    ytrain <- as.matrix(trainingData$Purchased)
                    # creating y for computation assigning +1 for purchased and 0 for not purchased
                    ytrain <- matrix(apply(ytrain, 1, function(x){
                      colnames(ytrain) <- c("Purchased")
                      ones <- matrix(rep(1,nrow(ytrain)), nrow = 1,
                      # Adding ones in first column of data for b
                      xtrain <- cbind(ones,trainingData$Age,trainingData$EstimatedSalary)
                      colnames(xtrain) <- c("ones","Age","EstimatedSalary")
                      head("Training Data: Input and Output" )
                      head(ytrain)
                      head(ytrain)
                      ytest <- as.matrix(testingData$Purchased)
                      # creating y for computation assigning +1 for purchased and 0 for not purchased
                      ytest <- matrix(apply(ytest, 1, function(x){
                        colnames(ytest) <- c("Purchased")
                        ones <- matrix(rep(1,nrow(ytest)), nrow = 1,
                        # Adding ones in first column of data for b
                        xtest <- cbind(ones,testingData$Age,testingData$EstimatedSalary)
                        colnames(xtest) <- c("ones","Age","EstimatedSalary")
                        head("Testing Data: Input and Output" )
                        head(ytest)
                        head(ytest)
                        ytrain <- as.matrix(trainingData$Purchased)
                        # creating y for computation assigning +1 for purchased and 0 for not purchased
                        ytrain <- matrix(apply(ytrain, 1, function(x){
                          colnames(ytrain) <- c("Purchased")
                          ones <- matrix(rep(1,nrow(ytrain)), nrow = 1,
                          # Adding ones in first column of data for b
                          xtrain <- cbind(ones,trainingData$Age,trainingData$EstimatedSalary)
                          colnames(xtrain) <- c("ones","Age","EstimatedSalary")
                          head("Training Data: Input and Output" )
                          head(ytrain)
                          head(ytrain)
                          ytest <- as.matrix(testingData$Purchased)
                          # creating y for computation assigning +1 for purchased and 0 for not purchased
                          ytest <- matrix(apply(ytest, 1, function(x){
                            colnames(ytest) <- c("Purchased")
                            ones <- matrix(rep(1,nrow(ytest)), nrow = 1,
                            # Adding ones in first column of data for b
                            xtest <- cbind(ones,testingData$Age,testingData$EstimatedSalary)
                            colnames(xtest) <- c("ones","Age","EstimatedSalary")
                            head("Testing Data: Input and Output" )
                            head(ytest)
                            head(ytest)
                            ytrain <- as.matrix(trainingData$Purchased)
                            # creating y for computation assigning +1 for purchased and 0 for not purchased
                            ytrain <- matrix(apply(ytrain, 1, function(x){
                              colnames(ytrain) <- c("Purchased")
                              ones <- matrix(rep(1,nrow(ytrain)), nrow = 1,
                              # Adding ones in first column of data for b
                              xtrain <- cbind(ones,trainingData$Age,trainingData$EstimatedSalary)
                              colnames(xtrain) <- c("ones","Age","EstimatedSalary")
                              head("Training Data: Input and Output" )
                              head(ytrain)
                              head(ytrain)
                              ytest <- as.matrix(testingData$Purchased)
                              # creating y for computation assigning +1 for purchased and 0 for not purchased
                              ytest <- matrix(apply(ytest, 1, function(x){
                                colnames(ytest) <- c("Purchased")
                                ones <- matrix(rep(1,nrow(ytest)), nrow = 1,
                                # Adding ones in first column of data for b
                                xtest <- cbind(ones,testingData$Age,testingData$EstimatedSalary)
                                colnames(xtest) <- c("ones","Age","EstimatedSalary")
                                head("Testing Data: Input and Output" )
                                head(ytest)
                                head(ytest)
                                ytrain <- as.matrix(trainingData$Purchased)
                                # creating y for computation assigning +1 for purchased and 0 for not purchased
                                ytrain <- matrix(apply(ytrain, 1, function(x){
                                  colnames(ytrain) <- c("Purchased")
                                  ones <- matrix(rep(1,nrow(ytrain)), nrow = 1,
                                  # Adding ones in first column of data for b
                                  xtrain <- cbind(ones,trainingData$Age,trainingData$EstimatedSalary)
                                  colnames(xtrain) <- c("ones","Age","EstimatedSalary")
                                  head("Training Data: Input and Output" )
                                  head(ytrain)
                                  head(ytrain)
                                  ytest <- as.matrix(testingData$Purchased)
                                  # creating y for computation assigning +1 for purchased and 0 for not purchased
                                  ytest <- matrix(apply(ytest, 1, function(x){
                                    colnames(ytest) <- c("Purchased")
                                    ones <- matrix(rep(1,nrow(ytest)), nrow = 1,
                                    # Adding ones in first column of data for b
                                    xtest <- cbind(ones,testingData$Age,testingData$EstimatedSalary)
                                    colnames(xtest) <- c("ones","Age","EstimatedSalary")
                                    head("Testing Data: Input and Output" )
                                    head(ytest)
                                    head(ytest)
                                    ytrain <- as.matrix(trainingData$Purchased)
                                    # creating y for computation assigning +1 for purchased and 0 for not purchased
                                    ytrain <- matrix(apply(ytrain, 1, function(x){
                                      colnames(ytrain) <- c("Purchased")
                                      ones <- matrix(rep(1,nrow(ytrain)), nrow = 1,
                                      # Adding ones in first column of data for b
                                      xtrain <- cbind(ones,trainingData$Age,trainingData$EstimatedSalary)
                                      colnames(xtrain) <- c("ones","Age","EstimatedSalary")
                                      head("Training Data: Input and Output" )
                                      head(ytrain)
                                      head(ytrain)
                                      ytest <- as.matrix(testingData$Purchased)
                                      # creating y for computation assigning +1 for purchased and 0 for not purchased
                                      ytest <- matrix(apply(ytest, 1, function(x){
                                        colnames(ytest) <- c("Purchased")
                                        ones <- matrix(rep(1,nrow(ytest)), nrow = 1,
                                        # Adding ones in first column of data for b
                                        xtest <- cbind(ones,testingData$Age,testingData$EstimatedSalary)
                                        colnames(xtest) <- c("ones","Age","EstimatedSalary")
                                        head("Testing Data: Input and Output" )
                                        head(ytest)
                                        head(ytest)
                                        ytrain <- as.matrix(trainingData$Purchased)
                                        # creating y for computation assigning +1 for purchased and 0 for not purchased
                                        ytrain <- matrix(apply(ytrain, 1, function(x){
                                          colnames(ytrain) <- c("Purchased")
                                          ones <- matrix(rep(1,nrow(ytrain)), nrow = 1,
                                          # Adding ones in first column of data for b
                                          xtrain <- cbind(ones,trainingData$Age,trainingData$EstimatedSalary)
                                          colnames(xtrain) <- c("ones","Age","EstimatedSalary")
                                          head("Training Data: Input and Output" )
                                          head(ytrain)
                                          head(ytrain)
                                          ytest <- as.matrix(testingData$Purchased)
                                          # creating y for computation assigning +1 for purchased and 0 for not purchased
                                          ytest <- matrix(apply(ytest, 1, function(x){
                                            colnames(ytest) <- c("Purchased")
                                            ones <- matrix(rep(1,nrow(ytest)), nrow = 1,
                                            # Adding ones in first column of data for b
                                            xtest <- cbind(ones,testingData$Age,testingData$EstimatedSalary)
                                            colnames(xtest) <- c("ones","Age","EstimatedSalary")
                                            head("Testing Data: Input and Output" )
                                            head(ytest)
                                            head(ytest)
                                            ytrain <- as.matrix(trainingData$Purchased)
                                            # creating y for computation assigning +1 for purchased and 0 for not purchased
                                            ytrain <- matrix(apply(ytrain, 1, function(x){
                                              colnames(ytrain) <- c("Purchased")
                                              ones <- matrix(rep(1,nrow(ytrain)), nrow = 1,
                                              # Adding ones in first column of data for b
                                              xtrain <- cbind(ones,trainingData$Age,trainingData$EstimatedSalary)
                                              colnames(xtrain) <- c("ones","Age","EstimatedSalary")
                                              head("Training Data: Input and Output" )
                                              head(ytrain)
                                              head(ytrain)
                                              ytest <- as.matrix(testingData$Purchased)
                                              # creating y for computation assigning +1 for purchased and 0 for not purchased
                                              ytest <- matrix(apply(ytest, 1, function(x){
                                                colnames(ytest) <- c("Purchased")
                                                ones <- matrix(rep(1,nrow(ytest)), nrow = 1,
                                                # Adding ones in first column of data for b
                                                xtest <- cbind(ones,testingData$Age,testingData$EstimatedSalary)
                                                colnames(xtest) <- c("ones","Age","EstimatedSalary")
                                                head("Testing Data: Input and Output" )
                                                head(ytest)
                                                head(ytest)
                                                ytrain <- as.matrix(trainingData$Purchased)
                                                # creating y for computation assigning +1 for purchased and 0 for not purchased
                                                ytrain <- matrix(apply(ytrain, 1, function(x){
                                                  colnames(ytrain) <- c("Purchased")
                                                  ones <- matrix(rep(1,nrow(ytrain)), nrow = 1,
                                                  # Adding ones in first column of data for b
                                                  xtrain <- cbind(ones,trainingData$Age,trainingData$EstimatedSalary)
                                                  colnames(xtrain) <- c("ones","Age","EstimatedSalary")
                                                  head("Training Data: Input and Output" )
                                                  head(ytrain)
                                                  head(ytrain)
                                                  ytest <- as.matrix(testingData$Purchased)
                                                  # creating y for computation assigning +1 for purchased and 0 for not purchased
                                                  ytest <- matrix(apply(ytest, 1, function(x){
                                                    colnames(ytest) <- c("Purchased")
                                                    ones <- matrix(rep(1,nrow(ytest)), nrow = 1,
                                                    # Adding ones in first column of data for b
                                                    xtest <- cbind(ones,testingData$Age,testingData$EstimatedSalary)
                                                    colnames(xtest) <- c("ones","Age","EstimatedSalary")
                                                    head("Testing Data: Input and Output" )
                                                    head(ytest)
                                                    head(ytest)
                                                    ytrain <- as.matrix(trainingData$Purchased)
                                                    # creating y for computation assigning +1 for purchased and 0 for not purchased
                                                    ytrain <- matrix(apply(ytrain, 1, function(x){
                                                      colnames(ytrain) <- c("Purchased")
                                                      ones <- matrix(rep(1,nrow(ytrain)), nrow = 1,
                                                      # Adding ones in first column of data for b
                                                      xtrain <- cbind(ones,trainingData$Age,trainingData$EstimatedSalary)
                                                      colnames(xtrain) <- c("ones","Age","EstimatedSalary")
                                                      head("Training Data: Input and Output" )
                                                      head(ytrain)
                                                      head(ytrain)
                                                      ytest <- as.matrix(testingData$Purchased)
                                                      # creating y for computation assigning +1 for purchased and 0 for not purchased
                                                      ytest <- matrix(apply(ytest, 1, function(x){
                                                        colnames(ytest) <- c("Purchased")
                                                        ones <- matrix(rep(1,nrow(ytest)), nrow = 1,
                                                        # Adding ones in first column of data for b
                                                        xtest <- cbind(ones,testingData$Age,testingData$EstimatedSalary)
                                                        colnames(xtest) <- c("ones","Age","EstimatedSalary")
                                                        head("Testing Data: Input and Output" )
                                                        head(ytest)
                                                        head(ytest)
                                                        ytrain <- as.matrix(trainingData$Purchased)
                                                        # creating y for computation assigning +1 for purchased and 0 for not purchased
                                                        ytrain <- matrix(apply(ytrain, 1, function(x){
                                                          colnames(ytrain) <- c("Purchased")
                                                          ones <- matrix(rep(1,nrow(ytrain)), nrow = 1,
                                                          # Adding ones in first column of data for b
                                                          xtrain <- cbind(ones,trainingData$Age,trainingData$EstimatedSalary)
                                                          colnames(xtrain) <- c("ones","Age","EstimatedSalary")
                                                          head("Training Data: Input and Output" )
                                                          head(ytrain)
                                                          head(ytrain)
                                                          ytest <- as.matrix(testingData$Purchased)
                                                          # creating y for computation assigning +1 for purchased and 0 for not purchased
                                                          ytest <- matrix(apply(ytest, 1, function(x){
                                                            colnames(ytest) <- c("Purchased")
                                                            ones <- matrix(rep(1,nrow(ytest)), nrow = 1,
                                                            # Adding ones in first column of data for b
                                                            xtest <- cbind(ones,testingData$Age,testingData$EstimatedSalary)
                                                            colnames(xtest) <- c("ones","Age","EstimatedSalary")
                                                            head("Testing Data: Input and Output" )
                                                            head(ytest)
                                                            head(ytest)
                                                            ytrain <- as.matrix(trainingData$Purchased)
                                                            # creating y for computation assigning +1 for purchased and 0 for not purchased
                                                            ytrain <- matrix(apply(ytrain, 1, function(x){
                                                              colnames(ytrain) <- c("Purchased")
                                                              ones <- matrix(rep(1,nrow(ytrain)), nrow = 1,
                                                              # Adding ones in first column of data for b
                                                              xtrain <- cbind(ones,trainingData$Age,trainingData$EstimatedSalary)
                                                              colnames(xtrain) <- c("ones","Age","EstimatedSalary")
                                                              head("Training Data: Input and Output" )
                                                              head(ytrain)
                                                              head(ytrain)
                                                              ytest <- as.matrix(testingData$Purchased)
                                                              # creating y for computation assigning +1 for purchased and 0 for not purchased
                                                              ytest <- matrix(apply(ytest, 1, function(x){
                                                                colnames(ytest) <- c("Purchased")
                                                                ones <- matrix(rep(1,nrow(ytest)), nrow = 1,
                                                                # Adding ones in first column of data for b
                                                                xtest <- cbind(ones,testingData$Age,testingData$EstimatedSalary)
                                                                colnames(xtest) <- c("ones","Age","EstimatedSalary")
                                                                head("Testing Data: Input and Output" )
                                                                head(ytest)
                                                                head(ytest)
                                                                ytrain <- as.matrix(trainingData$Purchased)
                                                                # creating y for computation assigning +1 for purchased and 0 for not purchased
                                                                ytrain <- matrix(apply(ytrain, 1, function(x){
                                                                  colnames(ytrain) <- c("Purchased")
                                                                  ones <- matrix(rep(1,nrow(ytrain)), nrow = 1,
                                                                  # Adding ones in first column of data for b
                                                                  xtrain <- cbind(ones,trainingData$Age,trainingData$EstimatedSalary)
                                                                  colnames(xtrain) <- c("ones","Age","EstimatedSalary")
                                                                  head("Training Data: Input and Output" )
                                                                  head(ytrain)
                                                                  head(ytrain)
                                                                  ytest <- as.matrix(testingData$Purchased)
                                                                  # creating y for computation assigning +1 for purchased and 0 for not purchased
                                                                  ytest <- matrix(apply(ytest, 1, function(x){
                                                                    colnames(ytest) <- c("Purchased")
                                                                    ones <- matrix(rep(1,nrow(ytest)), nrow = 1,
                                                                    # Adding ones in first column of data for b
                                                                    xtest <- cbind(ones,testingData$Age,testingData$EstimatedSalary)
                                                                    colnames(xtest) <- c("ones","Age","EstimatedSalary")
                                                                    head("Testing Data: Input and Output" )
                                                                    head(ytest)
                                                                    head(ytest)
                                                                    ytrain <- as.matrix(trainingData$Purchased)
                                                                    # creating y for computation assigning +1 for purchased and 0 for not purchased
                                                                    ytrain <- matrix(apply(ytrain, 1, function(x){
                                                                      colnames(ytrain) <- c("Purchased")
                                                                      ones <- matrix(rep(1,nrow(ytrain)), nrow = 1,
                                                                      # Adding ones in first column of data for b
                                                                      xtrain <- cbind(ones,trainingData$Age,trainingData$EstimatedSalary)
                                                                      colnames(xtrain) <- c("ones","Age","EstimatedSalary")
                                                                      head("Training Data: Input and Output" )
                                                                      head(ytrain)
                                                                      head(ytrain)
                                                                      ytest <- as.matrix(testingData$Purchased)
                                                                      # creating y for computation assigning +1 for purchased and 0 for not purchased
                                                                      ytest <- matrix(apply(ytest, 1, function(x){
                                                                        colnames(ytest) <- c("Purchased")
                                                                        ones <- matrix(rep(1,nrow(ytest)), nrow = 1,
                                                                        # Adding ones in first column of data for b
                                                                        xtest <- cbind(ones,testingData$Age,testingData$EstimatedSalary)
                                                                        colnames(xtest) <- c("ones","Age","EstimatedSalary")
                                                                        head("Testing Data: Input and Output" )
                                                                        head(ytest)
                                                                        head(ytest)
                                                                        ytrain <- as.matrix(trainingData$Purchased)
                                                                        # creating y for computation assigning +1 for purchased and 0 for not purchased
                                                                        ytrain <- matrix(apply(ytrain, 1, function(x){
                                                                          colnames(ytrain) <- c("Purchased")
                                                                          ones <- matrix(rep(1,nrow(ytrain)), nrow = 1,
                                                                          # Adding ones in first column of data for b
                                                                          xtrain <- cbind(ones,trainingData$Age,trainingData$EstimatedSalary)
                                                                          colnames(xtrain) <- c("ones","Age","EstimatedSalary")
                                                                          head("Training Data: Input and Output" )
                                                                          head(ytrain)
                                                                          head(ytrain)
                                                                          ytest <- as.matrix(testingData$Purchased)
                                                                          # creating y for computation assigning +1 for purchased and 0 for not purchased
                                                                          ytest <- matrix(apply(ytest, 1, function(x){
                                                                            colnames(ytest) <- c("Purchased")
                                                                            ones <- matrix(rep(1,nrow(ytest)), nrow = 1,
                                                                            # Adding ones in first column of data for b
                                                                            xtest <- cbind(ones,testingData$Age,testingData$EstimatedSalary)
                                                                            colnames(xtest) <- c("ones","Age","EstimatedSalary")
                                                                            head("Testing Data: Input and Output" )
                                                                            head(ytest)
                                                                            head(ytest)
                                                                            ytrain <- as.matrix(trainingData$Purchased)
                                                                            # creating y for computation assigning +1 for purchased and 0 for not purchased
                                                                            ytrain <- matrix(apply(ytrain, 1, function(x){
                                                                              colnames(ytrain) <- c("Purchased")
                                                                              ones <- matrix(rep(1,nrow(ytrain)), nrow = 1,
                                                                              # Adding ones in first column of data for b
                                                                              xtrain <- cbind(ones,trainingData$Age,trainingData$EstimatedSalary)
                                                                              colnames(xtrain) <- c("ones","Age","EstimatedSalary")
                                                                              head("Training Data: Input and Output" )
                                                                              head(ytrain)
                                                                              head(ytrain)
                                                                              ytest <- as.matrix(testingData$Purchased)
                                                                              # creating y for computation assigning +1 for purchased and 0 for not purchased
                                                                              ytest <- matrix(apply(ytest, 1, function(x){
                                                                                colnames(ytest) <- c("Purchased")
                                                                                ones <- matrix(rep(1,nrow(ytest)), nrow = 1,
                                                                                # Adding ones in first column of data for b
                                                                                xtest <- cbind(ones,testingData$Age,testingData$EstimatedSalary)
                                                                                colnames(xtest) <- c("ones","Age","EstimatedSalary")
                                                                                head("Testing Data: Input and Output" )
                                                                                head(ytest)
                                                                                head(ytest)
                                                                                ytrain <- as.matrix(trainingData$Purchased)
                                                                                # creating y for computation assigning +1 for purchased and 0 for not purchased
                                                                                ytrain <- matrix(apply(ytrain, 1, function(x){
                                                                                  colnames(ytrain) <- c("Purchased")
                                                                                  ones <- matrix(rep(1,nrow(ytrain)), nrow = 1,
                                                                                  # Adding ones in first column of data for b
                                                                                  xtrain <- cbind(ones,trainingData$Age,trainingData$EstimatedSalary)
                                                                                  colnames(xtrain) <- c("ones","Age","EstimatedSalary")
                                                                                  head("Training Data: Input and Output" )
                                                                                  head(ytrain)
                                                                                  head(ytrain)
                                                                                  ytest <- as.matrix(testingData$Purchased)
                                                                                  # creating y for computation assigning +1 for purchased and 0 for not purchased
                                                                                  ytest <- matrix(apply(ytest, 1, function(x){
                                                                                    colnames(ytest) <- c("Purchased")
                                                                                    ones <- matrix(rep(1,nrow(ytest)), nrow = 1,
                                                                                    # Adding ones in first column of data for b
                                                                                    xtest <- cbind(ones,testingData$Age,testingData$EstimatedSalary)
                                                                                    colnames(xtest) <- c("ones","Age","EstimatedSalary")
                                                                                    head("Testing Data: Input and Output" )
                                                                                    head(ytest)
                                                                                    head(ytest)
                                                                                    ytrain <- as.matrix(trainingData$Purchased)
                                                                                    # creating y for computation assigning +1 for purchased and 0 for not purchased
                                                                                    ytrain <- matrix(apply(ytrain, 1, function(x){
                                                                                      colnames(ytrain) <- c("Purchased")
                                                                                      ones <- matrix(rep(1,nrow(ytrain)), nrow = 1,
                                                                                      # Adding ones in first column of data for b
                                                                                      xtrain <- cbind(ones,trainingData$Age,trainingData$EstimatedSalary)
                                                                
```

Testing Data :: Size :: 100 5

```
colnames(xtest) <- c("ones","Age","EstimatedSalary")
cat("Testing Data:: Input and Output" )
head(xtest)
head(ytest)
```

Training Data:: Input and Output

| ones | Age | EstimatedSalary |
|------|-----|-----------------|
| 1 | 35 | 20000 |
| 1 | 26 | 43000 |
| 1 | 19 | 76000 |
| 1 | 25 | 33000 |
| 1 | 26 | 80000 |

Preprocessing data for modelling

```
In [108]... # converting dataframe into matrix with required data. We are using only Age and EstimatedSalary
ytrain <- as.matrix(trainingData$Purchased)
# creating yn for computation assigning +1 to 1 and -1 to 0
ytrain <- matrix(apply(ytrain, 1, function (var) {if (var == 1) return (1) else return (-1)}))
colnames(ytrain) <- c("Purchased")
ones <- matrix(rep(1,nrow(ytrain)), nrow = nrow(ytrain), ncol = 1)
# Adding ones in first column of data for bias parameter
xtrain <- cbind(ones,trainingData$Age,trainingData$EstimatedSalary)
colnames(xtrain) <- c("ones","Age","EstimatedSalary")
cat("Training Data:: Input and Output" )
head(xtrain)
head(ytrain)
```

Trainig Data:: Input and Output

| ones | Age | EstimatedSalary |
|------|-----|-----------------|
| 1 | 35 | 20000 |
| 1 | 26 | 43000 |
| 1 | 19 | 76000 |
| 1 | 25 | 33000 |
| 1 | 26 | 80000 |
| 1 | 20 | 86000 |

| Purchased |
|-----------|
| -1 |
| -1 |
| -1 |
| -1 |
| -1 |
| -1 |

Testing Data:: Input and Output

| ones | Age | EstimatedSalary |
|------|-----|-----------------|
| 1 | 19 | 19000 |
| 1 | 27 | 57000 |
| 1 | 27 | 58000 |
| 1 | 27 | 84000 |
| 1 | 32 | 150000 |
| 1 | 35 | 65000 |

| Purchased |
|-----------|
| -1 |
| -1 |
| -1 |
| -1 |
| 1 |
| -1 |

```
In [109]... #Scaling predictor variables for training data
xtrain[,2] <- (xtrain[,2] - mean(xtrain[,2]))/sd(xtrain[,2])
xtrain[,3] <- (xtrain[,3]- mean(xtrain[,3]))/sd(xtrain[,3])
cat("Training Input data after normalization")
head(xtrain)

#Scaling predictor variables for testing data
xtest[,2] <- (xtest[,2] - mean(xtest[,2]))/sd(xtest[,2])
xtest[,3] <- (xtest[,3]- mean(xtest[,3]))/sd(xtest[,3])
cat("Testing Input data after normalization")
head(xtest)
```

Training Input data after normalization

| ones | Age | EstimatedSalary |
|------|------------|-----------------|
| 1 | -0.3249205 | -1.4065133 |
| 1 | -1.1824821 | -0.7552187 |
| 1 | -1.8494744 | 0.1792476 |
| 1 | -1.2777667 | -1.0383903 |
| 1 | -1.1824821 | 0.2925163 |
| 1 | -1.7541898 | 0.4624192 |

Testing Input data after normalization

| ones | Age | EstimatedSalary |
|------|-------------|-----------------|
| 1 | -1.61236437 | -1.6809336 |
| 1 | -0.82536529 | -0.4274902 |
| 1 | -0.82536529 | -0.3945048 |
| 1 | -0.82536529 | 0.4631144 |
| 1 | -0.33349086 | 2.6401477 |
| 1 | -0.03836621 | -0.1636074 |

Defining functions for subgradient and loss function

```
In [110]... g <- function(t){
  if (t <= 1)
    return (-1)
  else
    return (0)
}

# define tn = yn<(w,xn)
# yn is the output for nth index
# xn is the input for nth index
# x = [b w1 w2]'

tn <- function(yn, x, xn){
  t <- yn * ((xn**x))
  return (t)
}

#compute loss as terminating condition
loss <-function(x,C){
  N <- dim(xtrain)[1]
  distances <- 1 - ytrain * (xtrain**x)
  distances[distances < 0] <- 0 # equivalent to max(0, distance)
  hinge_loss <- C * (sum(distances) / N)
  # calculate cost
  cost <- 1 / 2 * t(x)**x + hinge_loss
  return (cost)
}

gradient <- function(x, C){
  deltaF <- matrix(rep(0,3), nrow = 3, ncol = 1)
  sum<- matrix(rep(0,3), nrow = 3, ncol = 1)
  for (n in seq(length(ytrain))){
    t = tn(ytrain[n],x,xtrain[n,])
    gn = g(t)
    diff <- x + (C * gn * ytrain[n] * xtrain[n,])
    sum <- sum + diff
  }
  deltaF <- sum/length(ytrain)
  return (deltaF)
}
```

Defining functions execute gradient descent for SVM, generate prediction, compute accuracy and generate confusion matrix

```
In [111]... # Run gradient descent for SVM
gradientDescent <- function(x, C, alpha,thrs,maxi){
  converged<-FALSE
  i<-1
  x1<-x
  prev_lossvalue <- 0
  while(!((converged && i <= maxi))){
    {
      deltafx <- gradient(x1,C)
      if(!is.infinite(deltafx) || is.nan(norm(deltafx,type = "2"))){
        break
      }
      x1 <- x1 - (alpha*deltafx)
      lossvalue <- loss(x1,C)
      # terminating condition based on loss function
      converged <-abs(prev_lossvalue - lossvalue) < thrs * prev_lossvalue
      prev_lossvalue <- lossvalue
      i <- i+1
    }
  }
  return (list("x1"= x1,"iteration" = i-1,"converged" = converged, "lossValue" = prev_lossvalue))
}
```

generate prediction

```
predict <- function(data,featurecoefficients)
{
  result <- data**featurecoefficients
  result[result >= 0] <- -1
  result[result > 0] <- 1
  return(result)
}
```

compute accuracy

```
accuracy <- function(predicted, actual)
{
  return((sum(predicted==actual)/dim(predicted)[1])*100)
}
```

generate confusion matrix

```
generateconfusionmatrix <- function(predicted, actual)
{
  confusionMatrix <- matrix(rep(0,4), nrow = 2, ncol = 2)
  colnames(confusionMatrix) <- c("actual(1)","actual(-1)")
  rownames(confusionMatrix) <- c("pred(1)","pred(-1)")
  confusionMatrix
  for (i in seq(length(actual))){
    {
      if (actual[i] ==1 & predicted[i] ==1)
      {
        confusionMatrix[1,1] = confusionMatrix[1,1] + 1
      }
      else if (actual[i] ==1 & predicted[i] ==-1)
      {
        confusionMatrix[2,1] = confusionMatrix[2,1] + 1
      }
      else if (actual[i] ==-1 & predicted[i] ==1)
      {
        confusionMatrix[1,2] = confusionMatrix[1,2] + 1
      }
      else if (actual[i] ==-1 & predicted[i] ==-1)
      {
        confusionMatrix[2,2] = confusionMatrix[2,2] + 1
      }
    }
  }
  return (confusionMatrix)
}
```

Running SVM for tradeoff factor = 50

```
In [112]... #setting tradoff parameter to 50
C <- 50
# x = [w1 w2 b]'
x <- matrix(rep(0,3), nrow = 3, ncol = 1)
thres <- 10**(2)
maxiter <- 1000
alpha <- 0.01
answer <- gradientDescent(x, C,alpha,thres,maxiter)
wstar <- answer$x
cat("Coefficients")

#prediction
prediction <- predict(xtest,wstar)
#accuracy
accuracyper1 <- accuracy(prediction,ytest)
cat("Accuracy is :: ", accuracyper1,"%", "\n")
#confusion matrix
cmatrix1 <- generateconfusionmatrix(prediction,ytest)
cmatrix1
```

Coefficients

-0.5130687

0.9951247

0.4937978

Accuracy is :: 87 %


Confusion Matrix

| | actual(1) | actual(-1) |
|----------|-----------|------------|
| pred(1) | 26 | 6 |
| pred(-1) | 7 | 61 |

```
In [113]... # generating points to plot classification line
Age <- seq(-2,2,0.1)
# wstar[1] represents b, wstar[2] and wstar[3] represents the parameter for Age and salary
EstimatesSalary = -(wstar[2]*Age+wstar[1])/wstar[3]
data1 <- as.data.frame(cbind(Age,EstimatesSalary))
```

```
In [114]... data <- as.data.frame(cbind(xtrain,ytrain))
sp <- ggplot() + geom_point(data, mapping = aes(x = Age, y = EstimatedSalary,color = Purchased)) +
scale_colour_gradient(low = "red", high = "green")
sp + geom_line(data1, mapping = aes(x = Age, y = EstimatesSalary)) +
ggtitle("Visualisation for Training data with C = 50")
```

Visualisation for Training data with C = 50



```
In [115]... data <- as.data.frame(cbind(xtest,ytest))
library(ggplot2)
sp <- ggplot() + geom_point(data, mapping = aes(x = Age, y = EstimatedSalary, color = Purchased))+
scale_colour_gradient(low = "red", high = "green")
sp + geom_line(data1, mapping = aes(x = Age, y = EstimatesSalary))+
ggtitle("Visualisation for Testing data with C = 50")
```

Visualisation for Testing data with C = 50



Running SVM for tradeoff factor = 1, 75 and 100

```
In [116]... #setting tradoff parameter to 1
C <- 1
# x = [w1 w2 b]'
x <- matrix(rep(0,3), nrow = 3, ncol = 1)
thres <- 10**(2)
maxiter <- 1000
alpha <- 0.01
answer <- gradientDescent(x, C,alpha,thres,maxiter)
wstar <- answer$x
cat("Coefficients")

#prediction
prediction <- predict(xtest,wstar)
#accuracy
accuracyper2 <- accuracy(prediction,ytest)
cat("Accuracy is :: ", accuracyper2,"%", "\n")
#confusion matrix
cmatrix1 <- generateconfusionmatrix(prediction,ytest)
cmatrix1
```

Accuracy is :: 88 %

Confusion Matrix

| | actual(1) | actual(-1) |
|----------|-----------|------------|
| pred(1) | 27 | 6 |
| pred(-1) | 6 | 61 |

```
In [117]... #setting tradoff parameter to 75
C <- 75
# x = [w1 w2 b]'
x <- matrix(rep(0,3), nrow = 3, ncol = 1)
thres <- 10**(2)
maxiter <- 1000
alpha <- 0.01
answer <- gradientDescent(x, C,alpha,thres,maxiter)
wstar <- answer$x
cat("Coefficients")

#prediction
prediction <- predict(xtest,wstar)
#accuracy
accuracyper3 <- accuracy(prediction,ytest)
cat("Accuracy is :: ", accuracyper3,"%", "\n")
#confusion matrix
cmatrix3 <- generateconfusionmatrix(prediction,ytest)
cmatrix3
```

Accuracy is :: 87 %

Confusion Matrix

| | actual(1) | actual(-1) |
|----------|-----------|------------|
| pred(1) | 26 | 6 |
| pred(-1) | 7 | 61 |

```
In [118]... #setting tradoff parameter to 100
C <- 100
# x = [w1 w2 b]'
x <- matrix(rep(0,3), nrow = 3, ncol = 1)
thres <- 10**(2)
maxiter <- 1000
alpha <- 0.01
answer <- gradientDescent(x, C,alpha,thres,maxiter)
wstar <- answer$x
cat("Coefficients")

#prediction
prediction <- predict(xtest,wstar)
#accuracy
accuracyper4 <- accuracy(prediction,ytest)
cat("Accuracy is :: ", accuracyper4,"%", "\n")
#confusion matrix
cmatrix4 <- generateconfusionmatrix(prediction,ytest)
cmatrix4
```

Accuracy is :: 87 %

Confusion Matrix

| | actual(1) | actual(-1) |
|----------|-----------|------------|
| pred(1) | 26 | 6 |
| pred(-1) | 7 | 61 |

```
In [119]... cat("Confusion Matrix and accuracy (%) for C = 1")
accuracyper2
cat("Confusion Matrix and accuracy (%) for C = 50")
cmatrix1
accuracyper1
cat("Confusion Matrix and accuracy (%) for C = 75")
cmatrix3
accuracyper3
cat("Confusion Matrix and accuracy (%) for C = 100")
cmatrix4
accuracyper4
```

Confusion Matrix and accuracy (%) for C = 1

| | actual(1) | actual(-1) |
|----------|-----------|------------|
| pred(1) | 27 | 6 |
| pred(-1) | 6 | 61 |

88

Confusion Matrix and accuracy (%) for C = 50

| | actual(1) | actual(-1) |
|----------|-----------|------------|
| pred(1) | 26 | 6 |
| pred(-1) | 7 | 61 |

87

Confusion Matrix and accuracy (%) for C = 75

| | actual(1) | actual(-1) |
|----------|-----------|------------|
| pred(1) | 26 | 6 |
| pred(-1) | 7 | 61 |

87

Confusion Matrix and accuracy (%) for C = 100

| | actual(1) | actual(-1) |
|----------|-----------|------------|
| pred(1) | 26 | 6 |
| pred(-1) | 7 | 61 |

87

What happens to the confusion matrix if you use C = 100? What happens to the confusion matrix if you use C = 1? Comment on what the effect of C is on the entries of the confusion matrix. What choice of C gives you the best classification accuracy results on the test data?

I ran SVM for trade-off factors 1, 50, 75 and 100. Accuracy is best (88%) for trade-off factor C = 1 while accuracy for trade-off 50, 75 and 100 is same 87%. Also as trade-off is increased from 1, there is decrease in "TRUE POSITIVE" cases from 27 to 26 and increase in "TRUE NEGATIVE" cases from 6 to 7.

Given the observation, C = 1 gives the best accuracy.

Github link for the code

<https://github.com/jainsanyam786/OptimizationForMachineLearning.git>

