JMLR: Workshop and Conference Proceedings 1–31, 2027 Conference on Health, Inference, and Learning (CHIL) 2027

Sampled or Stated? Post-Training Moves a Language Model's Differential Diagnosis from Its Samples to Its List

Anonymous Authors
Anonymous Institution

Abstract

A language model's differential diagnosis can be read from the ranked list it states in one answer or from the spread of its answers over repeated samples; pass@k, self-consistency and sampling-based uncertainty use the second. Recent work shows that instruction-tuned models cannot sample from distributions they can describe. We test what this means for diagnosis, where a reference differential exists, with base/post-trained pairs from two open families at 7–32B (Qwen2.5-7B and -32B, Qwen3-8B, and every released stage of OLMo 3 7B and OLMo 3.1 32B) and three medical models, using 32 samples per case on DDXPlus and on rare-disease cases from Phenopacket Store. The sampled differential collapses: post-trained models trail their base models by 4–28 points at pass@32, give 1.3–3.6 distinct top answers per 32 samples against 3.8–8.2, and gain little from majority voting. The stated list does not: it moves closer to the reference differential and names fewer implausible conditions, robustly to list format, top-1 accuracy and the elicitation prompt, and drawing top answers from a model's own stated lists recovers more coverage than its base model's samples. Agreement between samples becomes a weaker error signal; whether the stated probability is better depends on the model, and a held-out audit on 100 labeled cases picks the better one in 82% of draws. On real rare-disease cases the same shifts appear but stop short of a crossover. Which post-training stage narrows the samples most depends on the recipe. Evaluations of diagnostic breadth should say which readout they use.

Data and Code Availability. All data are public: DDXPlus (Fansi Tchango et al., 2022b) (synthetic patients) and Phenopacket Store v0.1.27 (Danis et al., 2025) (cases from published literature). All models are public checkpoints (Table 4). Prompts and an example vignette are in Appendix A; code and sampled outputs will be released with the camera-ready version.

Institutional Review Board (IRB). This work uses only public synthetic or previously published, de-identified data and involves no human subjects, so it did not require IRB review.

1. Introduction

Clinicians reason over a differential diagnosis, a ranked set of conditions consistent with the presentation, and the conditions they keep in view determine which tests are ordered and which dangerous possibilities are ruled out. A language model's differential can be read in two ways: from the list it states in one answer, or from the distribution of its answers over repeated samples. Much current practice uses the second. Pass@k, self-consistency voting (Wang et al., 2023) and sampling-based uncertainty such as semantic entropy (Farquhar et al., 2024) draw on repeated samples, and so does the evidence that

© 2027 A. Authors.

reinforcement learning sharpens models, which win at pass@1 while their base models solve more problems given many samples (Yue et al., 2025; Wu et al., 2025; Oh et al., 2026). The two readouts agree for a model that samples from the distribution it states. Jang et al. (2026) show that instruction-tuned models do not: on synthetic and survey-response targets they sample worse than their own base models, more so at each post-training stage, while still describing the target accurately in one call (see also Meister et al., 2025; Zhang et al., 2026). Whether the same holds for a differential diagnosis, where the reference is a clinical distribution with a correct answer, and what it does to the tools built on repeated samples, has not been tested.

We test it with a design that holds the pretrained weights fixed and varies only the post-training: base/instruct pairs for Qwen2.5-7B, Qwen3-8B and Qwen2.5-32B; every released stage (SFT, DPO, RL) of OLMo 3 7B (Team Olmo et al., 2025) and OLMo 3.1 32B, plus a 7B checkpoint trained with RL directly from the base; and three medical models fine-tuned from Qwen2.5-7B-Instruct. On DDXPlus (Fansi Tchango et al., 2022b), which ships a reference differential for every synthetic patient, we score both readouts against that reference; on real rare-disease cases from Phenopacket Store (Danis et al., 2025) we score accuracy, voting and uncertainty. Our findings:

- **Post-training collapses the sampled differential** at 7–32B, and which stage narrows it most depends on the recipe: RL after SFT and DPO in OLMo 3 7B, SFT in OLMo 3.1 32B (§4.1).
- **The stated differential does not collapse; it improves.** One stated list moves closer to the reference and names severe conditions more often and implausible ones less often, while the samples move away, in every family and size (for OLMo 3 7B only with a full-distribution prompt). The gain is not format, accuracy or a floor effect, and sampling from the stated lists recovers the lost coverage (§4.2).
- **Sampling-based methods lose their value, and which signal to trust is model-dependent but checkable.** Majority voting stops helping, one list's top three beats 32 samples for post-trained Qwen models, and agreement weakens as an error signal. A held-out audit on 100 labeled cases picks the better of stated probability and agreement far more often than always using agreement. Neither readout tracks a case's true ambiguity (§4.3).
- **On real rare-disease cases** the same shifts appear but stop short of a crossover: post-training shrinks the gain from voting and weakens agreement as an error signal while strengthening the stated probability, which ends up tied with agreement; 32 samples still beat one list (§4.4).

2. Related work

Post-training and the sampled distribution. RL with verifiable rewards improves pass@1 while base models win at large k on math and code (Yue et al., 2025), reweighting solutions already in the base model's support (Wu et al., 2025); a "sharpening tax" appears across 14 base/post-trained pairs on agentic tasks (Oh et al., 2026), though RL can expand the boundary in domains under-represented in pretraining (Cheng et al., 2025). In medicine,

the one pass@k analysis we know of studies vision-language models (Jeddi et al., 2026). Instruction tuning and RLHF reduce output diversity (Kirk et al., 2024; West and Potts, 2025; Jiang et al., 2025; Murthy et al., 2025), more so with scale for SFT (Springer et al., 2026); Zhang et al. (2026) attribute this to typicality bias in preference data and track it across Tülu 3's checkpoints on creative writing, and Liu (2026) place the collapse at DPO in a Zephyr ablation.

Stated versus sampled distributions. Models asked to verbalize a distribution match it better than their samples do, on opinion surveys (Meister et al., 2025) and on synthetic and survey targets, where Jang et al. (2026) show the gap growing at each OLMo-2 post-training stage. Verbalized sampling recovers part of the lost diversity (Zhang et al., 2026). For uncertainty, RLHF models' verbalized confidence is better calibrated than their token probabilities (Tian et al., 2023), but sample consistency usually discriminates errors better than verbalized confidence (Xiong et al., 2024), including for medical diagnosis (Savage et al., 2025), and aligned models' samples can collapse enough to leave sampling-based uncertainty without signal (Liu, 2026). We extend this line to diagnosis with a correct reference distribution, two pipelines at 7–32B, and the consequences for aggregation and uncertainty.

Medical models and differential diagnosis. LLMs have been evaluated as differential-diagnosis aids on clinicopathological cases (Kanjee et al., 2023; McDuff et al., 2025). Medical post-training recipes include verifier-guided SFT and PPO (Chen et al., 2025), rule-based RL (Liu et al., 2025) and reasoning distillation (Huang et al., 2026); RL and reward models tend to favor confident answers (Leng et al., 2025; Damani et al., 2026; Mei et al., 2026). DDXPlus was built for diagnosis systems trained on differentials (Fansi Tchango et al., 2022a); LLM evaluations on it score hierarchical top-k accuracy (Lim et al., 2025) or interactive diagnosis (Rose et al., 2025), and Puri et al. (2026) train models to output several answers per completion. We score stated and sampled differentials against the reference *distribution*.

3. Setup

Tasks. DDXPlus (Fansi Tchango et al., 2022b): synthetic patients from a rule-based medical knowledge base, each with a true pathology and a reference differential, a probability distribution over 49 conditions. We use 980 test patients (20 per condition) rendered by template as vignettes (example in Appendix A). The prompt lists the 49 conditions and asks for the five most likely, with probabilities, as JSON, so this is a closed-set task. **Phenopacket Store** (Danis et al., 2025): 1,401 published rare-disease cases covering 749 diseases, rendered as phenotype vignettes with an open-ended differential; names are graded against the case's diagnosis via Mondo as exact, related (a specific ancestor group or subtype) or wrong (Appendix A).

Models. Qwen2.5-7B, Qwen3-8B and Qwen2.5-32B, each with its official post-trained version; OLMo-3-1025-7B and OLMo-3-1125-32B with the SFT, DPO and final RLVR (Instruct) checkpoints of OLMo 3 7B and OLMo 3.1 32B, plus OLMo-3-7B-RL-Zero-General, trained with RL from the 7B base; and AlphaMed (rule-based RL), HuatuoGPT-o1 (SFT then PPO) and m1 (SFT distillation), all fine-tuned from Qwen2.5-7B-Instruct (Table 4).

Sampling. 32 samples per case with vLLM, at T=0.7 (top-p 0.95) and, for the 7–8B models, T=1 (top-p 1), each model with its own chat template (OLMo base models get their SFT checkpoint's) and the same prompt. A sample is *valid* if its last JSON list names at least one condition; invalid samples count as wrong. They affect mainly base models (up to 47% of samples), so base-model coverage is a lower bound (Appendix C.3).

Two readouts. The *sampled* readout is the distribution of top-1 answers over a case's samples. We report pass@k (Chen et al., 2021), the number of distinct top-1 answers, the reference mass they cover (coverage@32), and total-variation distance (TV) of their empirical distribution to the reference. The *stated* readout is one sample's list, with its stated probabilities renormalized over the conditions it names (uniform if missing). We report its TV to the reference, the reference mass of the conditions it names, and whether it names each severe condition (DDXPlus severity 1–2) that the reference weights at least 0.1, averaged over valid samples. The *single-call answer* is the top answer of a model's first valid sample. Differences come with 95% paired case-bootstrap intervals and are computed from unrounded values; we read a non-significant difference as no detectable change, bounded by its interval, not as equivalence.

4. Results

4.1. Post-training collapses the sampled differential

Table 1 compares each base model with its post-trained versions. In both Qwen families at 7–8B the post-trained model is far better on its first answer (+12.6 to +27.5 points), but its pass@k curve crosses the base model's at k≈4–8, and at k=32 the base model leads by 9.7–14.6 points (all intervals exclude zero; Figure 2 in Appendix C.1). At 32B the pattern holds with smaller margins: Qwen2.5-32B-Instruct gains 10.4 points at k=1 and loses 4.9 [2.8, 7.1] at k=32, and OLMo 3.1 32B Instruct loses 4.0 [2.0, 5.9]. Post-trained models give fewer distinct top answers and cover less of the reference mass. All models but OLMo-3-7B-Instruct stay above a uniform guesser's pass@32 of 0.48. Which stage narrows the samples most depends on the recipe. In OLMo 3 7B, distinct answers fall from 4.93 to 4.01 after SFT, 3.30 after DPO and 2.37 after RLVR, and the RLVR step alone costs 19.1 [16.3, 21.8] points of pass@32 against the DPO model. In OLMo 3.1 32B, SFT costs most (12.1 [9.9, 14.4] points), DPO recovers most of it, and the RLVR step costs 2.8 [1.1, 4.3] (Appendix C.5). RL-Zero, trained with RL from the 7B base, narrows less; at T=1 it shows no detectable loss of pass@32 (−1.8 [−4.5, +0.8]; Appendix C.4). The sampled top answers also consider fewer severe conditions after post-training, but even base models do so less often than a guesser drawing from the average reference differential (0.56–0.61), so we assess can't-miss conditions on the stated list (Appendix C.2). The pattern survives a reworded prompt and conditioning on valid samples; a chain-of-thought prompt removes the large-k loss but not the loss of diversity (Appendix C.3).

4.2. The stated differential does not collapse

For the post-trained models the two readouts move in opposite directions (Figure 1a, Table 2). For every Qwen model at 7–32B and at both temperatures, the post-trained model's

Comparison	Model	Sampled top-1 answers pass@1	pass@32	Distinct	Cov@32	Drawn from stated lists pass@32	Distinct
Qwen3-8B, T=0.7	base	0.388	**0.730**	**3.76**	**0.322**	0.780	7.79
	post-trained	**0.558**	0.607	1.27	0.217	**0.811**	4.96
Qwen3-8B, T=1	base	0.282	**0.789**	**6.60**	**0.407**	**0.832**	9.82
	post-trained	**0.556**	0.643	1.53	0.236	0.820	5.40
Qwen2.5-7B, T=0.7	base	0.352	**0.695**	**4.91**	**0.335**	0.772	10.68
	instruct	**0.478**	0.598	1.82	0.239	**0.802**	6.81
Qwen2.5-7B, T=1	base	0.239	**0.766**	**8.23**	**0.422**	0.785	12.44
	instruct	**0.464**	0.663	2.65	0.290	**0.827**	7.76
Qwen2.5-32B, T=0.7	base	0.500	**0.795**	**3.78**	**0.352**	0.850	8.79
	instruct	**0.604**	0.746	1.68	0.276	**0.880**	6.49
OLMo 3 7B, T=0.7	base	0.178	**0.705**	**4.93**	**0.351**	**0.719**	8.66
	SFT	0.222	0.559	4.01	0.257	0.618	7.18
	SFT+DPO	**0.324**	0.613	3.30	0.272	0.702	6.88
	SFT+DPO+RLVR	0.266	0.422	2.37	0.195	0.577	5.65
	RL-Zero (from base)	0.295	0.572	4.06	0.286	0.701	9.66
OLMo 3.1 32B, T=0.7	base	0.326	**0.796**	**4.32**	**0.347**	0.839	8.11
	SFT	0.461	0.674	2.94	0.265	0.759	7.94
	SFT+DPO	**0.584**	0.784	2.29	0.293	**0.868**	6.64
	SFT+DPO+RLVR	0.560	0.756	2.15	0.283	0.853	6.75
Chance	uniform guesser	0.020	0.483	23.7	—		
	reference-prior guesser	—	0.45	21.8	—		

Table 1: Sampled readout on DDXPlus (980 cases, 32 samples). Distinct: distinct top-1 answers per case; Cov@32: reference mass they cover. *Drawn from stated lists*: each sample's top answer replaced by a draw from its own stated list. Bold: better model of each pair (OLMo: of the block). Invalid samples count as wrong, which mostly penalizes base models. Chance: a guesser drawing uniformly from the 49 conditions, or from the reference differential averaged over test cases.

single list is closer to the reference than the base model's (TV -0.043 to -0.086, all intervals exclude zero), covers more of its mass (+6.1 to +10.8 points), and names severe conditions more often (+9.0 to +13.4 points), while its sampled answers move farther from the reference (+0.029 to +0.071). OLMo 3.1 32B behaves the same way (Instruct: list TV -0.045, samples +0.021). Conditions that drop out of the top answer remain in the list: Qwen2.5-7B-Instruct names unstable angina as its top answer in 1 of 107 eligible cases but still lists it in half of them. OLMo 3 7B is the exception with the five-item prompt: its DPO and Instruct lists are no closer to the reference than its base model's (TV +0.000 and +0.028). Asked for a probability on every condition, its Instruct model's stated distribution is closer (-0.032 $[-0.038, -0.027]$), while the Qwen pairs reproduce their five-item results (Appendix D.1); for OLMo 3 7B the result therefore depends on the elicitation format.

The gain is not an artifact (Appendix D.2). *Format:* 81–99% of the general models' post-trained and T=0.7 base lists name five conditions with probabilities, and restricting to complete lists leaves the gaps unchanged. *Accuracy:* among samples whose top answer is correct, and among those whose top answer is wrong, the post-trained Qwen list is still closer to the reference (-0.018 to -0.034 and -0.036 to -0.079). *Floor:* relative to each readout's oracle (the reference's own top five; as many reference draws as valid samples),




Figure 1: Base (hollow) → post-trained (filled) on DDXPlus (980 cases; OLMo: base → final Instruct; 32B models at T=0.7). (a) TV distance to the reference differential of one stated list (blue circles) and of the sampled top-1 answers (orange squares): post-training moves the list toward the reference and the samples away from it, except for OLMo 3 7B's five-item lists. (b) AUROC for the single-call answer being correct, of its stated probability (blue) and of agreement across 31 further samples (orange). Agreement weakens in every family; the stated probability overtakes it for Qwen3-8B (significantly at T=0.7) and OLMo 3 7B at T=0.7.

post-training lowers the list's excess TV (Qwen3-8B 0.479 → 0.435) and raises the samples' (0.557 → 0.613). *Over-naming:* post-trained lists name fewer conditions the reference gives under 1% and fewer severe conditions it gives under 0.1 (Qwen2.5-32B 0.74 → 0.65 of named severe conditions), so the gain in naming severe conditions is not over-triage. The list also holds the coverage the samples lost: drawing each top answer from the sample's own stated list lifts post-trained pass@32 above the base model's sampled pass@32 in every comparison except OLMo 3 7B (Table 1; Qwen3-8B 0.811 vs. 0.730, Qwen2.5-32B-Instruct 0.880 vs. 0.795). In absolute terms every model is still far from the reference: one list covers 0.22–0.42 of its mass, against 0.74 for the reference's own top five.

4.3. Consequences for sampling-based methods

Table 3 asks what the gap does to two uses of repeated samples.

Aggregation. Majority voting over 32 samples (self-consistency) raises base models' accuracy by 3.4–8.4 points at T=0.7, but adds little for the final post-trained models (Qwen3-

Comparison (T=0.7)	Model	TV to reference↓ One list	TV to reference↓ Samples	Reference mass covered One list	Reference mass covered 5 samples	Severe named One list
Qwen3-8B	base	0.743	**0.749**	0.335	**0.245**	0.347
	post-trained	**0.700**	0.793	**0.396**	0.207	**0.437**
Qwen2.5-7B	base	0.779	**0.756**	0.291	**0.233**	0.345
	instruct	**0.716**	0.785	**0.364**	0.214	**0.440**
Qwen2.5-32B	base	0.726	**0.726**	0.352	**0.272**	0.382
	instruct	**0.674**	0.759	**0.418**	0.245	**0.472**
OLMo 3 7B	base	0.795	**0.757**	0.268	**0.237**	0.256
	SFT+DPO	0.795	0.804	0.277	0.193	**0.378**
	SFT+DPO+RLVR	0.823	0.851	0.257	0.150	0.317
	RL-Zero (from base)	**0.775**	0.793	**0.295**	0.197	0.274
OLMo 3.1 32B	base	0.746	**0.742**	0.335	**0.254**	0.371
	SFT+DPO	**0.694**	0.755	**0.397**	0.249	**0.423**
	SFT+DPO+RLVR	0.701	0.763	0.391	0.241	0.392
Oracle	reference	0.265	0.18–0.25	0.735	0.563	0.975

Table 2: Stated vs. sampled readouts on DDXPlus (T=0.7, 980 cases, valid samples). *One list*: one sample's stated differential (mean over samples). *Samples*: empirical distribution of top-1 answers; *5 samples*: reference mass of the distinct top answers of five random samples. The two readouts have different floors (Oracle row: the reference's own top five as a list, and as many draws from the reference as valid samples), so compare each readout across models; floor-corrected values are in Table 11. Bold: better model of each pair (OLMo: of the block). T=1 is in Figure 1.

8B +0.3, Qwen2.5-7B-Instruct +0.8, OLMo-3-7B-Instruct −0.2, OLMo-3.1-32B-Instruct +0.9, all n.s.; Qwen2.5-32B-Instruct +1.9). Models that reason before answering still gain (HuatuoGPT-o1 +4.8, m1 +3.8, Qwen3-8B with a CoT prompt +4.5). Counting an invalid first sample as wrong instead of skipping it raises the base models' voting gains (5.6–18.4 points) and leaves the final post-trained models' at most 1.7. For a top-three differential, the top three of one list contains the true pathology more often than the three most frequent of 32 sampled answers for the post-trained Qwen models (+13.7 [11.4, 15.9] for Qwen3-8B, +7.3 [5.3, 9.6] for Qwen2.5-7B-Instruct, +5.6 [3.6, 7.7] for Qwen2.5-32B-Instruct), while for every base model the samples win by 7.3–13.6 points.

Uncertainty. We score each signal by how well it ranks the correctness of the single-call answer (AUROC). The stated probability needs no extra calls; *agreement*, the share of other samples with the same top answer, needs 4 or 31. For base models agreement is far better (0.80–0.83 against 0.54–0.73). Post-training weakens it in every family (Qwen3-8B 0.810 → 0.655, Qwen2.5-7B 0.811 → 0.702, OLMo 3 7B 0.802 → 0.731, Qwen2.5-32B 0.797 → 0.721, OLMo 3.1 32B 0.831 → 0.772; Figure 1b), consistent with Liu (2026). For Qwen3-8B and OLMo-3-7B-Instruct the stated probability is then the better signal (+0.079 [0.046, 0.110] and +0.064 [0.027, 0.101] over 32-sample agreement); for Qwen2.5-32B-Instruct it ties 32-sample agreement and beats five-sample agreement; for Qwen2.5-7B-Instruct, OLMo-3.1-

Model	Single-call accuracy	Vote@32 gain	Top-3: list − 32 samples	AUROC, single-call answer correct		
				Stated p	Agree@5	Agree@32
Qwen3-8B-Base	0.456	+3.4	−7.3	0.595	0.772	**0.810**
Qwen3-8B	0.556	+0.3	+13.7	**0.734**	0.613	0.655
Qwen3-8B (CoT prompt)	0.648	+4.5	+0.0	0.718	0.725	**0.778**
Qwen2.5-7B	0.371	+5.2	−8.9	0.576	0.764	**0.811**
Qwen2.5-7B-Instruct	0.480	+0.8	+7.3	0.571	0.653	**0.702**
Qwen2.5-32B	0.510	+7.0	−8.3	0.730	0.759	**0.797**
Qwen2.5-32B-Instruct	0.598	+1.9	+5.6	0.709	0.663	**0.721**
OLMo-3 7B base	0.291	+4.0	−13.6	0.538	0.761	**0.802**
OLMo-3 7B SFT+DPO	0.327	−0.4	−7.8	0.738	0.702	**0.751**
OLMo-3-7B-Instruct	0.267	−0.2	+1.9	**0.796**	0.668	0.731
OLMo-3.1 32B base	0.441	+8.4	−13.2	0.629	0.805	**0.831**
OLMo-3.1-32B-Instruct	0.562	+0.9	−0.6	0.696	0.712	**0.772**
AlphaMed-7B	0.528	+0.9	+0.6	0.673	0.663	**0.715**
HuatuoGPT-o1-7B	0.532	+4.8	−0.4	0.590	0.715	**0.775**
m1-7B	0.495	+3.8	−4.6	0.680	0.736	**0.782**

Table 3: Aggregation and uncertainty on DDXPlus (T=0.7, 980 cases). Single-call accuracy uses the first valid sample, so it can exceed pass@1, which counts invalid samples as wrong. Vote@32 gain: accuracy of the majority top-1 over all valid samples minus single-call accuracy (points). Top-3: rate at which one list's top three contains the true pathology minus the rate for the three most frequent sampled answers (points). AUROC: stated probability of the single-call answer (no extra calls) vs. agreement of 4 or 31 further samples; bold marks the best signal.

32B-Instruct and the medical models, agreement stays better, in line with Savage et al. (2025). AUROCs are on each model's own answers and compare signals within a model.

Which signal to trust. Across 56 model–setting combinations (the models above at both temperatures and three prompts, our GRPO runs and a full-distribution prompt; they share weights, so we treat the correlations as descriptive), the stated probability's advantage over five-sample agreement tracks the share of cases whose five samples all agree (Spearman 0.75) and the stated probability's own AUROC (0.82). Always using agreement is right for 54% of the 39 post-trained combinations and loses 0.032 AUROC on average. Choosing the signal with the higher AUROC on 100 labeled cases with five samples each, and evaluating on the other 880, picks the better signal in 82% of draws and loses 0.007. It is reliable when the signals differ by more than 0.05 AUROC (96%) and close to a coin flip below 0.02 (53%), where the choice matters least. Its cost is gold labels for 100 cases from the target population (Appendix D.3).

Ambiguity. For every model and signal, the Spearman correlation between uncertainty and the entropy of the case's reference differential lies between −0.11 and +0.16, except AlphaMed's stated probability (+0.30): by either readout, a model's uncertainty says almost nothing about how ambiguous a case is.

4.4. Real rare-disease cases and medical post-training

Real rare-disease cases. Phenopacket Store has no reference differential and accuracy is near the floor, so here we count an answer as correct if it is the diagnosis or a closely related Mondo class (36–130 correct single-call answers per model; Appendix E.3). The DDXPlus shifts reappear, without a crossover. Majority voting over 32 samples helps the base models by 3.1–4.6 points but the final post-trained models by only 0.4–1.5 (Qwen3-8B +0.4, n.s.). Post-training weakens agreement as an error signal (Qwen3-8B 0.830 → 0.763, Qwen2.5-7B 0.845 → 0.745, OLMo 3 7B 0.814 → 0.726) and strengthens the stated probability (0.567 → 0.707, 0.598 → 0.717, 0.464 → 0.652): agreement beats the stated probability by 0.25–0.35 AUROC for the base models but by only 0.03–0.08 for the post-trained ones, significantly only for Qwen3-8B. On these open-ended cases the three most frequent of 32 sampled answers still contain a correct diagnosis more often than one list's top three, but the gap shrinks from 4.6–7.0 points for the base models to 2.7–3.6 for Qwen2.5-7B-Instruct and OLMo-3-7B-Instruct and to a tie for Qwen3-8B (+0.4, n.s.).

Medical models. Medical post-training on Qwen2.5-7B-Instruct adds DDXPlus accuracy without narrowing the samples further: AlphaMed (rule-based RL) improves on its parent at every k (+3.9 at k=1, +8.4 at k=32) with unchanged sampled diversity (1.87 vs. 1.82 distinct answers), and HuatuoGPT-o1 and m1, both trained on reasoning traces, widen the sampled differential (2.49 and 3.29). AlphaMed's checkpoint trained from the base model keeps most of the base model's diversity (3.14 distinct answers; Appendix E.1). On Phenopacket Store every model is near the floor (pass@32 2.5–7.0%), but stated confidence is not: medical RL raises it from 0.51 for the parent to 0.67–0.69 (0.71 for AlphaMed's base-initialized checkpoint) while accuracy gains stay under 1.5 points, and every OLMo 3 7B stage states 0.73–0.84 at about 1% accuracy. At this accuracy, ECE mostly restates confidence, so we read this as confidence rising without accuracy (Appendix E.2).

5. Discussion and limitations

Jang et al. (2026) show that instruction-tuned models cannot sample from distributions they can describe. We find the same in diagnosis, where the reference is a clinical differential with a correct answer, across two families at 7–32B: post-training improves the list the model states while collapsing the answers it samples, and drawing from the stated list recovers the lost coverage. Evaluations that read the differential from samples (pass@k at large k, sample diversity, self-consistency, agreement-based uncertainty) therefore report a loss that a clinician reading one answer would not see, and lose value as tools on post-trained models. The stated list is not a free replacement: it beats agreement as an error signal for only two of five final post-trained models, every model stays far from the reference differential, and neither readout tracks how ambiguous a case is; for a given model, 100 labeled cases tell which signal to use. Which post-training stage narrows the samples most is a property of the recipe, not of SFT, DPO or RL as such. Sampled diversity still matters for training, since GRPO learns nothing from a group whose samples agree; Appendix F shows that GRPO from Qwen3-8B-Base on DDXPlus nearly matches the official model's top-1 accuracy while keeping more than twice its sampled diversity.

Limitations. DDXPlus is synthetic and closed-set: its reference differential is the posterior of a rule-based engine, its test set is class-balanced (20 cases per condition), and the prompt lists all 49 conditions, so TV and coverage are distances to a *reference* posterior, not to clinical truth, and accuracies do not reflect real prevalence. Base models often give invalid answers (27–47% for OLMo), which we count as wrong; this makes large-k losses conservative but inflates small-k gains, and for OLMo no case has 32 valid base samples. The stated readout renormalizes each list over the conditions it names; a full-distribution prompt gives the same picture for Qwen but not for OLMo 3 7B's five-item lists. The audit is validated only within DDXPlus. We study open 7–32B models from two families, one RL-Zero checkpoint (7B, trained with an LM-judge reward on chat prompts), and the 32B models only at T=0.7. Phenopacket accuracy is near the floor, its grader is rule-based and not validated against clinicians, and its cases may be in pretraining data. We do not evaluate clinical utility with clinicians.

Statement on AI Use. An AI assistant (Claude, Anthropic) was used to write and run analysis code, to draft and edit text, and to check citations. The authors designed the study, reviewed all code, results and text, and take responsibility for the content.

References

Junying Chen, Zhenyang Cai, Ke Ji, Xidong Wang, Wanlong Liu, Rongsheng Wang, and Benyou Wang. Towards medical complex reasoning with LLMs through medical verifiable problems. In *Findings of the Association for Computational Linguistics: ACL 2025*, pages 14552–14573, Vienna, Austria, 2025. Association for Computational Linguistics. doi: 10.18653/v1/2025.findings-acl.751. arXiv version titled "HuatuoGPT-o1, Towards Medical Complex Reasoning with LLMs".

Mark Chen, Jerry Tworek, Heewoo Jun, Qiming Yuan, Henrique Ponde de Oliveira Pinto, Jared Kaplan, Harri Edwards, Yuri Burda, Nicholas Joseph, Greg Brockman, Alex Ray, Raul Puri, Gretchen Krueger, Michael Petrov, Heidy Khlaaf, Girish Sastry, Pamela Mishkin, Brooke Chan, Scott Gray, Nick Ryder, Mikhail Pavlov, Alethea Power, Lukasz Kaiser, Mohammad Bavarian, Clemens Winter, Philippe Tillet, Felipe Petroski Such, Dave Cummings, Matthias Plappert, Fotios Chantzis, Elizabeth Barnes, Ariel Herbert-Voss, William Hebgen Guss, Alex Nichol, Alex Paino, Nikolas Tezak, Jie Tang, Igor Babuschkin, Suchir Balaji, Shantanu Jain, William Saunders, Christopher Hesse, Andrew N. Carr, Jan Leike, Josh Achiam, Vedant Misra, Evan Morikawa, Alec Radford, Matthew Knight, Miles Brundage, Mira Murati, Katie Mayer, Peter Welinder, Bob McGrew, Dario Amodei, Sam McCandlish, Ilya Sutskever, and Wojciech Zaremba. Evaluating large language models trained on code. 2021.

Zhoujun Cheng, Shibo Hao, Tianyang Liu, Fan Zhou, Yutao Xie, Feng Yao, Yuexin Bian, Yonghao Zhuang, Nilabjo Dey, Yuheng Zha, Yi Gu, Kun Zhou, Yuqi Wang, Yuan Li, Richard Fan, Jianshu She, Chengqian Gao, Abulhair Saparov, Haonan Li, Taylor W. Killian, Mikhail Yurochkin, Zhengzhong Liu, Eric P. Xing, and Zhiting Hu. Revisiting reinforcement learning for LLM reasoning from a cross-domain perspective. In *Advances in Neural Information Processing Systems (NeurIPS 2025), Datasets and Benchmarks Track*, 2025.

Mehul Damani, Isha Puri, Stewart Slocum, Idan Shenfeld, Leshem Choshen, Yoon Kim, and Jacob Andreas. Beyond binary rewards: Training LMs to reason about their uncertainty. In *International Conference on Learning Representations (ICLR)*, 2026.

Daniel Danis, Michael J. Bamshad, Yasemin Bridges, Andrés Caballero-Oteyza, Pilar Cacheiro, Leigh C. Carmody, Leonardo Chimirri, Jessica X. Chong, Ben Coleman, Raymond Dalgleish, Peter J. Freeman, Adam S. L. Graefe, Tudor Groza, Peter Hansen, Julius O. B. Jacobsen, Adam Klocperk, Maaike Kusters, Markus S. Ladewig, Allison J. Marcello, Teresa Mattina, Christopher J. Mungall, Monica C. Munoz-Torres, Justin T. Reese, Filip Rehburg, Bárbara C. S. Reis, Catharina Schuetz, Damian Smedley, Timmy Strauss, Jagadish Chandrabose Sundaramurthi, Sylvia Thun, Kyran Wissink, John F. Wagstaff, David Zocche, Melissa A. Haendel, and Peter N. Robinson. A corpus of GA4GH phenopackets: Case-level phenotyping for genomic diagnostics and discovery. *Human Genetics and Genomics Advances*, 6(1):100371, 2025. doi: 10.1016/j.xhgg.2024.100371.

Arsene Fansi Tchango, Rishab Goel, Julien Martel, Zhi Wen, Gaetan Marceau Caron, and Joumana Ghosn. Towards trustworthy automatic diagnosis systems by emulating doctors' reasoning with deep reinforcement learning. In *Advances in Neural Information Processing Systems (NeurIPS 2022)*, volume 35, 2022a.

Arsene Fansi Tchango, Rishab Goel, Zhi Wen, Julien Martel, and Joumana Ghosn. DDXPlus: A new dataset for automatic medical diagnosis. In *Advances in Neural Information Processing Systems (NeurIPS 2022), Datasets and Benchmarks Track*, 2022b.

Sebastian Farquhar, Jannik Kossen, Lorenz Kuhn, and Yarin Gal. Detecting hallucinations in large language models using semantic entropy. *Nature*, 630(8017):625–630, 2024.

Xiaoke Huang, Juncheng Wu, Hui Liu, Xianfeng Tang, and Yuyin Zhou. m1: Unleash the potential of test-time scaling for medical reasoning with large language models. In *Proceedings of the Fifth Machine Learning for Health Symposium (ML4H 2025)*, volume 297 of *Proceedings of Machine Learning Research*, pages 369–383. PMLR, 2026.

Chaemin Jang, Dongman Lee, and Jihee Kim. Instruction-tuned language models cannot sample from distributions they can describe. In *Findings of the Association for Computational Linguistics: EMNLP 2026*, 2026.

Ahmadreza Jeddi, Kimia Shaban, Negin Baghbanzadeh, Natasha Sharan, Abhishek Moturu, Elham Dolatabadi, and Babak Taati. When does RL help medical VLMs? disentangling vision, SFT, and RL gains. 2026.

Liwei Jiang, Yuanjun Chai, Margaret Li, Mickel Liu, Raymond Fok, Nouha Dziri, Yulia Tsvetkov, Maarten Sap, Alon Albalak, and Yejin Choi. Artificial hivemind: The open-ended homogeneity of language models (and beyond). In *Advances in Neural Information Processing Systems (NeurIPS 2025), Datasets and Benchmarks Track*, 2025.

Zahir Kanjee, Byron Crowe, and Adam Rodman. Accuracy of a generative artificial intelligence model in a complex diagnostic challenge. *JAMA*, 330(1):78, 2023. doi: 10.1001/jama.2023.8288.

Robert Kirk, Ishita Mediratta, Christoforos Nalmpantis, Jelena Luketina, Eric Hambro, Edward Grefenstette, and Roberta Raileanu. Understanding the effects of RLHF on LLM generalisation and diversity. In *International Conference on Learning Representations (ICLR)*, 2024.

Jixuan Leng, Chengsong Huang, Banghua Zhu, and Jiaxin Huang. Taming overconfidence in LLMs: Reward calibration in RLHF. In *International Conference on Learning Representations (ICLR)*, 2025.

Seungseop Lim, Gibaeg Kim, Hyunkyung Lee, Wooseok Han, Jean Seo, Jaehyo Yoo, and Eunho Yang. H-DDx: A hierarchical evaluation framework for differential diagnosis. 2025. NeurIPS 2025 Workshop on Generative AI for Health (GenAI4Health).

Che Liu, Haozhe Wang, Jiazhen Pan, Zhongwei Wan, Yong Dai, Fangzhen Lin, Wenjia Bai, Daniel Rueckert, and Rossella Arcucci. Beyond distillation: Pushing the limits of medical LLM reasoning with minimalist rule-based RL. 2025. Introduces the AlphaMed model; NeurIPS 2025 Workshop on Generative AI for Health (GenAI4Health).

Mingyi Liu. The alignment tax: Response homogenization in aligned LLMs and its implications for uncertainty estimation, 2026.

Daniel McDuff, Mike Schaekermann, Tao Tu, Anil Palepu, Amy Wang, Jake Garrison, Karan Singhal, Yash Sharma, Shekoofeh Azizi, Kavita Kulkarni, et al. Towards accurate differential diagnosis with large language models. *Nature*, 642(8067):451–457, 2025. doi: 10.1038/s41586-025-08869-4.

Zhiting Mei, Christina Zhang, Tenny Yin, Justin Lidard, Ola Shorinwa, and Anirudha Majumdar. Reasoning about uncertainty: Do reasoning models know when they don't know? In *Findings of the Association for Computational Linguistics: EACL 2026*, pages 3408–3458, Rabat, Morocco, 2026. Association for Computational Linguistics. doi: 10.18653/v1/2026.findings-eacl.178.

Nicole Meister, Carlos Guestrin, and Tatsunori Hashimoto. Benchmarking distributional alignment of large language models. In *Proceedings of the 2025 Conference of the Nations of the Americas Chapter of the Association for Computational Linguistics: Human Language Technologies (Volume 1: Long Papers)*, pages 24–49, Albuquerque, New Mexico, 2025. Association for Computational Linguistics. doi: 10.18653/v1/2025.naacl-long.2.

Sonia Krishna Murthy, Tomer Ullman, and Jennifer Hu. One fish, two fish, but not the whole sea: Alignment reduces language models' conceptual diversity. In *Proceedings of the 2025 Conference of the Nations of the Americas Chapter of the Association for Computational Linguistics: Human Language Technologies (Volume 1: Long Papers)*, pages 11241–11258, 2025. doi: 10.18653/v1/2025.naacl-long.561.

Changdae Oh, Qi Zeng, Qi Qi, Andrey Zhmoginov, Deren Lei, Yun He, Hoang Phan, Hangoo Kang, Azalia Mirhoseini, and Sharon Li. Sharpening tax in post-training. 2026.

Isha Puri, Mehul Damani, Idan Shenfeld, Marzyeh Ghassemi, Jacob Andreas, and Yoon Kim. Escaping the mode: Multi-answer reinforcement learning in LMs. In *Proceedings of the 43rd International Conference on Machine Learning (ICML)*, volume 306 of *Proceedings of Machine Learning Research*, pages 100127–100146. PMLR, 2026. arXiv version titled "Reaching Beyond the Mode: RL for Distributional Reasoning in Language Models".

Daniel Philip Rose, Chia-Chien Hung, Marco Lepri, Israa Alqassem, Kiril Gashteovski, and Carolin Lawrence. MEDDxAgent: A unified modular agent framework for explainable automatic differential diagnosis. In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 13803–13826, 2025. doi: 10.18653/v1/2025.acl-long.677.

Thomas Savage, John Wang, Robert Gallo, Abdessalem Boukil, Vishwesh Patel, Seyed Amir Ahmad Safavi-Naini, Ali Soroush, and Jonathan H. Chen. Large language model uncertainty proxies: discrimination and calibration for medical diagnosis and treatment. *Journal of the American Medical Informatics Association*, 32(1):139–149, 2025. doi: 10.1093/jamia/ocae254.

Jacob Mitchell Springer, Madhu Advani, Lukas Aichberger, Arwen Bradley, Eran Malach, Omid Saremi, Sinead Williamson, Preetum Nakkiran, Etai Littwin, and Aditi Raghunathan. Annotations mitigate post-training mode collapse. In *Proceedings of the 43rd International Conference on Machine Learning (ICML)*, 2026.

Team Olmo, Allyson Ettinger, Amanda Bertsch, Bailey Kuehl, David Graham, David Heineman, Dirk Groeneveld, Faeze Brahman, Finbarr Timbers, Hamish Ivison, et al. Olmo 3, 2025.

Katherine Tian, Eric Mitchell, Allan Zhou, Archit Sharma, Rafael Rafailov, Huaxiu Yao, Chelsea Finn, and Christopher D. Manning. Just ask for calibration: Strategies for eliciting calibrated confidence scores from language models fine-tuned with human feedback. In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, 2023.

Xuezhi Wang, Jason Wei, Dale Schuurmans, Quoc Le, Ed Chi, Sharan Narang, Aakanksha Chowdhery, and Denny Zhou. Self-consistency improves chain of thought reasoning in language models. In *International Conference on Learning Representations (ICLR)*, 2023.

Peter West and Christopher Potts. Base models beat aligned models at randomness and creativity. In *Conference on Language Modeling (COLM)*, 2025.

Fang Wu, Weihao Xuan, Danny Xing, Ximing Lu, Mingjie Liu, Yi Dong, Zaid Harchaoui, and Yejin Choi. The invisible leash: Why RLVR may or may not escape its origin. 2025.

Miao Xiong, Zhiyuan Hu, Xinyang Lu, Yifei Li, Jie Fu, Junxian He, and Bryan Hooi. Can LLMs express their uncertainty? an empirical evaluation of confidence elicitation in LLMs. In *International Conference on Learning Representations (ICLR)*, 2024.

Yang Yue, Zhiqi Chen, Rui Lu, Andrew Zhao, Zhaokai Wang, Yang Yue, Shiji Song, and Gao Huang. Does reinforcement learning really incentivize reasoning capacity in LLMs beyond the base model? In *Advances in Neural Information Processing Systems (NeurIPS 2025)*, 2025.

Jiayi Zhang, Simon Yu, Derek Chong, Anthony Sicilia, Michael R. Tomz, Christopher D. Manning, and Weiyan Shi. Verbalized sampling: How to mitigate mode collapse and unlock LLM diversity. In *Proceedings of the 43rd International Conference on Machine Learning (ICML)*, volume 306 of *Proceedings of Machine Learning Research*, pages 160073–160152. PMLR, 2026.

Appendix A. Prompts, vignettes and grading

DDXPlus. Each patient's coded evidence is rendered by a fixed template into a vignette of the patient's answers and relevant history; we fix known mistranslations in the English evidence descriptions. An example (test case with true pathology chronic rhinosinusitis; the reference differential gives viral pharyngitis 0.17, chronic rhinosinusitis 0.16, cluster headache 0.15, acute rhinosinusitis 0.14, bronchitis 0.14, URTI 0.12):

> `A 13-year-old female presents for evaluation. Symptoms (patient answers): Do you have pain somewhere, related to your reason for consulting? Yes. Characterize your pain: burning. Do you feel pain somewhere? mouth, forehead, cheek(R), cheek(L), nose. How intense is the pain? (scale 0-10) 3. […] Have you lost your sense of smell? Yes. Do you have nasal congestion or a clear runny nose? Yes. Do you have a cough? Yes. Relevant history and risk factors: Have you had a cold in the last 2 weeks? Yes. […] Do you have polyps in your nose? Yes. […]`

System prompt: `You are an experienced emergency and primary care physician.` The user turn is the vignette followed by: `Based on the patient's answers above, give your differential diagnosis. Choose ONLY from this list of possible conditions: [the 49 conditions, one per line]. List the 5 most likely conditions from the list, most likely first, with your probability that each is the correct diagnosis. Use the condition names exactly as written in the list. End your answer with a JSON array in exactly this format: [{"diagnosis": "<name>", "probability": <number between 0 and 1>}, ...].` The full-distribution prompt (§D.1) instead asks for a probability on every condition, summing to one, most likely first. The plain and CoT variants are described in §C.3. Base models receive the same chat-formatted prompt; OLMo base models use their SFT checkpoint's chat template.

Phenopacket Store. The vignette lists the case's present and (up to ten) excluded HPO phenotypes with sex and age. System prompt: `You are an expert clinical geneticist and diagnostician.` Instructions: `List the 5 most likely specific diagnoses (use the specific disease or subtype name, e.g. 'Spastic paraplegia 7' rather than 'hereditary spastic paraplegia', when you can), most likely first, with your probability that each is the correct diagnosis`, followed by the same JSON format.

Grading open-ended names. Each predicted name is mapped to Mondo by exact lookup against Mondo labels and synonyms (also trying any parenthesized abbreviation and the name without it), then by fuzzy matching (token-sort ratio ≥ 92). It is *exact* if it maps to the Mondo class of the case's OMIM diagnosis, and *related* if it maps to a specific ancestor group of it (at most two is-a steps up, with at most 150 descendants) or to one of its subtypes; siblings sharing only a broad parent are wrong. The grader passes hand-written checks (e.g. "Hereditary spastic paraplegia type 7 (SPG7)" is exact for SPG7, "Hereditary spastic paraplegia" is related, and Turner syndrome is wrong for Jacobsen syndrome), but we did not validate it against clinician grading, so errors at the scale of the 1–2 point effects we report on this dataset are possible.

Appendix B. Models

Model	Parent	Post-training	Role
Qwen2.5-7B	n/a	none (pretrained)	base
Qwen2.5-7B-Instruct	Qwen2.5-7B	general SFT + RLHF	instruct; medical parent
AlphaMed-7B (Liu et al., 2025)	Qwen2.5-7B-Instruct	rule-based RL	medical
HuatuoGPT-o1-7B (Chen et al., 2025)	Qwen2.5-7B-Instruct	SFT + PPO (verifier)	medical
m1-7B-23K (Huang et al., 2026)	Qwen2.5-7B-Instruct	SFT distillation	medical
Qwen3-8B-Base	n/a	none (pretrained)	base
Qwen3-8B	Qwen3-8B-Base	general post-training	instruct
Qwen2.5-32B	n/a	none (pretrained)	base
Qwen2.5-32B-Instruct	Qwen2.5-32B	general SFT + RLHF	instruct
OLMo-3-1025-7B (Team Olmo et al., 2025)	n/a	none (pretrained)	base
OLMo-3-7B-Instruct-SFT	OLMo-3-1025-7B	SFT	stage 1
OLMo-3-7B-Instruct-DPO	OLMo-3 SFT	DPO	stage 2
OLMo-3-7B-Instruct	OLMo-3 DPO	RLVR	stage 3 (instruct)
OLMo-3-7B-RL-Zero-General	OLMo-3-1025-7B	RL (LM judge)	RL from base
OLMo-3-1125-32B	n/a	none (pretrained)	base
OLMo-3.1-32B-Instruct-SFT	OLMo-3-1125-32B	SFT	stage 1
OLMo-3.1-32B-Instruct-DPO	OLMo-3.1 SFT	DPO	stage 2
OLMo-3.1-32B-Instruct	OLMo-3.1 DPO	RLVR	stage 3 (instruct)

Table 4: Models studied. Each pair or family shares its pretrained weights, so differences reflect post-training. OLMo 3 and OLMo 3.1 release every stage of their instruct pipelines.

Appendix C. The sampled differential in detail

C.1. General post-training trades coverage for top-1 accuracy

Table 5 and Figure 2 compare each base model with its post-trained counterpart on DDXPlus. In both families the post-trained model is much better on its first answer: +27.5 points for Qwen3 and +22.5 for Qwen2.5 at T=1 (intervals $[+25.3, +29.6]$ and $[+20.7, +24.4]$). The advantage shrinks with k and reverses: the curves cross at k≈4–8, and at k=32 the base model leads by 14.6 points (Qwen3, $[+12.2, +17.1]$) and 10.3 points (Qwen2.5, $[+7.8, +12.8]$). The pattern is the same at T=0.7 for Qwen3, crossing at k=4 with a base lead of 12.2 points at k=32 ($[+9.9, +14.9]$). Unparsable base-model samples count as wrong,

Pair	Model	pass@1	pass@32	Distinct	Entropy	TV↓	Cov@32	ECE↓
Qwen3-8B, T=1	base	0.282	**0.789**	**6.60**	**1.31**	**0.712**	**0.407**	0.214
	post-trained	**0.556**	0.643	1.53	0.18	0.783	0.236	**0.061**
Qwen2.5-7B, T=1	base	0.239	**0.766**	**8.23**	**1.58**	**0.715**	**0.422**	0.303
	instruct	**0.464**	0.663	2.65	0.49	0.761	0.290	**0.137**
Qwen3-8B, T=0.7	base	0.388	**0.730**	**3.76**	**0.78**	**0.750**	**0.322**	0.121
	post-trained	**0.558**	0.607	1.27	0.11	0.793	0.217	**0.063**

Table 5: DDXPlus, 32 samples per case (980 cases). The reference differential has mean entropy 1.87. Distinct and entropy refer to the top-1 answers across samples; Cov@32 is the share of reference probability mass covered by those answers. ECE is for the stated top-1 probability.




Figure 2: pass@k on DDXPlus at T=1 (980 cases, 32 samples), base model (dashed) vs. its post-trained version (solid), with 95% case-bootstrap bands. "Gold": the top-1 answer is the true pathology; "gold or in ref. ddx": it is the true pathology or appears in the reference differential. In both families the post-trained model wins at small k and loses at large k.

so these gaps are lower bounds. Qwen2.5 at T=0.7 behaves the same way: +12.6 points at k=1 [+10.7, +14.5] and a base lead of 9.7 at k=32 [+7.3, +12.0].

C.2. The sampled differential collapses, while top-1 calibration improves

The gap at large k reflects a collapsed *sampled* differential. Across 32 samples, the post-trained Qwen models name 1.3–2.6 distinct diagnoses per case, against 3.8–8.3 for their base models. Their answer entropy is 0.11–0.49, against 0.78–1.58 for base models and 1.87 for the reference differential (Table 5). Sampling at T=1 widens the base models' answers but barely changes the post-trained models' (Qwen3 entropy 0.11 at T=0.7, 0.18 at T=1), so the collapse lives in the model's own distribution rather than in the decoding settings. As a result, post-trained models cover less of the reference differential: 0.24 vs. 0.41 of its probability mass at k=32 for Qwen3, and 0.29 vs. 0.42 for Qwen2.5. Their top-1 calibration, however, is markedly better (ECE 0.06 vs. 0.21 and 0.14 vs. 0.30). On every single-answer criterion (accuracy, small-k pass@k, calibration), the post-trained model therefore looks

strictly better, and the loss of breadth in its samples is invisible. Whether the breadth is lost from the model's stated differential as well is a separate question (§4.2).

Which diagnoses drop out? For each case and each condition that the reference differential weights at least 0.1, we ask whether the model names that condition as its top answer in at least one of its 32 samples. We call this *considering* the condition. We group the 49 conditions by DDXPlus severity (1 = most severe). Post-training lowers consideration in every tier (Table 6), and the severe tier (DDXPlus severity 1–2, the dataset's label rather than a clinical consensus list) is not spared. This metric needs a chance reference, though: a guesser that picks uniformly among the 49 conditions scores about 0.48 on it, and one that draws from the average reference differential 0.56–0.61, above every model, base models included. Considered@32 therefore measures the breadth of the sampled answers, not clinical judgement; we assess can't-miss conditions on the stated list instead (§D.2). For the 17 severity-1–2 conditions (e.g. NSTEMI/STEMI, acute pulmonary edema, anaphylaxis, pulmonary embolism, unstable angina), consideration falls from 0.45 to 0.27 for Qwen3 and from 0.51 to 0.34 for Qwen2.5 at T=1. The differences are -18.4 $[-20.8, -15.9]$ and -17.0 $[-19.7, -14.2]$ points. Some diagnoses disappear from the top answer almost entirely. Qwen2.5-7B-Instruct names unstable angina as its top answer in one of 107 eligible cases, where its base model does in 47%. When unstable angina is the true pathology, pass@32 falls from 1.00 to 0.00. Stable angina (0.89 to 0.06) and myocarditis (0.41 to 0.00) follow the same pattern. These conditions are not forgotten: they still appear lower in the listed differential (unstable angina in 50% of eligible cases, against 95% for the base model). The model ranks them but no longer commits to them. At the same time, post-trained models concentrate on a few salient "attractor" diagnoses. Qwen2.5-7B-Instruct gives NSTEMI/STEMI as its top answer in 13.1% of samples, against a reference rate of 4.4% and 6.4% for its base model. It also over-predicts pulmonary embolism (8.2% vs. 3.2%) and pneumonia (8.0% vs. 2.4%). Chest-pain presentations thus collapse onto the most dangerous candidate. That raises its accuracy (NSTEMI pass@1 0.99 vs. 0.44) at the cost of the alternatives, which is a defensible triage bias but not a differential.

C.3. Robustness to prompt and output format

Prompt. We repeat the Qwen3-8B pair with two other prompts (Table 7). *Plain* drops the system prompt and rewords the instructions. *CoT* asks the model to reason step by step before answering; Qwen3's thinking mode stays off in all runs. The plain prompt reproduces the pattern: the post-trained model gains $+23.0$ $[+20.9, +25.1]$ points at k=1 and loses -7.1 $[-9.3, -5.0]$ at k=32 (T=0.7; at T=1, $+34.2$ and -8.7 $[-11.0, -6.4]$), with 1.3–1.5 distinct answers against 3.7–5.6. Asking for reasoning changes the picture. With CoT, the post-trained model's pass@32 rises from 0.607 to 0.835: it leads the base model at every k at T=0.7 ($+4.7$ $[+2.9, +6.6]$ at k=32) and ties it at T=1 (0.0 $[-2.1, +1.9]$). Its samples remain far less diverse than the base model's (2.1–2.2 vs. 3.9–6.3 distinct answers), so reasoning recovers coverage at k=32 without restoring sampling diversity. The coverage loss is therefore largest when the model answers directly, as in most clinical decision-support deployments, and reasoning at inference time mitigates it. This matches the medical models: the reasoning-trained descendants widen the differential (§E.1).

Comparison	Considered@32 (base → post-trained) Severe (1–2)	Moderate (3)	Mild (4–5)
Qwen3-8B, T=1	0.45 → 0.27	0.50 → 0.32	0.45 → 0.20
	−18.4 [−20.8, −15.9]	−18.1 [−20.7, −15.7]	−24.2 [−27.0, −21.4]
Qwen2.5-7B, T=1	0.51 → 0.34	0.50 → 0.37	0.38 → 0.23
	−17.0 [−19.7, −14.2]	−12.1 [−14.7, −9.7]	−15.0 [−17.4, −12.6]
Qwen3-8B, T=0.7	0.34 → 0.24	0.44 → 0.29	0.31 → 0.18
	−9.8 [−11.8, −7.9]	−15.8 [−18.2, −13.5]	−13.4 [−15.8, −11.1]
Qwen2.5-7B, T=0.7	0.40 → 0.28	0.41 → 0.32	0.28 → 0.17
	−12.4 [−14.7, −10.2]	−9.1 [−11.2, −6.7]	−10.3 [−12.3, −8.3]
Instruct → AlphaMed, T=0.7	0.28 → 0.32	0.32 → 0.34	0.17 → 0.21
	+4.3 [+2.0, +6.6]	+2.2 [+0.4, +4.0]	+3.9 [+2.4, +5.4]
Instruct → HuatuoGPT-o1, T=0.7	0.28 → 0.36	0.32 → 0.37	0.17 → 0.27
	+8.4 [+6.1, +10.8]	+6.0 [+4.0, +7.9]	+9.5 [+7.5, +11.5]
Instruct → m1, T=0.7	0.28 → 0.41	0.32 → 0.41	0.17 → 0.29
	+13.5 [+10.8, +16.2]	+9.7 [+7.2, +12.2]	+11.4 [+9.2, +13.6]
Base → AlphaMed (base-RL), T=0.7	0.40 → 0.39	0.41 → 0.40	0.28 → 0.27
	−0.7 [−3.0, +1.7]	−0.4 [−2.6, +1.7]	−0.4 [−2.4, +1.7]
Base → `acc` GRPO (8B), T=0.7	0.34 → 0.31	0.44 → 0.42	0.31 → 0.27
	−2.8 [−4.4, −1.3]	−2.1 [−3.7, −0.6]	−4.3 [−6.2, −2.5]
Base → `gm` GRPO (8B), T=0.7	0.34 → 0.32	0.44 → 0.43	0.31 → 0.28
	−1.5 [−3.2, +0.1]	−1.3 [−3.0, +0.3]	−3.0 [−4.8, −1.2]

Table 6: Share of (case, condition) pairs with reference probability ≥ 0.1 in which the condition is a top-1 answer in at least one of 32 samples, by DDXPlus severity. Second rows give differences in points with 95% case-bootstrap intervals. All rows use the 980 test cases; GRPO rows are seed 0. General post-training lowers consideration in every tier, including the can't-miss tier; medical post-training raises it; our GRPO from the base model loses at most 4 points, and with the group reward the severe-tier loss is not significant.

Output format. Base models more often give invalid answers: unparsable, or with a top answer outside the 49 conditions. This affects 12% of Qwen3-8B-Base samples at T=0.7 and 25% at T=1 (Qwen2.5-7B: 1% and 21%), against at most 0.3% for the post-trained models. Invalid samples count as wrong, which deflates the base model at large k but inflates the post-trained model's gain at small k. Among valid samples only, the post-trained models still gain +12.0 [+9.8, +14.1] (Qwen3, T=0.7), +18.7 [+16.6, +20.7] (Qwen3, T=1), +12.2 [+10.4, +14.0] and +16.8 [+15.0, +18.5] points (Qwen2.5) at k=1, so a quarter to a third of the raw gain at T=1 is format. On the cases where every sample of both models is valid, the large-k loss persists: −15.2 [−21.9, −8.6] at k=32 for Qwen3 (105 cases) and −10.2 [−12.7, −7.6] for Qwen2.5 (748 cases), both at T=0.7. (At T=1 almost no case has 32 valid base samples.) The reported large-k losses are thus lower bounds.

C.4. Which post-training stage narrows the differential?

The Qwen pairs compare a base model with the end of a post-training pipeline. OLMo 3 (Team Olmo et al., 2025) releases every stage of its 7B instruct pipeline from




Figure 3: Change in Considered@32 per condition, Qwen2.5-7B-Instruct minus its base model (T=1, 980 cases), colored by DDXPlus severity (dark red = most severe). Conditions with fewer than five cases giving them reference probability ≥ 0.1 are omitted. Angina, acute pulmonary edema, anaphylaxis and myocarditis are among the largest drops.

one base model: supervised fine-tuning, then DPO, then RL with verifiable rewards on math, code, instruction-following and chat prompts (the released OLMo-3-7B-Instruct). It also releases RL-Zero checkpoints trained with RL directly from the base; we use the general one, trained on chat prompts with an LM-judge reward. (The RL-Zero-Mix checkpoint does not load in our vLLM version.) Table 8 gives the results.

The coverage loss replicates in this third family. At T=0.7, every post-trained stage is worse than the base at k=32: by -14.6 $[-17.5, -11.7]$ points after SFT, -9.2 $[-12.1, -6.1]$ after DPO, -28.3 $[-31.5, -25.0]$ after RLVR, and -13.3 $[-16.1, -10.5]$ for RL-Zero. Diversity falls at every stage of the pipeline, from 4.93 distinct answers for the base to 4.01 after SFT, 3.30 after DPO and 2.37 after RLVR.

Compared stage to stage, DPO recovers part of what SFT lost at large k ($+5.4$ $[+2.9, +8.0]$ points at k=32, and $+10.3$ $[+9.0, +11.6]$ at k=1) while narrowing the differential further (-0.71 distinct answers). The final RLVR stage is the largest single narrowing. Against the DPO model it loses -19.1 $[-21.8, -16.3]$ points at k=32, 0.92 distinct answers and 7.7 points of coverage@32, and it is also worse at k=1 (-5.9 $[-7.2, -4.6]$). It drops severe-tier Considered@32 to 0.25, a loss of -16.1 $[-18.6, -13.5]$ points relative to the base,

		pass@1		pass@32		Distinct	
Prompt	T	Base	Post	Base	Post	Base	Post
default	0.7	0.388	**0.558**	**0.730**	0.607	3.76	1.27
default	1.0	0.282	**0.556**	**0.789**	0.643	6.60	1.53
plain	0.7	0.352	**0.583**	**0.727**	0.655	3.72	1.28
plain	1.0	0.244	**0.586**	**0.792**	0.705	5.57	1.54
CoT	0.7	0.409	**0.652**	0.788	**0.835**	3.89	2.08
CoT	1.0	0.275	**0.642**	0.837	0.837	6.31	2.24

Table 7: Qwen3-8B-Base vs. Qwen3-8B on DDXPlus (980 cases, 32 samples) under three prompts. Bold marks the significantly better model (paired case bootstrap). Without reasoning, the base model wins at k=32; with CoT, the post-trained model matches or beats it, but its samples stay far less diverse.

against -7.4 for the DPO model. At T=1 the pattern is the same (RLVR vs. DPO: -12.7 $[-15.4, -9.9]$ at k=32).

RL applied directly to the base narrows the differential less. At T=1, RL-Zero shows no detectable loss of the base model's pass@32 (-1.8 $[-4.5, +0.8]$, so at most 4.5 points) and 6.28 of its 7.53 distinct answers, and it loses 4.0 $[1.2, 6.9]$ points of severe-tier consideration, against 14.4 for the full instruct pipeline. At T=0.7 it still loses 13.3 points at k=32, about as much as SFT.

The OLMo base model often breaks the output format: 40% of its samples are invalid at T=0.7 and 47% at T=1, while unparsable completions are 16–21% for the SFT model and at most 1.6% for the later stages. No case has 32 valid base samples, so the all-valid check of §C.3 is not possible here. Among valid samples, the post-trained models' gains at k=1 are small (-1.9 to $+4.0$ points at T=0.7, $+1.3$ to $+8.1$ at T=1), so most of OLMo's raw gain at k=1 is format. Invalid samples count as misses and are excluded from distinct answers and entropy, so the base model's coverage and diversity are understated and the losses above are conservative.

Across three families, then, the collapse of the sampled differential is not a necessary effect of RL. It accumulates over the instruction-tuning pipeline; in OLMo 3 7B its largest step is RL applied on top of SFT and DPO, but at 32B it is SFT (§C.5), so which stage narrows most depends on the recipe. RL applied directly to a base model (OLMo RL-Zero, AlphaMed's base-initialized checkpoint, and our GRPO runs in §F) narrows the differential less. On Phenopacket Store the instruct pipeline also loses coverage: every stage trails the base model at k=32 (-2.0 $[-3.0, -1.1]$ points after SFT, -1.5 after DPO, -1.4 after RLVR; all significant), while RL-Zero does not (-0.6 $[-1.4, +0.2]$), from a base model at 4.5% (§E.2).

C.5. Replication at 32B

We repeat the DDXPlus comparisons at T=0.7 with Qwen2.5-32B and its Instruct model, and with every released stage of OLMo 3.1 32B, whose base is OLMo-3-1125-32B; there is no 32B RL-Zero checkpoint (Table 9). The sampled differential collapses at 32B too, by

T	Stage	pass@1	pass@32	Distinct	Entropy	Cov@32	Severe C@32
0.7	Base	0.178	**0.705**	**4.93**	**1.16**	**0.351**	**0.412**
	SFT	0.222	0.559	4.01	0.87	0.257	0.373
	SFT+DPO	**0.324**	0.613	3.30	0.63	0.272	0.338
	SFT+DPO+RLVR (Instruct)	0.266	0.422	2.37	0.42	0.195	0.251
	RL-Zero (RL from base)	0.295	0.572	4.06	0.84	0.286	0.326
1.0	Base	0.128	**0.713**	**7.53**	**1.66**	**0.398**	**0.469**
	SFT	0.191	0.634	6.32	1.29	0.321	0.426
	SFT+DPO	**0.313**	0.688	4.48	0.87	0.312	0.410
	SFT+DPO+RLVR (Instruct)	0.272	0.561	3.58	0.68	0.259	0.325
	RL-Zero (RL from base)	0.279	0.695	6.28	1.21	0.367	0.429

Table 8: OLMo 3 7B post-training stages on DDXPlus (980 cases, 32 samples). Severe C@32 is severe-tier Considered@32 as in Table 6. Bold marks the best value in each block. Diversity falls at every stage of the instruct pipeline, and the RLVR stage loses the most coverage; RL from the base keeps the base model's pass@32 at T=1.

Model	pass@1	pass@32	Distinct	Cov@32	Severe C@32	TV one list↓	TV samples↓	Vote@32 gain
Qwen2.5-32B (base)	0.500	**0.795**	**3.78**	**0.352**	**0.35**	0.726	**0.726**	+7.0
Qwen2.5-32B-Instruct	**0.604**	0.746	1.68	0.276	0.29	**0.674**	0.759	+1.9
OLMo-3-1125-32B (base)	0.326	**0.796**	**4.32**	**0.347**	**0.39**	0.746	**0.742**	+8.4
SFT	0.461	0.674	2.94	0.265	0.27	0.736	0.776	+3.6
SFT+DPO	**0.584**	0.784	2.29	0.293	0.32	**0.694**	0.755	+2.1
SFT+DPO+RLVR (Instruct)	0.560	0.756	2.15	0.283	0.30	0.701	0.763	+0.9

Table 9: 32B replication on DDXPlus (T=0.7, 980 cases, 32 samples). TV columns: distance to the reference differential of one stated list and of the sampled top-1 answers (§4.2). Vote@32 gain: accuracy of the majority answer over 32 samples minus single-call accuracy, in points (§4.3). Bold: best value per family.

about half as much. Post-training costs 4.9 [2.8, 7.1] points at pass@32 for Qwen2.5-32B and 4.0 [2.0, 5.9] for OLMo 3.1 32B, halves the number of distinct answers (3.78 → 1.68 and 4.32 → 2.15), and lowers severe-tier consideration by 6.1 and 8.4 points. For Qwen the loss holds on the 421 cases where every base sample is valid (−4.8 [−7.8, −1.7]); the OLMo 32B base gives invalid answers on 27% of samples. The stage attribution differs from 7B. In OLMo 3.1 32B the largest narrowing is SFT (pass@32 −12.1 [−14.4, −9.9], distinct answers −1.39, severe tier −11.9); DPO recovers most of it (+10.9 against SFT), and the final RL step is small (−2.8 [−4.3, −1.1] at k=32, −0.14 distinct answers). OLMo 3.1 32B and OLMo 3 7B were post-trained with different recipes, so the stage that narrows the samples most is a property of the pipeline, not of SFT, DPO or RL as such. The stated readout improves in both 32B families (§4.2), and voting stops paying off: majority voting over 32 samples gains the base models 7.0 and 8.4 points and the Instruct models 1.9 and 0.9 (the latter n.s.).

Model	TV to reference↓ One distribution	TV to reference↓ Samples	AUROC, single-call answer correct Stated p	AUROC, single-call answer correct Agree@5	AUROC, single-call answer correct Agree@32	Top-3: one dist. − 32 samples
Qwen3-8B-Base	0.733	**0.752**	0.647	0.809	**0.845**	−6.7
Qwen3-8B	**0.681**	0.790	**0.717**	0.609	0.647	+14.6
Qwen2.5-7B	0.769	**0.758**	0.688	0.792	**0.827**	−10.2
Qwen2.5-7B-Instruct	**0.702**	0.770	0.674	0.715	**0.748**	+1.6
OLMo-3-1025-7B	0.807	**0.766**	0.610	0.744	**0.786**	−15.3
OLMo-3-7B-Instruct	**0.775**	0.787	0.749	0.705	**0.759**	−9.5

Table 10: Full-distribution prompt on DDXPlus (T=0.7, 980 cases): a probability on every condition, top answer = highest stated probability. TV: one sample's stated distribution vs. the sampled top-1 answers (bold: better model of each pair). AUROC: bold marks each model's best signal.

Appendix D. The stated readout: elicitation, robustness and audit

D.1. Robustness of the stated readout to elicitation

The stated readout above uses a five-item list. We repeat the Qwen pairs and OLMo 3 7B's base and Instruct models at T=0.7 with a prompt that asks for a probability on every one of the 49 conditions, summing to one, and take each sample's top answer to be its highest-probability condition (Table 10). The results match the short list. After post-training the stated distribution is closer to the reference (TV −0.052 for Qwen3-8B, −0.067 for Qwen2.5-7B-Instruct, −0.032 for OLMo-3-7B-Instruct) while the samples move away (+0.012 to +0.038). Qwen3-8B's stated probability again beats agreement over 32 samples (+0.069 [+0.033, +0.104]), Qwen2.5-7B-Instruct's again does not (−0.074), and OLMo-3-7B-Instruct's ties it (−0.010; +0.044 against five samples). The top three of one full distribution beats the three most frequent of 32 sampled answers for Qwen3-8B (+14.6 points) but not for the other two models.

D.2. Ruling out format, accuracy and floor effects

Table 11 tests simpler explanations of the stated-list result. *Format.* The general models' post-trained lists and base-model lists at T=0.7 are nearly all complete (81–99% name five on-list conditions with probabilities; Qwen base models at T=1, 61–62%; the medical models, 61–80%). Restricting to complete lists leaves the gaps unchanged (Qwen2.5-7B: 0.779 vs. 0.719). *Accuracy.* A more accurate model puts more stated mass on the true pathology, which the reference also favors. Within samples whose top answer is correct, and within those whose top answer is wrong, the post-trained Qwen list is still closer to the reference (−0.018 to −0.034 and −0.036 to −0.079 in TV). *Floor.* One list can do no better than the reference's own top five, and a finite set of samples no better than as many draws from the reference. Measured as excess over these floors, post-training lowers the list's TV (Qwen3-8B 0.479 → 0.435) and raises the samples' (0.557 → 0.613). *Over-naming.* Post-trained lists name fewer conditions that the reference gives less than 1% (Qwen3-8B 0.59 → 0.55 of named conditions) and fewer severe conditions it gives less than 0.1 (Qwen2.5-32B 0.74 → 0.65), so the gain in naming severe conditions is not over-triage.

Model (T=0.7)	Complete lists	TV of one list↓ complete only	top-1 right	top-1 wrong	Excess TV over floor↓ One list	Samples	Severe named ref. < 0.1	pass@32 list-sampled
Qwen3-8B-Base	0.90	0.743	0.663	0.806	0.479	**0.557**	0.752	0.780
Qwen3-8B	0.99	**0.701**	**0.646**	**0.769**	**0.435**	0.613	**0.680**	**0.811**
Qwen2.5-7B	0.95	0.779	0.689	0.828	0.514	**0.575**	0.823	0.772
Qwen2.5-7B-Instruct	0.91	**0.719**	**0.655**	**0.773**	**0.452**	0.605	**0.796**	**0.802**
Qwen2.5-32B	0.96	0.725	0.661	0.795	0.462	**0.543**	0.735	0.850
Qwen2.5-32B-Instruct	0.98	**0.674**	**0.639**	**0.726**	**0.409**	0.579	**0.645**	**0.880**
OLMo-3-1025-7B	0.81	**0.794**	0.687	**0.837**	**0.524**	**0.522**	**0.747**	**0.719**
OLMo-3-7B-Instruct	0.95	0.823	**0.659**	0.882	0.558	0.671	0.779	0.577
OLMo-3-1125-32B	0.89	0.744	0.662	0.812	0.481	**0.532**	0.706	0.839
OLMo-3.1-32B-Instruct	0.99	**0.701**	**0.644**	**0.774**	**0.436**	0.583	**0.634**	**0.853**

Table 11: Robustness of the stated-list result (DDXPlus, T=0.7, 980 cases, valid samples). Complete lists: share naming five on-list conditions with valid probabilities. TV of one list on complete lists only, and on samples whose top answer is right or wrong. Excess TV: TV minus the expected TV of the matching oracle (the reference's top five for one list; as many reference draws as the model has valid samples for the samples). Severe named, ref. $<$ 0.1: share of named severe conditions that the reference gives less than 0.1 (over-naming). pass@32 list-sampled: top answers drawn from each sample's stated list. Bold: better model of each pair. A uniform guesser scores about 0.48 at pass@32.

Sampling from the list. Replacing each sample's top answer with a draw from its own stated list restores the coverage the samples lost: post-trained models' pass@32 then exceeds their base models' sampled pass@32 in every comparison except OLMo 3 7B (Qwen3-8B 0.811 vs. 0.730; Qwen2.5-32B-Instruct 0.880 vs. 0.795; OLMo 3.1 32B Instruct 0.853 vs. 0.796), against about 0.48 for a uniform guesser. OLMo 3 7B remains the exception throughout: its Instruct list is closer to the reference when its top answer is correct but much farther when it is wrong.

D.3. Which readout to trust: a held-out audit

Whether the stated probability or agreement across samples is the better error signal varies across models, so we ask what predicts it and whether a practitioner can tell. We pool 56 model–setting combinations scored on DDXPlus: the base/post-trained pairs at both temperatures and with three prompts, the OLMo stages, the 32B models, the medical models, our GRPO runs, and the full-distribution prompt. They share weights, prompts and temperatures, so we treat the correlations below as descriptive. The stated probability's advantage over five-sample agreement correlates with the *single-answer rate*, the share of cases whose five samples all give the same top answer (Spearman 0.75), with the stated probability's own AUROC (0.82; the gap contains this term, so part of this is by construction), and negatively with the number of distinct answers (-0.74). The stated probability is the better signal for 19 of the 56. No single-answer threshold separates them: Qwen2.5-7B-Instruct still favors agreement, while OLMo 3 7B's DPO and Instruct models favor their unusually informative stated probability. The simplest rule, always using agreement, is right for 66% of the combinations (54% of the 39 post-trained ones) and loses 0.025 AUROC on average (0.032). An audit does better: choose the signal with the higher AUROC on 100 random

labeled cases, using five samples per case, and evaluate the choice on the other 880. Over 500 draws per combination it picks the better held-out signal 86% of the time (82% for post-trained models) and loses 0.005 AUROC (0.007); with 50 cases, 82% and 0.010; with 200, 90% and 0.003. It is reliable when the two signals differ by more than 0.05 AUROC (96% of draws, 39 combinations) and close to a coin flip when they differ by less than 0.02 (53%, 5 combinations), where the choice matters least. The audit's main cost is gold labels for 100 cases from the target population, and we validate it only within DDXPlus.

Appendix E. Medical post-training and rare disease

E.1. Medical post-training

Applied after instruction tuning, medical RL does not cost coverage. AlphaMed improves on its parent at every k (Figure 4): +3.9 points at k=1 ([+2.2, +5.5]), widening to +8.4 at k=32 ([+6.0, +10.6]). It reaches at least one correct sample for 47 of 49 conditions, against 39 for its parent. It does not restore breadth, though: distinct answers (1.87 vs. 1.82), entropy (0.29 vs. 0.30), and coverage (0.27 vs. 0.24) stay at the instruction-tuned level, far below the base model. AlphaMed also names off-list conditions more often than its parent, a mild loss of instruction following. By condition, AlphaMed slightly *raises* consideration in every severity tier (+2.2 to +4.3 points; Table 6). It still loses acute pulmonary edema (0.31 to 0.13), and it introduces an attractor of its own: spontaneous pneumothorax as the top answer in 10.3% of samples, against 4.3% for its parent and a reference rate of 1.0%. Medical post-training thus operates on an already collapsed distribution; the collapse comes from the general post-training stage. The other two descendants go further (Table 12). HuatuoGPT-o1 (SFT then PPO) and m1 (SFT distillation from a reasoning teacher) both *widen* the differential relative to their parent: 2.49 and 3.29 distinct answers vs. 1.82, and coverage@32 of 0.31 and 0.33 vs. 0.24. Their pass@32 rises by 13.7 [+11.3, +16.0] and 18.1 [+15.5, +20.7] points. m1 gains almost nothing at k=1 (+0.9, interval includes zero), so its improvement lies entirely in breadth. Both reasoning-trained models are also less calibrated (ECE 0.17 and 0.21 vs. 0.11). Medical post-training on an instruction-tuned model thus never adds to the collapse, and reasoning distillation partially reverses it.

Medical RL from the base model. Alongside the instruct-initialized AlphaMed-7B, the AlphaMed authors released a companion checkpoint, AlphaMed-7B-base-rl, initialized from Qwen2.5-7B rather than Qwen2.5-7B-Instruct (according to its configuration file). The paper (Liu et al., 2025) describes only the instruct-initialized models: GRPO with a binary correctness reward on about 19k multiple-choice questions from MedQA and MedMCQA, with a 64-question by 8-sample batch for 300 steps. It does not document the base-initialized checkpoint, so we cannot rule out differences in data or hyperparameters, and we treat it as corroborating rather than controlled evidence. It offers a third-party check on whether RL itself causes the collapse (Table 12, lower block). It does not. RL from the base model improves on the base at every k (+14.3 [+13.1, +15.7] points at k=1, +9.5 [+7.4, +11.6] at k=32). It keeps 3.14 distinct answers, against 1.87 for the instruct-initialized AlphaMed. Against that instruct-model AlphaMed, it is 2.2 [0.4, 3.9] points worse at k=1 and 10.8 [+8.6, +13.2] points better at k=32. Its severe-tier Considered@32 shows no detectable change relative to the base (−0.7 [−3.0, +1.7] points), against −12.4 for instruction tuning

Model	Post-training	pass@1	pass@32	Distinct	Entropy	Cov@32	ECE
Qwen2.5-7B-Instruct	(parent)	0.478	0.598	1.82	0.30	0.239	**0.106**
AlphaMed-7B	rule-based RL	0.516	0.682	1.87	0.28	0.266	0.121
HuatuoGPT-o1-7B	SFT + PPO	**0.536**	0.735	2.49	0.44	0.306	0.168
m1-7B-23K	SFT distillation	0.486	0.779	3.29	0.62	0.328	0.206
Qwen2.5-7B (base)	(parent)	0.352	0.695	**4.91**	**1.00**	**0.335**	0.291
AlphaMed-7B (base-RL)	rule-based RL	0.495	**0.790**	3.14	0.62	0.320	0.202

Table 12: Medical models on DDXPlus (980 cases, 32 samples, T=0.7). Upper block: descendants of Qwen2.5-7B-Instruct; none narrows the differential further, and the reasoning-trained models widen it. Lower block: AlphaMed's companion checkpoint trained from the base model, which keeps most of the base model's diversity and has the best pass@32 of any 7B model.




Figure 4: DDXPlus at T=0.7 (980 cases): Qwen2.5-7B-Instruct (dashed) vs. its medical descendants, with 95% case-bootstrap bands. Every descendant matches or beats its parent at every k, and the gaps widen with k: there is no sharpening tax at the medical stage.

and −8.1 for instruction tuning followed by AlphaMed's RL (Table 6; all well below the chance levels of §C.2). This is consistent with our own controlled GRPO-from-base result (§F): with a verifiable correctness reward, RL from a base model buys accuracy without the collapse, which is introduced by general instruction tuning and inherited by everything trained on top of it. OLMo 3 refines this (§C.4): within its instruct pipeline, the RL stage applied after SFT and DPO is the largest single narrowing.

E.2. Rare disease: overconfidence without accuracy

On 1,401 Phenopacket Store cases covering 749 diseases, every 7–8B model is near the floor: pass@1 is 1.4–2.2% and pass@32 is 3.7–7.0%. Stated confidence is not near the floor. Qwen2.5-7B-Instruct states a mean top-1 probability of 0.51, and its RL-trained medical descendants state 0.67 (HuatuoGPT-o1) and 0.69 (AlphaMed), while their accuracy is about

Model	≤2022 (n=901) pass@1	≤2022 (n=901) pass@32	2023–24 (n=348) pass@1	2023–24 (n=348) pass@32	2025+ (n=152) pass@1	2025+ (n=152) pass@32
Qwen2.5-7B (base)	2.0	8.2	0.0	0.3	0.6	3.3
Qwen2.5-7B-Instruct	2.3	7.7	0.0	0.9	0.8	3.9
AlphaMed-7B	3.0	9.0	0.3	1.4	1.4	3.9
AlphaMed-7B (base-RL)	2.4	8.8	0.1	1.1	1.4	4.6
HuatuoGPT-o1-7B	3.1	8.4	0.3	1.4	1.3	3.9
m1-7B	2.6	9.5	0.3	1.7	1.0	3.9
Qwen3-8B-Base	2.1	8.3	0.1	0.6	1.1	3.9
Qwen3-8B	3.1	5.2	0.1	0.3	2.0	2.6

Table 13: Phenopacket Store accuracy (%, exact diagnosis) by publication year of the source case report (1,401 cases, 32 samples, T=0.7). Every model is far more accurate on cases published up to 2022 than on 2023–24 cases; 2025+ cases fall in between.

2%. ECE accordingly rises from 0.49 to 0.64–0.67; at this accuracy ECE mostly restates mean confidence, so we read it as a rise in confidence without a matching rise in accuracy. Medical RL thus increases overconfidence exactly where the model is out of its depth. The effect also appears without instruction tuning: AlphaMed's base-initialized checkpoint is the most overconfident model we evaluate (mean confidence 0.71, ECE 0.70, accuracy 1.7%). The medical descendants do gain a little accuracy: AlphaMed beats its parent at every k (+0.6 [+0.2, +0.9] points at k=1, +1.0 [+0.1, +2.1] at k=32), HuatuoGPT-o1 at $k \leq 8$, and m1 at $k \geq 2$ (+1.4 [+0.4, +2.5] at k=32). These gains are an order of magnitude smaller than the rise in confidence. m1, trained only with supervised reasoning traces (at its intended 8k-token budget), is the exception on calibration and diversity: it is the most diverse model (15.3 distinct answers per 32 samples, against 11.5 for the parent and 9.2 for HuatuoGPT-o1), and its confidence rises least (0.57).

General post-training reproduces the DDXPlus pattern on Qwen3. Qwen3-8B beats its base at pass@1 (+0.7 [+0.4, +1.1]) and trails it from k=8 on, by −2.2 [−3.1, −1.3] points at pass@32 (a relative loss of 37%), with half the distinct answers (6.4 vs. 13.4). For Qwen2.5 no pass@k difference is significant. Unlike medical RL, general post-training *lowers* stated confidence here (0.61 to 0.46 for Qwen3, 0.61 to 0.51 for Qwen2.5), although base models also give invalid answers more often (8.5% of Qwen3-8B-Base samples). OLMo 3 does not share this: every stage of its pipeline states a mean confidence of 0.73–0.84 at about 1% accuracy (pass@32 2.5–4.5%), and its SFT checkpoint is the most overconfident model we evaluate (confidence 0.84, ECE 0.83). On the 500-case subset, our 8B GRPO runs (§F) are indistinguishable from their base (all pass@k differences within ±0.6 points).

Accuracy depends strongly on when the source case report was published (Table 13). For every model, pass@32 is 5–10% on cases published up to 2022 (n=901), at most 1.7% on 2023–24 cases (n=348), and 2.6–4.6% on 2025+ cases (n=152). The pattern is not monotone, since 2025+ cases score above 2023–24 cases, so case mix also matters; the gap between older and recent cases is consistent with, but does not establish, memorization of older case reports.

Model	Single-call correct	Vote@32 gain	Top-3: list − 32 samples	AUROC, single-call answer correct			Correct answers
				Stated p	Agree@5	Agree@32	
Qwen3-8B-Base	0.074	+4.6	−7.0	0.567	0.768	**0.830**	104
Qwen3-8B	0.080	+0.4	+0.4	0.707	0.726	**0.763**	112
Qwen2.5-7B	0.062	+3.8	−5.4	0.598	0.788	**0.845**	87
Qwen2.5-7B-Instruct	0.056	+1.5	−3.6	0.717	0.661	**0.745**	78
OLMo-3-1025-7B	0.060	+3.1	−4.6	0.464	0.765	**0.814**	84
SFT	0.035	+1.1	−3.6	0.628	0.730	**0.814**	49
SFT+DPO	0.026	+1.2	−3.3	0.651	0.673	**0.725**	36
SFT+DPO+RLVR (Instruct)	0.035	+0.9	−2.7	0.652	0.644	**0.726**	49
RL-Zero (from base)	0.065	+2.3	−3.1	0.583	0.791	**0.827**	91
AlphaMed-7B	0.071	+1.6	−3.0	0.586	0.755	**0.797**	100
HuatuoGPT-o1-7B	0.093	+2.6	−5.7	0.653	0.708	**0.756**	130
m1-7B	0.084	+2.9	−7.9	0.650	0.747	**0.800**	117
AlphaMed-7B (base-RL)	0.054	+2.5	−4.2	0.672	0.733	**0.789**	75

Table 14: Aggregation and uncertainty on Phenopacket Store (1,401 real rare-disease cases, 32 samples, T=0.7). An answer counts as correct if it is the diagnosis or a closely related Mondo class. Columns as in Table 3; Correct answers: number of correct single-call answers, the positives for the AUROCs. Bold: best signal.

E.3. Stated and sampled readouts on real rare-disease cases

Phenopacket Store cases are real, but they have no reference differential and accuracy is near the floor, so we can test only the consequences of §4.3, and we count an answer as correct if it is the diagnosis or a closely related Mondo class (exact matches give only 8–31 correct single-call answers per model). Top answers are grouped by Mondo class for voting and agreement (Table 14). The DDXPlus shifts reappear, without a crossover. Majority voting over 32 samples helps the base models by 3.1–4.6 points but the final post-trained models by only 0.4–1.5 (Qwen3-8B +0.4, n.s.). Post-training weakens agreement as an error signal (Qwen3-8B 0.830 → 0.763, Qwen2.5-7B 0.845 → 0.745, OLMo 3 7B 0.814 → 0.726) and strengthens the stated probability (0.567 → 0.707, 0.598 → 0.717, 0.464 → 0.652). Agreement beats the stated probability by 0.25–0.35 AUROC for the base models and by only 0.03–0.08 for the post-trained ones, significantly only for Qwen3-8B (−0.056 [−0.120, −0.002]). On these open-ended cases the three most frequent of 32 sampled answers still contain a correct diagnosis more often than one list's top three, but the gap shrinks from 4.6–7.0 points for the base models to 2.7–3.6 for Qwen2.5-7B-Instruct and OLMo-3-7B-Instruct and to a tie for Qwen3-8B (+0.4 [−0.8, +1.8]). The medical models behave like their post-trained parent, with agreement the better signal for all of them.

Appendix F. Training without collapsing the samples

The stated list survives post-training, but sampled diversity still matters: self-consistency and other sampling-based methods depend on it (§4.3), and so does reinforcement learning itself, since GRPO learns nothing from a group whose samples agree. Can reinforcement learning raise diagnostic accuracy without collapsing the sampled differential? We fine-tune Qwen3-1.7B with GRPO on DDXPlus training patients (9,800 cases, 200 per condition; disjoint from the test split) and evaluate exactly as in §3.

Setup. We train LoRA adapters (r=32) with GRPO for 200 steps. Each step uses 16 prompts and 16 sampled completions per prompt, generated with vLLM on the same GPU. A first sweep with a common aggressive configuration (learning rate 2×10^{-5}, no KL penalty, 8 samples per prompt, per-group reward standardization) was unstable. In three of seven runs, the policy collapsed to an input-independent answer: one condition for 88–100% of all patients, with completions shrinking to about 25 tokens. The starting policy is nearly deterministic (token entropy ≈0.06), so most GRPO groups have zero reward variance, and noisy updates drive the collapse. We therefore use learning rate 5×10^{-6}, KL coefficient 0.04, no reward standardization (as in Puri et al. (2026)), and 16 samples per prompt. A monitor tracks the number of distinct top-1 answers per case within each batch. All runs in this configuration were stable.

Rewards. Every recipe includes a format reward: the answer must parse into a list of distinct conditions with valid probabilities. `acc` is standard RLVR: 1 if the top-1 answer is the true pathology. `dist` adds two per-sample distributional terms to `acc`: a Brier score of the stated distribution against the truth, and the overlap of the stated distribution with the reference differential. Both are computed from a *single* completion. They cannot see that the policy gives the same answer in every sample, which is exactly the collapse of §C.2. `gm` adds to `acc` a *group-level* reward over the GRPO group of n samples for a case. If sample i's top-1 answer is a, and k_a samples in the group give a,

$$r_i^{\mathrm{gm}} = \mathrm{clip}\big(n\,p_{\mathrm{ref}}(a) - (k_a - 1),\ 0,\ 1\big), \tag{1}$$

where p_{ref} is the reference differential. This is sample i's marginal contribution to $n\sum_c \min(q_c, p_{\mathrm{ref}}(c))$, the overlap between the group's empirical answer distribution q and the reference. An answer earns credit while its condition is under-represented relative to its reference mass, and none once it is over-represented. In contrast to multi-answer rewards that score a set inside one completion (Puri et al., 2026), `gm` acts on the distribution of *sampled* answers, the quantity that collapses. Because the group reward fires only when a group contains dissenting samples, we also test a boosted variant, `gm`$^+$: `gm` weight 3 and training temperature 1.2. As baselines we adapt the multi-answer rewards of Puri et al. (2026) to our prompt. Multi-RLVR scores the share of listed conditions that belong to the reference differential, treated as a set of acceptable answers; Multi-RLCR adds their set-level Brier term on the per-answer probabilities. Both zero the reward for duplicate or invalid answers, as in the original, and use the same format reward, optimizer and settings as our recipes.

Results. Table 16 reports means over two seeds; intervals bootstrap cases and do not include seed-to-seed variation. All our recipes raise top-1 accuracy by 8–10 points; the multi-answer baselines barely move it (below). The per-sample recipes (`acc`, `dist`) slightly *reduce* diversity relative to the starting model, the sharpening documented in §C.1. The group reward removes this. `gm` matches the starting model's diversity, and `gm`$^+$ exceeds it while also being the most accurate recipe. Against `acc`, with paired bootstraps over cases averaged over seeds, `gm`$^+$ improves:

- pass@1 by +1.6 [+1.0, +2.3] and pass@32 by +1.7 [+1.0, +2.6] points;
- distinct answers by +0.10 [+0.07, +0.13] and entropy by +0.034 [+0.022, +0.047];

- coverage@32 by $+1.5$ $[+1.0, +2.1]$ points, and TV by -0.014 $[-0.019, -0.010]$.

Plain `gm` improves on `acc` in the same direction with smaller margins (e.g. pass@1 $+1.0$ $[+0.6, +1.6]$, entropy $+0.013$ $[+0.005, +0.021]$). Diversity increases monotonically with group-reward pressure, with no accuracy cost. The set-membership baselines of Puri et al. (2026) train stably (their reward rises from 0.27–0.31 to 0.32–0.35) but barely change sampled behavior. pass@1 rises by under 1 point over the untrained model, and diversity is unchanged. Against them, $\texttt{gm}^+$ is better on every metric, by $+8.9$ $[+7.4, +10.5]$ points at pass@1, $+0.07$ $[+0.03, +0.11]$ distinct answers and $+3.0$ $[+2.3, +3.8]$ points of coverage@32 (vs. Multi-RLVR; Multi-RLCR is similar). What they do improve is the differential written *inside* one completion: the reference mass covered by a single listed differential rises to 0.317 (Multi-RLVR), against 0.300 for `acc` and 0.309 for $\texttt{gm}^+$. The two objectives are complementary: a set reward shapes the list a model writes, while the group reward shapes which answer it commits to across samples, which is what collapses under post-training. The absolute effects are modest because the starting policy is already collapsed: there is little exploration for any reward to act on. None of the recipes changes rare-disease accuracy or confidence on Phenopacket Store, where a 1.7B model is at the floor; the same holds at 8B (§E.2).

Starting from a diverse base model. The 1.7B experiment starts from an already collapsed instruct model. We therefore repeat the comparison from Qwen3-8B-Base, the diverse base model of §C.1, with the same recipe and `acc` vs. `gm`. We compare against Qwen's own post-trained Qwen3-8B (Table 15; means of two seeds). Both RL recipes reach nearly the official model's top-1 accuracy (0.537 and 0.539 vs. 0.558; `gm`: -1.9 $[-3.9, +0.1]$ points). They keep more than twice its diversity (2.7–2.9 vs. 1.27 distinct answers) and beat it by 15–16 points at pass@32 (`gm`: $+16.3$ $[+14.0, +18.8]$). In this setting, then, the collapse produced by general post-training is not required for its top-1 accuracy (our runs train on in-distribution DDXPlus data, so this is an existence result, not a like-for-like comparison of recipes). Both runs still narrow the base model somewhat, and the group reward narrows it less. At equal pass@1 ($+0.2$, n.s.), `gm` beats `acc` on distinct answers $+0.14$ $[+0.11, +0.17]$, entropy $+0.035$ $[+0.029, +0.041]$, coverage@32 $+1.1$ $[+0.8, +1.5]$ points, and pass@32 $+1.2$ $[+0.5, +1.9]$. Each seed reproduces the ordering. The severe tier tells the same story (Table 6): official post-training removes 9.8 points of can't-miss consideration, `acc` 2.8, and `gm` 1.5 (not significant). Figure 5 shows the pass@k curves.




Figure 5: pass@k on DDXPlus (T=0.7, 980 cases) from the same pretrained weights: Qwen3-8B-Base, our GRPO runs (pooled over two seeds), and the official post-trained Qwen3-8B, with 95% case-bootstrap bands. Our RL lifts the whole curve; official post-training trades the right end for the left.

Model	pass@1	pass@32	Distinct	Entropy	Cov@32	TV↓
Qwen3-8B-Base (start)	0.389	0.732	**3.77**	**0.78**	**0.323**	0.749
+ `acc` GRPO (ours)	0.537	0.759	2.72	0.52	0.297	0.750
+ `gm` GRPO (ours)	0.539	**0.770**	2.86	0.56	0.308	**0.742**
Qwen3-8B (official post-training)	**0.558**	0.607	1.27	0.11	0.217	0.793

Table 15: GRPO from Qwen3-8B-Base vs. the official post-trained Qwen3-8B on DDXPlus (980 cases, 32 samples, T=0.7); GRPO rows are means of two seeds. Our RL nearly matches the official model's top-1 accuracy while keeping more than twice its diversity; the group reward preserves more than `acc`. The base row comes from this experiment's own sampling run, so it differs slightly from Table 5.

Recipe	pass@1	pass@32	Distinct	Entropy	Cov@32	TV↓
Qwen3-1.7B (untrained)	0.378	0.435	1.41	0.151	0.162	0.850
`acc`	0.458	0.499	1.36	0.142	0.181	0.829
`dist`	0.458	0.502	1.34	0.131	0.181	0.829
Multi-RLVR (Puri et al., 2026)	0.385	0.443	1.39	0.153	0.166	0.845
Multi-RLCR (Puri et al., 2026)	0.383	0.441	1.39	0.150	0.165	0.847
`gm`	0.469	0.510	1.40	0.155	0.186	0.825
`gm`$^+$	**0.474**	**0.516**	**1.46**	**0.176**	**0.196**	**0.815**

Table 16: GRPO on Qwen3-1.7B, evaluated on DDXPlus test (980 cases, 32 samples, T=0.7); means of two seeds. `gm`$^+$: group-reward weight 3, training temperature 1.2. Per-sample rewards slightly narrow the model; set-membership rewards barely move it; the group reward preserves, then widens, its differential while improving accuracy.