



Universidad
Politécnica
de Cartagena



Universidad
Politécnica
de Cartagena

JJA ALGORITHM

AUTORES:

Jairo Peña Iglesias

José A. López Pastor



Universidad
Politécnica
de Cartagena

JJA ALGORITHM

Jairo Peña Iglesias
José A. López Pastor
ALGORITHM

Jeffrey
Jacob
Abrams



**ORGULLO
FRIKI**
DOMINAMOS EL MUNDO



Initial considerations

Algorithm for an unique problem with specific parameters.


After some experimental calculations, we realized that:

- The cost of links between **CoreNodes** have a higher cost in the solution than rest of parameters. This is because CoreNodes links between them are more than **CoreToAccess** links.
- So as, our solution tries to **minimize the cost of chose the CoreNodes and their links.**
- Thus, we have based on the Greedy Algorithm.



Universidad
Politécnica
de Cartagena


Example



Chosed randomly




Example






Example



The nearest of
each CoreNode is
an AccessNode




Example






Example






Example






Example



The nearest of
each CoreNode is
an AccessNode



Example



After the iterations each
CoreNode have the same
AccessNode



Algorithm

Calculate **minCoreNodes** related to **maxNumAccessNodePerCoreNode** and **totalNodes**

First **CoreNode** chosen randomly

The nearest **minCore** are chosen


```
Foreach CoreNode in minCore{  
    nearest maxNumAccessNodePerCoreNode are chosen  
}
```

Cost is stored as **bestCost**

```
While(time){  
    Other First CoreNode choosen randomly  
    The nearest minCore are chosen  
    Foreach CoreNode in minCore{  
        nearest maxNumAccessNodePerCoreNode are chosen  
    }  
    If(cost<bestCost)  
        bestCostUpdated  
}
```



Flow chart





Objects are our friends

```
public class CoreNode{
```

Attributes

```
int coreNode;
```

```
List<Integer> connectedNodes = new ArrayList<Integer>();
```

```
public CoreNode(){}
```

```
public int getCoreNode() {  
    return coreNode;  
}
```

```
public void setCoreNode(int coreNode) {  
    this.coreNode = coreNode;  
}
```

```
public List<Integer> getConnectedNodes() {  
    return connectedNodes;  
}
```

```
public void setConnectedNodes(List<Integer> connectedNodes) {  
    this.connectedNodes = connectedNodes;  
}
```

```
public void addConnectedNode(Integer node){  
    this.connectedNodes.add(node);  
}
```

```
public int getNumberOfConnectedNodes(){  
    return this.connectedNodes.size();  
}
```


Get y Set

Working methods




Solutions


CoreNodeCost = 100
MaxNumAccessNode = 5




CoreNodeCost = 500
MaxNumAccessNode = 5



CoreNodeCost = 500
MaxNumAccessNode = 10



CoreNodeCost = 500
MaxNumAccessNode = 10





Universidad
Politécnica
de Cartagena

Bibliography:

- Optimization of Computer Networks – Modeling and Algorithms : A hands-On Approach.
- Notes and sketches from Pablo Pavón Mariño.
- Practice explanations from María Victoria Bueno Delgado and Juan Carlos J. Sánchez Aarnoutse.
- Api JavaDoc.

The end

AUTORES: Jairo Peña Iglesias y José A. López Pastor.