



PWM Solar Charge Controller  
**PC1500C Series**

**Feature:**

- 10A 20A 30A 40A 50A 60A solar charge controller
- Vivid LCD graphic symbols
- Simple button operation
- Automatic identification of system voltage level
- Intelligent PWM charging mode
- Adjustable charge-discharge protection
- Automatic temperature compensation
- Settable operation mode of load
- Battery reverse-discharge protection
- Battery low voltage disconnection(LVD)
- Battery reverse connection protection
- Over current protection
- USB output

**Introduction:**

This intelligent,multi-purpose solar charge and discharge controller has a very friendly interface of fixed LCD display. Various control parameters can be flexibly set, fully meet your various application requirements.

**Functions:**

LCD display

Protections

PWM

USB Output

Parameters adjustable

Temperature compensation

**PC1500C SERIES Controllers**

**Model: PC1500C-10A/20A**

Rated Voltage:12V/24V Auto identified  
Rated Current: 10A/20A  
USB Port: 5V, 2A x 2  
Product size: 133mm x 93mm x 30mm

Packing info: 50pcs / carton  
Product size: 540mm x 320mm x 200mm  
Gross weight: 14Kg  
Volume: 0.035CBM

**Model: PC1500C-30A/40A**

Rated Voltage:12V/24V Auto identified  
Rated Current: 30A/40A  
USB Port: 5V, 2A x 2  
Product size: 153mm x 101mm x 37mm

Packing info: 40pcs / carton  
Product size: 510mm x 370mm x 240mm  
Gross weight: 17Kg  
Volume: 0.045CBM

**Model: PC1500C-50A/60A**

Rated Voltage:12V/24V/48V Optional  
Rated Current: 50A/60A  
USB Port: 5V, 2A x 2  
Product size: 175mm x 115mm x 43mm

Packing info: 30pcs / carton  
Product size: 405mm x 400mm x 275mm  
Gross weight: 17.5Kg  
Volume: 0.044CBM

**Model: PC1500C-80A/100A**

Rated Voltage:12V/24V/48V Optional  
Rated Current: 80A/100A  
USB Port: 5V, 2A x 2  
Product size: 192mm x 162mm x 60mm

Packing info: 20pcs / carton  
Product size: 535mm x 475mm x 425mm  
Gross weight: 21.5Kg  
Volume: 0.1CBM

**Application**

RV, boat & field power supply solar system

Off-grid home solar system

Farm solar generation system

**PWM Product display**

| Model                              |     | PC1500C<br>-10A                                      | PC1500C<br>-20A | PC1500C<br>-30A | PC1500C<br>-40A | PC1500C<br>-50A   | PC1500C<br>-60A | PC1500C<br>-80A | PC1500C<br>-100A |
|------------------------------------|-----|------------------------------------------------------|-----------------|-----------------|-----------------|-------------------|-----------------|-----------------|------------------|
| Input                              |     |                                                      |                 |                 |                 |                   |                 |                 |                  |
| Maximum PV open<br>circuit voltage |     | <50V                                                 |                 |                 |                 | <50V(<100V)       |                 |                 |                  |
| System voltage                     |     | 12V/24V Auto                                         |                 |                 |                 | 12V/24V/(48V)Auto |                 |                 |                  |
| Rated Charge Current               |     | 10A                                                  | 20A             | 30A             | 40A             | 50A               | 60A             | 80A             | 100A             |
| PVmaximum<br>input power           | 12V | 130W                                                 | 260W            | 390W            | 520W            | 650W              | 780W            | 1040W           | 1300W            |
|                                    | 24V | 260W                                                 | 520W            | 780W            | 1040W           | 1300W             | 1560W           | 2080W           | 2600W            |
|                                    | 48V |                                                      |                 |                 |                 | 2600W             | 3120W           | 4160W           | 5200W            |
| Rated Discharge<br>Current         |     | 10A                                                  |                 | 20A             |                 | 30A               |                 | 40A             |                  |
| Charging control mode              |     | PWM                                                  |                 |                 |                 |                   |                 |                 |                  |
| Float charge                       |     | 13.8V/27.6V/(55.2V)                                  |                 |                 |                 |                   |                 |                 |                  |
| Absorption charge                  |     | 14.4V/28.8V/(57.6V)                                  |                 |                 |                 |                   |                 |                 |                  |
| Equalization charge                |     | 14.6V/29.2V/(58.4V)                                  |                 |                 |                 |                   |                 |                 |                  |
| Load disconnection(LVD)            |     | 10.8V/21.6V/(43.2V)                                  |                 |                 |                 |                   |                 |                 |                  |
| Load reconnection(LVR)             |     | 12.6V/25.2V/(50.4V)                                  |                 |                 |                 |                   |                 |                 |                  |
| Working temperature<br>range       |     | -20~+55℃                                             |                 |                 |                 |                   |                 |                 |                  |
| System voltage                     |     | 24mV/°C for 12V system                               |                 |                 |                 |                   |                 |                 |                  |
| Battery Type                       |     | GEL, SLD,FLD<br>Lithium batteries customization      |                 |                 |                 | GEL, SLD,FLD      |                 |                 |                  |
| Load controlmode                   |     | 24 hours work,light control,light and timing control |                 |                 |                 |                   |                 |                 |                  |