

Axpert VM II Premium+ LV Off-Grid Inverter



- Pure sine wave solar inverter
- Reserved communication port for BMS
- Wide PV input range, starts from 30VDC for 1K/2K
- Battery independent design
- Maximum charging current 90A or 100A based on models
- Battery equalization function to optimize battery performance and extend lifecycle
- Built-in anti-dust kit

Axpert VM II Premium+ LV Off-Grid Inverter Selection Guide

MODEL	Apkert VM II Premium+ LV 1K	Apkert VM II Premium+ LV 2K	Apkert VM II Premium+ LV 3K
Rated Power	1000VA/1000W	2000VA/2000W	3000VA/3000W
INPUT			
Voltage	120 VAC		
Selectable Voltage Range	95-140 VAC (For Personal Computers) ; 65-140 VAC (For Home Appliances)		
Frequency Range	50 Hz/60 Hz (Auto sensing)		
OUTPUT			
AC Voltage Regulation (Batt. Mode)	120VAC ± 5%		
Surge Power	2000VA	4000VA	6000VA
Efficiency (Peak)	91%		
Transfer Time	10 ms (For Personal Computers) ; 20 ms (For Home Appliances)		
Waveform	Pure sine wave		
BATTERY			
Battery Voltage	12 VDC	24 VDC	48 VDC
Floating Charge Voltage	13.5 VDC	27 VDC	54 VDC
Overcharge Protection	16 VDC	32 VDC	63 VDC
SOLAR CHARGER & AC CHARGER			
Solar Charger Type	MPPT		
Maximum PV Array Open Circuit Voltage	350 VDC	400 VDC	450 VDC
Maximum PV Array Power	2000W	4000W	6000W
Maximum PV Input Current	13 A	18A	18A
MPP Range @ Operating Voltage	30 ~ 300 VDC (Min. 60VDC without battery connected)	30 ~ 350 VDC (Min. 60VDC without battery connected)	90~400 VDC
Maximum Solar Charge Current	90A	100 A	100 A
Maximum AC Charge Current	50A	60 A	60 A
Maximum Charge Current	90A	100 A	100 A
PHYSICAL			
Dimension, D x W x H (mm)	90 x 288 x 357	120 x 300 x 400	120 x 300 x 400
Net Weight (kgs)	6.5	8.8	10
Communication Interface	RS232/RS485(BMS)/WiFi		
ENVIRONMENT			
Humidity	5% to 95% Relative Humidity (Non-condensing)		
Operating Temperature	-10°C to 50°C		
Storage Temperature	-15°C to 60°C		

Product specifications are subject to change without further notice.