

Rajalakshmi Engineering College

Name: Jai Shuriya J
Email: 240701200@rajalakshmi.edu.in
Roll no: 240701200
Phone: 8754381941
Branch: REC
Department: CSE - Section 10
Batch: 2028
Degree: B.E - CSE

Scan to verify results



2024_28_III_OOPS Using Java Lab

REC_2028_OOPS using Java_Week 10_CY

Attempt : 1
Total Mark : 40
Marks Obtained : 40

Section 1 : COD

1. Problem Statement

Arjun is working on a program that checks if one set of numbers is a subset of another. If Set B is a subset of Set A, the program should print "YES" followed by the sorted elements of Set B. If Set B is not a subset of Set A, the program should print "NO" followed by the average of all elements from both sets combined, rounded to two decimal places.

Implement a class Solution with the required method to perform the subset check using TreeSet in Java.

Input Format

The first line contains an integer n - the number of elements in Set A.

The second line contains n space-separated integers - the elements of Set A.

The third line contains an integer m - the number of elements in Set B.

The fourth line contains m space-separated integers - the elements of Set B.

Output Format

If Set B is a subset of Set A, print "YES" followed by the sorted values of Set B.

Otherwise, print "NO" followed by the average of all numbers in both sets (rounded to two decimal places).

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 5

1 2 3 4 5

3

2 3 5

Output: YES 2 3 5

Answer

```
import java.util.*;
```

```
// You are using Java
```

```
import java.util.*;
```

```
class Solution {
```

```
    public static void checkSubset(TreeSet<Integer> setA, TreeSet<Integer> setB,  
    int totalCount, long totalSum) {
```

```
        if (setA.containsAll(setB)) {
```

```
            System.out.print("YES ");
```

```
            for (int x : setB) {
```

```
                System.out.print(x + " ");
```

```
            }
```

```
        } else {
```

```
            double avg = (double) totalSum / totalCount;
```

```
            System.out.printf("NO %.2f", avg);
```

```
        }
```

```
    }
```

```

    }
    class Main {
        public static void main(String[] args) {
            Scanner sc = new Scanner(System.in);
            int n = sc.nextInt();
            TreeSet<Integer> setA = new TreeSet<>();
            long sum = 0;
            for (int i = 0; i < n; i++) {
                int num = sc.nextInt();
                setA.add(num);
                sum += num;
            }
            int m = sc.nextInt();
            TreeSet<Integer> setB = new TreeSet<>();
            for (int i = 0; i < m; i++) {
                int num = sc.nextInt();
                setB.add(num);
                sum += num;
            }
            Solution.checkSubset(setA, setB, n + m, sum);
            sc.close();
        }
    }
}

```

Status : Correct

Marks : 10/10

2. Problem Statement

A linguist named Meera is classifying a list of words based on their first character. She wants to store words grouped by their starting letter using a TreeMap so that the groups appear in sorted order of characters (i.e., 'a' to 'z'). For each letter, all words starting with that letter should be stored in the order they appear.

Implement the logic inside a class named WordClassifier using the TreeMap<Character, List<String>> collection.

Input Format

The first line of the input contains an integer n, representing the number of words.

The next n lines each contain a word.

Output Format

The first line of the output prints: "Grouped Words by Starting Letter:"

The next lines print each character key and its list of words in the format:

"letter: word1 word2 word3..."

..."

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 5

dog

deer

cat

cow

camel

Output: Grouped Words by Starting Letter:

c: cat cow camel

d: dog deer

Answer

```
import java.util.*;
```

```
import java.util.*;
```

```
class WordClassifier {
```

```
    public void classifyWords(List<String> words) {  
        TreeMap<Character, List<String>> map = new TreeMap<>();
```

```
        for (String word : words) {  
            char ch = word.charAt(0);  
            map.putIfAbsent(ch, new ArrayList<>());  
            map.get(ch).add(word);
```

```

    }
    System.out.println("Grouped Words by Starting Letter:");
    for (Map.Entry<Character, List<String>> entry : map.entrySet()) {
        System.out.print(entry.getKey() + ": ");
        for (String w : entry.getValue()) {
            System.out.print(w + " ");
        }
        System.out.println();
    }
}
}

public class Main {
    public static void main(String[] args) {
        Scanner sc = new Scanner(System.in);
        int n = Integer.parseInt(sc.nextLine());

        List<String> words = new ArrayList<>();
        for (int i = 0; i < n; i++) {
            words.add(sc.nextLine());
        }

        WordClassifier classifier = new WordClassifier();
        classifier.classifyWords(words);
    }
}

```

Status : Correct

Marks : 10/10

3. Problem Statement

Tony is an e-learning platform administrator, he oversees the user ratings for various online courses offered in the platform.

To enhance user experience, you should assist him in utilizing a HashMap to store course ratings given by learners. Regularly, he analyzes this data to identify the highest and lowest-rated courses, enabling targeted improvements and ensuring the quality of the educational content. This process assists in maintaining a competitive and engaging online learning environment for the users.

Input Format

The input consists of a string representing the course name followed by a double value representing the course's rating, in separate lines.

The input is terminated by entering "done".

Output Format

The first line of output prints the string "Highest Rated Course: " followed by the highest-rated course.

The second line prints the string "Lowest Rated Course: " followed by the lowest-rated courses.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: DSA

4.0

OOPS

4.2

C

3.2

done

Output: Highest Rated Course: OOPS

Lowest Rated Course: C

Answer

```
import java.util.HashMap;
```

```
import java.util.Map;
```

```
import java.util.Scanner;
```

```
// You are using Java
```

```
import java.util.*;
```

```
class CourseAnalyzer {
```

```
    public Map<String, String>
```

```
    identifyHighestAndLowestRatedCourses(Map<String, Double> courseRatings) {
```

```
Map<String, String> result = new HashMap<>();
```

```
String highestCourse = null;
```

```
String lowestCourse = null;
```

```
double highestRating = Double.MIN_VALUE;
```

```
double lowestRating = Double.MAX_VALUE;
```

```
for (Map.Entry<String, Double> entry : courseRatings.entrySet()) {
```

```
    String course = entry.getKey();
```

```
    double rating = entry.getValue();
```

```
    if (rating > highestRating) {
```

```
        highestRating = rating;
```

```
        highestCourse = course;
```

```
    }
```

```
    if (rating < lowestRating) {
```

```
        lowestRating = rating;
```

```
        lowestCourse = course;
```

```
    }
```

```
}
```

```
result.put("highest", highestCourse);
```

```
result.put("lowest", lowestCourse);
```

```
return result;
```

```
    }
```

```
public class Main {
```

```
    public static void main(String[] args) {
```

```
        Scanner scanner = new Scanner(System.in);
```

```
        Map<String, Double> courseRatings = new HashMap<>();
```

```
        while (true) {
```

```
            String courseName = scanner.nextLine();
```

```
            if (courseName.equalsIgnoreCase("done")) {
```

```
                break;
```

```
            }
```

```
            double rating = Double.parseDouble(scanner.nextLine().trim());
```

```
            courseRatings.put(courseName, rating);
```

```
        }
```

```
CourseAnalyzer analyzer = new CourseAnalyzer();
Map<String, String> result =
analyzer.identifyHighestAndLowestRatedCourses(courseRatings);

System.out.printf("Highest Rated Course: %s\n", result.get("highest"));
System.out.printf("Lowest Rated Course: %s", result.get("lowest"));

scanner.close();
}
}
```

Status : Correct

Marks : 10/10

4. Problem Statement

Aryan is developing a voting system for a college election. Each vote is recorded as an entry in an array, where every student's vote is represented by a candidate's ID. Since it's a majority-rule election, the winner is the candidate who receives more than $n/2$ votes, where n is the total number of votes cast.

To quickly determine the winner, Aryan decides to use a HashMap to count the occurrences of each vote and identify the candidate who has received more than half of the total votes.

Example

Input

7

2 2 1 2 2 2 3

Output

2

Explanation

The votes are: 2, 2, 1, 2, 2, 3, 2

Count of each candidate:

2 appears 5 times 1 appears once 3 appears once

The majority element is the one that appears more than $N/2$ times. Since $7/2 = 3.5$, a number must appear at least 4 times to be the majority.

The number 2 appears 5 times, which is greater than 3.5, so the output is 2.

Input Format

The first line contains an integer N representing the number of votes cast.

The second line contains N space-separated integers representing the votes, where each integer corresponds to a candidate.

Output Format

The output prints an integer representing the majority element (the candidate who received more than $N/2$ votes).

If no such candidate exists, print -1.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 7

2 2 1 2 2 2 3

Output: 2

Answer

```
import java.util.HashMap;  
import java.util.Scanner;
```

```
// You are using Java  
import java.util.Scanner;  
import java.util.HashMap;
```

```
class MajorityElementFinder {  
    public static int findMajorityElement(int[] arr) {  
        HashMap<Integer, Integer> map = new HashMap<>();  
        int n = arr.length;  
        for (int num : arr) {
```

```

        map.put(num, map.getDefault(num, 0) + 1);
    }
    for (Integer key : map.keySet()) {
        if (map.get(key) > n / 2) {
            return key;
        }
    }
    return -1;
}
}

class Main {
    public static void main(String[] args) {
        Scanner scanner = new Scanner(System.in);
        int N = scanner.nextInt();
        int[] arr = new int[N];

        for (int i = 0; i < N; i++) {
            arr[i] = scanner.nextInt();
        }

        int result = MajorityElementFinder.findMajorityElement(arr);
        System.out.println(result);

        scanner.close();
    }
}

```

Status : Correct

Marks : 10/10