

# Rajalakshmi Engineering College

Name: Jai Shuriya J  
Email: 240701200@rajalakshmi.edu.in  
Roll no: 240701200  
Phone: 8754381941  
Branch: REC  
Department: CSE - Section 10  
Batch: 2028  
Degree: B.E - CSE

Scan to verify results



## 2024\_28\_III\_OOPS Using Java Lab

### REC\_2028\_OOPS using Java\_Week 9\_CY

Attempt : 1  
Total Mark : 40  
Marks Obtained : 40

#### Section 1 : Coding

##### 1. Problem Statement

Rahul is working on a list manipulation problem where he needs to reverse a specific subarray using a stack. Given an array and two indices  $l$  and  $r$ , he wants to reverse only the portion of the array from index  $l$  to  $r$  (both inclusive) while keeping the rest of the array unchanged.

Since Rahul wants to solve this problem efficiently, he decides to use a stack to reverse the subarray in  $O(r - l)$  time.

Your task is to help Rahul by implementing this functionality.

##### ***Input Format***

The first line contains an integer  $n$ , the size of the array.

The second line contains n space-separated integers arr[i].

The third line contains two integers l and r, denoting the start and end indices of the subarray to reverse.

Note: The array follows 0-based indexing.

### **Output Format**

The output prints the modified array after reversing the subarray between indices l and r.

Refer to the sample output for formatting specifications.

### **Sample Test Case**

Input: 6

1 2 3 4 5 6

1 4

Output: 1 5 4 3 2 6

### **Answer**

```
import java.util.*;
```

```
public class Main {
```

```
    public static void main(String[] args) {  
        Scanner sc = new Scanner(System.in);  
        int n = sc.nextInt();  
        int[] arr = new int[n];
```

```
        for (int i = 0; i < n; i++) {  
            arr[i] = sc.nextInt();  
        }
```

```
        int l = sc.nextInt();  
        int r = sc.nextInt();  
        sc.close();
```

```
        Stack<Integer> stack = new Stack<>();
```

```

        for (int i = l; i <= r; i++) {
            stack.push(arr[i]);
        }

        for (int i = l; i <= r; i++) {
            arr[i] = stack.pop();
        }

        for (int i = 0; i < n; i++) {
            System.out.print(arr[i] + " ");
        }
    }
}

```

**Status :** Correct

**Marks :** 10/10

## 2. Problem Statement

Mesa, a store manager, needs a program to manage inventory items. Define a class `ItemType` with private attributes for name, deposit, and cost per day. Create an `ArrayList` in the Main class to store `ItemType` objects, allowing input and display.

Note: Use "%-20s%-20s%-20s" for formatting output in tabular format, display double values with 1 decimal place.

### **Input Format**

The first line of input consists of an integer `n`, representing the number of items.

For each of the `n` items, there are three lines:

1. The name of the item (a string)
2. The deposit amount (a double value)
3. The cost per day (a double value)

### **Output Format**

The output prints a formatted table with columns for name, deposit and cost per day.

Refer to the sample output for formatting specifications.

### **Sample Test Case**

Input: 3  
Laptop  
10000.0  
250.0  
Light  
1000.0  
50.0  
Fan  
1000.0  
100.0

Output: Name	Deposit	Cost Per Day
Laptop	10000.0	250.0
Light	1000.0	50.0
Fan	1000.0	100.0

### **Answer**

```
import java.util.ArrayList;
import java.util.List;
import java.util.Scanner;

class ItemType {
    private String name;
    private Double deposit;
    private Double costPerDay;

    public String toString() {
        return String.format("%-20s%-20s%-20s", name, deposit, costPerDay);
    }

    public ItemType(String name, Double deposit, Double costPerDay) {
        super();
        this.name = name;
        this.deposit = deposit;
        this.costPerDay = costPerDay;
    }
}
```

```

}
class ArrayListObjectMain {
    public static void main(String args[]) {
        List<ItemType> items = new ArrayList<>();
        Scanner sc = new Scanner(System.in);
        int n = Integer.parseInt(sc.nextLine());

        for (int i = 0; i < n; i++) {
            String name = sc.nextLine();
            Double deposit = Double.parseDouble(sc.nextLine());
            Double costPerDay = Double.parseDouble(sc.nextLine());
            items.add(new ItemType(name, deposit, costPerDay));
        }
        System.out.format("%-20s%-20s%-20s", "Name", "Deposit", "Cost Per Day");
        System.out.println();

        for (ItemType item : items) {
            System.out.println(item);
        }
    }
}

```

**Status :** Correct

**Marks :** 10/10

### 3. Problem Statement

Rahul, a stock trader, wants to analyze the stock prices of a company over several days. For each day, he wants to determine the stock span, which is the number of consecutive days (including the current day) where the stock price is less than or equal to the price on that day.

The stock span helps him understand how long a stock has been continuously increasing or staying the same. You need to help Rahul by computing the stock span for each day using a Stack data structure efficiently.

Example:

Input:

7

100 80 60 70 60 75 85

Output:

1 1 1 2 1 4 6

Explanation:

For each day:

Day 1: Price = 100 Span = 1 (Only this day) Day 2: Price = 80 Span = 1 (Only this day) Day 3: Price = 60 Span = 1 (Only this day) Day 4: Price = 70 Span = 2 (Includes today and previous day) Day 5: Price = 60 Span = 1 (Only this day) Day 6: Price = 75 Span = 4 (Includes today and previous three days) Day 7: Price = 85 Span = 6 (Includes today and previous five days)

### ***Input Format***

The first line contains an integer n, the number of days.

The second line contains n space-separated integers prices[i], where prices[i] represents the stock price on the i-th day.

### ***Output Format***

The output prints n space-separated integers representing the stock span for each day.

Refer to the sample output for formatting specifications.

### ***Sample Test Case***

Input: 7

100 80 60 70 60 75 85

Output: 1 1 1 2 1 4 6

### ***Answer***

```
import java.util.*;

public class Main {
```

```

public static void main(String[] args) {
    Scanner sc = new Scanner(System.in);
    int n = sc.nextInt();
    int[] prices = new int[n];
    for (int i = 0; i < n; i++) {
        prices[i] = sc.nextInt();
    }
    sc.close();

    int[] span = new int[n];
    Stack<Integer> stack = new Stack<>();

    for (int i = 0; i < n; i++) {
        while (!stack.isEmpty() && prices[stack.peek()] <= prices[i]) {
            stack.pop();
        }
        span[i] = stack.isEmpty() ? (i + 1) : (i - stack.peek());
        stack.push(i);
    }

    for (int i = 0; i < n; i++) {
        System.out.print(span[i] + " ");
    }
}

```

**Status :** Correct

**Marks :** 10/10

#### 4. Problem Statement

Aarav is developing a music playlist application where users can manage their favorite songs. He wants to implement a feature that allows users to reorder the playlist by moving a song from one position to another.

You need to implement a function that performs the following operations using a LinkedList:

Add songs to the playlist in the given order. Move a song from a specified position to another position in the playlist. Print the final playlist after all operations.

### ***Input Format***

The first line of the input consists of an integer  $n$  representing the number of songs.

The next  $n$  lines, each containing a string representing a song name.

After the songs are given the next line contains an integer  $m$ , the number of move operations.

The next  $m$  lines, each containing two integers  $x$  and  $y$  representing the move operation where the song at position  $x$  (0-based index) should be moved to position  $y$ .

### ***Output Format***

The output prints the final playlist, each song on a new line.

Refer to the sample output for formatting specifications.

### ***Sample Test Case***

Input: 5

SongA

SongB

SongC

SongD

SongE

2

2 4

0 3

Output: SongB

SongD

SongE

SongA

SongC

### ***Answer***

```
import java.util.*;
public class Main {
    public static void main(String[] args) {
```

```
Scanner sc = new Scanner(System.in);
int n = sc.nextInt();
sc.nextLine();
LinkedList<String> playlist = new LinkedList<>();
for (int i = 0; i < n; i++) playlist.add(sc.nextLine());
int m = sc.nextInt();
for (int i = 0; i < m; i++) {
    int x = sc.nextInt();
    int y = sc.nextInt();
    String song = playlist.remove(x);
    playlist.add(y, song);
}
for (String song : playlist) System.out.println(song);
}
```

**Status :** Correct

**Marks :** 10/10