

POLE CERTIFICATE

ID 292920



Client : **All Telecoms**
Carrier : **Optus**
Site Name : **Austins Ferry**
Site State : **TAS**
Site Number : **H8097**
Site Existence : **Existing site**

Pole Type : **SR3-BM27-585**
Pole Height AGL : **27.0m**
Pole Tip Diameter : **585mm**
Pole Strength Reduction Factor ($\emptyset$) : **0.9**
Pole general assembly drawing : **N/A**
Climbing System : **Step Bolts**
Exposure classification : **A2**

LOADING DATA

Geographic/Topographic data to AS1170.2:2021 and sail area data provided by or approved by client.
Refer to the Data Sheet provided by All Telecoms dated 20-May-2025.

Wind Region : **A4**
Terrain Category (TC) : **2.1**
Avg. Topographic Multiplier (Mt) : **1.28**
Wind Direction Multiplier (Md) : **1.00**
Shielding Multiplier (Ms) : **1.00**
Climate Change Multiplier (Mc) : **1.00**
Average Recurrence Interval (ARI) : **V500**
Regional Wind Speed (V_R) : **45 m/s**
Serviceability Wind Speed (V_S) : **27 m/s**

Distance (m)	Mass (kg)	ESA (m ²)	Attachment Description Load Case : Target Solution
3.9	159	3.33	1 x Commscope RRVV2VV-6533D-R8 @70° - New (Shared)+1 x Commscope RRVV2VV-6533D-R8 @200° - New (Shared)+1 x Commscope RRVV2VV-6533D-R8 @340° - New (Shared)
2.9	15	0.30	1 x ERICSSON AIR3268 (B78Y) @70° - New (Optus)
2.9	15	0.30	1 x ERICSSON AIR3268 (B78Y) @200° - New (Optus)
2.9	15	0.30	1 x ERICSSON AIR3268 (B78Y) @340° - New (Optus)
3.9	24	0.46	1 x NOKIA AVQL (NR35) @70° - New (Vodafone)
3.9	24	0.46	1 x NOKIA AVQL (NR35) @200° - New (Vodafone)
3.9	24	0.46	1 x NOKIA AVQL (NR35) @340° - New (Vodafone)
3.9	32	0.27	3 x ERICSSON RRU4480 (L7/NL9) - New (Optus)
3.9	45	0.34	3 x ERICSSON RRU4466 (L18/NL21/L26) - New (Optus)
2.9	32	0.68	6 x FUTURE ERICSSON RRU - Future (Optus)
2.9	24	0.20	3 x NOKIA AHPB (N7) - New (Vodafone)
2.9	17	0.19	3 x NOKIA AHCA (L850) - New (Vodafone)
3.9	32	0.50	6 x NOKIA AHEGG (18/21) - New (Vodafone)
3.9	8	0.50	3 x Commscope REJ FILTER (E14V00P21)- New (Optus)
3.9	11	0.50	3 x COM2g (E14F06P81) - New (Vodafone)
3.9	500	2.05	Collar Mount/Headframe - New (Optus)
6.1	50	0.75	1 x HUAWEI A11D06HS parabolic + 1 x ODU XMC-2H @120.89° - Existing (Optus)
0.0	33	1.93	2 x ARGUS RVVPX310B2 @90° - Existing (Telstra)
0.0	33	1.93	2 x ARGUS RVVPX310B2 @180° - Existing (Telstra)
0.0	33	1.93	2 x ARGUS RVVPX310B2 @340° - Existing (Telstra)
0.0	13	0.39	1 x ARGUS VVPX310R-V5 @90° - Existing (Telstra)
0.0	13	0.39	1 x ARGUS VVPX310R-V5 @180° - Existing (Telstra)
0.0	13	0.39	1 x ARGUS VVPX310R-V5 @340° - Existing (Telstra)
0.0	44	0.49	1 x ERICSSON AIR6488 @90° - Existing (Telstra)
0.0	44	0.49	1 x ERICSSON AIR6488 @180° - Existing (Telstra)
0.0	44	0.49	1 x ERICSSON AIR6488 @340° - Existing (Telstra)
-0.3	21	0.21	3 x ERICSSON RADIO 4415 (B3) (LTE1800) - Existing (Telstra)
0.5	21	0.21	3 x ERICSSON RADIO 4415 (B1) (LTE2100) - Existing (Telstra)
-0.3	21	0.21	3 x ERICSSON RRUS-32 (B7) (LTE2600) - Existing (Telstra)
0.0	1000	3.00	TRIANGULAR HEADFRAME 017866P105 - Existing (Telstra)

Start (m)	Finish (m)	Height (mm)	Width (mm)	Mass (kg/m)	Running Cables
3	22	200	300	50	Cable Tray 1
3	27	-	-	25	Internal Cables

POLE CERTIFICATE (Continued)

ID 292920



OUTPUT:

Limit State	GL Design Actions		Mo (max) at GL kNm	Base Loading	Rotation at 6.1m below tip		**Footing Rotation	
	M* kNm	V* kN			Calculated based on M*	Client specified limit	Used in M* calculations	At Mo (max)
SLS	854	43	N/A	36%	0.77°	1.00°	0.03°	N/A
ULS	2371	115	2390	99%	N/A	N/A	0.08°	0.07°

This pole is loaded to 99% of pole design strength under ULS.

The rotation of this pole is 77% of the specified rotation limit under SLS.

** Refer to Gamcorp Foundation Certificate 16721 dated 02-Sep-2025 by Lena Van Spaandonk NER 5038980 RPEQ 18703.

The pole foundation is loaded to 99% of its over-turning moment capacity under ULS (Mo foundation capacity = 2400 kNm).

NOTES :

- Civilmart poles are designed by the Product Design Section of Civilmart under the Civilmart Quality Management System which complies with ISO 9001:2015 and is certified by SAI Global Certification Services.
- Analysis based on COMMPOLE v1.0.0
Refer to the COMMPOLE User Guide UG2.0 for design assumptions, terms and other information.
- Reference standards AS4065:2010, AS1170.2:2021.
- The Exposure classification based on AS3600:-2018 Table 4.3 applies to the above-ground portion of the pole.
Protective coating is not required for any exposed joint components to exposure classification B1 or less.
- All attachments to the pole are to be shown in the Loading Data above. Distance is measured from top of the pole.
Negative distances signify attachments above the tip.
- ESA (m²) = Effective Sail Area = Projected vertical plane sail area x aerodynamic shape factor (drag coefficient).
- MPL = "maximum percentage loading" = (ultimate bending moment / design bending strength) %.
Design bending strength = strength reduction factor (SRF) x ultimate bending strength, where SRF = 0.9 or 1.0.
- SLS = Serviceability Limit State; ULS = Ultimate Limit State; GL = Ground Level.
- Design Actions include actions due to footing rotation.
- SLS Mo (max) corresponds to the serviceability rotation limit specified by the client.
- The structural adequacy of attachments to the pole have not been assessed in this certificate.
- Unless stated otherwise, only the loading data provided by the client has been used in this assessment.
- Civilmart accepts no responsibility for the accuracy and correctness of the loading data provided.

Assessment No. 292920_1:
03-Sep-25

Based on the loading data shown and information herein, and other inferred assumptions, the SR3-BM27-585 design is deemed appropriate for this application.

ASSESSED: Aaron Zhang
Applications Engineer (B.E.Civil)

CHECKED: Horatio Serbanescu | CPEng RPEQ NER 3078946
Sen. Prod. Design Engineer | RPEQ 12752