



**DEPARTMENT OF COMPUTER SCIENCE AND
ENGINEERING**

CSA05-DATABASE MANAGEMENT SYSTEMS

LAB MANUAL

DDL Commands – CREATE, ALTER, DROP

AIM:

To Create, Alter, Drop, Rename, Truncate using Data Definition Language (DDL) statements. **Description:**

Data Definition Language (DDL) statements are used to define the database structure or schema. **DDL Commands:** Create, Alter, Drop, Rename, Truncate

- CREATE - to create objects in the database
- ALTER - alters the structure of the database
- DROP - delete objects from the database
- TRUNCATE - remove all records from a table, including all spaces allocated for the records are removed
- RENAME - rename an object

SYNTAX:

```
CREATE TABLE table_name (  
    column1 datatype,  
    column2 datatype,  
    column3 datatype,  
    ...  
    columnN datatype  
);
```

ALTER A TABLE

To add a column in a table

```
ALTER TABLE table_name  
ADD column_namdatatype;
```

To delete a column in a table

ALTER TABLE table_name

DROP COLUMN column_name;

DROP TABLE

DROP TABLE table_name;

TRUNCATE TABLE

TRUNCATE TABLE table_name;

Questions:

1) Create a table name BANK RECORD with following structure.

SNO	NAME	PhoneNumber	Email	AccountType	Balance
1	JAISURIYA	9159233369	jaisuriya@gmail.com	Saving	15000
2	AKASH	6381125471	akash@gmail.com	Current	300000
3	GOPAL	8248357812	gopal@gmail.com	Saving	150000
4	JEEVA	6382914421	jeeva@gmail.com	Saving	2000
5	SHYAM	8216153842	shyam@gmail.com	Current	3000
6	SANJAY	9633349576	sanjay@gmail.com	Saving	12000
7	PREETHI	6738112541	preethi@gmail.com	Current	3500
8	PRIYA	9159444389	priya@gmail.com	Current	4000
9	VISHAL	6811353471	vishal@gmail.com	Saving	4000
10	LOKI	6739892549	loki@gmail.com	Current	5000

#	Column Name	Description	Data Type
1	SNO	Serial Number	INT
2	Name	Account Holder Name	VARCHAR(30)
3	PhoneNumber	Customer Phone Number	BIGINT

#	Column Name	Description	Data Type
4	Email	Customer Email Address	VARCHAR(50)
5	AccountType	Type of Bank Account (Saving/Current)	VARCHAR(20)
6	Balance	Account Balance	INT

2) Create a table name CUSTOMER with the following structure.

#	Column Name	Description	Data Type
1	CustomerID	Customer Identifier	INT
2	CustomerName	Customer Name	VARCHAR(30)
3	Gender	Customer Gender	CHAR(1)
4	DOB	Date of Birth	DATE
5	MobileNo	Mobile Number	BIGINT
6	City	Customer City	VARCHAR(30)

3) Create a table name ACCOUNT with the following structure.

#	Column Name	Description	Data Type
1	AccountNo	Account Number	BIGINT
2	HolderName	Account Holder Name	VARCHAR(30)
3	AccountType	Type of Account	VARCHAR(20)
4	Branch	Branch Name	VARCHAR(30)
5	IFSCCode	Bank IFSC Code	VARCHAR(15)
6	Balance	Account Balance	INT

- 4) Create a table name TRANSACTION with the following structure.

#	Column Name	Description	Data Type
1	TransactionID	Transaction Identifier	INT
2	AccountNo	Account Number	BIGINT
3	TransactionType	Credit or Debit	VARCHAR(10)
4	TransactionDate	Date of Transaction	DATE
5	Amount	Transaction Amount	INT
6	Status	Transaction Status	VARCHAR(15)

- 5) Modify the table ACCOUNT by adding a column named Branch of datatype VARCHAR(30).

OUTPUTS:

- 1)

```
MySQL Command Line Client
mysql> create table bankrecords(
-> SNO int(3),
-> Name char(30),
-> PhoneNumber bigint,
-> Email varchar(50),
-> AccountType char(10),
-> Balance int(10)
-> );
Query OK, 0 rows affected (0.14 sec)

mysql> desc bankrecords;
+-----+-----+-----+-----+-----+-----+
| Field | Type | Null | Key | Default | Extra |
+-----+-----+-----+-----+-----+-----+
| SNO   | int(3) | YES |     | NULL    |       |
| Name  | char(30) | YES |     | NULL    |       |
| PhoneNumber | bigint | YES |     | NULL    |       |
| Email | varchar(50) | YES |     | NULL    |       |
| AccountType | char(10) | YES |     | NULL    |       |
| Balance | int(10) | YES |     | NULL    |       |
+-----+-----+-----+-----+-----+-----+
6 rows in set (0.00 sec)

mysql> _
```

2)

```
MySQL Command Line Client
mysql> create table account(
-> AccountNo bigint,
-> HolderName char(30),
-> AccountType char(10),
-> Branch char(20),
-> IFSCCode char(15),
-> Balance int(10));
Query OK, 0 rows affected (0.06 sec)

mysql> desc account;
+-----+-----+-----+-----+-----+-----+
| Field | Type | Null | Key | Default | Extra |
+-----+-----+-----+-----+-----+-----+
| AccountNo | bigint | YES | | NULL | |
| HolderName | char(30) | YES | | NULL | |
| AccountType | char(10) | YES | | NULL | |
| Branch | char(20) | YES | | NULL | |
| IFSCCode | char(15) | YES | | NULL | |
| Balance | int(10) | YES | | NULL | |
+-----+-----+-----+-----+-----+-----+
6 rows in set (0.00 sec)

mysql> _
```

3)

```
MySQL Command Line Client
mysql> create table branch(
-> BranchID int(10),
-> BranchName char(20),
-> BranchManager char(30));
Query OK, 0 rows affected (0.11 sec)

mysql> desc branch;
+-----+-----+-----+-----+-----+-----+
| Field | Type | Null | Key | Default | Extra |
+-----+-----+-----+-----+-----+-----+
| BranchID | int(10) | YES | | NULL | |
| BranchName | char(20) | YES | | NULL | |
| BranchManager | char(30) | YES | | NULL | |
+-----+-----+-----+-----+-----+-----+
3 rows in set (0.00 sec)

mysql> _
```

4)

```
MySQL Command Line Client
mysql> create table transaction(
-> TransactionID int(3),
-> AccountNo bigint,
-> TransactionType char(10),
-> Amount int(10),
-> TransactionDate date,
-> BranchID int(10));
Query OK, 0 rows affected (0.09 sec)

mysql> desc transaction;
+-----+-----+-----+-----+-----+-----+
| Field | Type | Null | Key | Default | Extra |
+-----+-----+-----+-----+-----+-----+
| TransactionID | int(3) | YES | | NULL | |
| AccountNo | bigint | YES | | NULL | |
| TransactionType | char(10) | YES | | NULL | |
| Amount | int(10) | YES | | NULL | |
| TransactionDate | date | YES | | NULL | |
| BranchID | int(10) | YES | | NULL | |
+-----+-----+-----+-----+-----+-----+
6 rows in set (0.00 sec)

mysql>
```

5)

```
MySQL Command Line Client
mysql> alter table account add Branch char(20);
Query OK, 2 rows affected (0.09 sec)
Records: 2 Duplicates: 0 Warnings: 0

mysql> desc account;
+-----+-----+-----+-----+-----+-----+
| Field | Type | Null | Key | Default | Extra |
+-----+-----+-----+-----+-----+-----+
| AccountNo | bigint | YES | | NULL | |
mysql> desc account;
+-----+-----+-----+-----+-----+-----+
| Field | Type | Null | Key | Default | Extra |
+-----+-----+-----+-----+-----+-----+
| AccountNo | bigint | YES | | NULL | |
| HolderName | char(30) | YES | | NULL | |
| AccountType | char(10) | YES | | NULL | |
| IFSCCode | char(15) | YES | | NULL | |
| Balance | int(10) | YES | | NULL | |
| Branch | char(20) | YES | | NULL | |
+-----+-----+-----+-----+-----+-----+
6 rows in set (0.00 sec)

mysql>
```

RESULT:

Thus, the BANKRECORDS, ACCOUNT, BRANCH, and TRANSACTION tables were successfully created, altered, and modified using Data Definition Language (DDL) commands such as CREATE, ALTER, DROP, RENAME, and TRUNCATE.