

MySQL Workbench

Local instance MySQL80 x MySQL Model x

File Edit View Query Database Server Tools Scripting Help

ddl dml ACID Properties isolation data

Limit to 50000 rows

```

1
2 • USE bookFlow_db;
3
4 • CREATE TABLE orders (
5     ord_no INT PRIMARY KEY,
6     purch_amt DECIMAL(10,2),
7     ord_date DATE,
8     customer_id INT,
9     salesman_id INT
10 );

```

Result Grid

customer_id	total_purchase
3002	8870.86
3009	2590.90
3007	2400.60
3004	1983.43
3005	1099.00

orders 1 orders 2 orders 3 orders 4 orders 5 Result 6 Result 7 Result 8 Result 9 Result 10 Result 11 Result 12 Result 13 x Result 14 Result 15 Result 16

Output

Action Output

#	Time	Action	Message	Duration / Fetch
431	21:37:51	SELECT customer_id, SUM(purch_amt) AS total_purchase FROM orders GROUP BY customer_id HAVING SUM(purch_amt) > ...	2 row(s) returned	0.000 sec / 0.000 sec
432	21:37:51	SELECT customer_id, COUNT(*) AS total_orders FROM orders GROUP BY customer_id HAVING COUNT(*) > 1 LIMIT 0, 50000	3 row(s) returned	0.000 sec / 0.000 sec
433	21:37:51	SELECT customer_id, SUM(purch_amt) AS total_purchase FROM orders GROUP BY customer_id HAVING SUM(purch_amt) > ...	5 row(s) returned	0.000 sec / 0.000 sec
434	21:37:51	SELECT customer_id, MAX(purch_amt) AS max_purchase FROM orders GROUP BY customer_id HAVING MAX(purch_amt) BE...	3 row(s) returned	0.000 sec / 0.000 sec
435	21:37:51	SELECT salesman_id, COUNT(*) AS total_orders FROM orders GROUP BY salesman_id HAVING COUNT(*) >= 2 LIMIT 0, 50000	3 row(s) returned	0.000 sec / 0.000 sec
436	21:37:51	SELECT ord_date, MAX(purch_amt) AS highest_purchase FROM orders GROUP BY ord_date HAVING MAX(purch_amt) > 200...	4 row(s) returned	0.000 sec / 0.000 sec

Query Completed

MySQL Workbench

Local instance MySQL80 x MySQL Model x

File Edit View Query Database Server Tools Scripting Help

ddl dml ACID Properties isolation data

Limit to 50000 rows

```

1
2 • USE bookFlow_db;
3
4 • CREATE TABLE orders (
5     ord_no INT PRIMARY KEY,
6     purch_amt DECIMAL(10,2),
7     ord_date DATE,
8     customer_id INT,
9     salesman_id INT
10 );

```

Result Grid

customer_id	total_orders
3005	2
3002	3
3009	2

orders 1 orders 2 orders 3 orders 4 orders 5 Result 6 Result 7 Result 8 Result 9 Result 10 Result 11 Result 12 x Result 13 Result 14 Result 15 Result 16

Output

Action Output

#	Time	Action	Message	Duration / Fetch
431	21:37:51	SELECT customer_id, SUM(purch_amt) AS total_purchase FROM orders GROUP BY customer_id HAVING SUM(purch_amt) > ...	2 row(s) returned	0.000 sec / 0.000 sec
432	21:37:51	SELECT customer_id, COUNT(*) AS total_orders FROM orders GROUP BY customer_id HAVING COUNT(*) > 1 LIMIT 0, 50000	3 row(s) returned	0.000 sec / 0.000 sec
433	21:37:51	SELECT customer_id, SUM(purch_amt) AS total_purchase FROM orders GROUP BY customer_id HAVING SUM(purch_amt) > ...	5 row(s) returned	0.000 sec / 0.000 sec
434	21:37:51	SELECT customer_id, MAX(purch_amt) AS max_purchase FROM orders GROUP BY customer_id HAVING MAX(purch_amt) BE...	3 row(s) returned	0.000 sec / 0.000 sec
435	21:37:51	SELECT salesman_id, COUNT(*) AS total_orders FROM orders GROUP BY salesman_id HAVING COUNT(*) >= 2 LIMIT 0, 50000	3 row(s) returned	0.000 sec / 0.000 sec
436	21:37:51	SELECT ord_date, MAX(purch_amt) AS highest_purchase FROM orders GROUP BY ord_date HAVING MAX(purch_amt) > 200...	4 row(s) returned	0.000 sec / 0.000 sec

Query Completed

MySQL Workbench

Local instance MySQL80 x MySQL Model x

File Edit View Query Database Server Tools Scripting Help

ddl dml ACID Properties isolation data

Limit to 50000 rows

```

1
2 • USE bookflow_db;
3
4 • CREATE TABLE orders (
5     ord_no INT PRIMARY KEY,
6     purch_amt DECIMAL(10,2),
7     ord_date DATE,
8     customer_id INT,
9     salesman_id INT
10 );

```

Result Grid

customer_id	highest_purchase
3005	948.50
3002	5760.00
3009	2480.40
3007	2400.60
3001	270.65
3004	1983.43
3003	75.29
3008	250.45

orders 1 orders 2 orders 3 orders 4 orders 5 Result 6 Result 7 Result 8 Result 9 x Result 10 Result 11 Result 12 Result 13 Result 14 Result 15 Result 16 Read Only

Output

Action Output

#	Time	Action	Message	Duration / Fetch
431	21:37:51	SELECT customer_id, SUM(purch_amt) AS total_purchase FROM orders GROUP BY customer_id HAVING SUM(purch_amt) > ...	2 row(s) returned	0.000 sec / 0.000 sec
432	21:37:51	SELECT customer_id, COUNT(*) AS total_orders FROM orders GROUP BY customer_id HAVING COUNT(*) > 1 LIMIT 0.50000	3 row(s) returned	0.000 sec / 0.000 sec
433	21:37:51	SELECT customer_id, SUM(purch_amt) AS total_purchase FROM orders GROUP BY customer_id HAVING SUM(purch_amt) > ...	5 row(s) returned	0.000 sec / 0.000 sec
434	21:37:51	SELECT customer_id, MAX(purch_amt) AS max_purchase FROM orders GROUP BY customer_id HAVING MAX(purch_amt) BE...	3 row(s) returned	0.000 sec / 0.000 sec
435	21:37:51	SELECT salesman_id, COUNT(*) AS total_orders FROM orders GROUP BY salesman_id HAVING COUNT(*) >= 2 LIMIT 0.50000	3 row(s) returned	0.000 sec / 0.000 sec
436	21:37:51	SELECT ord_date, MAX(purch_amt) AS highest_purchase FROM orders GROUP BY ord_date HAVING MAX(purch_amt) > 200...	4 row(s) returned	0.000 sec / 0.000 sec

Query Completed

MySQL Workbench

Local instance MySQL80 x MySQL Model x

File Edit View Query Database Server Tools Scripting Help

ddl dml ACID Properties isolation data

Limit to 50000 rows

```

1
2 • USE bookflow_db;
3
4 • CREATE TABLE orders (
5     ord_no INT PRIMARY KEY,
6     purch_amt DECIMAL(10,2),
7     ord_date DATE,
8     customer_id INT,
9     salesman_id INT
10 );

```

Result Grid

total_revenue	average_order	highest_order	lowest_order	total_orders
17541.18	1461.765000	5760.00	65.26	12

orders 1 orders 2 orders 3 orders 4 orders 5 Result 6 x Result 7 Result 8 Result 9 Result 10 Result 11 Result 12 Result 13 Result 14 Result 15 Result 16 Read Only

Output

Action Output

#	Time	Action	Message	Duration / Fetch
431	21:37:51	SELECT customer_id, SUM(purch_amt) AS total_purchase FROM orders GROUP BY customer_id HAVING SUM(purch_amt) > ...	2 row(s) returned	0.000 sec / 0.000 sec
432	21:37:51	SELECT customer_id, COUNT(*) AS total_orders FROM orders GROUP BY customer_id HAVING COUNT(*) > 1 LIMIT 0.50000	3 row(s) returned	0.000 sec / 0.000 sec
433	21:37:51	SELECT customer_id, SUM(purch_amt) AS total_purchase FROM orders GROUP BY customer_id HAVING SUM(purch_amt) > ...	5 row(s) returned	0.000 sec / 0.000 sec
434	21:37:51	SELECT customer_id, MAX(purch_amt) AS max_purchase FROM orders GROUP BY customer_id HAVING MAX(purch_amt) BE...	3 row(s) returned	0.000 sec / 0.000 sec
435	21:37:51	SELECT salesman_id, COUNT(*) AS total_orders FROM orders GROUP BY salesman_id HAVING COUNT(*) >= 2 LIMIT 0.50000	3 row(s) returned	0.000 sec / 0.000 sec
436	21:37:51	SELECT ord_date, MAX(purch_amt) AS highest_purchase FROM orders GROUP BY ord_date HAVING MAX(purch_amt) > 200...	4 row(s) returned	0.000 sec / 0.000 sec

Query Completed

MySQL Workbench

Local instance MySQL80 x MySQL Model x

File Edit View Query Database Server Tools Scripting Help

ddl dml ACID Properties isolation data

Limit to 50000 rows

```

1
2 • USE bookflow_db;
3
4 • CREATE TABLE orders (
5     ord_no INT PRIMARY KEY,
6     purch_amt DECIMAL(10,2),
7     ord_date DATE,
8     customer_id INT,
9     salesman_id INT
10 );

```

Result Grid

ord_no	purch_amt	ord_date	customer_id	salesman_id
70013	3045.60	2012-04-25	3002	5001
70012	250.45	2012-06-27	3008	5002
70005	2400.60	2012-07-27	3007	5001
70004	110.50	2012-08-17	3009	5003
70011	75.29	2012-08-17	3003	5007
70007	948.50	2012-09-10	3005	5002
70008	5760.00	2012-09-10	3002	5001
70009	270.65	2012-09-10	3001	5005
70001	150.50	2012-10-05	3005	5002
70002	65.26	2012-10-05	3002	5001
70003	2480.40	2012-10-10	3009	5003

orders 1 orders 2 orders 3 orders 4 orders 5 x Result 6 Result 7 Result 8 Result 9 Result 10 Result 11 Result 12 Result 13 Result 14 Result 15 Result 16

Output

Action Output

#	Time	Action	Message	Duration / Fetch
431	21:37:51	SELECT customer_id, SUM(purch_amt) AS total_purchase FROM orders GROUP BY customer_id HAVING SUM(purch_amt) > ...	2 row(s) returned	0.000 sec / 0.000 sec
432	21:37:51	SELECT customer_id, COUNT(*) AS total_orders FROM orders GROUP BY customer_id HAVING COUNT(*) > 1 LIMIT 0, 50000	3 row(s) returned	0.000 sec / 0.000 sec
433	21:37:51	SELECT customer_id, SUM(purch_amt) AS total_purchase FROM orders GROUP BY customer_id HAVING SUM(purch_amt) > ...	5 row(s) returned	0.000 sec / 0.000 sec
434	21:37:51	SELECT customer_id, MAX(purch_amt) AS max_purchase FROM orders GROUP BY customer_id HAVING MAX(purch_amt) BE...	3 row(s) returned	0.000 sec / 0.000 sec
435	21:37:51	SELECT salesman_id, COUNT(*) AS total_orders FROM orders GROUP BY salesman_id HAVING COUNT(*) >= 2 LIMIT 0, 50000	3 row(s) returned	0.000 sec / 0.000 sec
436	21:37:51	SELECT ord_date, MAX(purch_amt) AS highest_purchase FROM orders GROUP BY ord_date HAVING MAX(purch_amt) > 200...	4 row(s) returned	0.000 sec / 0.000 sec

Query Completed

MySQL Workbench

Local instance MySQL80 x MySQL Model x

File Edit View Query Database Server Tools Scripting Help

ddl dml ACID Properties isolation data

Limit to 50000 rows

```

1
2 • USE bookflow_db;
3
4 • CREATE TABLE orders (
5     ord_no INT PRIMARY KEY,
6     purch_amt DECIMAL(10,2),
7     ord_date DATE,
8     customer_id INT,
9     salesman_id INT
10 );

```

Result Grid

ord_no	purch_amt	ord_date	customer_id	salesman_id
70008	5760.00	2012-09-10	3002	5001
70013	3045.60	2012-04-25	3002	5001
70003	2480.40	2012-10-10	3009	5003
70005	2400.60	2012-07-27	3007	5001
70010	1983.43	2012-10-10	3004	5006
70007	948.50	2012-09-10	3005	5002
70009	270.65	2012-09-10	3001	5005
70012	250.45	2012-06-27	3008	5002
70001	150.50	2012-10-05	3005	5002
70004	110.50	2012-08-17	3009	5003
70011	75.29	2012-08-17	3003	5007

orders 1 orders 2 orders 3 orders 4 x orders 5 Result 6 Result 7 Result 8 Result 9 Result 10 Result 11 Result 12 Result 13 Result 14 Result 15 Result 16

Output

Action Output

#	Time	Action	Message	Duration / Fetch
431	21:37:51	SELECT customer_id, SUM(purch_amt) AS total_purchase FROM orders GROUP BY customer_id HAVING SUM(purch_amt) > ...	2 row(s) returned	0.000 sec / 0.000 sec
432	21:37:51	SELECT customer_id, COUNT(*) AS total_orders FROM orders GROUP BY customer_id HAVING COUNT(*) > 1 LIMIT 0, 50000	3 row(s) returned	0.000 sec / 0.000 sec
433	21:37:51	SELECT customer_id, SUM(purch_amt) AS total_purchase FROM orders GROUP BY customer_id HAVING SUM(purch_amt) > ...	5 row(s) returned	0.000 sec / 0.000 sec
434	21:37:51	SELECT customer_id, MAX(purch_amt) AS max_purchase FROM orders GROUP BY customer_id HAVING MAX(purch_amt) BE...	3 row(s) returned	0.000 sec / 0.000 sec
435	21:37:51	SELECT salesman_id, COUNT(*) AS total_orders FROM orders GROUP BY salesman_id HAVING COUNT(*) >= 2 LIMIT 0, 50000	3 row(s) returned	0.000 sec / 0.000 sec
436	21:37:51	SELECT ord_date, MAX(purch_amt) AS highest_purchase FROM orders GROUP BY ord_date HAVING MAX(purch_amt) > 200...	4 row(s) returned	0.000 sec / 0.000 sec

Query Completed

MySQL Workbench

Local instance MySQL80 x MySQL Model x

File Edit View Query Database Server Tools Scripting Help

ddl dml ACID Properties isolation data

Limit to 50000 rows

```

1
2 • USE bookFlow_db;
3
4 • CREATE TABLE orders (
5     ord_no INT PRIMARY KEY,
6     purch_amt DECIMAL(10,2),
7     ord_date DATE,
8     customer_id INT,
9     salesman_id INT
10 );

```

Result Grid

ord_no	purch_amt	ord_date	customer_id	salesman_id
70002	65.26	2012-10-05	3002	5001
70005	2400.60	2012-07-27	3007	5001
70008	5760.00	2012-09-10	3002	5001
70013	3045.60	2012-04-25	3002	5001

orders 1 orders 2 orders 3 x orders 4 orders 5 Result 6 Result 7 Result 8 Result 9 Result 10 Result 11 Result 12 Result 13 Result 14 Result 15 Result 16 Apply Revert

Output

Action Output

#	Time	Action	Message	Duration / Fetch
431	21:37:51	SELECT customer_id, SUM(purch_amt) AS total_purchase FROM orders GROUP BY customer_id HAVING SUM(purch_amt) > ...	2 row(s) returned	0.000 sec / 0.000 sec
432	21:37:51	SELECT customer_id, COUNT(*) AS total_orders FROM orders GROUP BY customer_id HAVING COUNT(*) > 1 LIMIT 0, 50000	3 row(s) returned	0.000 sec / 0.000 sec
433	21:37:51	SELECT customer_id, SUM(purch_amt) AS total_purchase FROM orders GROUP BY customer_id HAVING SUM(purch_amt) > ...	5 row(s) returned	0.000 sec / 0.000 sec
434	21:37:51	SELECT customer_id, MAX(purch_amt) AS max_purchase FROM orders GROUP BY customer_id HAVING MAX(purch_amt) BE...	3 row(s) returned	0.000 sec / 0.000 sec
435	21:37:51	SELECT salesman_id, COUNT(*) AS total_orders FROM orders GROUP BY salesman_id HAVING COUNT(*) >= 2 LIMIT 0, 50000	3 row(s) returned	0.000 sec / 0.000 sec
436	21:37:51	SELECT ord_date, MAX(purch_amt) AS highest_purchase FROM orders GROUP BY ord_date HAVING MAX(purch_amt) > 200...	4 row(s) returned	0.000 sec / 0.000 sec

Query Completed

MySQL Workbench

Local instance MySQL80 x MySQL Model x

File Edit View Query Database Server Tools Scripting Help

ddl dml ACID Properties isolation data

Limit to 50000 rows

```

1
2 • USE bookFlow_db;
3
4 • CREATE TABLE orders (
5     ord_no INT PRIMARY KEY,
6     purch_amt DECIMAL(10,2),
7     ord_date DATE,
8     customer_id INT,
9     salesman_id INT
10 );

```

Result Grid

ord_no	purch_amt	ord_date	customer_id	salesman_id
70007	948.50	2012-09-10	3005	5002
70008	5760.00	2012-09-10	3002	5001
70009	270.65	2012-09-10	3001	5005

orders 1 orders 2 x orders 3 orders 4 orders 5 Result 6 Result 7 Result 8 Result 9 Result 10 Result 11 Result 12 Result 13 Result 14 Result 15 Result 16 Apply Revert

Output

Action Output

#	Time	Action	Message	Duration / Fetch
431	21:37:51	SELECT customer_id, SUM(purch_amt) AS total_purchase FROM orders GROUP BY customer_id HAVING SUM(purch_amt) > ...	2 row(s) returned	0.000 sec / 0.000 sec
432	21:37:51	SELECT customer_id, COUNT(*) AS total_orders FROM orders GROUP BY customer_id HAVING COUNT(*) > 1 LIMIT 0, 50000	3 row(s) returned	0.000 sec / 0.000 sec
433	21:37:51	SELECT customer_id, SUM(purch_amt) AS total_purchase FROM orders GROUP BY customer_id HAVING SUM(purch_amt) > ...	5 row(s) returned	0.000 sec / 0.000 sec
434	21:37:51	SELECT customer_id, MAX(purch_amt) AS max_purchase FROM orders GROUP BY customer_id HAVING MAX(purch_amt) BE...	3 row(s) returned	0.000 sec / 0.000 sec
435	21:37:51	SELECT salesman_id, COUNT(*) AS total_orders FROM orders GROUP BY salesman_id HAVING COUNT(*) >= 2 LIMIT 0, 50000	3 row(s) returned	0.000 sec / 0.000 sec
436	21:37:51	SELECT ord_date, MAX(purch_amt) AS highest_purchase FROM orders GROUP BY ord_date HAVING MAX(purch_amt) > 200...	4 row(s) returned	0.000 sec / 0.000 sec

Query Completed

MySQL Workbench

Local instance MySQL80 x MySQL Model x

File Edit View Query Database Server Tools Scripting Help

ddl dml ACID Properties isolation data

Limit to 50000 rows

```
1
2 USE bookFlow_db;
3
4 CREATE TABLE orders (
5     ord_no INT PRIMARY KEY,
6     purch_amt DECIMAL(10,2),
7     ord_date DATE,
8     customer_id INT,
9     salesman_id INT
10 );
```

Result Grid

ord_no	purch_amt	ord_date	customer_id	salesman_id
70003	2480.40	2012-10-10	3009	5003
70005	2400.60	2012-07-27	3007	5001
70008	5760.00	2012-09-10	3002	5001
70013	3045.60	2012-04-25	3002	5001

orders 1 x orders 2 orders 3 orders 4 orders 5 Result 6 Result 7 Result 8 Result 9 Result 10 Result 11 Result 12 Result 13 Result 14 Result 15 Result 16 Apply Revert

Output

Action Output

#	Time	Action	Message	Duration / Fetch
431	21:37:51	SELECT customer_id, SUM(purch_amt) AS total_purchase FROM orders GROUP BY customer_id HAVING SUM(purch_amt) > ...	2 row(s) returned	0.000 sec / 0.000 sec
432	21:37:51	SELECT customer_id, COUNT(*) AS total_orders FROM orders GROUP BY customer_id HAVING COUNT(*) > 1 LIMIT 0, 50000	3 row(s) returned	0.000 sec / 0.000 sec
433	21:37:51	SELECT customer_id, SUM(purch_amt) AS total_purchase FROM orders GROUP BY customer_id HAVING SUM(purch_amt) > ...	5 row(s) returned	0.000 sec / 0.000 sec
434	21:37:51	SELECT customer_id, MAX(purch_amt) AS max_purchase FROM orders GROUP BY customer_id HAVING MAX(purch_amt) BE...	3 row(s) returned	0.000 sec / 0.000 sec
435	21:37:51	SELECT salesman_id, COUNT(*) AS total_orders FROM orders GROUP BY salesman_id HAVING COUNT(*) >= 2 LIMIT 0, 50000	3 row(s) returned	0.000 sec / 0.000 sec
436	21:37:51	SELECT ord_date, MAX(purch_amt) AS highest_purchase FROM orders GROUP BY ord_date HAVING MAX(purch_amt) > 200...	4 row(s) returned	0.000 sec / 0.000 sec

Query Completed