← Back to CCAR-P Tests

Developer Productivity & Operational Enablement - Test Complete!

Here's how you performed on this CCAR-P domain

100%
Overall Score

10
Correct Answers

12:11
Time Taken

Excellent! You're well-prepared for this domain.

This was a sample test from a limited pool of questions.
Upgrade to Premium for access to the complete CCAR-P question bank with 200+ questions!

Upgrade to Premium

Get unlimited access to:

- Unlimited practice tests across all 7 domains
- Full-length mock exams
- AI-powered explanations and study guides
- Progress tracking and performance analytics
- Smart practice focusing on weak areas

Question Review

Review your answers and explanations

Show Explanations

1 A platform team has 45 developers contributing to the same monorepo. Developers using Claude-assisted tooling repeatedly provide different build commands, test locations, and pull-request requirements. This has caused generated changes to bypass required integration tests, and new developers need several days to learn the conventions. Some developers also want to retain personal formatting and explanation preferences. Which configuration approach should the architect recommend?

A. Let each developer maintain a complete local instruction file and distribute an example through the onboarding wiki.

B. Store mandatory repository workflows in reviewed, version-controlled project instructions and keep optional personal preferences in user-specific configuration. **Correct**

C. Embed all repository and personal instructions in a wrapper script maintained outside the repository by the platform team.

D. Require developers to paste the current contribution guide into every session and review generated changes for missing steps.

2 A payments company is enabling Claude-assisted development in a repository that contains deployment scripts. The current environment gives the assistant unrestricted shell access and inherits each developer's

production credentials. Developers need Claude to inspect source files, edit a working branch, run approved local tests, and query a sanitized test database. Security requires structural prevention of production changes and secret exposure; retaining a command log alone is not sufficient. Which design BEST meets these requirements?

A. Keep unrestricted shell access, add instructions prohibiting production commands, and alert security when sensitive command patterns appear.

B. Run sessions in an isolated workspace with scoped file access, allowlisted test commands, test-only credentials, and no production deployment capability. **Correct**

C. Permit read-only production access, block file writes by default, and let developers temporarily enable unrestricted access when implementation begins.

D. Retain developer credentials but require explicit confirmation before every shell command and archive complete session transcripts for audit.

3 A manufacturer plans to use Claude to modernize a 220,000-line order-allocation service. Documentation is incomplete, test coverage is 28%, and several undocumented allocation rules affect contractual delivery commitments. The replacement must remain behaviorally compatible, and releases need a reversible path. Management wants useful increments within three months rather than a prolonged analysis phase. Which delivery workflow should the architect recommend?

A. Characterize critical behavior with executable tests, map dependencies, modernize bounded slices, and require regression gates and developer approval for each increment. **Correct**

B. Generate a full replacement from the existing source, compare API schemas, and deploy it once both implementations compile without warnings.

C. Expand unit coverage for the entire legacy service before changing code, then perform the modernization as one reviewed release.

D. Run the generated replacement beside production, compare aggregate outputs for one week, and automatically redirect all traffic when agreement is high.

4 A product organization expects Claude to create approximately 300 pull requests per week. Unit tests currently pass on 96% of generated changes, but a pilot found authorization defects and incompatible dependency updates in several passing pull requests. The organization wants faster delivery while retaining accountable ownership for security-sensitive code. Which pull-request policy BEST balances these requirements?

A. Automatically merge every pull request that passes unit tests, then use production monitoring and automated rollback to address escaped defects.

B. Require identical manual security and architecture review for every generated pull request, regardless of affected files or change type.

C. Apply automated unit, integration, static-analysis, and dependency gates, then route changes to risk-based human review using code ownership. **Correct**

D. Ask Claude to critique each generated change, merge when its critique reports no concerns, and sample ten percent for human review.

5 An operations team is introducing a Claude-based assistant for severity-one incidents. It must inspect logs, traces, deployment records, source code, and current configuration. During incidents, evidence is incomplete and an incorrect command could extend an outage affecting 80,000 users. Existing production changes require an approved operator and a documented rollback plan. What should the assistant's initial capability boundary be?

A. Provide read-only diagnostic tools and require approved operators to execute proposed remediation through the existing change process. **Correct**

B. Provide unrestricted production shell access but require the assistant to explain each command before running it.

C. Allow automatic rollback of any recent deployment while keeping all other production actions read-only.

D. Allow configuration writes during severity-one incidents and rely on command logging for post-incident accountability.

6 A travel platform has an intermittent booking failure spanning six services. About 0.4% of requests fail, primarily after a recent configuration rollout, but individual service dashboards remain within normal ranges. Raw logs total 18 TB per day and cannot fit into a useful model context. Logs and traces include request IDs, deployment versions, and timestamps. The operations team needs a defensible root cause, not merely a plausible summary. Which troubleshooting design is BEST?

A. Summarize each service's daily logs independently, provide the six summaries to Claude, and select the explanation mentioned most frequently.

B. Increase the model context allocation, sample equal volumes from every service, and ask Claude to infer the most likely failure sequence.

C. Create a permanent vector index over all raw logs, retrieve semantically similar messages, and use similarity frequency as causal evidence.

D. Correlate failed requests by trace identifiers and versions, retrieve evidence iteratively for

explicit hypotheses, and preserve provenance and contradictions. **Correct**

7 An enterprise has 70 repositories across mobile, data, embedded, and cloud teams. All teams must follow common security and release controls, but their build systems and domain procedures differ. A pilot used one universal instruction prompt; it has grown to 38 pages, contains conflicting commands, and consumes context even when most sections are irrelevant. Which enablement architecture should replace it?

A. Maintain separate complete prompts for every repository and have each team manually copy enterprise controls into its local version.

B. Shorten the universal prompt by removing detailed procedures and depend on developers to supply missing team instructions during each session.

C. Create governed reusable components for enterprise controls, load owned domain modules when relevant, and permit reviewed repository-level extensions. **Correct**

D. Place all standards in a semantic index and let Claude retrieve any instructions that appear related to the developer's current request.

8 A retailer piloted Claude-assisted development with 600 engineers. Organization-wide suggestion acceptance is 61%, and reported coding time fell 14%. However, two payments teams report longer reviews, and security rework increased after generated changes. Leadership wants an immediate rollout to 4,000 engineers. Telemetry cannot retain source code, secrets, or raw prompts. What should the architect recommend FIRST?

A. Proceed with the rollout because aggregate acceptance and coding-time metrics demonstrate net productivity, then correct team-specific issues afterward.

B. Pause all usage until the platform can retain complete prompts and generated source so every accepted suggestion can be reconstructed.

C. Replace the current model with a more capable model across all teams and compare organization-wide acceptance after one month.

D. Define net-value and safety measures, segment results by team and task risk, instrument privacy-preserving telemetry, and expand through gated phases. **Correct**

9 A media company gives 90 employees and 35 contractors access to Claude-assisted tooling. Users work across public websites, internal analytics, and embargoed-content repositories. Contractor assignments last from two weeks to six months, and access must be revoked within 15 minutes of contract termination. Security requires user-level attribution and enforcement of existing repository permissions. Which access design BEST satisfies the requirements?

A. Issue one rotated credential per project, record the workstation address with each request, and remove contractors from project chat when assignments end.

B. Use individual federated identities, derive repository and tool permissions from managed roles, and apply time-bounded contractor access with centralized revocation. **Correct**

C. Give every user an individual assistant account, place prohibited repositories in project instructions, and review access logs weekly for violations.

D. Run a shared assistant service account, require contractors to include their names in prompts, and filter embargoed content from generated responses.

10 A financial software provider must upgrade a shared authentication library across 480 repositories in eight weeks. Repositories use four language versions, test coverage ranges from 20% to 92%, and 30 systems process regulated transactions. Most migrations are mechanical, but deprecated authentication callbacks require behavioral changes in some services. Every failure must be traceable to its repository, and high-risk regressions require a defined revert path. Which workflow should the architect implement?

A. Classify repositories by compatibility, coverage, and criticality; automate routine migrations with per-repository gates; and route exceptions to owners with revert procedures. **Correct**

B. Apply one generated patch to all repositories in parallel, merge successful builds

automatically, and investigate production failures by migration batch.

C. Assign a separate autonomous agent to each repository, permit agents to choose their own validation strategy, and compare aggregate completion rates.

D. Manually migrate the regulated systems first, then use the same approved patch unchanged for every remaining repository without additional classification.

Take Test Again

Try Other Domains