ANALYSIS TEMPLATE REPORT

50mm thick p Materials : Concret 10-365 10-470	premixed bitumenous carpetting with stone chi	-				
Materials : Concret	t <u>e</u>	-				
Materials : Concret	t <u>e</u>	-				
	Sand, FM >= 0.8					
10-470		0.0120	cum	@ Tkper	cum	Tk
	Stone, Chips: 25mm down graded	0.0600	cum	<pre>@ Tkper Sub Total ——</pre>	cum	Tk Tk
Materials : Misc.						
20-125	Bitumen: 80/100	4.3200	kg	<pre>@ Tkper Sub Total ——</pre>	kg	Tk
Wood Work						
30-425	Wood, Fire	3.1968	kg	<pre>@ Tkper Sub Total ———</pre>	kg	$\begin{array}{ll} Tk. \dots & \\ Tk. \dots & \end{array}$
Equipment, Tools						
70-345	Road Roller: 8 hrs day (with fuel etc.)	0.0007	day	@ Tkper	day	$Tk. \dots \dots$
				Sub Total ——		$Tk. \dots \\$
<u>Labour</u>						
80-305	Head Man	0.0108	day	@ Tkper	day	$Tk.\dots . \\$
80-370	Labour, Skilled	0.1076	day	@ Tkper	day	$Tk.\dots\dots$
80-375	Labour, Unskilled	0.2152	day	@ Tkper	day	$Tk.\dots\dots$
				Sub Total —		$Tk.\dots\dots$
				Sum of Sub Total		Tk
				Overhead &	2.5	$Tk. \dots \\$
				Item Total		Tk
				Contractor's	10 %	Tk
				Total		Tk
					5.5 %	Tk
I	20-125 Wood Work 30-425 Equipment, Tools 70-345 Labour 80-305 80-370	20-125 Bitumen: 80/100	20-125 Bitumen: 80/100	20-125 Bitumen: 80/100	Materials : Misc. 20-125 Bitumen : 80/100	Materials : Misc. 20-125 Bitumen : 80/100