



FIXING KIT FOR CONCRETE

Product information

- Plugs to fix objects with screws in walls and ceilings of concrete or solid surfaces.
- Performs a double expansion, it opens towards the four cardinal four cardinal points.
- It consists of 2 flaps that do not allow the socket to rotate inside the hole when the screw is inserted in.
- It has a collar that prevents the socket from sinking, even when the borehole is deeper.
- It has a guide that allows the screw to be inserted correctly.
- Free of burrs that prevent double expansion.
- Flexible

Product properties

- Impact and extraction resistant.
- Operation temperature:
Polyethylene: -50°C to +80°C (-58°F to 176°F)
Acero Galvanizado: -20°C to + 80 °C (-4°F to 176°F)
- Color: Thorquets: red, yellow, white, brown and blue;
Nail: natural and drill bit; Body: C45 and the tip is an alloy YG8

Application/Market



Home



Office



Industry

Materials

- Thorquets: Manufactured with high density polyethylene.
- Nail: Galvanized Steel



	THORQUETE TP3 WITH SCREW	THORQUETE TP2B WITH SCREW	THORQUETE TP2X WITH SCREW	THORQUETE TP1X WITH SCREW	THORQUETE TP0 WITH SCREW
RECOMMENDED LOAD CARGA RECOMENDADA CHARGE RECOMMANDÉE	140 kg (308.647 Lb)	120 kg (264.555 Lb)	60 kg (132.277 Lb)	50 kg (110.231 Lb)	40 kg (88.1849 Lb)
RECOMMENDED DRILL (INCLUDED) BROCA RECOMENDADA (INCLUIDA) FORÊT RECOMMANDÉE (INCLUS)	3/8" (9.52 mm)	5/16" (7.93 mm)	1/4" (6.35 mm)	7/32" / 1/4" (5.5 mm / 6.35 mm)	3/16" / 7/32" (4.7 mm / 5.5 mm)
RECOMMENDED SCREW (INCLUDED) PIJA RECOMENDADA (INCLUIDA) VIS RECOMMANDÉE (INCLUSE)	12 X 2" 5.48 X 50.8 mm	10 X 1 3/4" (4.82 X 44.45 mm)	10 X 1 1/2" (4.82 X 38.1 mm)	8 X 1" (4.16 X 25.4 mm)	8 X 3/4" (4.16 X 19.05 mm)



ISO 9001-2015

THORSMEX, S.A. DE C.V.

Blvd. Manuel Ávila Camacho 2900-701, Fracc. Los Pirules, Tlalnepantla,
Edo. de México, C.P.54040 • Tel: (55) 5379-67-47 Área comercial:

EXT 104, 105, 119, 120 y 128 • info@thorsmex.mx

www.thorsmex.mx



APPLICATION




Item	Code	Bar Code	Display Box	Dimensions
FIXING KIT FOR CONCRETE	3701-02000	7506218113035	Box with 104 pieces	L 43 mm (1.692 in) x W 137 mm (5.393 in) x H 181 mm (7.125 in)

DRILL



THORQUETE
TP3 WITH SCREW




THORQUETE
TP2B WITH SCREW




THORQUETE
TP2X WITH SCREW



THORQUETE
TP1X WITH SCREW



THORQUETE
TP0 WITH SCREW



CONTENTS: 104 PIECES

1 drill 3/16 (4.7 mm)

1 drill 5/16" (7.93 mm)

1 drill 1/4" (6.35 mm)

1 drill 3/8" (9.52 mm)

5 wall plugs TP3 3/8" (9.52 mm) with screw 12X2" (5.48 X 50.8 mm)


10 wall plugs TP2B 5/16" (7.93 mm) with screw 10 x 1 3/4" (4.82 X 44.45 mm)

15 wall plugs TP2X 1/4" (6.35 mm) with screw 10 X 1 1/2" (4.82 X 38.1 mm)

10 wall plugs TP1X 7/32" / 1/4" (5.5 mm / 6.35 mm) with screw 8 X 1" (4.16 X 25.4 mm)

10 wall plugs TP0 3/16" / 7/32" (4.7 mm / 5.5 mm) with screw 8 x 3/4" (4.16 X 19.05 mm)

SUPPORT SCHEME



WALL PLUG DIMENSIONS

	TP0	TP1X	TP2X	TP2B	TP3
A	8 mm (0.315 in)	8 mm (0.315 in)	9 mm (0.354 in)	10.5 mm (0.413 in)	13.5 mm (0.531 in)
B	14 mm (0.551 in)	15 mm (0.591 in)	19.8 mm (0.78 in)	30 mm (1.181 in)	33 mm (1.299 in)
C	19.5 mm (0.768 in)	22 mm (0.866 in)	34 mm (1.339 in)	39.4 mm (1.551 in)	45.5 mm (1.791 in)
D	6.25 mm (0.246 in)	6.25 mm (0.246 in)	6.5 mm (0.256 in)	7.5 mm (0.295 in)	10 mm (0.394 in)



ISO 9001-2015

THORSMEX, S.A. DE C.V.

Blvd. Manuel Ávila Camacho 2900-701, Fracc. Los Pirules, Tlalnepantla,
Edo. de México, C.P.54040 • Tel: (55) 5379-67-47 Área comercial:

EXT 104, 105, 119, 120 y 128 • info@thorsmex.mx

www.thorsmex.mx