THORSMAN®

by **thorsmex** group

FIJATHOR TSP

















ISO 9001-2015

THORSMEX, S.A. DE C.V.

Blvd. Manuel Ávila Camacho 2900-701, Fracc. Los Pirules, Tlalnepantla, Edo. de México, C.P.54040 • Tel: (55) 5379-67-47 Área comercial: EXT 104, 105, 119, 120 y 128 • info@thorsmex.mx www.thorsmex.mx

FIXING SYSTEM

FIJATHOR (DRY WALL PLUG)

Product information

- Butterfly type dowel with integrated screw for fixing and fastening objects in walls such as plasterboard, masonry and hollow partition walls
- For indoor use
- Easy to install

Product properties

- Drywall load capacity 20 Kg (44.09 lb)
- Fijathor TSP:
 - 3/8" drill bit (9.5 mm)
 - Extraction resistance: 7 Kg (15.43 lb)
 - Operation temperature -50°C a + 80°C (-58°F to + 176°F)
- Fijathor TMM:
 - Extraction resistance: 6 Kg (13.22 lb)
 - Gypsum board load capacity 20 Kg (44.09 lb)
 - Operation temperature
 - -40°C to +80°C (-88.18°F to +176°F)
 - Screw presentation
- Requires only a 15 mm deep drilling in the wall for installation
 - 5/16" drill bit (7.93 mm)
 - Stays fixed even without screw
 - No tools required

Application/Market







Industry

Materials


- Fijathor TSP:
 - Color: white and blue
 - Made of high density polyethylene (butterfly and spiral)
 - Galvanized steel screw and nut
- Fijathor TMM:
 - PA Nylon
 - Color: natural




FIXING SYSTEM



FIJATHOR (DRY WALL PLUG)



Fii	iat	hor	T٨	٨M
	u		17.7	



Item	Code	Bar Code	Display Box	Color	Dimensions
Fijathor TSP	2208-06025	7501509901957	Box with 25 pieces	White and blue	H 75 mm (2.953 in) x W 4.7 mm (0.185 in)
Fijathor TMM	2209-02000 2209-06025	7501509908987 7501509908970	4 pieces Blister Box with 25 pieces	Natural	H 52 mm (2.047 in) x W 13 mm (0.511 in)

APPLICATION



