

# Command and Control Subsystems Report

Jake Vossen: OREPACKAGERS

April 2, 2019

## 1 Subsystem Description

The Command and Control subsystem is the subsystem responsible for converting the requests that have been collected into downloaded data to be distributed to users. It starts by receiving a list of **request** objects - a structure for containing information about each request. To prevent confusion, the mono-spaced **request** will refer to the Python object itself, whereas plain “request” refers to the concept of a user request.

With this list of requests, the first thing it does is use Python's **multiprocessing**[1] library to split work up between the different threads on the computer. While this software is designed for low end machines to be more accessible to developing areas, most computers[2] in recent times will have more than 1 CPU core (including the Raspberry Pi[3]). This allows for the processor to split up all the requests, and execute them in parallel, instead of waiting for each one to finish individually, which can provide a large performance boost.

When downloading a **request**, it determines the type of request. The types are URL, search, youtube, and ipfs. It follows this flow chart to decide what to do:




Figure 1: Diagram describing flow chart of downloading each **request**. Jake Vossen, 2019-04-01

The steps for each type of request is outlined below.

## 1.1 URLs

URLs are your basic websites, such as `https://en.wikipedia.org/wiki/Monty_Python_and_the_Holy_Grail`, or `https://www.nytimes.com/2019/03/27/technology/turing-award-ai.html`. This is for users who already know the content they want. In the backend, the Python program is going to use the `wget`[4] utility. Specifically, `wget -E -H -k -K -p -P path url robots=off` where `path` is the output directory and `url` is the url that has been requested. To break it down:

- `-E` tells `wget` to change the file extension if the url isn't a `.html` file. This allows for the downloading of PDF files as well as HTML files
- `-H` Tells `wget` that it is okay to download material from hosts that aren't from the specified URL. While this seems backwards at first, many websites host their fonts or pictures in a place that isn't the same as the document that is being request. This allows the page to appear just as it would when visited in a web browser
- `-k` This stands for "convert links", which means that when the download is complete, it converts the links on the page so they are sudible for browsing on the local machine. For example, if a blog has `otherwebsite.com/picture` on it, it will replace that with just `picture` to ensure that the browser will use the local versions of that picture
- `-K` This means that `wget` will make a backup of the HTML file when converting links with the `-k` option.
- `-p` is the most important option, as it tells `wget` to download all the requirements as well as the url. So if the site links to an outside source (such as `otherwebsite.com/picture`) also gets downloaded if it is linked in the requested url.

All of those options ensures that downloading the URL requested get's the website exactly as it appears in a browser, including linked images. Additionally, it works with PDF and ZIP files, which is really important to ensure all possible media can be obtained. This method is also used by other parts of the program.

## 1.2 Search

Sometimes the user will not know exactly what they want, so we added an option to get the first page of Google results (top 10 results). The `googlesearch`[5] library was very helpful for this. This library provides a list of URLs, and then we use the `URL` method to download those results (or the youtube download option if it is a youtube link). The results are each in thier own folder nammed based on the google search rank (1 is first result, 2 is second result, etc).

## 1.3 YouTube

It is well known that lot of quality educational and entertainment content is in video format, and the majority of that content is on YouTube. That is why we are adding functionality to request YouTube videos (through a link, or a result from the search function). In this case, the `youtube-dl` program allows for content retrieval.

## 1.4 IPFS

IPFS stands for "InterPlanetary File System", which is a "A peer-to-peer hypermedia protocol to make the web faster, safer, and more open"[7]. The internet that is familiar to most people is the client-server model[8], but IPFS changes that so everyone is both a client and a server. Media is distribtued based of their cryptographic hash, a unique ID for each object instead of a URL. Anybody can add objects, and when requesting an object, it can be downloaded from any number of servers, not just the origional person hosting the server. The `ipfs` command line utility[9] is used to retreive objects.

## 2 Interfaces with Other Subsystems

Software is all about abstraction, so there are a handful of points in which the Command and Control subsystem will interface with the other subsystems. Ideally, all the other subsystems will work independently and a couple of links will get everything working together.

### 2.1 Input - List of Requests

Python only stores objects in memory while the program is running. That means when the program is shut down (or the machine is powered off), the data generated must be saved somewhere on the device or else that information would be lost. In this case, what is important is to be able to store the `request` objects. This is completed by the data management subsystem. This means my subsystem will call `get_all_requests()` which will retrieve the data about the requests, create the objects again (as they were destroyed from memory when the program shut down), and return that information to Command and Control.

### 2.2 Output - Download path and status

Once my subsystem completes its download, it needs to update the database about the new status. This is again through the Data Management subsystem. To ensure we only download each object once, each `request` has two properties: `file_location` and `downloaded_status`. Once Command and Control has completed a download, it will call the Data Management method `update_request(r)` where `r` include the changes to `file_location` and `downloaded_status`. So the Data Management subsystem knows which database entry to update, we use a Universally Unique Identifier (UUID)[10] to identify each request.




Figure 2: Diagram describing the inputs and outputs of the Command and Control sub-system `request`.  
Jake Vossen, 2019-04-01

## 3 Stakeholder Considerations

## 4 Validation

Testing is one of the most fundamentally important things in software development. It is easy to write code, but it is not useful if it can't work under a variety of difficult tests.

Table 1: Tests Preformed Jake Vossen, 2019-04-01

Type	Value	Expected Result	Analysis Method	Expected = Actual?
URL	<a href="https://www.gutenberg.org/cache/epub/2265/pg2265.txt">https://www.gutenberg.org/cache/epub/2265/pg2265.txt</a>	Text of "Hamlet" By Shakesphere	Hash	Yes
URL	<a href="https://static.googleusercontent.com/media/research.google.com/en//pubs/archive/46507.pdf">https://static.googleusercontent.com/media/research.google.com/en//pubs/archive/46507.pdf</a>	PDF of Google Machine Learning Research Paper	Hash	Yes
URL	<a href="https://en.wikipedia.org/wiki/Monty_Python_and_the_Holy_Grail">https://en.wikipedia.org/wiki/Monty_Python_and_the_Holy_Grail</a>	Wikipedia entry for "Monty Python and the Holy Grail"	Visual	Yes
search	What Is the Airspeed Velocity of an Unladen Swallow?	Google search results	Visual	Yes
ipfs	<a href="https://ipfs/QmS4ustL54uo8FzR9455qaxZwuMiUhyvMcX9Ba8nUH4uVv/readme">/ipfs/QmS4ustL54uo8FzR9455qaxZwuMiUhyvMcX9Ba8nUH4uVv/readme</a>	IPFS introduction document	Hash	Yes
ipfs	<a href="https://ipfs/QmVLTMHtLRhnft3QspDx4qTJeXY6hiib1j77UfQmY54CGe/mosaic.png">/ipfs/QmVLTMHtLRhnft3QspDx4qTJeXY6hiib1j77UfQmY54CGe/mosaic.png</a>	300 MB picture of the moon	Hash	Yes