

Deep Learning

Assignment- Week 10

TYPE OF QUESTION: MCQ/MSQ

Number of questions: 10

Total mark: 10 X 1 = 10

QUESTION 1:

What is not a reason for using batch-normalization??

- a. Prevent overfitting
- b. Faster convergence
- c. Faster inference time
- d. Prevent Co-variant shift

Correct Answer: c


Detailed Solution:

Inference time does not become faster due to batch normalization. It increases the computational burden. So, inference time increases.

QUESTION 2:

A neural network has 3 neurons in a hidden layer. Activations of the neurons for three batches are $\begin{bmatrix} 1 \\ 2 \\ 3 \end{bmatrix}$, $\begin{bmatrix} 0 \\ 2 \\ 5 \end{bmatrix}$, $\begin{bmatrix} 6 \\ 9 \\ 2 \end{bmatrix}$ respectively. What will be the value of mean if we use batch normalization in this layer?

- a. $\begin{bmatrix} 2.33 \\ 4.33 \\ 3.33 \end{bmatrix}$
- b. $\begin{bmatrix} 2.00 \\ 2.33 \\ 5.66 \end{bmatrix}$
- c. $\begin{bmatrix} 1.00 \\ 1.00 \\ 1.00 \end{bmatrix}$
- d. $\begin{bmatrix} 0.00 \\ 0.00 \\ 0.00 \end{bmatrix}$



Correct Answer: a

Detailed Solution:

$$\frac{1}{3} \times \left(\begin{bmatrix} 1 \\ 2 \\ 3 \end{bmatrix} + \begin{bmatrix} 0 \\ 2 \\ 5 \end{bmatrix} + \begin{bmatrix} 6 \\ 9 \\ 2 \end{bmatrix} \right) = \begin{bmatrix} 2.33 \\ 4.33 \\ 3.33 \end{bmatrix}$$

QUESTION 3:

How can we prevent underfitting?

- a. Increase the number of data samples
- b. Increase the number of features
- c. Decrease the number of features
- d. Decrease the number of data samples

Correct Answer: b

Detailed Solution:

Underfitting happens whenever feature samples are capable enough to capture the data distribution. We need to increase the feature size, so data can be fitted perfectly well.

QUESTION 4:

How do we generally calculate mean and variance during testing?

- a. Batch normalization is not required during testing
- b. Mean and variance based on test image
- c. Estimated mean and variance statistics during training
- d. None of the above

Correct Answer: c

Detailed Solution:

We generally calculate batch mean and variance statistics during training and use the estimated batch mean and variance during testing.



QUESTION 5:

Which one of the following is not an advantage of dropout?

- a. Regularization
- b. Prevent Overfitting
- c. Improve Accuracy
- d. Reduce computational cost during testing

Correct Answer: d

Detailed Solution:

Dropout makes some random features during training but while testing we don't zero-down any feature. So there is no question of reduction of computational cost.

QUESTION 6:

What is the main advantage of layer normalization over batch normalization?

- a. Faster convergence
- b. Lesser computation
- c. Useful in recurrent neural network
- d. None of these


Correct Answer: c


Detailed Solution:

See the lectures/lecture materials.

QUESTION 7:

While training a neural network for image recognition task, we plot the graph of training error and validation error. Which is the best for early stopping?





- a. A
- b. B
- c. C
- d. D

Correct Answer: c

Detailed Solution:

Minimum validation point is the best for early stopping.

QUESTION 8:

Which among the following is NOT a data augmentation technique?

- a. Random horizontal and vertical flip of image
- b. Random shuffle all the pixels of an image
- c. Random color jittering
- d. All the above are data augmentation techniques

Correct Answer: b

Detailed Solution:

Random shuffle of all the pixels of the image will distort the image and neural network will be unable to learn anything. So, it is not a data augmentation technique.

QUESTION 9:

Which of the following is true about model capacity (where model capacity means the ability of neural network to approximate complex functions)?

- a. As number of hidden layers increase, model capacity increases
- b. As dropout ratio increases, model capacity increases
- c. As learning rate increases, model capacity increases
- d. None of these

Correct Answer: a

Detailed Solution:



Dropout and learning rate has nothing to do with model capacity. If hidden layers increase, it increases the number of learnable parameter. Therefore, model capacity increases.

QUESTION 10:

Batch Normalization is helpful because

- a. It normalizes all the input before sending it to the next layer
- b. It returns back the normalized mean and standard deviation of weights
- c. It is a very efficient back-propagation technique
- d. None of these

Correct Answer: a

Detailed Solution:

Batch normalization layer normalizes the input.

*****END*****