

PRODUCTION TEST SPECIFICATION

FOA Barra Body Electronics Module
High and Low Series

F005 VP 0067

Page 2 of 29

Issue	ECR Number	Alteration	By	Valid From	Checked
7	V001119	Sect 3: Add comment: "This specification shall be read in conjunction with the Production Test Specification for the FoA Barra Alarm Body Electronics Module High and Low Series, F005VP0355. Any modifications to the Production Test Specification for the FoA Barra Body Electronics Module High and Low Series, F005VP0067 will apply to F005VP0355 by default. F005VP0355 only details additional requirements specific to the FoA Barra Alarm Body Electronics Module." Sect 6.3: Update Sunload Sensor load to 1kΩ from 4kΩ to fall in line with test circuit. Limits adjusted \$64 to \$96 range. Sect 8.2: Update characteristics for CAN Global Wakeup, Front Washer Motor Control and Door Lock Motor. Sect15: Update EEprom Table with the following changes - Hlamp_Hselect (\$08A0) - Change from ROM default setting of 340Hz to 300Hz for more sensitive operation of Auto Headlamp turn on by changing to the following " 07 - Threshold 7 from pick of 0 to 7 thresholds for Auto headlamp turn off thresholds (Note Auto EEprom download will write \$55, the Final tester must re-write this to \$07 and verify accordingly)". - Hlamp_Hselect (\$08A1) - Update comment to identify default setting by adding "\$55 - Default threshold 0 from Pick 0 to 7 thresholds from 0 to 7 for Auto headlamp turn on thresholds" - Rom_Check_Sum (\$0938) - When a new version firmware (ROM) is programmed to the BEM (See \$093F), a new Checksum is automatically generated by the BEM and downloaded to this EEprom location. - Module_Serial_Number[24] (Reference Part 2 Diagnostics Specification, F005VP0058) (\$09B0) - Update to Bosch preferred method of detailing the serial number. Add "Reference Part 2 Diagnostics Specification, F005VP0058".	EGE3-JEV	23/09/02	EGE3-MS
6	V001062	To support Version 13 Software: Sect 4: Add comment: "The Final Tester and the ICT shall keep a log of the pass/fail rate per BEM to obtain production yield data" Sect 9.1: TemicCrashTest flag is the right flag to set for this test. Sect 5: Update Fixed Feed, Source & Return Characteristics with a complete list verifying continuity Sect 7: Update functions to identify if High series only to reduce final test time Sect 8.2: Update functions to identify if High series only to reduce final test time. Added CTS output driver characteristics. Adjusted limits to conform with Production's Method 3 Compatibility Study. Sect 12.3: Update checksum for Production Programmer of standalone Motorola Microprocessor for Version 13 software to \$896101 (8bit) and \$4534E889 (16 bit). Sect15: Update checksum (address \$0938) for Version 13 software to \$3882 using Flasher if pre-programmed with Version 12 software using Flasher. - Update checksum for Version 13 software to \$3387 if pre-programmed with Version 13 software using the production programmer with no previous version programmed. - Add \$93F EEprom for auto-detect version change for Checksum update. Sect16: Change Diagnostic Specification reference from F005VP0067 to F005VP0058.	EGE3-JEV	9/08/02	EGE3-SM
5	V000979	To support Version 12 Software Sect 4.9: Add note that final tester can switch between the 2 pairs of wires too guarantee continuity using the CCP commands to perform the final test. Sect 12.3: Update checksum for Production Programmer of standalone Motorola Microprocessor for Version 12 software to \$8A4B73 (8bit) and \$4541C5FC (16 bit). Sect 8.1: Add Relay contact cleaning requirement and change Section 8 contents to Section 8.2 Sect15: Update checksum (address \$0938) for Version 12 software to \$F36D using Flasher if pre-programmed with Version 11 software using Flasher. - Update checksum for Version 12 software to \$EB75 if pre-programmed with Version 12 software using the production programmer with no previous version programmed. - Reduction in Final Test time can be achieved by storing serial number in addresses \$09B0 to \$09B3. Update example to reflect this change - DTC and function disable bit definitions detailed for address \$0930 - RF Key Unlock Mode set to 1 stage door unlock as a production default (previously 2 stage door unlock) for address \$0821	EGE3-JEV	19/06/02	EGE3/JEV