

3. GENERAL

This specification describes the tests required for final testing the Barra Body Electronics Module (BBEM) at Robert Bosch Australia (RBAU).

This specification gives details of each functional test to assist the development of test software, maintenance of the system and future development.

The BBEM has communication protocols such as CCP and the Ford interface protocol implemented for diagnostics and testing.

Unless otherwise specified all references to BEM in this document refer to the BBEM. High and Low Series Modules may also be identified as BEM/H and BEM/L or High and Low respectively.

See the Wiring Diagram or Schematic for connector pin numbers

All currents are defined as follows: Positive (+) for currents into BEM
Negative (-) for currents out of BEM

All data and addresses are in Hexadecimal format unless otherwise specified.

Final Test time excluding loading and unloading of the BEM shall not exceed 20s. To achieve this requirement the ICT will be required to perform some of the tests normally done by the final tester.

The ICT will write to an EEPROM location identifying a pass or fail. If an ICT has not been performed then the final tester will fail the unit immediately.

A list of components that the ICT cannot test shall be provided to development for review.

The final tester shall have a "Warranty Return Test Sequence" that includes testing conducted during ICT, as the ICT cannot be used on returned parts.

The Final Tester and the ICT shall keep a log of the pass/fail rate per BEM to obtain production yield data.

This specification shall be read in conjunction with the Production Test Specification for the FoA Barra Alarm Body Electronics Module High and Low Series, F005VP0355. Any modifications to the Production Test Specification for the FoA Barra Body Electronics Module High and Low Series, F005VP0067 will apply to F005VP0355 by default. F005VP0355 only details additional requirements specific to the FoA Barra Alarm Body Electronics Module.