PENETRATION TESTING & NETWORK SECURITY REPORT

ZENMAP-BASED NETWORK SCANNING AND SECURITY ASSESSMENT

| WEEK 2 CYBERSECURITY INTERNSHIP PROJECT

Project Information	Details
Student Name	Jakku Siddhartha
Batch	B84
Project Code	W2-PM1/PM5
Project Category	Network Security / Foot printing / Network Scanning
Primary Tools	Kali Linux, Nmap, Zenmap (GUI evidence to be added)
Assessment Target	networkwalks.com (192.232.216.135)
Report Date	11 November 2026

ACADEMIC / INTERNSHIP SUBMISSION

This report documents only the activities and results supplied by the student. Missing GUI screenshots and additional evidence are intentionally represented by editable placeholders.

Table of Contents

1. Executive Summary

2. Introduction to Network Scanning

3. Project Objectives

4. Tools and Technologies

5. Project Environment and Setup

6. Scanning Methodology

7. Practical Implementation and Scan Results

8. Port and Service Analysis

9. Security Findings and Risk Assessment

10. Recommendations and Mitigation

11. Challenges and Learning Outcomes

12. Conclusion

13. References

14. Appendix

.

1. Executive Summary

This report documents the Week 2 W2-PM5 practical project, titled "Zenmap-Based Network Scanning and Security Assessment". It combines footprinting activities against the domain networkwalks.com with network-service discovery using Nmap. The report is prepared in the style of the supplied reference report and uses the command outputs and screenshots made available by the student.

The footprinting activities included WHOIS lookup, DNS resolution, HTTP response-header inspection, Web Application Firewall fingerprinting and DNS record enumeration. The supplied evidence identifies the domain's IPv4 address as 192.232.216.135, identifies ModSecurity (SpiderLabs) through WAFW00F, and shows HTTP/2 200 in the supplied curl response.

A default Nmap scan of networkwalks.com resolved to 192.232.216.135 and reported the host as up. Across the default 1,000 TCP ports, Nmap reported 14 open ports, 2 filtered ports and 984 closed ports. The open ports include web, mail, DNS, remote administration, file transfer and database-related service labels. The scan did not include service-version detection, operating-system detection or vulnerability scripts; therefore, product versions and vulnerabilities cannot be confirmed from this output.

A successful DNSRecon output was subsequently supplied. It reported SOA, NS, MX, A, TXT and SRV information, including two name servers, mail routing information, an SPF record and eight SRV records. DNSRecon also reported recursion enabled on both listed name-server IPs and displayed a BIND version string. These observations require authorized validation and should not be treated as confirmed exploitable vulnerabilities.

Overall, the exercise demonstrates how public DNS and web metadata, together with a basic TCP port scan, can help build an initial picture of a domain's externally visible services. No exploitation or vulnerability validation is documented in the supplied evidence.

1.1 Scope and evidence limitations

- The confirmed Nmap evidence is command-line output from `nmap networkwalks.com`. A Zenmap GUI scan screenshot has not yet been supplied; editable placeholders are provided.
- The scan output shows service names associated with port numbers. Since `-sV` was not used, these labels do not confirm the actual software product or version.
- The scan is a point-in-time observation and does not establish whether a service is misconfigured or vulnerable.
- Written authorization for the target must be confirmed and recorded before this report is submitted as an authorized assessment.

2. Introduction to Network Scanning

2.1 What is network scanning?

Network scanning is a technical process used to identify reachable systems and examine how they communicate over a network. Depending on the scan type, it can reveal live hosts, TCP or UDP port states, service names, service versions and other network characteristics.

2.2 Why network scanning is important

Network scanning supports asset discovery, attack-surface mapping, firewall verification, troubleshooting and security assessments. Security teams use scan results to understand which services are reachable and whether the exposed services are expected and appropriately protected.

2.3 What is Nmap?

Nmap (Network Mapper) is an open-source network discovery and security auditing utility. It can perform host discovery, port scanning, service/version detection, operating-system detection and script-based checks. The exact capabilities exercised depend on the command-line options used.

2.4 What is Zenmap?

Zenmap is the graphical user interface associated with Nmap. It provides scan profiles, a target field, command preview, output tabs and a topology view. Zenmap uses Nmap as its scanning engine; the GUI does not make the underlying scan more authoritative than the command and output it runs.

2.5 Difference between Nmap and Zenmap

Nmap	Zenmap
Command-line network scanning utility.	Graphical interface for Nmap.
Commands and options are entered in a terminal.	Targets and profiles can be selected in a GUI.
Output is primarily text-based unless saved/exported.	Provides output views and a visual topology presentation.
Suitable for scripting and automation.	Useful for visual review and learning scan options.

3. Project Objectives

- Collect publicly available domain registration and DNS information.
- Resolve the target domain to its IPv4 address.
- Inspect HTTP response headers returned by the web server.
- Identify whether a Web Application Firewall fingerprint is detectable.
- Enumerate available DNS record information using DNSRecon.
- Identify whether the target host responds to an Nmap scan.
- Record open, closed and filtered TCP port states.
- Interpret the service labels reported by Nmap without treating them as proof of software versions.
- Document potential exposure and recommend proportionate defensive review.
- Maintain a clear evidence trail and distinguish confirmed observations from unverified risks.

4. Tools and Technologies

Tool / Technology	Purpose in this project	Evidence / status
Kali Linux	Linux environment used for command-line reconnaissance and Nmap/DNSRecon work.	Commands supplied by student.
Nmap 7.99	Host and TCP port discovery against networkwalks.com.	Actual scan output supplied.
Zenmap	GUI for configuring and reviewing Nmap scans and topology.	GUI screenshots pending.
WHOIS	Retrieve domain registration and registrar information.	Screenshot supplied.
nslookup	Resolve a domain through DNS.	Screenshot supplied.
curl -I	Retrieve HTTP response headers without downloading the full page body.	Command output supplied.
WAFW00F 2.3.2	Fingerprint a web application firewall.	Screenshot supplied.
Whatweb	Technology Detection	Screenshot supplied
DNSRecon	Enumerate DNS records and related DNS configuration information.	Successful output supplied; screenshot pending.
TCP/IP	Protocol suite used for communication across IP networks.	Conceptual foundation.
Windows PowerShell / ipconfig	Display Windows interface configuration.	Output supplied.

TCP is a connection-oriented transport protocol. A TCP port identifies an application endpoint on a host. Nmap reports port states such as open, closed and filtered based on the responses it receives; these states describe scan observations, not security verdicts.

5. Project Environment and Setup

5.1 Operating environment

Parameter	Observed value
Windows network adapter	Wi-Fi
IPv4 address	172.22.137.206
Subnet mask	255.255.248.0
Default gateway	172.22.136.1
Network prefix	172.22.136.0/21
Connection-specific DNS suffix	lpu.com
Nmap version shown in output	7.99
Nmap execution environment	Kali

The Windows `ipconfig` output contains several virtual adapters. The active Wi-Fi adapter is the relevant physical network connection in the supplied output. The WSL and VMware adapters have separate private addresses and no default gateway in the displayed configuration.

5.2 Target information

Parameter	Value
Domain	networkwalks.com
Resolved IPv4 address	192.232.216.135
Reverse DNS shown by Nmap	192-232-216-135.unifiedlayer.com
Scan command	nmap networkwalks.com
Scan date/time shown by Nmap	11 November 2026, 12:42 (+0530)

5.3 Authorization and scope

The target in the supplied commands is a public domain. Before submission, the student must confirm that the domain owner or internship authority explicitly authorized the activities described. The local Wi-Fi network is identified as an LPU connection, but the supplied Nmap command targets networkwalks.com, not the local Wi-Fi subnet. No scan of the university subnet is documented in the supplied evidence.

Authorization confirmation: [INSERT APPROVAL / LAB SCOPE DETAILS, DATE AND AUTHORIZING PARTY]. Do not represent the work as authorized unless this can be verified.

5.4 Installation and version notes

The supplied Nmap output identifies version 7.99. No Zenmap installation command or Zenmap version was provided. Add the exact installation method and version only if verified on the system used.

```
nmap --version
zenmap --version   # Use only if supported by the installed package
```

6. Scanning Methodology

1. **Define the authorized target:** Confirm the target domain/IP and written scope before scanning.
2. **Resolve the hostname:** Use DNS lookup to identify the IP address associated with the domain.
3. **Choose the scan method:** Use an appropriate Nmap/Zenmap profile. The supplied scan used the basic command `nmap networkwalks.com`.
4. **Execute the scan:** Nmap resolves the hostname, probes TCP ports in its default scan range and classifies responses.
5. **Review host status:** Check whether Nmap reports the host as up and record latency if shown.
6. **Review port states:** Separate open, closed and filtered results. Do not interpret filtered as open.
7. **Review service labels:** Treat the SERVICE column as a port/service-name mapping unless service detection is performed.
8. **Save evidence:** Retain raw output, screenshots, date/time, target and exact command.
9. **Assess findings:** Identify exposure requiring review; do not declare vulnerabilities without validation.
10. **Document limitations:** Record options not used, such as `-sV`, `-O` or `-A`, and note that versions/OS are unconfirmed.

6.1 Technical note on port states

- Open: Nmap received a response indicating that an application is accepting connections on that port.
- Closed: Nmap received a response indicating that the port is reachable but no application is listening.
- Filtered: Nmap could not determine whether the port is open because packet filtering or another network condition prevented a definitive response.

7. Practical Implementation and Scan Results

7.1 Foot printing: WHOIS lookup

Objective: collect publicly available domain registration information.

```
whois networkwalks.com
```

Field	Observed result
Domain	NETWORKWALKS.COM
Registrar	GoDaddy.com, LLC
Registrar WHOIS server	whois.godaddy.com
Creation date	2019-11-06 22:51:46Z
Updated date	2025-11-12 10:08:43Z
Registry expiry date	2027-11-06 22:51:46Z
Registrar IANA ID	146

Observation: WHOIS disclosed registration lifecycle and registrar details. Registration metadata is informational and is not, by itself, a vulnerability.




Figure 1. WHOIS output for networkwalks.com.

7.2 Foot printing: DNS resolution with nslookup

```
nslookup networkwalks.com
```

Field	Observed result
DNS resolver shown	10.255.255.254
Resolver port	53
Domain	networkwalks.com
IPv4 address returned	192.232.216.135

Observation: the domain resolved to 192.232.216.135. A non-authoritative answer generally means the responding resolver supplied the answer from its cache or recursive resolution rather than acting as the domain's authoritative name server.




Figure 2. nslookup resolving networkwalks.com to 192.232.216.135.

7.3 Footprinting: HTTP response headers

```
curl -I https://networkwalks.com
```

Header / field	Observed value
HTTP status	HTTP/2 200
Server	Apache
Content-Type	text/html; charset=UTF-8
WordPress REST API link	https://networkwalks.com/wp-json/
Alternate JSON endpoint	/wp-json/wp/v2/pages/53
Cache header	x-nginx-cache: WordPress
Cookie	__wpdm_client (Secure; HttpOnly)
Date	Wed, 11 Nov 2026 07:08:53 GMT

Observation: the response indicates a successful HTTP response and exposes several implementation-related headers and links. The WordPress REST API link indicates a WordPress-related endpoint, but the header output alone does not establish the exact WordPress version or a vulnerability.




Figure 3. HTTP response headers returned by curl -I.

7.4 Footprinting: WAF fingerprinting

```
wafw00f networkwalks.com
```

Observed result: WAFW00F v2.3.2 identified the site as being behind ModSecurity (SpiderLabs). The tool reported two requests. This is a fingerprinting observation and does not prove that every attack is blocked or that the WAF is correctly configured.




Figure 4. WAFW00F identifying ModSecurity (SpiderLabs).


7.5 Foot printing: DNS enumeration with DNSRecon

```
dnsrecon -d networkwalks.com
```


Record / observation	Result
SOA	ns6135.hostgator.com — 50.87.144.87
NS	ns6135.hostgator.com — 50.87.144.87
NS	ns6136.hostgator.com — 192.232.216.131
MX	mail.networkwalks.com — 192.232.216.135
A	networkwalks.com — 192.232.216.135
TXT	google-site-verification=rr04eRmqHoWY3XemnizDNVK4q75X-Ij-mjgEeg-UsYI
TXT / SPF	v=spf1 +a +mx +ip4:50.87.144.87 +include:websitewelcome.com ~all
SRV	8 _autodiscover._tcp records, each referencing cPanel email discovery hosts on port 443
DNS software string	BIND 9.11.26-RedHat-9.11.26-4.el8_4
DNSSEC query	DNSRecon logged: No answer for DNSSEC query
Recursion	DNSRecon reported recursion enabled on both listed name-server IPs

The successful output reports eight records found. The recursion messages are tool observations and require controlled validation to determine whether recursion is available to unauthorized external clients. The DNSSEC query message does not, on its own, prove that DNSSEC is disabled.

A prior attempt failed with an Attribute Error involving `urllib.request.FancyURLopener`. The later successful run shows that DNSRecon subsequently executed and returned records. The earlier error screenshot may be included as troubleshooting evidence, not as the final enumeration result.



Foot printing: Whatweb



Executive Summary

A passive reconnaissance and technology fingerprinting exercise was performed against networkwalks.com using WhatWeb. The aim was to identify the web technologies, software versions and server configuration exposed to an external observer, and to assess the resulting attack surface.

The target is a **WordPress** website running on **Apache**, hosted in the United States behind a caching layer. HTTP traffic is redirected to HTTPS, and the session cookie carries the `HttpOnly` flag. These are positive practices.

The main weakness found is **information disclosure**: the exact WordPress core version, the WordPress Download Manager plugin version, and a public contact email are all visible without authentication. This does not confirm an exploitable vulnerability by itself, but it lets an attacker match the target against known CVEs and plan targeted attacks. No intrusive testing or exploitation was carried out.

Overall risk rating (based on findings so far): Low, pending verification of the items in Section 7.

Findings Summary

ID	Finding	Severity	Status
F-01	WordPress core version disclosed via generator meta tag	Low	Confirmed
F-02	WordPress Download Manager plugin and version disclosed	Low	Confirmed
F-03	Web server and hosting stack details disclosed (Apache, nginx cache headers)	Informational	Confirmed

F-04	Possible missing security headers (CSP, X-Frame-Options, HSTS)	Low	To be verified
F-05	Public email address exposed	Informational	Confirmed
F-06	Third-party tracking script (Google Tag Manager) in use	Informational	Confirmed
P-01	HTTP to HTTPS redirect enforced	Positive	Confirmed
P-02	`HttpOnly` flag set on session cookie	Positive	Confirmed
P-03	`permissions-policy` and `referrer-policy` headers present	Positive	Confirmed

7.6 Network scanning: Nmap TCP port scan

Objective: identify the target host's TCP port states and the service names associated with the responding port numbers.

```
nmap networkwalks.com
```


Scan parameter	Observed result
Nmap version	7.99
Target hostname	networkwalks.com
Resolved target IP	192.232.216.135
Host status	Host is up
Latency	0.32 seconds
Reverse DNS	192-232-216-135.unifiedlayer.com
Ports considered	Default Nmap top 1,000 TCP ports
Closed ports	984 (reset)
Open ports	14
Filtered ports	2
Duration	3.65 seconds


The command did not include `-sV`, `-O`, `-A` or `-sC`. Accordingly, this evidence does not confirm service software versions, operating-system details, or vulnerability-script results.


7.7 Actual Nmap output

```
Starting Nmap 7.99 ( https://nmap.org ) at 2026-11-11 12:42 +0530
Nmap scan report for networkwalks.com (192.232.216.135)
Host is up (0.32s latency).
rDNS record for 192.232.216.135: 192-232-216-135.unifiedlayer.com
Not shown: 984 closed tcp ports (reset)
PORT     STATE    SERVICE
21/tcp   open     ftp
22/tcp   open     ssh
26/tcp   open     rsftp
53/tcp   open     domain
80/tcp   open     http
110/tcp  open     pop3
143/tcp  open     imap
443/tcp  open     https
465/tcp  open     smtps
587/tcp  open     submission
993/tcp  open     imaps
995/tcp  open     pop3s
2222/tcp open     EtherNetIP-1
3306/tcp open     mysql
3389/tcp filtered ms-wbt-server
5432/tcp filtered postgresql

Nmap done: 1 IP address (1 host up) scanned in 3.65 seconds
```







Insert the topology view if generated. If not generated, delete this placeholder.

8. Port and Service Analysis

The table below reproduces the states and service labels from the supplied Nmap output. The service column is Nmap's service-name mapping for the port; it is not a verified software fingerprint because service/version detection was not performed.

Port	State	Nmap service label	Version	Security observation
21/tcp	Open	ftp	Not detected	FTP service label; review whether clear-text FTP is required and protected.
22/tcp	Open	ssh	Not detected	Remote administration endpoint; restrict access and enforce strong authentication.
26/tcp	Open	rsftp	Not detected	Nmap service-name mapping; exact application not confirmed.
53/tcp	Open	domain	Not detected	DNS service label; review authoritative/recursive behavior and exposure.
80/tcp	Open	http	Not detected	HTTP endpoint; verify redirect and secure transport configuration.
110/tcp	Open	pop3	Not detected	Mail retrieval service; review whether unencrypted access is disabled.
143/tcp	Open	imap	Not detected	Mail retrieval service; enforce secure transport.
443/tcp	Open	https	Not detected	HTTPS endpoint; TLS configuration was not assessed by this scan.
465/tcp	Open	smtps	Not detected	Secure mail submission service label; verify configuration.
587/tcp	Open	submission	Not detected	Mail submission service; verify authentication and TLS enforcement.
993/tcp	Open	imaps	Not detected	IMAP over TLS service label; verify certificate and protocol settings.
995/tcp	Open	pop3s	Not detected	POP3 over TLS service label; verify certificate and protocol settings.
2222/tcp	Open	EtherNetIP-1	Not detected	Port-name mapping only; actual application/service requires version detection.
3306/tcp	Open	mysql	Not detected	Database port reachable; verify whether public exposure is necessary and restrict source access.
3389/tcp	Filtered	ms-wbt-server	Not detected	Filtering prevented a definitive open/closed determination.
5432/tcp	Filtered	postgresql	Not detected	Filtering prevented a definitive open/closed determination.

8.1 Interpretation

Open ports indicate reachable listening services from the scanner's network path. They are not automatically vulnerabilities. Closed ports responded in a way that indicated no listening application at the time of the scan. Filtered ports indicate that a filtering device or network condition prevented Nmap from determining the state.

The presence of FTP, mail protocols, SSH and database-related port labels should prompt the system owner to verify business need, authentication, encryption, source-IP restrictions and monitoring. The supplied scan does not establish whether those controls are present.

9. Security Findings and Risk Assessment

The following are evidence-based exposure observations, not confirmed vulnerabilities. Risk levels are preliminary review priorities based only on external reachability and the limited scan evidence. A formal risk rating requires service identification, business context and authorized validation.

ID	Observation	Affected asset	Evidence	Recommended review	Preliminary priority
OBS-01	FTP port reachable	192.232.216.135:21/tcp	Nmap reports open/ftp.	Review whether FTP is required; confirm encryption and access controls.	Review required / provisional Medium
OBS-02	Remote administration port reachable	192.232.216.135:22/tcp	Nmap reports open/ssh.	Restrict administrative access, use key-based authentication and monitor login attempts.	Review required / provisional Medium
OBS-03	Mail services reachable	Ports 110, 143, 465, 587, 993, 995	Nmap reports mail-related service labels.	Verify plaintext protocols are disabled or protected, TLS is enforced and authentication is secure.	Review required / provisional Medium
OBS-04	Database service port reachable	192.232.216.135:3306/tcp	Nmap reports open/mysql.	Confirm database must be reachable externally; restrict to application hosts/VPN/allowlisted sources.	Review required / provisional High if unintended; not confirmed
OBS-05	DNS recursion reported	50.87.144.87 and 192.232.216.131	DNSRecon reports recursion enabled on both name servers.	Validate recursion from an authorized external test point; disable public recursion unless explicitly required.	Unverified / provisional Medium
OBS-06	DNS software version string exposed	Two name-server IPs	DNSRecon displayed BIND 9.11.26-RedHat-9.11.26-4.el8_4.	Verify actual installed package and patch status against vendor advisories; banner may not prove exact patch state.	Informational pending validation
OBS-07	HTTP and WordPress-related metadata visible	networkwalks.com	curl response includes Apache, WordPress cache and /wp-json/ links.	Keep CMS, plugins and server components updated; review unnecessary headers and public endpoints.	Informational
OBS-08	WAF fingerprint identifiable	networkwalks.com	WAFW00F identified ModSecurity (SpiderLabs).	Maintain and tune WAF rules; verify logs and bypass resistance through authorized testing.	Informational

9.1 What was not established

- No confirmed exploitable vulnerability is demonstrated by the supplied outputs.
- No service versions were obtained by the Nmap command.
- No operating-system detection result was supplied.
- No exploit, authentication test, database login attempt or vulnerability scan is documented.
- The filtered state of TCP/3389 and TCP/5432 does not prove those services are running or vulnerable.

10. Recommendations and Mitigation

11. **Review externally reachable services:** The system owner should compare each open port with the approved service inventory and disable services that are not required.
12. **Restrict administrative access:** Limit SSH and any other administration interfaces to approved management IPs or VPN access. Use strong authentication, keys, MFA where supported and centralized logging.
13. **Review FTP:** If file transfer is required, prefer SFTP or another securely configured encrypted transfer method. Disable legacy FTP where unnecessary.
14. **Protect mail services:** Require TLS for mail access and submission, enforce secure authentication, and disable plaintext POP3/IMAP access if not needed.
15. **Restrict database exposure:** Avoid exposing database listeners directly to the public Internet. Use network allowlists, private network paths, firewall rules and strong database authentication.
16. **Review DNS recursion:** Ensure recursive DNS is available only to intended clients. Use split-horizon or access-controlled recursive resolvers where appropriate.
17. **Review DNS software lifecycle:** Confirm the actual BIND package, vendor support status and security patch level. Do not rely solely on a banner string.
18. **Maintain web and WAF security:** Keep the CMS, plugins, web server and WAF rules updated. Review public REST endpoints and remove unnecessary information disclosure where practical.
19. **Monitor and document:** Retain scan records, compare periodic results against approved baselines and investigate unexpected changes.
20. **Retest within authorization:** Repeat scanning only within a written scope and use additional detection options only when approved.

11. Challenges and Learning Outcomes

11.1 Challenges observed

An initial DNSRecon execution failed with an Attribute Error indicating that the installed code attempted to reference `urllib.request.FancyURLopener`, which was unavailable in the Python runtime. A later execution completed successfully and returned eight DNS records. The report records both the initial error and the later successful output without assuming a specific repair method, because the exact corrective steps were not supplied.

The student also had to distinguish the active Wi-Fi adapter from virtual interfaces displayed by Windows `ipconfig`. The Wi-Fi adapter showed IPv4 address 172.22.137.206, subnet mask 255.255.248.0 and gateway 172.22.136.1. Other interfaces belonged to WSL, VMware or disconnected adapters.

11.2 Learning outcomes

- Understanding how WHOIS provides domain registration information.
- Learning how DNS resolution maps a domain to an IP address.
- Understanding how HTTP response headers reveal server and application metadata.
- Learning the purpose of WAF fingerprinting and DNS record enumeration.
- Understanding Nmap port states: open, closed and filtered.
- Recognizing that a port's service label does not confirm software version or vulnerability.
- Learning to document evidence, limitations and recommendations accurately.
- Understanding the importance of written authorization and defined scope.

12. Conclusion

The W2-PM5 project documented a practical sequence of domain footprinting and network-service discovery. WHOIS provided domain registration information; nslookup resolved networkwalks.com to 192.232.216.135; curl returned HTTP/2 200 and exposed web response metadata; WAFW00F identified ModSecurity (SpiderLabs); and DNSRecon successfully enumerated SOA, NS, MX, A, TXT and SRV information.

The supplied Nmap 7.99 output reported the target host as up and identified 14 open TCP ports, 2 filtered TCP ports and 984 closed TCP ports within the default scan range. These results provide an initial view of externally reachable services. They do not establish the software versions, security configuration or exploitability of the services.

The exercise reinforced the importance of interpreting technical evidence carefully. A professional assessment distinguishes between an observation, a potential risk and a confirmed vulnerability. Further testing would require explicit authorization, a defined scope and additional evidence such as service-version detection, configuration review and controlled validation.

The report is complete as an evidence-based draft. Before final submission, the student should confirm authorization details, insert the missing Zenmap screenshots and update the contents/page numbers after editing.

13. References

- Nmap Project. Nmap Reference Guide. https://nmap.org/book/man.html
- Nmap Project. Zenmap GUI. https://nmap.org/book/zenmap.html
- Nmap Project. Nmap Network Scanning documentation. https://nmap.org/book/
- DNSRecon project documentation and source repository. https://github.com/darkoperator/dnsrecon
- OWASP Foundation. Web Security Testing Guide. https://owasp.org/www-project-web-security-testing-guide/
- OWASP Foundation. Application Security Verification Standard. https://owasp.org/www-project-application-security-verification-standard/
- RFC 1034. Domain Names – Concepts and Facilities. https://www.rfc-editor.org/rfc/rfc1034
- RFC 1035. Domain Names – Implementation and Specification. https://www.rfc-editor.org/rfc/rfc1035
- RFC 8446. The Transport Layer Security (TLS) Protocol Version 1.3. https://www.rfc-editor.org/rfc/rfc8446

14. Appendix

Appendix A – Raw Nmap command and output

```
Command:
nmap networkwalks.com

Target:
networkwalks.com (192.232.216.135)

Summary:
Host up; 14 open TCP ports; 2 filtered TCP ports; 984 closed TCP ports.
Scan duration: 3.65 seconds.
Nmap version: 7.99.
```

Appendix B – Screenshot register

Figure	Evidence	Status
1	WHOIS terminal output	Screenshot is uploaded
2	nslookup terminal output	Screenshot is uploaded
3	curl -I response headers	Screenshot is uploaded
4	WAFW00F detection output	Screenshot is uploaded
5	Successful DNSRecon output	Screenshot is uploaded
6	Zenmap Nmap Output tab	Screenshot is uploaded
7	Zenmap Ports/Hosts tab	Screenshot is uploaded
8	Zenmap Topology tab	Screenshot is uploaded
9	Windows ipconfig output	Screenshot is uploaded

Appendix C – Student declaration

I declare that this report reflects the commands, outputs and observations available to me at the time of preparation. I have not intentionally represented an unverified observation as a confirmed vulnerability. I will ensure that all testing described as authorized was performed within an approved scope.

Student signature: ___J.siddhartha_____

Date: _____11/11/2026_____