

Tutorial on Mixed Integer Linear Programming (MIP) and Pseudo-Boolean Optimization

Jakob Nordström

University of Copenhagen and Lund University

SAT + SMT Winter School
Chennai, India
December 15, 2022

Outline of Lecture on MIP Solving and PB Optimization

- ① Mixed Integer Linear Programming (MIP) and Integer Linear Programming (ILP)
 - MIP Preliminaries
 - Branch-and-Bound and Branch-and-Cut
 - Additional Techniques

- ② Combining PB and MIP Techniques
 - Some Challenges When Integrating PB and LP Solving
 - A Proof-of-Concept Hybrid PB-LP Solver
 - Evaluation and Conclusions

An Acknowledgement and an Apology

The MIP material relies heavily on the presentation *Computational Mixed-Integer Programming* by Ambros Gleixner at the Casa Matemática Oaxaca (CMO) workshop *Theory and Practice of Satisfiability Solving* in 2018 (<https://tinyurl.com/MIPtutorial>)

A bit too many references are still missing — see Gleixner' slides for full details

Mixed Integer Linear Programming

Mixed integer linear program

- Minimize $\sum_j a_j x_j$
- Subject to $\sum_j a_{i,j} x_j \leq A_i, i = 1, \dots, m$
- $x_j \in \mathbb{N}$ for $j = 1, \dots, n$
- $x_j \in \mathbb{R}_{\geq 0}$ for $j = n + 1, \dots, N$

Mixed Integer Linear Programming

Mixed integer linear program

- Minimize $\sum_j a_j x_j$
- Subject to $\sum_j a_{i,j} x_j \leq A_i, i = 1, \dots, m$
- $x_j \in \mathbb{N}$ for $j = 1, \dots, n$
- $x_j \in \mathbb{R}_{\geq 0}$ for $j = n + 1, \dots, N$

- Linear constraints
- Integer-valued variables
- Real-valued variables
- Linear objective function

Mixed Integer Linear Programming

Mixed integer linear program

- Minimize $\sum_j a_j x_j$
- Subject to $\sum_j a_{i,j} x_j \leq A_i, i = 1, \dots, m$
- $x_j \in \mathbb{N}$ for $j = 1, \dots, n$
- $x_j \in \mathbb{R}_{\geq 0}$ for $j = n + 1, \dots, N$

- Linear constraints
- Integer-valued variables
- Real-valued variables
- Linear objective function

- No real-valued variables:
integer linear program (ILP)
- $0 \leq x_j \leq 1$ for all j : 0-1 ILP
- Vacuous objective $\sum_j 0 \cdot x_j$:
decision problem
- But MIP best for optimization

Two Differences Compared to SAT/PB

Academia vs. industry

- Best solvers are commercial and closed-source
- E.g., CPLEX [CPL], GUROBI [Gur], and XPRESS [Xpr]
- Academic solvers like SCIP [SCI] are excellent but not as good

Two Differences Compared to SAT/PB

Academia vs. industry

- Best solvers are commercial and closed-source
- E.g., CPLEX [CPL], GUROBI [Gur], and XPRESS [Xpr]
- Academic solvers like SCIP [SCI] are excellent but not as good

Search vs. backtracking

- SAT/PB: Fast decisions; careful, slow(er) conflict analysis
- MIP: Lots of time & effort on decisions; backtracking not so advanced

MIP Solving at a High Level

- 1 Preprocessing (called **presolving**)
- 2 Linear programming + **branch-and-bound**
- 3 Add **cutting planes** ruling out infeasible LP-solutions
(**branch-and-cut** method going back to [Gom58])
- 4 Heuristics for quickly finding good feasible solutions

Linear Programming Relaxation

Linear Programming Relaxation (LPR)

- Minimize $\sum_j a_j x_j$
 - Subject to $\sum_j a_{i,j} x_j \leq A_i, i = 1, \dots, m$
 - ~~$x_j \in \mathbb{N}$ for $j = 1, \dots, n$~~ $x_j \in \mathbb{R}_{\geq 0}$ for $j = 1, \dots, n$
 - $x_j \in \mathbb{R}_{\geq 0}$ for $j = n + 1, \dots, N$
-
- Fast to solve (just linear programming)
 - LP solution x^* yields lower bound
 - Or, if x^* “accidentally” feasible, have optimal solution
 - Use simplex algorithm — will have many LP calls for same problem with different variable bounds; need efficient hot restarts

LP-Based Branch-and-Bound

Branch-and-bound

Choose integer-valued x_j and $B \in \mathbb{N}$

- Solve MIP plus constraint $x_j \geq B$
- Solve MIP plus constraint $x_j \leq B - 1$

LP-Based Branch-and-Bound

Branch-and-bound

Choose integer-valued x_j and $B \in \mathbb{N}$

- Solve MIP plus constraint $x_j \geq B$
- Solve MIP plus constraint $x_j \leq B - 1$

Creates (growing) branch-and-bound tree of subproblems

Prune subproblem/node when

- LP is infeasible
- LP bound $>$ **incumbent** (current best solution)

LP-Based Branch-and-Bound

Branch-and-bound

Choose integer-valued x_j and $B \in \mathbb{N}$

- Solve MIP plus constraint $x_j \geq B$
- Solve MIP plus constraint $x_j \leq B - 1$

Creates (growing) branch-and-bound tree of subproblems

Prune subproblem/node when

- LP is infeasible
- LP bound $>$ **incumbent** (current best solution)

Branch on

- Variables
- General linear constraints (powerful but difficult)
Corresponds to **stabbing planes** proof system [BFI⁺18]

Branch-and-Cut

General cutting plane method

- 1 Solve LP relaxation
- 2 If solution x^* feasible for MIP \Rightarrow found optimum
- 3 Otherwise generate and add constraint $\sum_j b_j x_j \leq B$ that is
 - valid for MIP
 - violated by LP solution x^*
- 4 Repeat from the top

Branch-and-Cut

General cutting plane method

- ① Solve LP relaxation
- ② If solution x^* feasible for MIP \Rightarrow found optimum
- ③ Otherwise generate and add constraint $\sum_j b_j x_j \leq B$ that is
 - valid for MIP
 - violated by LP solution x^*
- ④ Repeat from the top

PB solving rules **division** and **saturation** are examples of cut rules

Branch-and-Cut

General cutting plane method

- ① Solve LP relaxation
- ② If solution x^* feasible for MIP \Rightarrow found optimum
- ③ Otherwise generate and add constraint $\sum_j b_j x_j \leq B$ that is
 - valid for MIP
 - violated by LP solution x^*
- ④ Repeat from the top

PB solving rules **division** and **saturation** are examples of cut rules

Branch-and-cut

- Run branch-and-bound
- But in each subproblem, use cutting plane method to repeatedly
 - solve LP relaxation
 - add cut

Example Cut 1: Knapsack Cover Cut

Given constraint

$$\sum_{j \in I} a_j x_j \leq A$$

for $x_j \in \{0, 1\}$ and $a_j, A \in \mathbb{N}^+$

Example Cut 1: Knapsack Cover Cut

Given constraint

$$\sum_{j \in I} a_j x_j \leq A$$

for $x_j \in \{0, 1\}$ and $a_j, A \in \mathbb{N}^+$

Find **minimal cover** $C \subset I$ such that

$$\sum_{j \in C} a_j > A$$

$$\sum_{j \in C \setminus \{i\}} a_j \leq A$$

for all $i \in C$

Example Cut 1: Knapsack Cover Cut

Given constraint

$$\sum_{j \in I} a_j x_j \leq A$$

for $x_j \in \{0, 1\}$ and $a_j, A \in \mathbb{N}^+$

Find **minimal cover** $C \subset I$ such that

$$\sum_{j \in C} a_j > A$$

$$\sum_{j \in C \setminus \{i\}} a_j \leq A \quad \text{for all } i \in C$$

Then can derive

$$\sum_{j \in C} x_j \leq |C| - 1$$

Example Cut 1: Knapsack Cover Cut

Given constraint

$$\sum_{j \in I} a_j x_j \leq A$$

for $x_j \in \{0, 1\}$ and $a_j, A \in \mathbb{N}^+$

Find **minimal cover** $C \subset I$ such that

$$\sum_{j \in C} a_j > A$$

$$\sum_{j \in C \setminus \{i\}} a_j \leq A \quad \text{for all } i \in C$$

Then can derive

$$\sum_{j \in C} x_j \leq |C| - 1$$

(In cutting planes, weaken & divide $\sum_{j \in I} a_j \bar{x}_j \geq -A + \sum_{j \in I} a_j$ to get disjunctive clause $\sum_{j \in C} \bar{x}_j \geq 1$)

Example Cut 2: Mixed Integer Rounding (MIR) Cut

Mixed integer rounding (MIR) cut [MW01] applied to (normalized) pseudo-Boolean constraint

$$\sum_i a_i \ell_i \geq A$$

with divisor $d \in \mathbb{N}^+$ produces constraint

$$\sum_i \left(\min(a_i \bmod d, A \bmod d) + \lfloor \frac{a_i}{d} \rfloor (A \bmod d) \right) \ell_i \geq \left\lceil \frac{A}{d} \right\rceil (A \bmod d)$$

Example Cut 2: Mixed Integer Rounding (MIR) Cut

Mixed integer rounding (MIR) cut [MW01] applied to (normalized) pseudo-Boolean constraint

$$\sum_i a_i \ell_i \geq A$$

with divisor $d \in \mathbb{N}^+$ produces constraint

$$\sum_i \left(\min(a_i \bmod d, A \bmod d) + \lfloor \frac{a_i}{d} \rfloor (A \bmod d) \right) \ell_i \geq \left\lceil \frac{A}{d} \right\rceil (A \bmod d)$$

Concretely, MIR cut with divisor 3 applied on

$$x + 2y + 3z + 4w + 5u \geq 5$$

(so $(A \bmod d) = (5 \bmod 3) = 2$)

Example Cut 2: Mixed Integer Rounding (MIR) Cut

Mixed integer rounding (MIR) cut [MW01] applied to (normalized) pseudo-Boolean constraint

$$\sum_i a_i \ell_i \geq A$$

with divisor $d \in \mathbb{N}^+$ produces constraint

$$\sum_i \left(\min(a_i \bmod d, A \bmod d) + \lfloor \frac{a_i}{d} \rfloor (A \bmod d) \right) \ell_i \geq \left\lceil \frac{A}{d} \right\rceil (A \bmod d)$$

Concretely, MIR cut with divisor 3 applied on

$$x + 2y + 3z + 4w + 5u \geq 5$$

(so $(A \bmod d) = (5 \bmod 3) = 2$) yields

$$x + 2y + 2z + 3w + 4u \geq 4$$

Example Cut 2: Mixed Integer Rounding (MIR) Cut

Mixed integer rounding (MIR) cut [MW01] applied to (normalized) pseudo-Boolean constraint

$$\sum_i a_i \ell_i \geq A$$

with divisor $d \in \mathbb{N}^+$ produces constraint

$$\sum_i \left(\min(a_i \bmod d, A \bmod d) + \lfloor \frac{a_i}{d} \rfloor (A \bmod d) \right) \ell_i \geq \left\lceil \frac{A}{d} \right\rceil (A \bmod d)$$

Concretely, MIR cut with divisor 3 applied on

$$x + 2y + 3z + 4w + 5u \geq 5$$

(so $(A \bmod d) = (5 \bmod 3) = 2$) yields

$$x + 2y + 2z + 3w + 4u \geq 4$$

For comparison, division by 3 and multiplication by 2 produces

$$2x + 2y + 2z + 4w + 4u \geq 4$$

Presolving

Presolving is a topic for a full separate lecture or two
(well, like most other aspects of MIP solving that we touch on. . .)

Important for performance (but not as important as in CDCL?)

Presolving

Presolving is a topic for a full separate lecture or two
(well, like most other aspects of MIP solving that we touch on. . .)

Important for performance (but not as important as in CDCL?)

Some simple (but efficient) techniques:

- **Substitution** of fixed variables
- **Normalization** of constraints: divide integer constraints by gcd on left-hand side and round on right-hand side
- **Probing**: tentatively assign binary variables and propagate
- **Dominance test**: remove constraints implied by other constraints

Presolving

Presolving is a topic for a full separate lecture or two
(well, like most other aspects of MIP solving that we touch on. . .)

Important for performance (but not as important as in CDCL?)

Some simple (but efficient) techniques:

- **Substitution** of fixed variables
- **Normalization** of constraints: divide integer constraints by gcd on left-hand side and round on right-hand side
- **Probing**: tentatively assign binary variables and propagate
- **Dominance test**: remove constraints implied by other constraints

For more details, see talk by Gleixner <https://tinyurl.com/MIPtutorial>

MIP Conflict Analysis

MIP conflict analysis [Ach07] analogous to CDCL, but

- operate on clausal reasons extracted from constraints
- **not** on constraints themselves

Exponential loss in power!

MIP Conflict Analysis

MIP conflict analysis [Ach07] analogous to CDCL, but

- operate on clausal reasons extracted from constraints
- **not** on constraints themselves

Exponential loss in power!

Pigeonhole principle

$$\sum_{j=1}^n x_{i,j} \geq 1 \qquad i \in [n+1]$$

$$\sum_{i=1}^{n+1} x_{i,j} \leq 1 \qquad j \in [n]$$

Conflict analysis with clausal reasons \Rightarrow same as resolution on CNF encoding \Rightarrow exponential lower bound in [Hak85] applies

MIP Conflict Analysis

MIP conflict analysis [Ach07] analogous to CDCL, but

- operate on clausal reasons extracted from constraints
- **not** on constraints themselves

Exponential loss in power!

Pigeonhole principle

$$\sum_{j=1}^n x_{i,j} \geq 1 \qquad i \in [n+1]$$

$$\sum_{i=1}^{n+1} x_{i,j} \leq 1 \qquad j \in [n]$$

Conflict analysis with clausal reasons \Rightarrow same as resolution on CNF encoding \Rightarrow exponential lower bound in [Hak85] applies

Perhaps a bit stupid example—solved immediately, since LP relaxation is infeasible. . .

MIP Conflict Analysis

MIP conflict analysis [Ach07] analogous to CDCL, but

- operate on clausal reasons extracted from constraints
- **not** on constraints themselves

Exponential loss in power!

Pigeonhole principle

$$\sum_{j=1}^n x_{i,j} \geq 1 \qquad i \in [n+1]$$

$$\sum_{i=1}^{n+1} x_{i,j} \leq 1 \qquad j \in [n]$$

Conflict analysis with clausal reasons \Rightarrow same as resolution on CNF encoding \Rightarrow exponential lower bound in [Hak85] applies

Perhaps a bit stupid example—solved immediately, since LP relaxation is infeasible. . .

But can find other, more interesting benchmarks where MIP conflict analysis seems to really suffer from this problem [DGN21]

Branching Heuristics

Dual gain

Given LP solution x^* , branch on x_j such that $x_j \geq \lceil x_j^* \rceil$ and $x_j \leq \lfloor x_j^* \rfloor$ both provide good lower bound increase

Branching Heuristics

Dual gain

Given LP solution x^* , branch on x_j such that $x_j \geq \lceil x_j^* \rceil$ and $x_j \leq \lfloor x_j^* \rfloor$ both provide good lower bound increase

Look ahead (strong branching)

- Consider all free variables x_j
- Solve LP for all branching decisions $x_j \geq \lceil x_j^* \rceil$ and $x_j \leq \lfloor x_j^* \rfloor$
- Pick best variable

Branching Heuristics

Dual gain

Given LP solution x^* , branch on x_j such that $x_j \geq \lceil x_j^* \rceil$ and $x_j \leq \lfloor x_j^* \rfloor$ both provide good lower bound increase

Look ahead (strong branching)

- Consider all free variables x_j
- Solve LP for all branching decisions $x_j \geq \lceil x_j^* \rceil$ and $x_j \leq \lfloor x_j^* \rfloor$
- Pick best variable

Look back

Compute estimate on gains based on past branching history
(pseudo-costs)

Branching Heuristics

Dual gain

Given LP solution x^* , branch on x_j such that $x_j \geq \lceil x_j^* \rceil$ and $x_j \leq \lfloor x_j^* \rfloor$ both provide good lower bound increase

Look ahead (strong branching)

- Consider all free variables x_j
- Solve LP for all branching decisions $x_j \geq \lceil x_j^* \rceil$ and $x_j \leq \lfloor x_j^* \rfloor$
- Pick best variable

Look back

Compute estimate on gains based on past branching history
(pseudo-costs)

Keep also other statistics about variables to guide search

Node Selection

How to grow search tree?

- **Depth-first search (DFS)**: keeps cost for simplex calls small
*[corresponds to what SAT and PB solvers **always** do]*
- **Best bound search (BBS)**: Focus on improving lower bound
(dual bound)
- **Best estimate search (BES)**: Focus on improving solution
(primal bound)

Node Selection

How to grow search tree?

- **Depth-first search (DFS)**: keeps cost for simplex calls small
*[corresponds to what SAT and PB solvers **always** do]*
- **Best bound search (BBS)**: Focus on improving lower bound
(dual bound)
- **Best estimate search (BES)**: Focus on improving solution
(primal bound)

Combine BBS and BES with **DFS plunges** to exploit simplex hot restarts

Primal Heuristics

- Improve solution (primal bound)
- Guide remaining search

Primal Heuristics

- Improve solution (primal bound)
- Guide remaining search

Example: Relaxation-enforced neighbourhood search

- 1 Solve LP relaxation to get x^*
- 2 Fix values of all x_j such that $x_j^* \in \mathbb{N}$
- 3 For x_j with fractional solution, reduce domain to $x_j \in \{\lfloor x_j^* \rfloor, \lceil x_j^* \rceil\}$
- 4 Solve new subproblem

Primal Heuristics

- Improve solution (primal bound)
- Guide remaining search

Example: Relaxation-enforced neighbourhood search

- 1 Solve LP relaxation to get x^*
- 2 Fix values of all x_j such that $x_j^* \in \mathbb{N}$
- 3 For x_j with fractional solution, reduce domain to $x_j \in \{\lfloor x_j^* \rfloor, \lceil x_j^* \rceil\}$
- 4 Solve new subproblem

Example of “fix-and-MIP” local neighbourhood search heuristic
(Note that, interestingly, this turns ILP into 0-1 ILP subproblem)

And More. . .

1 Decomposition

- Branch-and-price / column generation
- Bender's decomposition
*[Core-guided and IHS search similar in spirit to logic-based
Benders decomposition [HO03]]*

2 Symmetry handling

- Via graph automorphism
- Or dedicated symmetry detection (commercial solvers)

3 Extended formulations (with new variables and constraints)

4 Parallelization

5 Restarts

Numerics and Correctness

Numerics

- Use floating point for efficiency reasons
- Can lead to rounding errors
- Exact MIP solvers like [CKSW13, EG21]
 - are significantly slower
 - don't support the full range of state-of-the-art techniques

Numerics and Correctness

Numerics

- Use floating point for efficiency reasons
- Can lead to rounding errors
- Exact MIP solvers like [CKSW13, EG21]
 - are significantly slower
 - don't support the full range of state-of-the-art techniques

Proof logging / certification

- Currently not available for state-of-the-art MIP solvers
- Though known that even best commercial solvers sometimes give wrong results
- Some work on proof logging in [CGS17, EG21] — challenges:
 - How to capture wide diversity of techniques?
 - What is a convenient format?
 - How to generate proofs efficiently on-the-fly?

Some Interesting MIP Questions

- 1 Develop better heuristics to branch on general linear constraints (cf. **stabbing planes** [BFI⁺18])
- 2 Design stronger conflict analysis operating directly on linear constraints (borrow ideas from native pseudo-Boolean solvers?)
- 3 Provide rigorous understanding of MIP solver performance
- 4 Develop families of theory benchmarks and computational complexity results for them (cf. SAT solving and proof complexity [BN21])
- 5 Steal best MIP ideas and use for pseudo-Boolean solving!?

Some Interesting MIP Questions

- 1 Develop better heuristics to branch on general linear constraints (cf. **stabbing planes** [BFI⁺18])
- 2 Design stronger conflict analysis operating directly on linear constraints (borrow ideas from native pseudo-Boolean solvers?)
- 3 Provide rigorous understanding of MIP solver performance
- 4 Develop families of theory benchmarks and computational complexity results for them (cf. SAT solving and proof complexity [BN21])
- 5 Steal best MIP ideas and use for pseudo-Boolean solving!?
[next and final topic]

Combining PB Solving and Mixed Integer Programming

Pseudo-Boolean solvers

- Sophisticated conflict analysis using cutting planes method
- Sometimes terrible performance even when LP relaxation infeasible [EGNV18]

Combining PB Solving and Mixed Integer Programming

Pseudo-Boolean solvers

- Sophisticated conflict analysis using cutting planes method
- Sometimes terrible performance even when LP relaxation infeasible [EGNV18]

Mixed integer linear programming solvers

- Powerful search
- Exploits information from LP relaxations
- Rich variety of cut generation routines
- But conflict analysis not so great. . .

Combining PB Solving and Mixed Integer Programming

Pseudo-Boolean solvers

- Sophisticated conflict analysis using cutting planes method
- Sometimes terrible performance even when LP relaxation infeasible [EGNV18]

Mixed integer linear programming solvers

- Powerful search
- Exploits information from LP relaxations
- Rich variety of cut generation routines
- But conflict analysis not so great. . .

Why not merge the two to get the best of both worlds of SAT-style conflict-driven search and MIP-style branch-and-cut?

Balance Time Allocation for PB and LP Solving?

High-level idea: Give pseudo-Boolean solver access to LP solver

Balance Time Allocation for PB and LP Solving?

High-level idea: Give pseudo-Boolean solver access to LP solver

First challenge:

- ❶ Using LP solver as preprocessor not sufficient
 - PB formulas can have feasible LP relaxations
 - but quickly turn infeasible after just a couple of decisions
 - Some such benchmarks very hard for PB solvers [EGNV18]

Balance Time Allocation for PB and LP Solving?

High-level idea: Give pseudo-Boolean solver access to LP solver

First challenge:

- ① Using LP solver as preprocessor not sufficient
 - PB formulas can have feasible LP relaxations
 - but quickly turn infeasible after just a couple of decisions
 - Some such benchmarks very hard for PB solvers [EGNV18]
- ② Consulting LP solver before each variable decision impractical
 - PB solving based on rapid alternation of decisions and propagations
 - Solving an LP relaxation is orders of magnitude slower

Balance Time Allocation for PB and LP Solving?

High-level idea: Give pseudo-Boolean solver access to LP solver

First challenge:

- ① Using LP solver as preprocessor not sufficient
 - PB formulas can have feasible LP relaxations
 - but quickly turn infeasible after just a couple of decisions
 - Some such benchmarks very hard for PB solvers [EGNV18]
- ② Consulting LP solver before each variable decision impractical
 - PB solving based on rapid alternation of decisions and propagations
 - Solving an LP relaxation is orders of magnitude slower

Need to **carefully balance time allocation** for PB solver and LP solver

Backtracking from LP Infeasibility?

What to do if LP call shows LP relaxation infeasible under current trail?

- Obviously, PB solver should backtrack
- But can only do conflict analysis on violated PB constraint
- And PB solver blissfully unaware of any conflict. . .

Backtracking from LP Infeasibility?

What to do if LP call shows LP relaxation infeasible under current trail?

- Obviously, PB solver should backtrack
- But can only do conflict analysis on violated PB constraint
- And PB solver blissfully unaware of any conflict. . .

More subtle issue:

- Efficient LP solvers use inexact floating-point arithmetic
- How to incorporate into Boolean solver that must maintain perfectly sound reasoning?

Sharing of Cut Constraints?

Cut constraints from LP solver

- When LP relaxation feasible, MIP solver generates cut constraint to remove the found LP solution
- Should such constraints be shared with the PB solver?

Sharing of Cut Constraints?

Cut constraints from LP solver

- When LP relaxation feasible, MIP solver generates cut constraint to remove the found LP solution
- Should such constraints be shared with the PB solver?

Cut constraints from PB solver

- PB solvers learn new constraints at high rate from conflict analysis
- These learned constraints can also be viewed as cuts
- Should such constraints be passed from PB solver to LP solver?

Report on Proof-of-Concept PB-LP Integration [DGN21]

- ① Interleave LP solving within conflict-driven PB search
 - Limit LP time by enforcing **total #LP pivots \leq #PB conflicts**
 - Only run LP solver when this condition holds
 - **Abort if $> P$ pivots in single LP call**; but if so also double limit P to avoid wasted LP calls in future

Report on Proof-of-Concept PB-LP Integration [DGN21]

- ① Interleave LP solving within conflict-driven PB search
 - Limit LP time by enforcing **total #LP pivots \leq #PB conflicts**
 - Only run LP solver when this condition holds
 - **Abort if $> P$ pivots in single LP call**; but if so also double limit P to avoid wasted LP calls in future
- ② When LP solver detects that LP relaxation infeasible
 - **Farkas' lemma** \Rightarrow violated linear combination of constraints
 - Use this **Farkas constraint** as starting point for conflict analysis
 - Computed using exact arithmetic, so no rounding errors
 - But might not be violated — if so, ignore and continue PB search

Report on Proof-of-Concept PB-LP Integration [DGN21]

- ❶ Interleave LP solving within conflict-driven PB search
 - Limit LP time by enforcing $\text{total \#LP pivots} \leq \text{\#PB conflicts}$
 - Only run LP solver when this condition holds
 - **Abort if $> P$ pivots in single LP call**; but if so also double limit P to avoid wasted LP calls in future
- ❷ When LP solver detects that LP relaxation infeasible
 - **Farkas' lemma** \Rightarrow violated linear combination of constraints
 - Use this **Farkas constraint** as starting point for conflict analysis
 - Computed using exact arithmetic, so no rounding errors
 - But might not be violated — if so, ignore and continue PB search
- ❸ When LP solver finds solution to LP relaxation
 - Generate MIP-style Gomory cut
 - Share constraint to tighten search space on both PB and LP side
 - Try to use LP solution to guide PB search (e.g., variable decisions)

Report on Proof-of-Concept PB-LP Integration [DGN21]

- ❶ Interleave LP solving within conflict-driven PB search
 - Limit LP time by enforcing **total #LP pivots \leq #PB conflicts**
 - Only run LP solver when this condition holds
 - **Abort if $> P$ pivots in single LP call**; but if so also double limit P to avoid wasted LP calls in future
- ❷ When LP solver detects that LP relaxation infeasible
 - **Farkas' lemma** \Rightarrow violated linear combination of constraints
 - Use this **Farkas constraint** as starting point for conflict analysis
 - Computed using exact arithmetic, so no rounding errors
 - But might not be violated — if so, ignore and continue PB search
- ❸ When LP solver finds solution to LP relaxation
 - Generate MIP-style Gomory cut
 - Share constraint to tighten search space on both PB and LP side
 - Try to use LP solution to guide PB search (e.g., variable decisions)
- ❹ Also explore letting PB solver pass learned constraints to LP solver

(What We Need from) Farkas Lemma [Far02]

Pseudo-Boolean Farkas Lemma

Given

- Pseudo-Boolean formula $F = \{C_1, \dots, C_m\}$,
- partial assignment ρ ,

such that LP relaxation of residual formula $F|_\rho$ infeasible

Then \exists coefficients $k_i \in \mathbb{N}$ such that linear combination

$$\sum_{i=1}^m k_i \cdot C_i$$

is violated by ρ , i.e.,

$$\text{slack}(\sum_{i=1}^m k_i \cdot C_i; \rho) < 0$$

Observed in [MM04] that $\sum_{i=1}^m k_i \cdot C_i$ is valid starting point for pseudo-Boolean conflict analysis

Relation to MIP Solvers with Conflict Analysis?

MIP solvers also combine constraint propagation and SAT-style clause learning with LP solving

- Implemented in SCIP [ABKW08]
- And also in closed-source solvers (see [AW13])

Important to understand similarities and differences — let's give high-level description of PB search and conflict analysis phrased in MIP language

Relation to MIP Solvers with Conflict Analysis?

MIP solvers also combine constraint propagation and SAT-style clause learning with LP solving

- Implemented in SCIP [ABKW08]
- And also in closed-source solvers (see [AW13])

Important to understand similarities and differences — let's give high-level description of PB search and conflict analysis phrased in MIP language

Pseudo-Boolean search

- 1 Make **decision** to assign free variable to 0 or 1
- 2 **Propagate** all assignments implied by some linear constraint until saturation
- 3 If no contradiction, go to step 1
- 4 Otherwise some constraint C violated \Rightarrow trigger **conflict analysis**

PB Conflict Analysis “in MIP Language”

Pseudo-Boolean conflict analysis (simplified description)

- 1 Find **reason constraint** R responsible for propagating last variable x in C to “wrong value”

PB Conflict Analysis “in MIP Language”

Pseudo-Boolean conflict analysis (simplified description)

- 1 Find **reason constraint** R responsible for propagating last variable x in C to “wrong value”
- 2 Apply division/saturation to generate (globally valid) **cut** R_{cut} propagating x to $\{0, 1\}$ -value (over the reals)

PB Conflict Analysis “in MIP Language”

Pseudo-Boolean conflict analysis (simplified description)

- 1 Find **reason constraint** R responsible for propagating last variable x in C to “wrong value”
- 2 Apply division/saturation to generate (globally valid) **cut** R_{cut} propagating x to $\{0, 1\}$ -value (over the reals)
- 3 Set $D :=$ smallest integer linear combination of R_{cut} and C for which x cancels — D violated by current solvers assignment with x removed

PB Conflict Analysis “in MIP Language”

Pseudo-Boolean conflict analysis (simplified description)

- 1 Find **reason constraint** R responsible for propagating last variable x in C to “wrong value”
- 2 Apply division/saturation to generate (globally valid) **cut** R_{cut} propagating x to $\{0, 1\}$ -value (over the reals)
- 3 Set $D :=$ smallest integer linear combination of R_{cut} and C for which x cancels — D violated by current solvers assignment with x removed
- 4 Unless D satisfies termination criterion (**assertiveness**), set $C := D$ and go to step 1

PB Conflict Analysis “in MIP Language”

Pseudo-Boolean conflict analysis (simplified description)

- 1 Find **reason constraint** R responsible for propagating last variable x in C to “wrong value”
- 2 Apply division/saturation to generate (globally valid) **cut** R_{cut} propagating x to $\{0, 1\}$ -value (over the reals)
- 3 Set $D :=$ smallest integer linear combination of R_{cut} and C for which x cancels — D violated by current solvers assignment with x removed
- 4 Unless D satisfies termination criterion (**assertiveness**), set $C := D$ and go to step 1
- 5 **Learn** assertive D , i.e., add to solver database of constraints

PB Conflict Analysis “in MIP Language”

Pseudo-Boolean conflict analysis (simplified description)

- 1 Find **reason constraint** R responsible for propagating last variable x in C to “wrong value”
- 2 Apply division/saturation to generate (globally valid) **cut** R_{cut} propagating x to $\{0, 1\}$ -value (over the reals)
- 3 Set $D :=$ smallest integer linear combination of R_{cut} and C for which x cancels — D violated by current solvers assignment with x removed
- 4 Unless D satisfies termination criterion (**assertiveness**), set $C := D$ and go to step 1
- 5 **Learn** assertive D , i.e., add to solver database of constraints
- 6 **Backjump** by undoing further assignments in reverse chronological order until D is no longer violated

PB Conflict Analysis “in MIP Language”

Pseudo-Boolean conflict analysis (simplified description)

- 1 Find **reason constraint** R responsible for propagating last variable x in C to “wrong value”
- 2 Apply division/saturation to generate (globally valid) **cut** R_{cut} propagating x to $\{0, 1\}$ -value (over the reals)
- 3 Set $D :=$ smallest integer linear combination of R_{cut} and C for which x cancels — D violated by current solvers assignment with x removed
- 4 Unless D satisfies termination criterion (**assertiveness**), set $C := D$ and go to step 1
- 5 **Learn** assertive D , i.e., add to solver database of constraints
- 6 **Backjump** by undoing further assignments in reverse chronological order until D is no longer violated
- 7 Switch back to **search** phase

Comparison to MIP Propagation and Conflict Analysis

Propagation in SCIP

- Fast, simple propagation in PB solvers
- Plus powerful, but slower, method of solving LP relaxations

Comparison to MIP Propagation and Conflict Analysis

Propagation in SCIP

- Fast, simple propagation in PB solvers
- Plus powerful, but slower, method of solving LP relaxations

Conflict analysis in SCIP [Ach07]

- Perform derivation not on reason constraints R as described above
- Instead use disjunctive clauses extracted from reason constraints
- Incurs exponential loss in power compared to operating on actual linear constraints (follows from [BKS04, CCT87, Hak85])

Comparison to MIP Propagation and Conflict Analysis

Propagation in SCIP

- Fast, simple propagation in PB solvers
- Plus powerful, but slower, method of solving LP relaxations

Conflict analysis in SCIP [Ach07]

- Perform derivation not on reason constraints R as described above
- Instead use disjunctive clauses extracted from reason constraints
- Incurs exponential loss in power compared to operating on actual linear constraints (follows from [BKS04, CCT87, Hak85])

Arithmetic


- SCIP uses floating point
- Reasoning steps in PB solver computed with exact integer arithmetic
- No issues with possible rounding errors

Experimental Results for Knapsack Benchmarks [Pis05]

ROUNDINGSAT (RS)
enhanced with

- LP solver
SoPLeX (SPX)
(from SCIP)
- Gomory
cuts (GC)
- shared learned
PB cuts (LC)

compared to other
solvers



Experimental Results for PB and MIPLIB Benchmarks

ROUNDINGSAT (RS) run on PB and 0-1 ILP instances with

- LP solver (+SPX)
- plus Gomory cuts (+GC)
- plus sharing cuts learned by PB solver (+LC)

compared to other solvers

instances solved (to optimality for optimization problems)

Highlighting **1st**, **2nd**, and **3rd** best

Experimental Results for PB and MIPLIB Benchmarks

ROUNDINGSAT (RS) run on PB and 0-1 ILP instances with

- LP solver (+SPX)
- plus Gomory cuts (+GC)
- plus sharing cuts learned by PB solver (+LC)

compared to other solvers

instances solved (to optimality for optimization problems)

Highlighting **1st**, **2nd**, and **3rd** best

| | SCIP | RS | +SPX | +GC | +LC | SAT4J | NAPS |
|----------------|-------------|-------------|-------------|-------------|------------|-------|------|
| PB16dec (1783) | 1123 | 1472 | 1453 | 1452 | 1451 | 1432 | 1400 |
| PB16opt (1600) | 1057 | 862 | 988 | 986 | 993 | 776 | 896 |
| MIPdec (556) | 264 | 203 | 263 | 261 | 259 | 169 | 170 |
| MIPopt (291) | 125 | 78 | 101 | 102 | 102 | 62 | 65 |

Performance of Integrated PB-LP Solver

- ① Best of both worlds?
 - At least well-rounded performance
 - Hybrid PB-LP solver always competitive with best solver
 - Pretty dramatic improvements for optimization problems compared to pseudo-Boolean state of the art
 - SCIP is hard to beat, but also pulls quite a few extra tricks that we haven't implemented

Performance of Integrated PB-LP Solver

- ① Best of both worlds?
 - At least well-rounded performance
 - Hybrid PB-LP solver always competitive with best solver
 - Pretty dramatic improvements for optimization problems compared to pseudo-Boolean state of the art
 - SCIP is hard to beat, but also pulls quite a few extra tricks that we haven't implemented
- ② Adding LP solving causes performance loss on PB decision instances
 - Worse results on satisfiable instances
 - Better search (lower conflict count) but slower — doesn't pay off in terms of running time

Performance of Integrated PB-LP Solver

- ❶ Best of both worlds?
 - At least well-rounded performance
 - Hybrid PB-LP solver always competitive with best solver
 - Pretty dramatic improvements for optimization problems compared to pseudo-Boolean state of the art
 - SCIP is hard to beat, but also pulls quite a few extra tricks that we haven't implemented
- ❷ Adding LP solving causes performance loss on PB decision instances
 - Worse results on satisfiable instances
 - Better search (lower conflict count) but slower — doesn't pay off in terms of running time
- ❸ Sharing Gomory cuts and learned cuts not so helpful
 - Except for knapsack benchmarks, where they help a lot
 - And maybe we could/should fine-tune how sharing is done?

Usefulness/Usage of Constraints

Estimate usefulness of different types of constraints

- Proxy: how often used in conflict analysis?
- Certainly not perfect measure
- But hopefully tells us something interesting

Usefulness/Usage of Constraints

Estimate usefulness of different types of constraints

- Proxy: how often used in conflict analysis?
- Certainly not perfect measure
- But hopefully tells us something interesting

Farkas constraints

- More useful than regular learned constraints for optimization problems
- Not so for decision problems

Usefulness/Usage of Constraints

Estimate usefulness of different types of constraints

- Proxy: how often used in conflict analysis?
- Certainly not perfect measure
- But hopefully tells us something interesting

Farkas constraints

- More useful than regular learned constraints for optimization problems
- Not so for decision problems

Constraints learned after Farkas-based conflicts

- Less useful than regular learned constraints
- But big spread in usage measurements

PB Solver Performance: Balancing the Picture

Actually, ROUNDINGSAT can also outperform commercial MIP solvers by 1-2 orders of magnitude for, e.g.,

- matching of children with adoptive families [DGG⁺19]
- automated planning using binarized neural networks [SS18]

as reported by authors of these papers

(See also our paper [SDNS20])

PB Solver Performance: Balancing the Picture

Actually, ROUNDINGSAT can also outperform commercial MIP solvers by 1-2 orders of magnitude for, e.g.,

- matching of children with adoptive families [DGG⁺19]
- automated planning using binarized neural networks [SS18]

as reported by authors of these papers

(See also our paper [SDNS20])

ROUNDINGSAT seems particularly good for “big- M constraints” like

$$A\bar{z} + \sum_i a_i \ell_i \geq A$$

encoding $z \Rightarrow \sum_i a_i \ell_i \geq A$

LP relaxations are quite uninformative for such constraints

Future Research Directions for PB-LP Integration (1/2)

- 1 Fine-tune heuristics
 - Improved LP-based cut generation?
 - Smarter sharing of PB constraints with LP solver?
 - Dynamic allocation of PB and LP solving time based on contributions?

Future Research Directions for PB-LP Integration (1/2)

- ① Fine-tune heuristics
 - Improved LP-based cut generation?
 - Smarter sharing of PB constraints with LP solver?
 - Dynamic allocation of PB and LP solving time based on contributions?
- ② Understand better how constraints from LP solver contribute
 - Why are Farkas constraints so useful?
 - But constraints learned from Farkas conflicts **not** useful?

Future Research Directions for PB-LP Integration (1/2)

- ❶ Fine-tune heuristics
 - Improved LP-based cut generation?
 - Smarter sharing of PB constraints with LP solver?
 - Dynamic allocation of PB and LP solving time based on contributions?
- ❷ Understand better how constraints from LP solver contribute
 - Why are Farkas constraints so useful?
 - But constraints learned from Farkas conflicts **not** useful?
- ❸ Make more intelligent use in PB solver of information from solutions to LP relaxations

Future Research Directions for PB-LP Integration (1/2)

- ① Fine-tune heuristics
 - Improved LP-based cut generation?
 - Smarter sharing of PB constraints with LP solver?
 - Dynamic allocation of PB and LP solving time based on contributions?
- ② Understand better how constraints from LP solver contribute
 - Why are Farkas constraints so useful?
 - But constraints learned from Farkas conflicts **not** useful?
- ③ Make more intelligent use in PB solver of information from solutions to LP relaxations
- ④ Use MIP presolving in pseudo-Boolean solvers

Future Research Directions for PB-LP Integration (1/2)

- ❶ Fine-tune heuristics
 - Improved LP-based cut generation?
 - Smarter sharing of PB constraints with LP solver?
 - Dynamic allocation of PB and LP solving time based on contributions?
- ❷ Understand better how constraints from LP solver contribute
 - Why are Farkas constraints so useful?
 - But constraints learned from Farkas conflicts **not** useful?
- ❸ Make more intelligent use in PB solver of information from solutions to LP relaxations
- ❹ Use MIP presolving in pseudo-Boolean solvers
- ❺ Use MIR cuts and/or other MIP cut rules to improve pseudo-Boolean conflict analysis

Future Research Directions for PB-LP Integration (2/2)

- 6 Combine LP solver with core-guided search or IHS approach

Future Research Directions for PB-LP Integration (2/2)

- ⑥ Combine LP solver with core-guided search or IHS approach
- ⑦ Improve pseudo-Boolean search
 - ROUNDINGSAT with LP integration or core-guided search seems to be state of the art for PB solving
 - But solver much better on unsatisfiable instances (proving optimality) than on satisfiable ones (finding solutions)

Future Research Directions for PB-LP Integration (2/2)

- ⑥ Combine LP solver with core-guided search or IHS approach
- ⑦ Improve pseudo-Boolean search
 - ROUNDINGSAT with LP integration or core-guided search seems to be state of the art for PB solving
 - But solver much better on unsatisfiable instances (proving optimality) than on satisfiable ones (finding solutions)
- ⑧ Export pseudo-Boolean conflict analysis to MIP

Future Research Directions for PB-LP Integration (2/2)

- ⑥ Combine LP solver with core-guided search or IHS approach
- ⑦ Improve pseudo-Boolean search
 - ROUNDINGSAT with LP integration or core-guided search seems to be state of the art for PB solving
 - But solver much better on unsatisfiable instances (proving optimality) than on satisfiable ones (finding solutions)
- ⑧ Export pseudo-Boolean conflict analysis to MIP
- ⑨ Use hybrid PB-LP solver to solve 0-1 MIP problems à la Bender
 - PB solver decides on Boolean variables and propagates
 - LP solver takes care of real-valued variables

Summing up

- Revolution in performance last two decades in
 - Boolean satisfiability (SAT) solving
 - Mixed integer linear programming (MIP)
- More recent addition Cutting-planes-based conflict-driven search
- Quite different approaches
 - Complementary strengths
 - Lots of room for synergies?
- Lots of exciting research waiting to be done 😊

Summing up

- Revolution in performance last two decades in
 - Boolean satisfiability (SAT) solving
 - Mixed integer linear programming (MIP)
- More recent addition Cutting-planes-based conflict-driven search
- Quite different approaches
 - Complementary strengths
 - Lots of room for synergies?
- Lots of **exciting research waiting to be done** 😊
- We're hiring! See www.jakobnordstrom.se/openings

Summing up

- Revolution in performance last two decades in
 - Boolean satisfiability (SAT) solving
 - Mixed integer linear programming (MIP)
- More recent addition Cutting-planes-based conflict-driven search
- Quite different approaches
 - Complementary strengths
 - Lots of room for synergies?
- Lots of **exciting research waiting to be done** 😊
- We're hiring! See www.jakobnordstrom.se/openings

Thanks for sticking till the end!

References I

- [ABKW08] Tobias Achterberg, Timo Berthold, Thorsten Koch, and Kati Wolter. Constraint integer programming: A new approach to integrate CP and MIP. In *Proceedings of the 5th International Conference on the Integration of AI and OR Techniques in Constraint Programming for Combinatorial Optimization Problems (CPAIOR '08)*, volume 5015 of *Lecture Notes in Computer Science*, pages 6–20. Springer, May 2008.
- [Ach07] Tobias Achterberg. Conflict analysis in mixed integer programming. *Discrete Optimization*, 4(1):4–20, March 2007.
- [AW13] Tobias Achterberg and Roland Wunderling. Mixed integer programming: Analyzing 12 years of progress. In Michael Jünger and Gerhard Reinelt, editors, *Facets of Combinatorial Optimization*, pages 449–481. Springer, 2013.
- [BFI⁺18] Paul Beame, Noah Fleming, Russell Impagliazzo, Antonina Kolokolova, Denis Pankratov, Toniann Pitassi, and Robert Robere. Stabbing planes. In *Proceedings of the 9th Innovations in Theoretical Computer Science Conference (ITCS '18)*, volume 94 of *Leibniz International Proceedings in Informatics (LIPIcs)*, pages 10:1–10:20, January 2018.

References II

- [BKS04] Paul Beame, Henry Kautz, and Ashish Sabharwal. Towards understanding and harnessing the potential of clause learning. *Journal of Artificial Intelligence Research*, 22:319–351, December 2004. Preliminary version in *IJCAI '03*.
- [BN21] Samuel R. Buss and Jakob Nordström. Proof complexity and SAT solving. In Armin Biere, Marijn J. H. Heule, Hans van Maaren, and Toby Walsh, editors, *Handbook of Satisfiability*, volume 336 of *Frontiers in Artificial Intelligence and Applications*, chapter 7, pages 233–350. IOS Press, 2nd edition, February 2021.
- [CCT87] William Cook, Collette Rene Coullard, and György Turán. On the complexity of cutting-plane proofs. *Discrete Applied Mathematics*, 18(1):25–38, November 1987.
- [CGS17] Kevin K. H. Cheung, Ambros M. Gleixner, and Daniel E. Steffy. Verifying integer programming results. In *Proceedings of the 19th International Conference on Integer Programming and Combinatorial Optimization (IPCO '17)*, volume 10328 of *Lecture Notes in Computer Science*, pages 148–160. Springer, June 2017.

References III

- [CKSW13] William Cook, Thorsten Koch, Daniel E. Steffy, and Kati Wolter. A hybrid branch-and-bound approach for exact rational mixed-integer programming. *Mathematical Programming Computation*, 5(3):305–344, September 2013.
- [CPL] IBM ILOG CPLEX optimization studio.
<https://www.ibm.com/products/ilog-cplex-optimization-studio>.
- [DGG⁺19] Maxence Delorme, Sergio García, Jacek Gondzioa, Jörg Kalcsics, David Manlove, and William Pettersson. Mathematical models for stable matching problems with ties and incomplete lists. *European Journal of Operational Research*, 277(2):426–441, September 2019.
- [DGN21] Jo Devriendt, Ambros Gleixner, and Jakob Nordström. Learn to relax: Integrating 0-1 integer linear programming with pseudo-Boolean conflict-driven search. *Constraints*, 26(1–4):26–55, October 2021. Preliminary version in *CPAIOR '20*.

References IV

- [EG21] Leon Eifler and Ambros Gleixner. A computational status update for exact rational mixed integer programming. In *Proceedings of the 22nd International Conference on Integer Programming and Combinatorial Optimization (IPCO '21)*, volume 12707 of *Lecture Notes in Computer Science*, pages 163–177. Springer, May 2021.
- [EGNV18] Jan Elffers, Jesús Giráldez-Cru, Jakob Nordström, and Marc Vinyals. Using combinatorial benchmarks to probe the reasoning power of pseudo-Boolean solvers. In *Proceedings of the 21st International Conference on Theory and Applications of Satisfiability Testing (SAT '18)*, volume 10929 of *Lecture Notes in Computer Science*, pages 75–93. Springer, July 2018.
- [Far02] Julius Farkas. Theorie der einfachen Ungleichungen. *Journal für die Reine und Angewandte Mathematik*, 1902(124):1–27, 1902.
- [Gom58] Ralph E. Gomory. Outline of an algorithm for integer solutions to linear programs. *Bulletin of the American Mathematical Society*, 64(5):275–278, 1958.
- [Gur] Gurobi optimizer. <https://www.gurobi.com/>.

References V

- [Hak85] Armin Haken. The intractability of resolution. *Theoretical Computer Science*, 39(2-3):297–308, August 1985.
- [HO03] J. Hooker and G. Ottosson. Logic-based Benders decomposition. *Mathematical Programming*, 96(1):33–60, April 2003.
- [MM04] Vasco M. Manquinho and João P. Marques-Silva. Satisfiability-based algorithms for Boolean optimization. *Annals of Mathematics and Artificial Intelligence*, 40(1):353–372, March 2004.
- [MW01] Hugues Marchand and Laurence A. Wolsey. Aggregation and mixed integer rounding to solve MIPs. *Operations Research*, 49(3):325–468, June 2001.
- [Pis05] David Pisinger. Where are the hard knapsack problems? *Computers & Operations Research*, 32(9):2271–2284, September 2005.
- [SCI] SCIP: Solving constraint integer programs. <http://scip.zib.de/>.

References VI

- [SDNS20] Buser Say, Jo Devriendt, Jakob Nordström, and Peter Stuckey. Theoretical and experimental results for planning with learned binarized neural network transition models. In *Proceedings of the 26th International Conference on Principles and Practice of Constraint Programming (CP '20)*, volume 12333 of *Lecture Notes in Computer Science*, pages 917–934. Springer, September 2020.
- [SS18] Buser Say and Scott Sanner. Planning in factored state and action spaces with learned binarized neural network transition models. In *Proceedings of the 27th International Joint Conference on Artificial Intelligence (IJCAI '18)*, pages 4815–4821, July 2018.
- [Xpr] FICO Xpress optimization.
<https://www.fico.com/en/products/fico-xpress-optimization>.