


Certifying Correctness for Combinatorial Algorithms by Using Pseudo-Boolean Reasoning


Stephan Gocht

1st June 2022


Do you trust your computer?



Do you trust your computer?



Do you trust your computer?



- ▶ what if answer is used for high-stakes decision?
 - ▶ e.g., combinatorial auction, kidney exchange program

Software Verification — How to ensure software behaves as intended?

- ▶ Software testing
 - ▶ run collection of test cases to check if software behaves as intended
 - depends on quality of test cases, likely to miss non-trivial defects
 - can't show absence of bugs, only their presence


Software Verification — How to ensure software behaves as intended?

- ▶ Software testing
 - ▶ run collection of test cases to check if software behaves as intended
 - depends on quality of test cases, likely to miss non-trivial defects
 - can't show absence of bugs, only their presence
- ▶ Formal verification
 - ▶ formally verify that implementation adheres to specification on all possible inputs
 - out of reach for complex, performance-critical software


Software Verification — How to ensure software behaves as intended?

- ▶ Software testing
 - ▶ run collection of test cases to check if software behaves as intended
 - depends on quality of test cases, likely to miss non-trivial defects
 - can't show absence of bugs, only their presence
- ▶ Formal verification
 - ▶ formally verify that implementation adheres to specification on all possible inputs
 - out of reach for complex, performance-critical software
- ▶ Certifying algorithms, also known as proof logging (this talk)
 - ▶ let algorithm output answer and *proof* that answer is correct
 - ▶ **proof**: sequence of simple, efficiently machine-verifiable steps

Detecting Bugs with Certifying Algorithms




Detecting Bugs with Certifying Algorithms



- verification of answer with external tool can detect bugs

Guaranteeing Correctness with Certifying Algorithms



- ▶ successful verification of answer with external tool guarantees correct answer

Why Certifying Algorithms?

- ▶ while solving
 - ▶ increase trust in solution
 - ▶ detect hardware errors

Why Certifying Algorithms?

- ▶ while solving
 - ▶ increase trust in solution
 - ▶ detect hardware errors
- ▶ after solving
 - ▶ analyse certificate to understand and improve solving process
 - ▶ could use certificate to audit solution afterwards

Why Certifying Algorithms?

- ▶ while solving
 - ▶ increase trust in solution
 - ▶ detect hardware errors
- ▶ after solving
 - ▶ analyse certificate to understand and improve solving process
 - ▶ could use certificate to audit solution afterwards
- ▶ during development
 - ▶ simplifies testing: not necessary to know correct answer a priori
 - ▶ find bugs even if result is correct
 - ▶ locate first unsound step

Requirements for Certifying Algorithms

- ▶ certificate verification
 - ▶ should be efficiently machine-verifiable
 - ▶ ideally so simple that proof checker can be formally verified
 - ▶ want: simple, easy to verify steps / rules

Requirements for Certifying Algorithms

- ▶ certificate verification
 - ▶ should be efficiently machine-verifiable
 - ▶ ideally so simple that proof checker can be formally verified
 - ▶ want: simple, easy to verify steps / rules
- ▶ certificate production
 - ▶ should be easy to implement in any solver
 - ▶ should only incur small performance overhead
 - ▶ want: expressive rules for concise reasoning

Requirements for Certifying Algorithms

- ▶ certificate verification
 - ▶ should be efficiently machine-verifiable
 - ▶ ideally so simple that proof checker can be formally verified
 - ▶ want: simple, easy to verify steps / rules
- ▶ certificate production
 - ▶ should be easy to implement in any solver
 - ▶ should only incur small performance overhead
 - ▶ want: expressive rules for concise reasoning

But how?

SAT Solving — A Success Story for Certifying Algorithms ...

- ▶ SAT = satisfiability of propositional formulas in conjunctive normal form (CNF)
- ▶ SAT competition requires solver to produce certificate (aka **proof logging**)

SAT Solving — A Success Story for Certifying Algorithms ...

- ▶ SAT = satisfiability of propositional formulas in conjunctive normal form (CNF)
- ▶ SAT competition requires solver to produce certificate (aka **proof logging**)
- ▶ proof formats such as RUP [GN03], TraceCheck [Bie06], GRIT [CMS17], LRAT [CHH⁺17]; **DRAT** [WHH14] has become standard

... But Need for Further Research

- ▶ some SAT techniques don't have efficient DRAT proof logging
 - ▶ parity reasoning
 - ▶ symmetry breaking
 - ▶ symmetric explanation learning

... But Need for Further Research

- ▶ some SAT techniques don't have efficient DRAT proof logging
 - ▶ parity reasoning
 - ▶ symmetry breaking
 - ▶ symmetric explanation learning
- ▶ not using these techniques \Rightarrow exponential loss in reasoning power / performance

... But Need for Further Research

- ▶ some SAT techniques don't have efficient DRAT proof logging
 - ▶ parity reasoning
 - ▶ symmetry breaking
 - ▶ symmetric explanation learning
- ▶ not using these techniques \Rightarrow exponential loss in reasoning power / performance
- ▶ How about practical proof logging for other solving paradigms?
 - ▶ MaxSAT solving
 - ▶ constraint programming (CP)
 - ▶ mixed integer programming (MIP)
 - ▶ algebraic reasoning / Gröbner basis computations
 - ▶ pseudo-Boolean satisfiability and optimization

... But Need for Further Research

- ▶ some SAT techniques don't have efficient DRAT proof logging
 - ▶ parity reasoning
 - ▶ symmetry breaking
 - ▶ symmetric explanation learning
- ▶ not using these techniques \Rightarrow exponential loss in reasoning power / performance
- ▶ How about practical proof logging for other solving paradigms?
 - ▶ MaxSAT solving
 - ▶ constraint programming (CP)
 - ▶ mixed integer programming (MIP)
 - ▶ algebraic reasoning / Gröbner basis computations
 - ▶ pseudo-Boolean satisfiability and optimization

Need to look beyond DRAT!

New Proof Systems are Being Developed

many new proof systems

- ▶ propagation redundancy (PR) [HKB17]
- ▶ branch and bound in integer programming [CGS17, EG21]
- ▶ practical polynomial calculus (PAC) [RBK18, KFB20, KFBK22]
- ▶ extensible RAT (FRAT) [BCH21]
- ▶ propagation redundancy for BDDs [BB21]
- ▶ Max-SAT resolution [PCH21]
- ▶ **pseudo-Boolean proofs** [EGMN20, GN21, BGMN22]

High Level Idea of Pseudo-Boolean Proofs

- ▶ use **pseudo-Boolean constraints** (0-1 linear inequalities) to describe problem
 - ▶ e.g., $x_1 + x_2 + x_3 \geq 1$ or $2z + x_1 + x_2 + x_3 \geq 2$
 - ▶ solution is assignment satisfying all constraints
 - ▶ NP-complete \Rightarrow very expressive, but in general difficult to find solution

High Level Idea of Pseudo-Boolean Proofs

- ▶ use **pseudo-Boolean constraints** (0-1 linear inequalities) to describe problem
 - ▶ e.g., $x_1 + x_2 + x_3 \geq 1$ or $2z + x_1 + x_2 + x_3 \geq 2$
 - ▶ solution is assignment satisfying all constraints
 - ▶ NP-complete \Rightarrow very expressive, but in general difficult to find solution
- ▶ **proof system** is small set of rules that
 - ▶ are easy to verify
 - ▶ allow to add new constraints using previous constraints
 - ▶ guarantee that at least one (optimal) solution satisfies all constraints (given that original problem has solution)

High Level Idea of Pseudo-Boolean Proofs

- ▶ use **pseudo-Boolean constraints** (0-1 linear inequalities) to describe problem
 - ▶ e.g., $x_1 + x_2 + x_3 \geq 1$ or $2z + x_1 + x_2 + x_3 \geq 2$
 - ▶ solution is assignment satisfying all constraints
 - ▶ NP-complete \Rightarrow very expressive, but in general difficult to find solution
- ▶ **proof system** is small set of rules that
 - ▶ are easy to verify
 - ▶ allow to add new constraints using previous constraints
 - ▶ guarantee that at least one (optimal) solution satisfies all constraints (given that original problem has solution)
- ▶ **proof** constructs sequence of constraints $D_1, D_2, D_3, \dots, D_L$
 - ▶ each constraint is derived by rule in proof system
 - ▶ annotation can contain additional information necessary for efficient verification
 - ▶ proves there is no solution if D_L is $0 \geq 1$
 - ▶ proves optimality if D_L is bound on objective matching known solution
- ▶ rest of this talk will explain and refine these concepts

Our Approach

- ▶ use pseudo-Boolean proofs (PBP)
- ▶ reference implementation of verifier: VeriPB¹
- ▶ **multi-purpose** format: proof logging for wide range of problems / algorithms
 - ▶ reasoning with 0-1 linear inequalities (by design)

¹<https://gitlab.com/MIAOresearch/VeriPB>

Our Approach

- ▶ use pseudo-Boolean proofs (PBP)
- ▶ reference implementation of verifier: VeriPB¹
- ▶ **multi-purpose** format: proof logging for wide range of problems / algorithms
 - ▶ reasoning with 0-1 linear inequalities (by design)
 - ▶ constraint programming, including all-different constraints [EGMN20, GMN22]

¹<https://gitlab.com/MIA0research/VeriPB>

Our Approach

- ▶ use pseudo-Boolean proofs (PBP)
- ▶ reference implementation of verifier: VeriPB¹
- ▶ **multi-purpose** format: proof logging for wide range of problems / algorithms
 - ▶ reasoning with 0-1 linear inequalities (by design)
 - ▶ constraint programming, including all-different constraints [EGMN20, GMN22]
 - ▶ subgraph isomorphism [GMN20]
 - ▶ clique and maximum common (connected) subgraph [GMM⁺20]

¹<https://gitlab.com/MIA0research/VeriPB>

Our Approach

- ▶ use pseudo-Boolean proofs (PBP)
- ▶ reference implementation of verifier: VeriPB¹
- ▶ **multi-purpose** format: proof logging for wide range of problems / algorithms
 - ▶ reasoning with 0-1 linear inequalities (by design)
 - ▶ constraint programming, including all-different constraints [EGMN20, GMN22]
 - ▶ subgraph isomorphism [GMN20]
 - ▶ clique and maximum common (connected) subgraph [GMM⁺20]
 - ▶ SAT solving by generalizing DRAT [GN21]
 - ▶ parity/ XOR reasoning [GN21]
 - ▶ symmetry and dominance breaking (for SAT, PB, CP, clique) [BGMN22]

¹<https://gitlab.com/MIA0research/VeriPB>

Our Approach

- ▶ use pseudo-Boolean proofs (PBP)
- ▶ reference implementation of verifier: VeriPB¹
- ▶ **multi-purpose** format: proof logging for wide range of problems / algorithms
 - ▶ reasoning with 0-1 linear inequalities (by design)
 - ▶ constraint programming, including all-different constraints [EGMN20, GMN22]
 - ▶ subgraph isomorphism [GMN20]
 - ▶ clique and maximum common (connected) subgraph [GMM⁺20]
 - ▶ SAT solving by generalizing DRAT [GN21]
 - ▶ parity/ XOR reasoning [GN21]
 - ▶ symmetry and dominance breaking (for SAT, PB, CP, clique) [BGMN22]
 - ▶ pseudo-Boolean solving via translation to CNF [GMNO22]

¹<https://gitlab.com/MIA0research/VeriPB>

Running Example — Matching

- ▶ bipartite graph $G = (U \cup V, E)$
- ▶ find maximum matching $M \subseteq E$
- ▶ such that no node is incident to two edges in M



1

Basics — Pseudo-Boolean Problems

- ▶ **Boolean variable** x is 0 (false) or 1 (true)
- ▶ **Literal**: x or its negation $\bar{x} = 1 - x$
- ▶ **pseudo-Boolean constraint**: linear inequality over literals
e.g., $\bar{x}_1 + \bar{x}_2 \geq 1$ or $x_1 + 2x_2 + \bar{x}_3 \geq 2$
- ▶ **formula** F : set of constraints
- ▶ **objective function** f to be minimized
- ▶ **Clause**: at-least-one constraint, e.g., $\bar{x}_1 + \bar{x}_2 \geq 1$
- ▶ **Contradiction**: \perp or $0 \geq 1$ is constraint that can't be satisfied

Goal: find assignment minimizing objective and satisfying all constraints



Literal Axioms

$$\overline{x \geq 0}$$

$$\overline{\bar{x} \geq 0}$$

- ▶ can add variable bound
- ▶ rule is annotated by literal



3

Addition Rule

$$\frac{\bar{x}_1 + \bar{x}_2 \geq 1 \quad \bar{x}_2 + \bar{x}_3 \geq 1}{\bar{x}_1 + 2\bar{x}_2 + \bar{x}_3 \geq 2}$$

- ▶ can add two pseudo-Boolean constraints
- ▶ rule is annotated by (reference to) the constraints to be added



Multiplication Rule

$$\frac{\bar{x}_1 + \bar{x}_2 \geq 1}{2\bar{x}_1 + 2\bar{x}_2 \geq 2}$$

- ▶ can multiply constraint by positive number
- ▶ rule is annotated by (reference to) the constraint and used factor

Division Rule

$$\frac{2\bar{x}_1 + 2\bar{x}_2 + 2\bar{x}_2 \geq 3}{\bar{x}_1 + \bar{x}_2 + \bar{x}_2 \geq 2}$$

- ▶ can divide constraint by positive number and round up
- ▶ rule is annotated by (reference to) the constraint and used divisor
- ▶ rules so far are known as the cutting planes proof system [CCT87]



Saturation Rule

$$\frac{4\bar{x}_1 + 3\bar{x}_2 + 2\bar{x}_2 \geq 3}{3\bar{x}_1 + 3\bar{x}_2 + 2\bar{x}_2 \geq 3}$$

- ▶ can reduce too large coefficients (assuming all coefficients are positive)
- ▶ rule is annotated by (reference to) the constraint

Basics — Manipulating Constraints

- ▶ can negate constraint

$$C : x + y + z \geq 2$$

$$\neg C : \bar{x} + \bar{y} + \bar{z} \geq 2$$

Basics — Manipulating Constraints

- ▶ can negate constraint

$$C : x + y + z \geq 2$$

$$\neg C : \bar{x} + \bar{y} + \bar{z} \geq 2$$

- ▶ substitution ω replaces variables by literals or 0, 1

$$\omega = \{ x \mapsto z, y \mapsto 1 \}$$

$$C|_{\omega} : z + 1 + z \geq 2$$

$$2z \geq 1$$

Basics — Manipulating Constraints

- ▶ can negate constraint

$$C : x + y + z \geq 2$$

$$\neg C : \bar{x} + \bar{y} + \bar{z} \geq 2$$

- ▶ substitution ω replaces variables by literals or 0, 1

$$\omega = \{x \mapsto z, y \mapsto 1\}$$

$$C|_{\omega} : z + 1 + z \geq 2$$

$$2z \geq 1$$

- ▶ (total) assignment ρ is substitution setting all variables to 0 or 1

$$\rho = \{x \mapsto 1, y \mapsto 1, z \mapsto 0\}$$

$$C|_{\rho} : 1 + 1 + 0 \geq 2$$

Basics — Manipulating Constraints

- ▶ can negate constraint

$$C : x + y + z \geq 2$$

$$\neg C : \bar{x} + \bar{y} + \bar{z} \geq 2$$

- ▶ substitution ω replaces variables by literals or 0, 1

$$\omega = \{ x \mapsto z, y \mapsto 1 \}$$

$$C|_{\omega} : z + 1 + z \geq 2$$

$$2z \geq 1$$

- ▶ (total) assignment ρ is substitution setting all variables to 0 or 1

$$\rho = \{ x \mapsto 1, y \mapsto 1, z \mapsto 0 \}$$

$$C|_{\rho} : 1 + 1 + 0 \geq 2$$

- ▶ compose substitutions $\rho \circ \omega(x) = \rho(\omega(x))$

Basics — Manipulating Constraints

- ▶ can negate constraint

$$C : x + y + z \geq 2$$

$$\neg C : \bar{x} + \bar{y} + \bar{z} \geq 2$$

- ▶ substitution ω replaces variables by literals or 0, 1

$$\omega = \{ x \mapsto z, y \mapsto 1 \}$$

$$C|_{\omega} : z + 1 + z \geq 2$$

$$2z \geq 1$$

- ▶ (total) assignment ρ is substitution setting all variables to 0 or 1

$$\rho = \{ x \mapsto 1, y \mapsto 1, z \mapsto 0 \}$$

$$C|_{\rho} : 1 + 1 + 0 \geq 2$$

- ▶ compose substitutions $\rho \circ \omega(x) = \rho(\omega(x))$

- ▶ **Implication:** $F \models C$ if every assignment satisfying F also satisfies C

Constraints that Remove Solutions

- ▶ so far, any solution satisfying F also satisfies added constraints (rules are implicational)
- ▶ however, only need to guarantee that solutions with minimal objective f remain



6

Constraints that Remove Solutions

- ▶ so far, any solution satisfying F also satisfies added constraints (rules are implicational)
- ▶ however, only need to guarantee that solutions with minimal objective f remain



6

- ▶ initial idea:
 - ▶ assume we want to add C
 - ▶ but there is assignment α satisfying F but falsifying C

Constraints that Remove Solutions

- ▶ so far, any solution satisfying F also satisfies added constraints (rules are implicational)
- ▶ however, only need to guarantee that solutions with minimal objective f remain



6

- ▶ initial idea:
 - ▶ assume we want to add C
 - ▶ but there is assignment α satisfying F but falsifying C
 - ▶ if we find assignment α' satisfying F and $f_{\upharpoonright\alpha'} < f_{\upharpoonright\alpha}$

Constraints that Remove Solutions

- ▶ so far, any solution satisfying F also satisfies added constraints (rules are implicational)
- ▶ however, only need to guarantee that solutions with minimal objective f remain



6

- ▶ initial idea:
 - ▶ assume we want to add C
 - ▶ but there is assignment α satisfying F but falsifying C
 - ▶ if we find assignment α' satisfying F and $f_{\upharpoonright\alpha'} < f_{\upharpoonright\alpha}$
 - ▶ then α wasn't optimal \rightarrow OK that α falsifies C
 - ▶ save to add C if for all α falsifying C we find such an α'

Verifying Constraints that Remove Solutions

- ▶ initial idea: add C if for all α falsifying C there is α' satisfying F and $f_{\upharpoonright\alpha'} < f_{\upharpoonright\alpha}$
- ▶ problem:
 - ▶ needs to be efficiently verifiable
 - ▶ listing all α' would be prohibitive

Verifying Constraints that Remove Solutions

- ▶ initial idea: add C if for all α falsifying C there is α' satisfying F and $f_{\upharpoonright\alpha'} < f_{\upharpoonright\alpha}$
- ▶ problem:
 - ▶ needs to be efficiently verifiable
 - ▶ listing all α' would be prohibitive
- ▶ solution: only provide instruction (substitution ω) how to alter α , check that

$$F \cup \{ \neg C \} \models F_{\upharpoonright\omega} \cup \{ f_{\upharpoonright\omega} < f \}$$

Verifying Constraints that Remove Solutions

- ▶ initial idea: add C if for all α falsifying C there is α' satisfying F and $f_{\upharpoonright\alpha'} < f_{\upharpoonright\alpha}$
- ▶ problem:
 - ▶ needs to be efficiently verifiable
 - ▶ listing all α' would be prohibitive
- ▶ solution: only provide instruction (substitution ω) how to alter α , check that

$$F \cup \{ \neg C \} \models F_{\upharpoonright\omega} \cup \{ f_{\upharpoonright\omega} < f \}$$

- ▶ assume α satisfies $F \cup \{ \neg C \}$ (i.e., α satisfies F and falsifies C)
- ▶ by implication above, α satisfies $F_{\upharpoonright\omega} \cup \{ f_{\upharpoonright\omega} < f \}$
- ▶ hence $\alpha' = \alpha \circ \omega$ satisfies F and has better objective value:

$$\begin{aligned} & (F_{\upharpoonright\omega} \cup \{ f_{\upharpoonright\omega} < f \})_{\upharpoonright\alpha} \\ &= F_{\upharpoonright\alpha \circ \omega} \cup \{ f_{\upharpoonright\alpha \circ \omega} < f_{\upharpoonright\alpha} \} \\ &= F_{\upharpoonright\alpha'} \cup \{ f_{\upharpoonright\alpha'} < f_{\upharpoonright\alpha} \} \end{aligned}$$

Verifying the Condition

- ▶ only provide instruction (substitution ω) how to alter α , check that

$$F \cup \{ \neg C \} \models F_{\upharpoonright \omega} \cup \{ f_{\upharpoonright \omega} < f \}$$

- ▶ problem: implication hard to check in general

Verifying the Condition

- ▶ only provide instruction (substitution ω) how to alter α , check that

$$F \cup \{ \neg C \} \models F_{\upharpoonright \omega} \cup \{ f_{\upharpoonright \omega} < f \}$$

- ▶ problem: implication hard to check in general
- ▶ solution: provide proof (using previous rules), showing

$$F \cup \{ \neg C, \neg D \} \models \perp \text{ for } D \in F_{\upharpoonright \omega} \cup \{ f_{\upharpoonright \omega} < f \}$$

Dominance Rule (simplified)

$$\frac{F \cup \{\neg C\} \models F_{\upharpoonright \omega} \cup \{f_{\upharpoonright \omega} < f\}}{C}$$

- ▶ rule is annotated by:
 - ▶ used substitution ω
 - ▶ for each $D \in F_{\upharpoonright \omega} \cup \{f_{\upharpoonright \omega} < f\}$ a proof showing $F \cup \{\neg C, \neg D\} \models \perp$



Redundance Rule (simplified)

- ▶ idea: (generalize redundancy from SAT [HKB17, BT19] to PB and optimization)
 - ▶ don't need to improve objective strictly
 - ▶ sufficient if one optimal solution remains



Redundance Rule (simplified)

- ▶ idea: (generalize redundancy from SAT [HKB17, BT19] to PB and optimization)
 - ▶ don't need to improve objective strictly
 - ▶ sufficient if one optimal solution remains
 - ▶ let G_i , be set of constraints added so far ($G_i = F \cup \{D_1, \dots, D_{i-1}\}$)



$$\frac{G_i \cup \{\neg D_i\} \models (G_i \cup D_i)_{\upharpoonright \omega} \cup \{f_{\upharpoonright \omega} \leq f\}}{D_i}$$

- ▶ rule is annotated by:
 - ▶ used substitution ω
 - ▶ for each $C \in (G_i \cup D_i)_{\upharpoonright \omega} \cup \{f_{\upharpoonright \omega} \leq f\}$ a proof showing $G_i \cup \{\neg D_i, \neg C\} \models \perp$

Proving Soundness of Proof System

Remember:

- ▶ rules need to guarantee that at least one (optimal) solution satisfies all constraints (given that original problem has solution)

Proving Soundness of Proof System

Remember:

- ▶ rules need to guarantee that at least one (optimal) solution satisfies all constraints (given that original problem has solution)

Rules presented so far maintain invariant:

- ▶ if there is optimal assignment ρ satisfying $F \cup \{ D_1, \dots, D_{i-1} \}$,
- ▶ then there is assignment ρ' satisfying $F \cup \{ D_1, \dots, D_i \}$,
- ▶ and $f_{\upharpoonright \rho'} = f_{\upharpoonright \rho}$



Proving Soundness of Proof System

Remember:

- ▶ rules need to guarantee that at least one (optimal) solution satisfies all constraints (given that original problem has solution)



Rules presented so far maintain invariant:

- ▶ if there is optimal assignment ρ satisfying $F \cup \{ D_1, \dots, D_{i-1} \}$,
- ▶ then there is assignment ρ' satisfying $F \cup \{ D_1, \dots, D_i \}$,
- ▶ and $f_{\upharpoonright \rho'} = f_{\upharpoonright \rho}$



8

Rule for Objective Bound Update

idea:

- ▶ incremental solver finds solution ρ to F
- ▶ now only looking for better solution
- ▶ finished if no better solution can be found

Rule for Objective Bound Update

idea:

- ▶ incremental solver finds solution ρ to F
- ▶ now only looking for better solution
- ▶ finished if no better solution can be found

$$\frac{\rho \text{ satisfies } F}{f < f_{\upharpoonright\rho}}$$

rule is annotated by:

- ▶ solution ρ



Rule for Objective Bound Update

idea:

- ▶ incremental solver finds solution ρ to F
- ▶ now only looking for better solution
- ▶ finished if no better solution can be found

$$\frac{\rho \text{ satisfies } F}{f < f_{\upharpoonright\rho}}$$

rule is annotated by:

- ▶ solution ρ



note:

- ▶ can terminate all proofs with contradiction ($0 \geq 1$)

Deletion Rule

deleting constraints ...

- ▶ important for performance and memory efficiency
- ▶ only makes problem more satisfiable
(except in connection with dominance — explanation in second part)

Dealing with Lazy Programmers ;-)

- ▶ goal: proof system should be easy to use
- ▶ problem: often “obvious” that adding constraint is OK, but tedious to write down
- ▶ solution: let verifier take care of “obvious” cases

Omitting Obvious Steps

from dominance rule:

- ▶ for each $D \in F_{\upharpoonright\omega} \cup \{f_{\upharpoonright\omega} < f\}$ a proof showing $F \cup \{\neg C, \neg D\} \models \perp$

can omit proof if

- ▶ $\neg D = \perp$
- ▶ $D \in F$ (because $\neg D + D = \perp$)
- ▶ $\neg C + \neg D = \perp$

Reverse Unit Propagation [GN03, Van08]

- ▶ assume we have

$$C_1 : x + y \geq 1$$

$$C_2 : \bar{y} + z \geq 1$$

- ▶ and want to add

$$C_3 : x + z \geq 1$$

Reverse Unit Propagation [GN03, Van08]

- ▶ assume we have

$$C_1 : x + y \geq 1$$

$$C_2 : \bar{y} + z \geq 1$$

- ▶ and want to add

$$C_3 : x + z \geq 1$$

- ▶ simply claim there is no solution satisfying C_1, C_2 but falsifying C_3

Reverse Unit Propagation [GN03, Van08]

- ▶ assume we have

$$C_1 : x + y \geq 1$$

$$C_2 : \bar{y} + z \geq 1$$

- ▶ and want to add

$$C_3 : x + z \geq 1$$

- ▶ simply claim there is no solution satisfying C_1, C_2 but falsifying C_3
- ▶ easy to check by propagation (setting forced variables):
 - ▶ C_3 only false if $\rho(x) = \rho(z) = 0$

Reverse Unit Propagation [GN03, Van08]

- ▶ assume we have

$$C_1 : x + y \geq 1$$

$$C_2 : \bar{y} + z \geq 1$$

- ▶ and want to add

$$C_3 : x + z \geq 1$$

- ▶ simply claim there is no solution satisfying C_1, C_2 but falsifying C_3
- ▶ easy to check by propagation (setting forced variables):
 - ▶ C_3 only false if $\rho(x) = \rho(z) = 0$
 - ▶ but then C_1 only true if $\rho(y) = 1$

Reverse Unit Propagation [GN03, Van08]

- ▶ assume we have

$$C_1 : x + y \geq 1$$

$$C_2 : \bar{y} + z \geq 1$$

- ▶ and want to add

$$C_3 : x + z \geq 1$$

- ▶ simply claim there is no solution satisfying C_1, C_2 but falsifying C_3
- ▶ easy to check by propagation (setting forced variables):
 - ▶ C_3 only false if $\rho(x) = \rho(z) = 0$
 - ▶ but then C_1 only true if $\rho(y) = 1$
 - ▶ but now C_2 falsified by ρ

Reverse Unit Propagation [GN03, Van08]

- ▶ assume we have

$$C_1 : x + y \geq 1$$

$$C_2 : \bar{y} + z \geq 1$$

- ▶ and want to add

$$C_3 : x + z \geq 1$$

- ▶ simply claim there is no solution satisfying C_1, C_2 but falsifying C_3
- ▶ easy to check by propagation (setting forced variables):
 - ▶ C_3 only false if $\rho(x) = \rho(z) = 0$
 - ▶ but then C_1 only true if $\rho(y) = 1$
 - ▶ but now C_2 falsified by ρ
 - ▶ \Rightarrow no assignment ρ satisfies C_1, C_2 and $\neg C_3$

Future Work

improve performance:

- ▶ binary format / on-the-fly compression
- ▶ trimming proof while verifying (as for DRAT [HHW13])

Future Work

improve performance:

- ▶ binary format / on-the-fly compression
- ▶ trimming proof while verifying (as for DRAT [HHW13])

increase trustworthiness:

- ▶ formally verified verifier

Future Work

improve performance:

- ▶ binary format / on-the-fly compression
- ▶ trimming proof while verifying (as for DRAT [HHW13])

increase trustworthiness:

- ▶ formally verified verifier

proof logging for more algorithms and problems:

- ▶ MaxSAT (optimization for SAT)
- ▶ more propagators in constraint programming
- ▶ symmetric explanation learning
- ▶ integer programming

Conclusion

- ▶ proof logging is well-established standard for SAT solving
- ▶ so far not usable for
 - ▶ some techniques in SAT (e.g. symmetry breaking)
 - ▶ richer problem formalisms including optimization

Conclusion

- ▶ proof logging is well-established standard for SAT solving
- ▶ so far not usable for
 - ▶ some techniques in SAT (e.g. symmetry breaking)
 - ▶ richer problem formalisms including optimization

our work: proof logging via pseudo-Boolean proofs + verification (VeriPB²)

- ▶ simple to implement + efficient proof checking
- ▶ applicable to wide range of combinatorial problems / algorithms
- ▶ resolve open problems for proof logging in SAT

²<https://gitlab.com/MIA0research/VeriPB>

Menu for second part

- ▶ live demo
- ▶ translating DRAT proofs
- ▶ full form of dominance / redundance
- ▶ deletion and dominance

Translating DRAT Proof to Pseudo-Boolean Proof

- ▶ step in DRAT proof is clausal form of redundancy rule
- ▶ witness ω implicitly set by first literal
- ▶ literals represented by numbers

```
c DRAT PROOF
```

```
c loads formula implicitly
```

```
1 2 -3 0
```

```
pseudo-Boolean proof version 1.3
```

```
* load formula explicitly
```

```
f
```

```
red 1 x1 1 x2 1 ~x3 >= 1 ; x1 -> 1
```

Dominance Rule (explanation in second part)

in [BGMN22] rule is more general:

- ▶ allow to improve arbitrary preorder \preceq instead of objective
- ▶ define preorder as set of constraints $\mathcal{O}_{\preceq}(\vec{u}, \vec{v})$
- ▶ proof file shows that $\mathcal{O}_{\preceq}(\vec{u}, \vec{v})$ defines preorder
- ▶ \mathcal{C} is set of constraints last time preorder was changed
- ▶ \mathcal{D} is set of constraints added after last time preorder was changed
- ▶ allows to use constraints in \mathcal{D}
- ▶ check $\alpha' \preceq \alpha$

$$\mathcal{C} \cup \mathcal{D} \cup \{ \neg C \} \models \mathcal{C}_{\upharpoonright \omega} \cup \mathcal{O}_{\preceq}(\vec{x}_{\upharpoonright \omega}, \vec{x}) \cup \{ f_{\upharpoonright \omega} \leq f \}$$

- ▶ check $\alpha \not\preceq \alpha'$

$$\mathcal{C} \cup \mathcal{D} \cup \{ \neg C \} \cup \mathcal{O}_{\preceq}(\vec{x}, \vec{x}_{\upharpoonright \omega}) \models \perp$$

Redundance Rule (explanation in second part)

in [BGMN22] rule is more general:

- ▶ preorder defined through $\mathcal{O}_{\preceq}(\vec{u}, \vec{v})$
- ▶ \mathcal{C} is set of constraints last time preorder was changed
- ▶ \mathcal{D} is set of constraints added after last time preorder was changed

$$\frac{\mathcal{C} \cup \mathcal{D} \cup \{\neg C\} \models (\mathcal{C} \cup \mathcal{D} \cup \{C\})_{\upharpoonright \omega} \cup \mathcal{O}_{\preceq}(\vec{x}_{\upharpoonright \omega}, \vec{x}) \cup \{f_{\upharpoonright \omega} \leq f\}}{C}$$

References I

- [BB21] Lee A. Barnett and Armin Biere.
Non-clausal Redundancy Properties.
In André Platzer and Geoff Sutcliffe, editors, *Proceedings of the 28th International Conference on Automated Deduction (CADE 28)*, volume 12699 of *Lecture Notes in Computer Science*, pages 252–272, 2021.
- [BCH21] Seulkee Baek, Mario Carneiro, and Marijn J. H. Heule.
A Flexible Proof Format for SAT Solver-Elaborator Communication.
In *Proceedings of the 27th International Conference on Tools and Algorithms for the Construction and Analysis of Systems (TACAS '21)*, volume 12651 of *Lecture Notes in Computer Science*, pages 59–75. Springer, MarchApril 2021.
- [BGMN22] Bart Bogaerts, Stephan Gocht, Ciaran McCreesh, and Jakob Nordström.
Certified Symmetry and Dominance Breaking for Combinatorial Optimisation.
In *Proceedings of the 36th AAAI Conference on Artificial Intelligence (AAAI '22)*, February 2022.
To appear.
- [Bie06] Armin Biere.
TraceCheck.
<http://fmv.jku.at/tracecheck/>, 2006.

References II

- [BT19] Samuel R. Buss and Neil Thapen.
DRAT Proofs, Propagation Redundancy, and Extended Resolution.
In Proceedings of the 22nd International Conference on Theory and Applications of Satisfiability Testing (SAT '19), volume 11628 of *Lecture Notes in Computer Science*, pages 71–89. Springer, July 2019.
- [CCT87] William Cook, Collette Rene Coullard, and György Turán.
On the Complexity of Cutting-Plane Proofs.
Discrete Applied Mathematics, 18(1):25–38, November 1987.
- [CGS17] Kevin K. H. Cheung, Ambros M. Gleixner, and Daniel E. Steffy.
Verifying Integer Programming Results.
In Proceedings of the 19th International Conference on Integer Programming and Combinatorial Optimization (IPCO '17), volume 10328 of *Lecture Notes in Computer Science*, pages 148–160. Springer, June 2017.
- [CHH⁺17] Luís Cruz-Filipe, Marijn J. H. Heule, Warren A. Hunt Jr., Matt Kaufmann, and Peter Schneider-Kamp.
Efficient Certified RAT Verification.
In Proceedings of the 26th International Conference on Automated Deduction (CADE-26), volume 10395 of *Lecture Notes in Computer Science*, pages 220–236. Springer, August 2017.

References III

- [CMS17] Luís Cruz-Filipe, João P. Marques-Silva, and Peter Schneider-Kamp.
Efficient Certified Resolution Proof Checking.
In *Proceedings of the 23rd International Conference on Tools and Algorithms for the Construction and Analysis of Systems (TACAS '17)*, volume 10205 of *Lecture Notes in Computer Science*, pages 118–135. Springer, April 2017.
- [EG21] Leon Eifler and Ambros Gleixner.
A Computational Status Update for Exact Rational Mixed Integer Programming.
In *Proceedings of the 22nd International Conference on Integer Programming and Combinatorial Optimization (IPCO '21)*, volume 12707 of *Lecture Notes in Computer Science*, pages 163–177. Springer, May 2021.
- [EGMN20] Jan Elffers, Stephan Gocht, Ciaran McCreesh, and Jakob Nordström.
Justifying All Differences Using Pseudo-Boolean Reasoning.
In *Proceedings of the AAAI Conference on Artificial Intelligence (AAAI '20)*, volume 34, pages 1486–1494. AAAI Press, 2020.

References IV

- [GMM⁺20] Stephan Gocht, Ross McBride, Ciaran McCreesh, Jakob Nordström, Patrick Prosser, and James Trimble.
Certifying Solvers for Clique and Maximum Common (Connected) Subgraph Problems.
In Proceedings of the 26th International Conference on Principles and Practice of Constraint Programming (CP '20), volume 12333 of *Lecture Notes in Computer Science*, pages 338–357. Springer, 2020.
- [GMN20] Stephan Gocht, Ciaran McCreesh, and Jakob Nordström.
Subgraph Isomorphism Meets Cutting Planes: Solving With Certified Solutions.
In Proceedings of the Twenty-Ninth International Joint Conference on Artificial Intelligence, (IJCAI '20), pages 1134–1140, 2020.
- [GMN22] Stephan Gocht, Ciaran McCreesh, and Jakob Nordström.
An Auditable Constraint Programming Solver.
In Proceedings of the 28th International Conference on Principles and Practice of Constraint Programming (CP '22), 2022.
- [GMNO22] Stephan Gocht, Ruben Martins, Jakob Nordström, and Andy Oertel.
Certified CNF Translations for Pseudo-Boolean Solving.
In Proceedings of the 25nd International Conference on Theory and Applications of Satisfiability Testing (SAT '22), 2022.

References V

- [GN03] Evgueni Goldberg and Yakov Novikov.
Verification of Proofs of Unsatisfiability for CNF Formulas.
In Proceedings of the Conference on Design, Automation and Test in Europe (DATE '03), pages 886–891, March 2003.
- [GN21] Stephan Gocht and Jakob Nordström.
Certifying Parity Reasoning Efficiently Using Pseudo-Boolean Proofs.
In Proceedings of the 35th AAAI Conference on Artificial Intelligence (AAAI '21), pages 3768–3777, February 2021.
- [HHW13] Marijn J. H. Heule, Warren A. Hunt Jr., and Nathan Wetzler.
Trimming While Checking Clausal Proofs.
In Proceedings of the 13th International Conference on Formal Methods in Computer-Aided Design (FMCAD '13), pages 181–188, October 2013.
- [HKB17] Marijn J. H. Heule, Benjamin Kiesl, and Armin Biere.
Short Proofs Without New Variables.
In Proceedings of the 26th International Conference on Automated Deduction (CADE-26), volume 10395 of *Lecture Notes in Computer Science*, pages 130–147. Springer, August 2017.
- [KFB20] Daniela Kaufmann, Mathias Fleury, and Armin Biere.
The Proof Checkers Pacheck and Pastèque for the Practical Algebraic Calculus.
In Proceedings of Formal Methods in Computer Aided Design, FMCAD 2020, pages 264–269, 2020.

References VI

- [KFBK22] Daniela Kaufmann, Mathias Fleury, Armin Biere, and Manuel Kauers.
Practical algebraic calculus and Nullstellensatz with the checkers Pacheck and Pastèque and Nuss-Checker.
Formal Methods in System Design, 2022.
- [PCH21] Matthieu Py, Mohamed Sami Cherif, and Djamal Habet.
A Proof Builder for Max-SAT.
In *Theory and Applications of Satisfiability Testing – SAT 2021*, pages 488–498, 2021.
- [RBK18] Daniela Ritirc, Armin Biere, and Manuel Kauers.
A practical polynomial calculus for arithmetic circuit verification.
In *Proceedings of the 3rd International Workshop on Satisfiability Checking and Symbolic Computation (SC2'18)*, pages 61–76, 2018.
- [Van08] Allen Van Gelder.
Verifying RUP Proofs of Propositional Unsatisfiability.
In *10th International Symposium on Artificial Intelligence and Mathematics (ISAIM '08)*, 2008.
Available at <http://isaim2008.unl.edu/index.php?page=proceedings>.

References VII

- [WHH14] Nathan Wetzler, Marijn J. H. Heule, and Warren A. Hunt Jr.
DRAT-trim: Efficient Checking and Trimming Using Expressive Clausal Proofs.
In *Proceedings of the 17th International Conference on Theory and Applications of Satisfiability Testing (SAT '14)*, volume 8561 of *Lecture Notes in Computer Science*, pages 422–429. Springer, July 2014.