

Introduction to Boolean Satisfiability (SAT) Solving

Jakob Nordström

University of Copenhagen and Lund University

SAT + SMT Winter School

Chennai, India

December 15, 2022

This Is Me...

Jakob Nordström

Professor

University of Copenhagen
and Lund University

www.jakobnordstrom.se



... And This Is What I Do for a Living

$$\begin{aligned} & (x_{1,1} \vee x_{1,2} \vee x_{1,3} \vee x_{1,4} \vee x_{1,5} \vee x_{1,6} \vee x_{1,7}) \wedge (x_{2,1} \vee x_{2,2} \vee x_{2,3} \vee x_{2,4} \vee x_{2,5} \vee x_{2,6} \vee x_{2,7}) \wedge \\ & (x_{3,1} \vee x_{3,2} \vee x_{3,3} \vee x_{3,4} \vee x_{3,5} \vee x_{3,6} \vee x_{3,7}) \wedge (x_{4,1} \vee x_{4,2} \vee x_{4,3} \vee x_{4,4} \vee x_{4,5} \vee x_{4,6} \vee x_{4,7}) \wedge (x_{5,1} \vee \\ & x_{5,2} \vee x_{5,3} \vee x_{5,4} \vee x_{5,5} \vee x_{5,6} \vee x_{5,7}) \wedge (x_{6,1} \vee x_{6,2} \vee x_{6,3} \vee x_{6,4} \vee x_{6,5} \vee x_{6,6} \vee x_{6,7}) \wedge (x_{7,1} \vee x_{7,2} \vee \\ & x_{7,3} \vee x_{7,4} \vee x_{7,5} \vee x_{7,6} \vee x_{7,7}) \wedge (x_{8,1} \vee x_{8,2} \vee x_{8,3} \vee x_{8,4} \vee x_{8,5} \vee x_{8,6} \vee x_{8,7}) \wedge (\neg x_{1,1} \vee \neg x_{2,1}) \wedge \\ & (\neg x_{1,1} \vee \neg x_{3,1}) \wedge (\neg x_{1,1} \vee \neg x_{4,1}) \wedge (\neg x_{1,1} \vee \neg x_{5,1}) \wedge (\neg x_{1,1} \vee \neg x_{6,1}) \wedge (\neg x_{1,1} \vee \neg x_{7,1}) \wedge \\ & (\neg x_{1,1} \vee \neg x_{8,1}) \wedge (\neg x_{2,1} \vee \neg x_{3,1}) \wedge (\neg x_{2,1} \vee \neg x_{4,1}) \wedge (\neg x_{2,1} \vee \neg x_{5,1}) \wedge (\neg x_{2,1} \vee \neg x_{6,1}) \wedge \\ & (\neg x_{2,1} \vee \neg x_{7,1}) \wedge (\neg x_{2,1} \vee \neg x_{8,1}) \wedge (\neg x_{3,1} \vee \neg x_{4,1}) \wedge (\neg x_{3,1} \vee \neg x_{5,1}) \wedge (\neg x_{3,1} \vee \neg x_{6,1}) \wedge (\neg x_{3,1} \vee \\ & \neg x_{7,1}) \wedge (\neg x_{3,1} \vee \neg x_{8,1}) \wedge (\neg x_{4,1} \vee \neg x_{5,1}) \wedge (\neg x_{4,1} \vee \neg x_{6,1}) \wedge (\neg x_{4,1} \vee \neg x_{7,1}) \wedge (\neg x_{4,1} \vee \neg x_{8,1}) \wedge \\ & (\neg x_{5,1} \vee \neg x_{6,1}) \wedge (\neg x_{5,1} \vee \neg x_{7,1}) \wedge (\neg x_{5,1} \vee \neg x_{8,1}) \wedge (\neg x_{6,1} \vee \neg x_{7,1}) \wedge (\neg x_{6,1} \vee \neg x_{8,1}) \wedge (\neg x_{7,1} \vee \\ & \neg x_{8,1}) \wedge (\neg x_{1,2} \vee \neg x_{2,2}) \wedge (\neg x_{1,2} \vee \neg x_{3,2}) \wedge (\neg x_{1,2} \vee \neg x_{4,2}) \wedge (\neg x_{1,2} \vee \neg x_{5,2}) \wedge (\neg x_{1,2} \vee \neg x_{6,2}) \wedge \\ & (\neg x_{1,2} \vee \neg x_{7,2}) \wedge (\neg x_{1,2} \vee \neg x_{8,2}) \wedge (\neg x_{2,2} \vee \neg x_{3,2}) \wedge (\neg x_{2,2} \vee \neg x_{4,2}) \wedge (\neg x_{2,2} \vee \neg x_{5,2}) \wedge (\neg x_{2,2} \vee \\ & \neg x_{6,2}) \wedge (\neg x_{2,2} \vee \neg x_{7,2}) \wedge (\neg x_{2,2} \vee \neg x_{8,2}) \wedge (\neg x_{3,2} \vee \neg x_{4,2}) \wedge (\neg x_{3,2} \vee \neg x_{5,2}) \wedge (\neg x_{3,2} \vee \neg x_{6,2}) \wedge \\ & (\neg x_{3,2} \vee \neg x_{7,2}) \wedge (\neg x_{3,2} \vee \neg x_{8,2}) \wedge (\neg x_{4,2} \vee \neg x_{5,2}) \wedge (\neg x_{4,2} \vee \neg x_{6,2}) \wedge (\neg x_{4,2} \vee \neg x_{7,2}) \wedge (\neg x_{4,2} \vee \\ & \neg x_{8,2}) \wedge (\neg x_{5,2} \vee \neg x_{6,2}) \wedge (\neg x_{5,2} \vee \neg x_{7,2}) \wedge (\neg x_{5,2} \vee \neg x_{8,2}) \wedge (\neg x_{6,2} \vee \neg x_{7,2}) \wedge (\neg x_{6,2} \vee \neg x_{8,2}) \wedge \\ & (\neg x_{7,2} \vee \neg x_{8,2}) \wedge (\neg x_{1,3} \vee \neg x_{2,3}) \wedge (\neg x_{1,3} \vee \neg x_{3,3}) \wedge (\neg x_{1,3} \vee \neg x_{4,3}) \wedge (\neg x_{1,3} \vee \neg x_{5,3}) \wedge (\neg x_{1,3} \vee \\ & \neg x_{6,3}) \wedge (\neg x_{1,3} \vee \neg x_{7,3}) \wedge (\neg x_{1,3} \vee \neg x_{8,3}) \wedge (\neg x_{2,3} \vee \neg x_{3,3}) \wedge (\neg x_{2,3} \vee \neg x_{4,3}) \wedge (\neg x_{2,3} \vee \neg x_{5,3}) \end{aligned}$$

Three Simple Problems. . .


COLOURING

Does the graph $G = (V, E)$ have a **colouring** with k colours such that all neighbours have distinct colours?

Three Simple Problems...

COLOURING

Does the graph $G = (V, E)$ have a **colouring** with k colours such that all neighbours have distinct colours?




3-colouring?

Three Simple Problems...

COLOURING

Does the graph $G = (V, E)$ have a **colouring** with k colours such that all neighbours have distinct colours?




3-colouring? Yes

Three Simple Problems. . .

COLOURING

Does the graph $G = (V, E)$ have a **colouring** with k colours such that all neighbours have distinct colours?




3-colouring? Yes, but no 2-colouring

Three Simple Problems...

CLIQUE

Is there a **clique** in the graph $G = (V, E)$ with k vertices that are all pairwise connected by edges in E ?

Three Simple Problems...




3-clique?

CLIQUE

Is there a **clique** in the graph $G = (V, E)$ with k vertices that are all pairwise connected by edges in E ?

Three Simple Problems...




3-clique? Yes

CLIQUE

Is there a **clique** in the graph $G = (V, E)$ with k vertices that are all pairwise connected by edges in E ?

Three Simple Problems...



3-clique? Yes, but no 4-clique

CLIQUE

Is there a **clique** in the graph $G = (V, E)$ with k vertices that are all pairwise connected by edges in E ?

Three Simple Problems...

COLOURING

Does the graph $G = (V, E)$ have a **colouring** with k colours such that all neighbours have distinct colours?

CLIQUE

Is there a **clique** in the graph $G = (V, E)$ with k vertices that are all pairwise connected by edges in E ?

SAT

Given propositional logic formula, is there a **satisfying assignment**?

Three Simple Problems...

COLOURING

Does the graph $G = (V, E)$ have a **colouring** with k colours such that all neighbours have distinct colours?

CLIQUE

Is there a **clique** in the graph $G = (V, E)$ with k vertices that are all pairwise connected by edges in E ?

SAT

Given propositional logic formula, is there a **satisfying assignment**?

$$(x \vee z) \wedge (y \vee \neg z) \wedge (x \vee \neg y \vee u) \wedge (\neg y \vee \neg u) \\ \wedge (u \vee v) \wedge (\neg x \vee \neg v) \wedge (\neg u \vee w) \wedge (\neg x \vee \neg u \vee \neg w)$$

Three Simple Problems...

COLOURING

Does the graph $G = (V, E)$ have a **colouring** with k colours such that all neighbours have distinct colours?

CLIQUE

Is there a **clique** in the graph $G = (V, E)$ with k vertices that are all pairwise connected by edges in E ?

SAT

Given propositional logic formula, is there a **satisfying assignment**?

$$(x \vee z) \wedge (y \vee \neg z) \wedge (x \vee \neg y \vee u) \wedge (\neg y \vee \neg u) \\ \wedge (u \vee v) \wedge (\neg x \vee \neg v) \wedge (\neg u \vee w) \wedge (\neg x \vee \neg u \vee \neg w)$$

- Variables should be set to **true** or **false**
- Constraint $(x \vee \neg y \vee z)$: means x or z should be true or y false
- \wedge means all constraints should hold simultaneously
- Is there a truth value assignment satisfying all constraints?

Three Simple Problems...

COLOURING

Does the graph $G = (V, E)$ have a **colouring** with k colours such that all neighbours have distinct colours?

CLIQUE

Is there a **clique** in the graph $G = (V, E)$ with k vertices that are all pairwise connected by edges in E ?

SAT

Given propositional logic formula, is there a **satisfying assignment**?

COLOURING: frequency allocation for mobile base stations

CLIQUE: bioinformatics, computational chemistry

SAT: easily models these and many other problems

...with Huge Practical Implications

- Some more examples of problems that can be encoded as propositional logic formulas:
 - computer hardware verification
 - computer software testing
 - artificial intelligence
 - cryptography
 - bioinformatics
 - et cetera...
- Leads to **humongous formulas** (100,000s or even 1,000,000s of variables)
- Can we use computers to solve these problems efficiently?
- Question mentioned already in Gödel's famous letter in 1956 to von Neumann (the "father of computer science")
- Topic of intense research in computer science ever since 1960s

Solving Logic Formulas in Practice

- Dramatic progress last 20–25 years on so-called SAT solvers
Today routinely used to solve large-scale real-world problems

Solving Logic Formulas in Practice

- Dramatic progress last 20–25 years on so-called SAT solvers
Today routinely used to solve large-scale real-world problems
- But... There are also small formulas (just ~ 100 variables) that are completely beyond reach of even the very best SAT solvers

Solving Logic Formulas in Practice

- **Dramatic progress last 20–25 years** on so-called **SAT solvers**
Today routinely used to solve large-scale real-world problems
- But... There are also **small formulas** (just ~ 100 variables) that are **completely beyond reach** of even the very best SAT solvers
- Best known SAT solving algorithms based on Davis-Putnam-Logemann-Loveland or **DPLL** method from early 1960s (although with many clever optimizations)

Solving Logic Formulas in Practice

- **Dramatic progress last 20–25 years** on so-called **SAT solvers**
Today routinely used to solve large-scale real-world problems
- But... There are also **small formulas** (just ~ 100 variables) that are **completely beyond reach** of even the very best SAT solvers
- Best known SAT solving algorithms based on Davis-Putnam-Logemann-Loveland or **DPLL** method from early 1960s (although with many clever optimizations)
- Some natural questions:
 - How do these SAT solvers work?

Solving Logic Formulas in Practice

- **Dramatic progress last 20–25 years** on so-called **SAT solvers**
Today routinely used to solve large-scale real-world problems
- But... There are also **small formulas** (just ~ 100 variables) that are **completely beyond reach** of even the very best SAT solvers
- Best known SAT solving algorithms based on Davis-Putnam-Logemann-Loveland or **DPLL** method from early 1960s (although with many clever optimizations)
- Some natural questions:
 - How do these SAT solvers work?
 - How can they be so good in practice?

Solving Logic Formulas in Practice

- **Dramatic progress last 20–25 years** on so-called **SAT solvers**
Today routinely used to solve large-scale real-world problems
- But... There are also **small formulas** (just ~ 100 variables) that are **completely beyond reach** of even the very best SAT solvers
- Best known SAT solving algorithms based on Davis-Putnam-Logemann-Loveland or **DPLL** method from early 1960s (although with many clever optimizations)
- Some natural questions:
 - How do these SAT solvers work?
 - How can they be so good in practice?
 - When they fail to be efficient, can we understand why?

Solving Logic Formulas in Practice

- **Dramatic progress last 20–25 years** on so-called **SAT solvers**
Today routinely used to solve large-scale real-world problems
- But... There are also **small formulas** (just ~ 100 variables) that are **completely beyond reach** of even the very best SAT solvers
- Best known SAT solving algorithms based on Davis-Putnam-Logemann-Loveland or **DPLL** method from early 1960s (although with many clever optimizations)
- Some natural questions:
 - How do these SAT solvers work?
 - How can they be so good in practice?
 - When they fail to be efficient, can we understand why?
 - It's 2022 now — can we go beyond techniques from 1960s?

Plan for Today

What we will cover today:

Plan for Today

What we will cover today:

- Define more precisely the computational problem

Plan for Today

What we will cover today:

- Define more precisely the computational problem
- Give (simplified) description of how modern SAT solvers work

Plan for Today

What we will cover today:

- Define more precisely the computational problem
- Give (simplified) description of how modern SAT solvers work
- Present tools to analyze SAT solver performance

Plan for Today

What we will cover today:


- Define more precisely the computational problem
- Give (simplified) description of how modern SAT solvers work
- Present tools to analyze SAT solver performance
- Discuss possible ways to go beyond the current state of the art
[in the pseudo-Boolean tutorial]

Plan for Today

What we will cover today:

- Define more precisely the computational problem
- Give (simplified) description of how modern SAT solvers work
- Present tools to analyze SAT solver performance
- Discuss possible ways to go beyond the current state of the art
[in the pseudo-Boolean tutorial]

... And in the process also touch on some of the research being done in the *Mathematical Insights into Algorithms for Optimization (MIAO)* group



Formal Description of SAT Problem

- **Variable** x : takes value 1 (**true**) or 0 (**false**)
- **Literal** ℓ : variable x or its negation \bar{x} (write \bar{x} instead of $\neg x$)
- **Clause** $C = \ell_1 \vee \dots \vee \ell_k$: disjunction of literals
(Consider as sets, so no repetitions and order irrelevant)
- **Conjunctive normal form (CNF) formula** $F = C_1 \wedge \dots \wedge C_m$:
conjunction of clauses

Formal Description of SAT Problem

- **Variable** x : takes value 1 (**true**) or 0 (**false**)
- **Literal** ℓ : variable x or its negation \bar{x} (write \bar{x} instead of $\neg x$)
- **Clause** $C = \ell_1 \vee \dots \vee \ell_k$: disjunction of literals
(Consider as sets, so no repetitions and order irrelevant)
- **Conjunctive normal form (CNF) formula** $F = C_1 \wedge \dots \wedge C_m$:
conjunction of clauses

The SATISFIABILITY (or just SAT) Problem

Given a CNF formula F , is it satisfiable?

Formal Description of SAT Problem

- **Variable** x : takes value 1 (**true**) or 0 (**false**)
- **Literal** ℓ : variable x or its negation \bar{x} (write \bar{x} instead of $\neg x$)
- **Clause** $C = \ell_1 \vee \dots \vee \ell_k$: disjunction of literals
(Consider as sets, so no repetitions and order irrelevant)
- **Conjunctive normal form (CNF) formula** $F = C_1 \wedge \dots \wedge C_m$:
conjunction of clauses

The SATISFIABILITY (or just SAT) Problem

Given a CNF formula F , is it satisfiable?

For instance, what about our example formula?

$$(x \vee z) \wedge (y \vee \bar{z}) \wedge (x \vee \bar{y} \vee u) \wedge (\bar{y} \vee \bar{u}) \\ \wedge (u \vee v) \wedge (\bar{x} \vee \bar{v}) \wedge (\bar{u} \vee w) \wedge (\bar{x} \vee \bar{u} \vee \bar{w})$$

How to Solve the SAT Problem?

- Let computer check all possible assignments! Isn't this exactly the kind of monotone routine work at which computers excel?
- But how many cases to check?
- Suppose formula has n variables
- Each variable can be either true or false, so all in all get 2^n different cases
- If formula contains, say, one million variables, we get $2^{1,000,000}$ cases (a number with more than 300,000 digits)

How to Solve the SAT Problem?

- Let computer check all possible assignments! Isn't this exactly the kind of monotone routine work at which computers excel?
- But how many cases to check?
- Suppose formula has n variables
- Each variable can be either true or false, so all in all get 2^n different cases
- If formula contains, say, one million variables, we get $2^{1,000,000}$ cases (a number with more than 300,000 digits)

To understand how large this number is, consider that even if every atom in the known universe was a modern supercomputer that had been running at full speed ever since the beginning of time some 13.7 billion years ago, all of them together would only have covered a completely negligible fraction of these cases by now. So we really would not have time to wait for them to finish...

An Interesting Feature of the SAT Problem

- Deciding whether a satisfying assignment exists may take a long time
- But if you happen to know a satisfying assignment, easy to convince someone else that formula is satisfiable
- How? Just give assignment — can be verified in linear time
- So SAT problem **might seem hard to solve**, but **verifying a solution is easy** (not all problems have this property — how do you verify a winning position in chess?)
- The family of problems for which solutions are easy to check have a name: **NP**

How to Solve the SAT Problem, Take 2

- SAT problem can be used to describe any problem in NP — it is **NP-complete** [Coo71, Lev73]
- If you can solve SAT efficiently, then you can solve any problem in NP efficiently (this is why SAT is so useful)
- So **how hard is it to solve SAT?** (Ok, brute force didn't work, but it usually doesn't — maybe can do something smarter?)

How to Solve the SAT Problem, Take 2

- SAT problem can be used to describe any problem in NP — it is **NP-complete** [Coo71, Lev73]
- If you can solve SAT efficiently, then you can solve any problem in NP efficiently (this is why SAT is so useful)
- So **how hard is it to solve SAT?** (Ok, brute force didn't work, but it usually doesn't — maybe can do something smarter?)
- We don't know
- This one of the **million-dollar “Millennium Prize Problems”** posed as the main challenges for mathematics in the new millennium
- Widely believe to be impossible to solve efficiently on computer in the worst case, but we really don't know

An Attempt at a Smarter Case Analysis: DPLL

Ok, but suppose you're out there in reality and actually have to solve the problem — then what do you do?

An Attempt at a Smarter Case Analysis: DPLL

Ok, but suppose you're out there in reality and actually have to solve the problem — then what do you do?

Chances are you'll use some variant of the [DPLL method](#) developed by Davis, Putnam, Logemann & Loveland [DP60, DLL62]

An Attempt at a Smarter Case Analysis: DPLL

Ok, but suppose you're out there in reality and actually have to solve the problem — then what do you do?

Chances are you'll use some variant of the [DPLL method](#) developed by Davis, Putnam, Logemann & Loveland [DP60, DLL62]

DPLL (somewhat simplified description)

An Attempt at a Smarter Case Analysis: DPLL

Ok, but suppose you're out there in reality and actually have to solve the problem — then what do you do?

Chances are you'll use some variant of the **DPLL method** developed by Davis, Putnam, Logemann & Loveland [DP60, DLL62]

DPLL (somewhat simplified description)

- If F contains empty clause (without literals), report “unsatisfiable” and return — refer to as **conflict**

An Attempt at a Smarter Case Analysis: DPLL

Ok, but suppose you're out there in reality and actually have to solve the problem — then what do you do?

Chances are you'll use some variant of the **DPLL method** developed by Davis, Putnam, Logemann & Loveland [DP60, DLL62]

DPLL (somewhat simplified description)

- If F contains empty clause (without literals), report **“unsatisfiable”** and return — refer to as **conflict**
- If F contains no clauses, report **“satisfiable”** and terminate

An Attempt at a Smarter Case Analysis: DPLL

Ok, but suppose you're out there in reality and actually have to solve the problem — then what do you do?

Chances are you'll use some variant of the **DPLL method** developed by Davis, Putnam, Logemann & Loveland [DP60, DLL62]

DPLL (somewhat simplified description)

- If F contains empty clause (without literals), report “**unsatisfiable**” and return — refer to as **conflict**
- If F contains no clauses, report “**satisfiable**” and terminate
- Otherwise pick some variable x in F

An Attempt at a Smarter Case Analysis: DPLL

Ok, but suppose you're out there in reality and actually have to solve the problem — then what do you do?

Chances are you'll use some variant of the **DPLL method** developed by Davis, Putnam, Logemann & Loveland [DP60, DLL62]

DPLL (somewhat simplified description)

- If F contains empty clause (without literals), report **“unsatisfiable”** and return — refer to as **conflict**
- If F contains no clauses, report **“satisfiable”** and terminate
- Otherwise pick some variable x in F
- Set $x = 0$, simplify F and **make recursive call**

An Attempt at a Smarter Case Analysis: DPLL

Ok, but suppose you're out there in reality and actually have to solve the problem — then what do you do?

Chances are you'll use some variant of the **DPLL method** developed by Davis, Putnam, Logemann & Loveland [DP60, DLL62]

DPLL (somewhat simplified description)

- If F contains empty clause (without literals), report **"unsatisfiable"** and return — refer to as **conflict**
- If F contains no clauses, report **"satisfiable"** and terminate
- Otherwise pick some variable x in F
- Set $x = 0$, simplify F and **make recursive call**
- Set $x = 1$, simplify F and **make recursive call**

An Attempt at a Smarter Case Analysis: DPLL

Ok, but suppose you're out there in reality and actually have to solve the problem — then what do you do?

Chances are you'll use some variant of the **DPLL method** developed by Davis, Putnam, Logemann & Loveland [DP60, DLL62]

DPLL (somewhat simplified description)

- If F contains empty clause (without literals), report **"unsatisfiable"** and return — refer to as **conflict**
- If F contains no clauses, report **"satisfiable"** and terminate
- Otherwise pick some variable x in F
- Set $x = 0$, simplify F and **make recursive call**
- Set $x = 1$, simplify F and **make recursive call**
- If result in both cases **"unsatisfiable"**, then report **"unsatisfiable"** and return

A DPLL Toy Example

$$F = (x \vee z) \wedge (y \vee \bar{z}) \wedge (x \vee \bar{y} \vee u) \wedge (\bar{y} \vee \bar{u}) \\ \wedge (u \vee v) \wedge (\bar{x} \vee \bar{v}) \wedge (\bar{u} \vee w) \wedge (\bar{x} \vee \bar{u} \vee \bar{w})$$

A DPLL Toy Example

$$F = (x \vee z) \wedge (y \vee \bar{z}) \wedge (x \vee \bar{y} \vee u) \wedge (\bar{y} \vee \bar{u}) \\ \wedge (u \vee v) \wedge (\bar{x} \vee \bar{v}) \wedge (\bar{u} \vee w) \wedge (\bar{x} \vee \bar{u} \vee \bar{w})$$

Visualize execution of DPLL algorithm as search tree

Pick variables in internal nodes; terminate in leaves when falsified clause found (i.e., when conflict reached)

“Simplify formula” by (mentally) removing

- satisfied clauses
- falsified literals

A DPLL Toy Example

$$F = (x \vee z) \wedge (y \vee \bar{z}) \wedge (x \vee \bar{y} \vee u) \wedge (\bar{y} \vee \bar{u}) \\ \wedge (u \vee v) \wedge (\bar{x} \vee \bar{v}) \wedge (\bar{u} \vee w) \wedge (\bar{x} \vee \bar{u} \vee \bar{w})$$

Visualize execution of DPLL algorithm as search tree

Pick variables in internal nodes; terminate in leaves when falsified clause found (i.e., when conflict reached)

“Simplify formula” by (mentally) removing

- satisfied clauses
- falsified literals



A DPLL Toy Example

$$F = (z \wedge (y \vee \bar{z}) \wedge (\bar{y} \vee u) \wedge (\bar{y} \vee \bar{u}) \\ \wedge (u \vee v) \wedge (\bar{x} \vee \bar{v}) \wedge (\bar{u} \vee w) \wedge (\bar{x} \vee \bar{u} \vee \bar{w}))$$

Visualize execution of DPLL algorithm as search tree

Pick variables in internal nodes; terminate in leaves when falsified clause found (i.e., when conflict reached)

“Simplify formula” by (mentally) removing

- satisfied clauses
- falsified literals



A DPLL Toy Example


$$F = (z) \wedge (\bar{z}) \wedge (\bar{y} \vee u) \wedge (\bar{y} \vee \bar{u}) \\ \wedge (u \vee v) \wedge (\bar{x} \vee \bar{v}) \wedge (\bar{u} \vee w) \wedge (\bar{x} \vee \bar{u} \vee \bar{w})$$

Visualize execution of DPLL algorithm as search tree

Pick variables in internal nodes; terminate in leaves when falsified clause found (i.e., when conflict reached)

“Simplify formula” by (mentally) removing

- satisfied clauses
- falsified literals



A DPLL Toy Example


$$F = (x \vee z) \wedge (\bar{z}) \wedge (\bar{y} \vee u) \wedge (\bar{y} \vee \bar{u}) \\ \wedge (u \vee v) \wedge (\bar{x} \vee \bar{v}) \wedge (\bar{u} \vee w) \wedge (\bar{x} \vee \bar{u} \vee \bar{w})$$

Visualize execution of DPLL algorithm as search tree

Pick variables in internal nodes; terminate in leaves when falsified clause found (i.e., when conflict reached)

“Simplify formula” by (mentally) removing

- satisfied clauses
- falsified literals



A DPLL Toy Example


$$F = (z \wedge (y \vee \bar{z}) \wedge (\bar{y} \vee u) \wedge (\bar{y} \vee \bar{u}) \\ \wedge (u \vee v) \wedge (\bar{x} \vee \bar{v}) \wedge (\bar{u} \vee w) \wedge (\bar{x} \vee \bar{u} \vee \bar{w})$$

Visualize execution of DPLL algorithm as search tree

Pick variables in internal nodes; terminate in leaves when falsified clause found (i.e., when conflict reached)

“Simplify formula” by (mentally) removing

- satisfied clauses
- falsified literals



A DPLL Toy Example


$$F = (z) \wedge (\textcolor{teal}{y} \vee \bar{z}) \wedge (u) \wedge (\bar{u}) \\ \wedge (u \vee v) \wedge (\bar{\textcolor{teal}{x}} \vee \bar{v}) \wedge (\bar{u} \vee w) \wedge (\bar{\textcolor{teal}{x}} \vee \bar{u} \vee \bar{w})$$

Visualize execution of DPLL algorithm as search tree

Pick variables in internal nodes; terminate in leaves when falsified clause found (i.e., when conflict reached)

“Simplify formula” by (mentally) removing

- satisfied clauses
- falsified literals



A DPLL Toy Example


$$F = (z) \wedge (y \vee \bar{z}) \wedge (x \vee \bar{y} \vee u) \wedge (\bar{u}) \\ \wedge (v) \wedge (\bar{x} \vee \bar{v}) \wedge (\bar{u} \vee w) \wedge (\bar{x} \vee \bar{u} \vee \bar{w})$$

Visualize execution of DPLL algorithm as search tree

Pick variables in internal nodes; terminate in leaves when falsified clause found (i.e., when conflict reached)

“Simplify formula” by (mentally) removing

- satisfied clauses
- falsified literals



A DPLL Toy Example


$$F = (z \wedge (y \vee \bar{z}) \wedge (u \wedge (\bar{y} \vee \bar{u}) \\ \wedge (u \vee v) \wedge (\bar{x} \vee \bar{v}) \wedge (w) \wedge (\bar{x} \vee \bar{w}))$$

Visualize execution of DPLL algorithm as search tree

Pick variables in internal nodes; terminate in leaves when falsified clause found (i.e., when conflict reached)

“Simplify formula” by (mentally) removing

- satisfied clauses
- falsified literals



A DPLL Toy Example


$$F = (x \vee z) \wedge (y \vee \bar{z}) \wedge (x \vee \bar{y} \vee u) \wedge (\bar{y} \vee \bar{u}) \\ \wedge (u \vee v) \wedge (\bar{v}) \wedge (\bar{u} \vee w) \wedge (\bar{u} \vee \bar{w})$$

Visualize execution of DPLL algorithm as search tree

Pick variables in internal nodes; terminate in leaves when falsified clause found (i.e., when conflict reached)

“Simplify formula” by (mentally) removing

- satisfied clauses
- falsified literals



A DPLL Toy Example


$$F = (x \vee z) \wedge (y \vee \bar{z}) \wedge (x \vee \bar{y}) \wedge (\bar{y} \vee \bar{u}) \\ \wedge (v) \wedge (\bar{v}) \wedge (\bar{u} \vee w) \wedge (\bar{u} \vee \bar{w})$$

Visualize execution of DPLL algorithm as search tree

Pick variables in internal nodes; terminate in leaves when falsified clause found (i.e., when conflict reached)

“Simplify formula” by (mentally) removing

- satisfied clauses
- falsified literals



A DPLL Toy Example


$$F = (x \vee z) \wedge (y \vee \bar{z}) \wedge (x \vee \bar{y}) \wedge (\bar{y} \vee \bar{u}) \\ \wedge (u \vee v) \wedge (\bar{v}) \wedge (\bar{u} \vee w) \wedge (\bar{u} \vee \bar{w})$$

Visualize execution of DPLL algorithm as search tree

Pick variables in internal nodes; terminate in leaves when falsified clause found (i.e., when conflict reached)

“Simplify formula” by (mentally) removing

- satisfied clauses
- falsified literals



A DPLL Toy Example


$$F = (x \vee z) \wedge (y \vee \bar{z}) \wedge (x \vee \bar{y}) \wedge (\bar{y} \vee \bar{u}) \\ \wedge (v \wedge (\bar{x} \vee \bar{v}) \wedge (\bar{u} \vee w) \wedge (\bar{u} \vee \bar{w}))$$

Visualize execution of DPLL algorithm as search tree

Pick variables in internal nodes; terminate in leaves when falsified clause found (i.e., when conflict reached)

“Simplify formula” by (mentally) removing

- satisfied clauses
- falsified literals



A DPLL Toy Example


$$F = (x \vee z) \wedge (y \vee \bar{z}) \wedge (x \vee \bar{y} \vee u) \wedge (\bar{y} \vee \bar{u}) \\ \wedge (u \vee v) \wedge (\bar{v}) \wedge (w) \wedge (\bar{w})$$

Visualize execution of DPLL algorithm as search tree

Pick variables in internal nodes; terminate in leaves when falsified clause found (i.e., when conflict reached)

“Simplify formula” by (mentally) removing

- satisfied clauses
- falsified literals



A DPLL Toy Example


$$F = (x \vee z) \wedge (y \vee \bar{z}) \wedge (x \vee \bar{y} \vee u) \wedge (\bar{y} \vee \bar{u}) \\ \wedge (u \vee v) \wedge (\bar{v}) \wedge (\bar{u} \vee w) \wedge (\bar{w})$$

Visualize execution of DPLL algorithm as search tree

Pick variables in internal nodes; terminate in leaves when falsified clause found (i.e., when conflict reached)

“Simplify formula” by (mentally) removing

- satisfied clauses
- falsified literals



A DPLL Toy Example


$$F = (x \vee z) \wedge (y \vee \bar{z}) \wedge (x \vee \bar{y} \vee u) \wedge (\bar{y} \vee \bar{u}) \\ \wedge (u \vee v) \wedge (\bar{v}) \wedge (w) \wedge (\bar{x} \vee \bar{u} \vee \bar{w})$$

Visualize execution of DPLL algorithm as search tree

Pick variables in internal nodes; terminate in leaves when falsified clause found (i.e., when conflict reached)

“Simplify formula” by (mentally) removing

- satisfied clauses
- falsified literals



A DPLL Toy Example


$$F = (x \vee z) \wedge (y \vee \bar{z}) \wedge (x \vee \bar{y} \vee u) \wedge (\bar{y} \vee \bar{u}) \\ \wedge (u \vee v) \wedge (\bar{x} \vee \bar{v}) \wedge (\bar{u} \vee w) \wedge (\bar{x} \vee \bar{u} \vee \bar{w})$$

Visualize execution of DPLL algorithm as search tree

Pick variables in internal nodes; terminate in leaves when falsified clause found (i.e., when conflict reached)

“Simplify formula” by (mentally) removing

- satisfied clauses
- falsified literals



State-of-the-art SAT solvers: Ingredients

Many more ingredients in modern **conflict-driven clause learning (CDCL)** SAT solvers (as pioneered in [MS99, MMZ⁺01]), e.g.:

- **Branching** or **decision heuristic** (choice of pivot variables crucial)
- When reaching leaf, **compute explanation for conflict** and **add to formula** as new clause (**clause learning**)
- Every once in a while, **restart** from beginning (but save computed info)

Let us discuss these ingredients

Variable Assignment Heuristics

Unit propagation

- Suppose current assignment ρ falsifies all literals in $C = \ell_1 \vee \ell_2 \vee \dots \vee \ell_k$ except one (say ℓ_k) — C is **unit under ρ**
- Then ℓ_k has to be true, so set it to true
- Known as **unit propagation** or **Boolean constraint propagation**
- Always propagate if possible — in modern solvers aim for $\approx 99\%$ of assignments being unit propagations

Variable Assignment Heuristics

Unit propagation

- Suppose current assignment ρ falsifies all literals in $C = \ell_1 \vee \ell_2 \vee \dots \vee \ell_k$ except one (say ℓ_k) — C is **unit** under ρ
- Then ℓ_k has to be true, so set it to true
- Known as **unit propagation** or **Boolean constraint propagation**
- Always propagate if possible — in modern solvers aim for $\approx 99\%$ of assignments being unit propagations

VSIDS (Variable state independent decaying sum)

- When backtracking, score $+1$ for variables “causing conflict”
- Also multiply all scores with factor $\kappa < 1$ — exponential filter rewarding variables involved in recent conflicts
- When no propagations, **decide** on variable with highest score

Clause Learning

- At conflict, want to add clause avoiding same part of search tree being explored again

Clause Learning

- At conflict, want to add clause avoiding same part of search tree being explored again
- Suppose we can compute that **decisions** $x = 1, y = 0, z = 1$ responsible for conflict

Clause Learning

- At conflict, want to add clause avoiding same part of search tree being explored again
- Suppose we can compute that decisions $x = 1, y = 0, z = 1$ responsible for conflict
- Then can add $\bar{x} \vee y \vee \bar{z}$ to avoid these decisions being made again — decision learning scheme

Clause Learning

- At conflict, want to add clause avoiding same part of search tree being explored again
- Suppose we can compute that decisions $x = 1, y = 0, z = 1$ responsible for conflict
- Then can add $\bar{x} \vee y \vee \bar{z}$ to avoid these decisions being made again — decision learning scheme
- In practice, more advanced learning schemes

Clause Learning

- At conflict, want to add clause avoiding same part of search tree being explored again
- Suppose we can compute that decisions $x = 1, y = 0, z = 1$ responsible for conflict
- Then can add $\bar{x} \vee y \vee \bar{z}$ to avoid these decisions being made again — decision learning scheme
- In practice, more advanced learning schemes
- Derive new clause from clauses unit propagating on the way to conflict

Decisions, Unit Propagations, and Conflict

Two kinds of assignments — illustrate on example formula:

$$(p \vee \bar{u}) \wedge (q \vee r) \wedge (\bar{r} \vee w) \wedge (u \vee x \vee y) \wedge (x \vee \bar{y} \vee z) \wedge (\bar{x} \vee z) \wedge (\bar{y} \vee \bar{z}) \wedge (\bar{x} \vee \bar{z}) \wedge (\bar{p} \vee \bar{u})$$

Decisions, Unit Propagations, and Conflict

Two kinds of assignments — illustrate on example formula:

$$(p \vee \bar{u}) \wedge (q \vee r) \wedge (\bar{r} \vee w) \wedge (u \vee x \vee y) \wedge (x \vee \bar{y} \vee z) \wedge (\bar{x} \vee z) \wedge (\bar{y} \vee \bar{z}) \wedge (\bar{x} \vee \bar{z}) \wedge (\bar{p} \vee \bar{u})$$

Decision

Free choice to assign value to variable

Notation $p \stackrel{d}{=} 0$

Decisions, Unit Propagations, and Conflict

Two kinds of assignments — illustrate on example formula:

$$(p \vee \bar{u}) \wedge (q \vee r) \wedge (\bar{r} \vee w) \wedge (u \vee x \vee y) \wedge (x \vee \bar{y} \vee z) \wedge (\bar{x} \vee z) \wedge (\bar{y} \vee \bar{z}) \wedge (\bar{x} \vee \bar{z}) \wedge (\bar{p} \vee \bar{u})$$

$$p \stackrel{d}{=} 0$$

Decision

Free choice to assign value to variable

Notation $p \stackrel{d}{=} 0$

Decisions, Unit Propagations, and Conflict

Two kinds of assignments — illustrate on example formula:

$$(p \vee \bar{u}) \wedge (q \vee r) \wedge (\bar{r} \vee w) \wedge (u \vee x \vee y) \wedge (x \vee \bar{y} \vee z) \wedge (\bar{x} \vee z) \wedge (\bar{y} \vee \bar{z}) \wedge (\bar{x} \vee \bar{z}) \wedge (\bar{p} \vee \bar{u})$$

$$p \stackrel{d}{=} 0$$

Decision

Free choice to assign value to variable

Notation $p \stackrel{d}{=} 0$

Unit propagation

Forced choice to avoid falsifying clause

Given $p = 0$, clause $p \vee \bar{u}$ forces $u = 0$

Notation $u \stackrel{p \vee \bar{u}}{=} 0$ ($p \vee \bar{u}$ is **reason clause**)

Decisions, Unit Propagations, and Conflict

Two kinds of assignments — illustrate on example formula:

$$(p \vee \bar{u}) \wedge (q \vee r) \wedge (\bar{r} \vee w) \wedge (u \vee x \vee y) \wedge (x \vee \bar{y} \vee z) \wedge (\bar{x} \vee z) \wedge (\bar{y} \vee \bar{z}) \wedge (\bar{x} \vee \bar{z}) \wedge (\bar{p} \vee \bar{u})$$

$$p \stackrel{d}{=} 0$$

$$u \stackrel{p \vee \bar{u}}{=} 0$$

Decision

Free choice to assign value to variable

Notation $p \stackrel{d}{=} 0$

Unit propagation

Forced choice to avoid falsifying clause

Given $p = 0$, clause $p \vee \bar{u}$ forces $u = 0$

Notation $u \stackrel{p \vee \bar{u}}{=} 0$ ($p \vee \bar{u}$ is **reason clause**)

Decisions, Unit Propagations, and Conflict

Two kinds of assignments — illustrate on example formula:

$$(p \vee \bar{u}) \wedge (q \vee r) \wedge (\bar{r} \vee w) \wedge (u \vee x \vee y) \wedge (x \vee \bar{y} \vee z) \wedge (\bar{x} \vee z) \wedge (\bar{y} \vee \bar{z}) \wedge (\bar{x} \vee \bar{z}) \wedge (\bar{p} \vee \bar{u})$$

$$p \stackrel{d}{=} 0$$

$$u \stackrel{p \vee \bar{u}}{=} 0$$

$$q \stackrel{d}{=} 0$$

Decision

Free choice to assign value to variable

Notation $p \stackrel{d}{=} 0$

Unit propagation

Forced choice to avoid falsifying clause

Given $p = 0$, clause $p \vee \bar{u}$ forces $u = 0$

Notation $u \stackrel{p \vee \bar{u}}{=} 0$ ($p \vee \bar{u}$ is **reason clause**)

Always propagate if possible, else decide

Add to assignment **trail**

Until satisfying assignment or **conflict**

Decisions, Unit Propagations, and Conflict

Two kinds of assignments — illustrate on example formula:

$$(p \vee \bar{u}) \wedge (\textcolor{red}{q} \vee \textcolor{red}{r}) \wedge (\bar{r} \vee w) \wedge (u \vee x \vee y) \wedge (x \vee \bar{y} \vee z) \wedge (\bar{x} \vee z) \wedge (\bar{y} \vee \bar{z}) \wedge (\bar{x} \vee \bar{z}) \wedge (\bar{p} \vee \bar{u})$$

$$p \stackrel{d}{=} 0$$

$$u \stackrel{p \vee \bar{u}}{=} 0$$

$$q \stackrel{d}{=} 0$$

$$r \stackrel{q \vee r}{=} 1$$

Decision

Free choice to assign value to variable

Notation $p \stackrel{d}{=} 0$

Unit propagation

Forced choice to avoid falsifying clause

Given $p = 0$, clause $p \vee \bar{u}$ forces $u = 0$

Notation $u \stackrel{p \vee \bar{u}}{=} 0$ ($p \vee \bar{u}$ is **reason clause**)

Always propagate if possible, else decide

Add to assignment **trail**

Until satisfying assignment or **conflict**

Decisions, Unit Propagations, and Conflict

Two kinds of assignments — illustrate on example formula:

$$(p \vee \bar{u}) \wedge (q \vee r) \wedge (\bar{r} \vee w) \wedge (u \vee x \vee y) \wedge (x \vee \bar{y} \vee z) \wedge (\bar{x} \vee z) \wedge (\bar{y} \vee \bar{z}) \wedge (\bar{x} \vee \bar{z}) \wedge (\bar{p} \vee \bar{u})$$

$$p \stackrel{d}{=} 0$$

$$u \stackrel{p \vee \bar{u}}{=} 0$$

$$q \stackrel{d}{=} 0$$

$$r \stackrel{q \vee r}{=} 1$$

$$w \stackrel{\bar{r} \vee w}{=} 1$$

Decision

Free choice to assign value to variable

Notation $p \stackrel{d}{=} 0$

Unit propagation

Forced choice to avoid falsifying clause

Given $p = 0$, clause $p \vee \bar{u}$ forces $u = 0$

Notation $u \stackrel{p \vee \bar{u}}{=} 0$ ($p \vee \bar{u}$ is **reason clause**)

Always propagate if possible, else decide

Add to assignment **trail**

Until satisfying assignment or **conflict**

Decisions, Unit Propagations, and Conflict

Two kinds of assignments — illustrate on example formula:

$$(p \vee \bar{u}) \wedge (q \vee r) \wedge (\bar{r} \vee w) \wedge (u \vee x \vee y) \wedge (x \vee \bar{y} \vee z) \wedge (\bar{x} \vee z) \wedge (\bar{y} \vee \bar{z}) \wedge (\bar{x} \vee \bar{z}) \wedge (\bar{p} \vee \bar{u})$$

$$p \stackrel{d}{=} 0$$

$$u \stackrel{p \vee \bar{u}}{=} 0$$

$$q \stackrel{d}{=} 0$$

$$r \stackrel{q \vee r}{=} 1$$

$$w \stackrel{\bar{r} \vee w}{=} 1$$

$$x \stackrel{d}{=} 0$$

Decision

Free choice to assign value to variable

Notation $p \stackrel{d}{=} 0$

Unit propagation

Forced choice to avoid falsifying clause

Given $p = 0$, clause $p \vee \bar{u}$ forces $u = 0$

Notation $u \stackrel{p \vee \bar{u}}{=} 0$ ($p \vee \bar{u}$ is **reason clause**)

Always propagate if possible, else decide

Add to assignment **trail**

Until satisfying assignment or **conflict**

Decisions, Unit Propagations, and Conflict

Two kinds of assignments — illustrate on example formula:

$$(p \vee \bar{u}) \wedge (q \vee r) \wedge (\bar{r} \vee w) \wedge (u \vee x \vee y) \wedge (x \vee \bar{y} \vee z) \wedge (\bar{x} \vee z) \wedge (\bar{y} \vee \bar{z}) \wedge (\bar{x} \vee \bar{z}) \wedge (\bar{p} \vee \bar{u})$$

$$p \stackrel{d}{=} 0$$

$$u \stackrel{p \vee \bar{u}}{=} 0$$

$$q \stackrel{d}{=} 0$$

$$r \stackrel{q \vee r}{=} 1$$

$$w \stackrel{\bar{r} \vee w}{=} 1$$

$$x \stackrel{d}{=} 0$$

$$y \stackrel{u \vee x \vee y}{=} 1$$

Decision

Free choice to assign value to variable

Notation $p \stackrel{d}{=} 0$

Unit propagation

Forced choice to avoid falsifying clause

Given $p = 0$, clause $p \vee \bar{u}$ forces $u = 0$

Notation $u \stackrel{p \vee \bar{u}}{=} 0$ ($p \vee \bar{u}$ is **reason clause**)

Always propagate if possible, else decide

Add to assignment **trail**

Until satisfying assignment or **conflict**

Decisions, Unit Propagations, and Conflict

Two kinds of assignments — illustrate on example formula:

$$(p \vee \bar{u}) \wedge (q \vee r) \wedge (\bar{r} \vee w) \wedge (u \vee x \vee y) \wedge (x \vee \bar{y} \vee z) \wedge (\bar{x} \vee z) \wedge (\bar{y} \vee \bar{z}) \wedge (\bar{x} \vee \bar{z}) \wedge (\bar{p} \vee \bar{u})$$

$$p \stackrel{d}{=} 0$$

$$u \stackrel{p \vee \bar{u}}{=} 0$$

$$q \stackrel{d}{=} 0$$

$$r \stackrel{q \vee r}{=} 1$$

$$w \stackrel{\bar{r} \vee w}{=} 1$$

$$x \stackrel{d}{=} 0$$

$$y \stackrel{u \vee x \vee y}{=} 1$$

$$z \stackrel{x \vee \bar{y} \vee z}{=} 1$$

Decision

Free choice to assign value to variable

Notation $p \stackrel{d}{=} 0$

Unit propagation

Forced choice to avoid falsifying clause

Given $p = 0$, clause $p \vee \bar{u}$ forces $u = 0$

Notation $u \stackrel{p \vee \bar{u}}{=} 0$ ($p \vee \bar{u}$ is **reason clause**)

Always propagate if possible, else decide

Add to assignment **trail**

Until satisfying assignment or **conflict**

Decisions, Unit Propagations, and Conflict

Two kinds of assignments — illustrate on example formula:

$$(p \vee \bar{u}) \wedge (q \vee r) \wedge (\bar{r} \vee w) \wedge (u \vee x \vee y) \wedge (x \vee \bar{y} \vee z) \wedge (\bar{x} \vee z) \wedge (\bar{y} \vee \bar{z}) \wedge (\bar{x} \vee \bar{z}) \wedge (\bar{p} \vee \bar{u})$$

$$p \stackrel{d}{=} 0$$

$$u \stackrel{p \vee \bar{u}}{=} 0$$

$$q \stackrel{d}{=} 0$$

$$r \stackrel{q \vee r}{=} 1$$

$$w \stackrel{\bar{r} \vee w}{=} 1$$

$$x \stackrel{d}{=} 0$$

$$y \stackrel{u \vee x \vee y}{=} 1$$

$$z \stackrel{x \vee \bar{y} \vee z}{=} 1$$

$$\bar{y} \vee \bar{z}$$

$$\perp$$

Decision

Free choice to assign value to variable

Notation $p \stackrel{d}{=} 0$

Unit propagation

Forced choice to avoid falsifying clause

Given $p = 0$, clause $p \vee \bar{u}$ forces $u = 0$

Notation $u \stackrel{p \vee \bar{u}}{=} 0$ ($p \vee \bar{u}$ is **reason clause**)

Always propagate if possible, else decide

Add to assignment **trail**

Until satisfying assignment or **conflict**

Decisions, Unit Propagations, and Conflict

Two kinds of assignments — illustrate on example formula:

$$(p \vee \bar{u}) \wedge (q \vee r) \wedge (\bar{r} \vee w) \wedge (u \vee x \vee y) \wedge (x \vee \bar{y} \vee z) \wedge (\bar{x} \vee z) \wedge (\bar{y} \vee \bar{z}) \wedge (\bar{x} \vee \bar{z}) \wedge (\bar{p} \vee \bar{u})$$

$$\left. \begin{array}{l} p \stackrel{d}{=} 0 \\ u \stackrel{p \vee \bar{u}}{=} 0 \end{array} \right\} \begin{array}{l} \text{decision} \\ \text{level 1} \end{array}$$

$$\left. \begin{array}{l} q \stackrel{d}{=} 0 \\ r \stackrel{q \vee r}{=} 1 \\ w \stackrel{\bar{r} \vee w}{=} 1 \end{array} \right\} \begin{array}{l} \text{decision} \\ \text{level 2} \end{array}$$

$$\left. \begin{array}{l} x \stackrel{d}{=} 0 \\ y \stackrel{u \vee x \vee y}{=} 1 \\ z \stackrel{x \vee \bar{y} \vee z}{=} 1 \end{array} \right\} \begin{array}{l} \text{decision} \\ \text{level 3} \end{array}$$

$$\bar{y} \vee \bar{z} \stackrel{\perp}{=}$$

Decision

Free choice to assign value to variable

Notation $p \stackrel{d}{=} 0$

Unit propagation

Forced choice to avoid falsifying clause

Given $p = 0$, clause $p \vee \bar{u}$ forces $u = 0$

Notation $u \stackrel{p \vee \bar{u}}{=} 0$ ($p \vee \bar{u}$ is **reason clause**)

Always propagate if possible, else decide


Add to assignment **trail**

Until satisfying assignment or **conflict**

Conflict Analysis

Time to analyse this conflict and learn from it!


$$(p \vee \bar{u}) \wedge (q \vee r) \wedge (\bar{r} \vee w) \wedge (u \vee x \vee y) \wedge (x \vee \bar{y} \vee z) \wedge (\bar{x} \vee z) \wedge (\bar{y} \vee \bar{z}) \wedge (\bar{x} \vee \bar{z}) \wedge (\bar{p} \vee \bar{u})$$



Conflict Analysis

Time to analyse this conflict and learn from it!


$$(p \vee \bar{u}) \wedge (q \vee r) \wedge (\bar{r} \vee w) \wedge (u \vee x \vee y) \wedge (x \vee \bar{y} \vee z) \wedge (\bar{x} \vee z) \wedge (\bar{y} \vee \bar{z}) \wedge (\bar{x} \vee \bar{z}) \wedge (\bar{p} \vee \bar{u})$$



Conflict Analysis

Time to analyse this conflict and learn from it!

$$(p \vee \bar{u}) \wedge (q \vee r) \wedge (\bar{r} \vee w) \wedge (u \vee x \vee y) \wedge (x \vee \bar{y} \vee z) \wedge (\bar{x} \vee z) \wedge (\bar{y} \vee \bar{z}) \wedge (\bar{x} \vee \bar{z}) \wedge (\bar{p} \vee \bar{u})$$




Could backtrack by removing last decision level & flipping last decision

But want to **learn** from conflict and cut away as much of search space as possible

Conflict Analysis

Time to analyse this conflict and learn from it!

$$(p \vee \bar{u}) \wedge (q \vee r) \wedge (\bar{r} \vee w) \wedge (u \vee x \vee y) \wedge (x \vee \bar{y} \vee z) \wedge (\bar{x} \vee z) \wedge (\bar{y} \vee \bar{z}) \wedge (\bar{x} \vee \bar{z}) \wedge (\bar{p} \vee \bar{u})$$



Could backtrack by removing last decision level & flipping last decision

But want to **learn** from conflict and cut away as much of search space as possible


Case analysis over z for last two clauses:

- $x \vee \bar{y} \vee z$ wants $z = 1$
- $\bar{y} \vee \bar{z}$ wants $z = 0$
- **Resolve** clauses by merging them & removing z — must satisfy $x \vee \bar{y}$

Conflict Analysis

Time to analyse this conflict and learn from it!

$$(p \vee \bar{u}) \wedge (q \vee r) \wedge (\bar{r} \vee w) \wedge (u \vee x \vee y) \wedge (x \vee \bar{y} \vee z) \wedge (\bar{x} \vee z) \wedge (\bar{y} \vee \bar{z}) \wedge (\bar{x} \vee \bar{z}) \wedge (\bar{p} \vee \bar{u})$$



Could backtrack by removing last decision level & flipping last decision

But want to **learn** from conflict and cut away as much of search space as possible

Case analysis over z for last two clauses:


- $x \vee \bar{y} \vee z$ wants $z = 1$
- $\bar{y} \vee \bar{z}$ wants $z = 0$
- **Resolve** clauses by merging them & removing z — must satisfy $x \vee \bar{y}$

Repeat until **UIP clause** with only 1 variable after last decision — **learn** and **backjump**

Complete Example of CDCL Execution

Backjump: undo max #decisions while learned clause propagates


$$(p \vee \bar{u}) \wedge (q \vee r) \wedge (\bar{r} \vee w) \wedge (u \vee x \vee y) \wedge (x \vee \bar{y} \vee z) \wedge (\bar{x} \vee z) \wedge (\bar{y} \vee \bar{z}) \wedge (\bar{x} \vee \bar{z}) \wedge (\bar{p} \vee \bar{u})$$



Complete Example of CDCL Execution

Backjump: undo max #decisions while learned clause propagates

$$(p \vee \bar{u}) \wedge (q \vee r) \wedge (\bar{r} \vee w) \wedge (u \vee x \vee y) \wedge (x \vee \bar{y} \vee z) \wedge (\bar{x} \vee z) \wedge (\bar{y} \vee \bar{z}) \wedge (\bar{x} \vee \bar{z}) \wedge (\bar{p} \vee \bar{u})$$





Assertion level 1 (max for non-UIP literal in learned clause) — trim trail to that level

Complete Example of CDCL Execution

Backjump: undo max #decisions while learned clause propagates

$$(p \vee \bar{u}) \wedge (q \vee r) \wedge (\bar{r} \vee w) \wedge (u \vee x \vee y) \wedge (x \vee \bar{y} \vee z) \wedge (\bar{x} \vee z) \wedge (\bar{y} \vee \bar{z}) \wedge (\bar{x} \vee \bar{z}) \wedge (\bar{p} \vee \bar{u})$$





Assertion level 1 (max for non-UIP literal in learned clause) — trim trail to that level

Now UIP literal guaranteed to flip (**assert**) — but this is a **propagation**, not a decision

Complete Example of CDCL Execution

Backjump: undo max #decisions while learned clause propagates

$$(p \vee \bar{u}) \wedge (q \vee r) \wedge (\bar{r} \vee w) \wedge (u \vee x \vee y) \wedge (x \vee \bar{y} \vee z) \wedge (\bar{x} \vee z) \wedge (\bar{y} \vee \bar{z}) \wedge (\bar{x} \vee \bar{z}) \wedge (\bar{p} \vee \bar{u})$$



Assertion level 1 (max for non-UIP literal in learned clause) — trim trail to that level


Now UIP literal guaranteed to flip (**assert**) — but this is a **propagation**, not a decision

Then continue as before...

Complete Example of CDCL Execution

Backjump: undo max #decisions while learned clause propagates


$$(p \vee \bar{u}) \wedge (q \vee r) \wedge (\bar{r} \vee w) \wedge (u \vee x \vee y) \wedge (x \vee \bar{y} \vee z) \wedge (\bar{x} \vee z) \wedge (\bar{y} \vee \bar{z}) \wedge (\bar{x} \vee \bar{z}) \wedge (\bar{p} \vee \bar{u})$$



Complete Example of CDCL Execution

Backjump: undo max #decisions while learned clause propagates


$$(p \vee \bar{u}) \wedge (q \vee r) \wedge (\bar{r} \vee w) \wedge (u \vee x \vee y) \wedge (x \vee \bar{y} \vee z) \wedge (\bar{x} \vee z) \wedge (\bar{y} \vee \bar{z}) \wedge (\bar{x} \vee \bar{z}) \wedge (\bar{p} \vee \bar{u})$$




Complete Example of CDCL Execution

Backjump: undo max #decisions while learned clause propagates

$$(p \vee \bar{u}) \wedge (q \vee r) \wedge (\bar{r} \vee w) \wedge (u \vee x \vee y) \wedge (x \vee \bar{y} \vee z) \wedge (\bar{x} \vee z) \wedge (\bar{y} \vee \bar{z}) \wedge (\bar{x} \vee \bar{z}) \wedge (\bar{p} \vee \bar{u})$$




Backjump: undo max #decisions while learned clause propagates

$$(p \vee \bar{u}) \wedge (q \vee r) \wedge (\bar{r} \vee w) \wedge (u \vee x \vee y) \wedge (x \vee \bar{y} \vee z) \wedge (\bar{x} \vee z) \wedge (\bar{y} \vee \bar{z}) \wedge (\bar{x} \vee \bar{z}) \wedge (\bar{p} \vee \bar{u})$$


Complete Example of CDCL Execution

Backjump: undo max #decisions while learned clause propagates


$$(p \vee \bar{u}) \wedge (q \vee r) \wedge (\bar{r} \vee w) \wedge (u \vee x \vee y) \wedge (x \vee \bar{y} \vee z) \wedge (\bar{x} \vee z) \wedge (\bar{y} \vee \bar{z}) \wedge (\bar{x} \vee \bar{z}) \wedge (\bar{p} \vee \bar{u})$$



Complete Example of CDCL Execution

Backjump: undo max #decisions while learned clause propagates


$$(p \vee \bar{u}) \wedge (q \vee r) \wedge (\bar{r} \vee w) \wedge (u \vee x \vee y) \wedge (x \vee \bar{y} \vee z) \wedge (\bar{x} \vee z) \wedge (\bar{y} \vee \bar{z}) \wedge (\bar{x} \vee \bar{z}) \wedge (\bar{p} \vee \bar{u})$$



Complete Example of CDCL Execution

Backjump: undo max #decisions while learned clause propagates


$$(p \vee \bar{u}) \wedge (q \vee r) \wedge (\bar{r} \vee w) \wedge (u \vee x \vee y) \wedge (x \vee \bar{y} \vee z) \wedge (\bar{x} \vee z) \wedge (\bar{y} \vee \bar{z}) \wedge (\bar{x} \vee \bar{z}) \wedge (\bar{p} \vee \bar{u})$$



Complete Example of CDCL Execution

Backjump: undo max #decisions while learned clause propagates




$$(p \vee \bar{u}) \wedge (q \vee r) \wedge (\bar{r} \vee w) \wedge (u \vee x \vee y) \wedge (x \vee \bar{y} \vee z) \wedge (\bar{x} \vee z) \wedge (\bar{y} \vee \bar{z}) \wedge (\bar{x} \vee \bar{z}) \wedge (\bar{p} \vee \bar{u})$$



Complete Example of CDCL Execution

Backjump: undo max #decisions while learned clause propagates

$$(p \vee \bar{u}) \wedge (q \vee r) \wedge (\bar{r} \vee w) \wedge (u \vee x \vee y) \wedge (x \vee \bar{y} \vee z) \wedge (\bar{x} \vee z) \wedge (\bar{y} \vee \bar{z}) \wedge (\bar{x} \vee \bar{z}) \wedge (\bar{p} \vee \bar{u})$$



Clause Database Reduction

- In addition to learning clauses, also **erase learned clauses that don't seem useful**
- Modern solvers do this **very aggressively**
- Speeds up CDCL search (in particular, unit propagation, which dominates running time)
- But erasing too aggressively can throw away clauses that would have made solver terminate faster [EGG⁺18]
- So **trade-off** between **search speed** and **search quality**
- Except sometimes getting rid of clauses improves search quality too! [KN20]

Restarts

- Fairly frequently, **start search all over** (but keep learned clauses)
- Original intuition: stuck in bad part of search tree — go somewhere else
- Not the reason this is done now
- Popular variables with high VSIDS scores get set again [MMZ⁺01]
- Are even set to same values (**phase saving**) [PD07]
- Current intuition: improves the search by focusing on important variables
- Restart at fixed intervals or (better) make **adaptive restarts** depending on “quality” of learned clauses [AS09, AS12]

CDCL Main Loop Pseudocode

CDCL(F)

```

1  $\mathcal{D} \leftarrow F$  ; // initialize clause database to contain formula
2  $\rho \leftarrow \emptyset$  ; // initialize assignment trail to empty
3 forever do
4   if  $\rho$  falsifies some clause  $C \in \mathcal{D}$  then
5      $A \leftarrow \text{analyzeConflict}(\mathcal{D}, \rho, C)$  ;
6     if  $A = \perp$  then output UNSATISFIABLE and exit;
7     else
8        $\perp$  add  $A$  to  $\mathcal{D}$  and backjump by shrinking  $\rho$  ;
9   else if exists clause  $C \in \mathcal{D}$  unit propagating  $x$  to  $b \in \{0, 1\}$  under  $\rho$  then
10    add propagated assignment  $x \stackrel{D}{=} b$  to  $\rho$  ;
11   else if time to restart then  $\rho \leftarrow \emptyset$  ;
12   else if time for clause database reduction then
13    erase (roughly) half of learned clauses in  $\mathcal{D} \setminus F$  from  $\mathcal{D}$ 
14   else if all variables assigned then output SATISFIABLE and exit;
15   else
16    use decision scheme to choose assignment  $x \stackrel{d}{=} b$  to add to  $\rho$  ;

```

CDCL Main Loop Pseudocode

CDCL(F)

```

1  $\mathcal{D} \leftarrow F$  ; // initialize clause database to contain formula
2  $\rho \leftarrow \emptyset$  ; // initialize assignment trail to empty
3 forever do
4   if  $\rho$  falsifies some clause  $C \in \mathcal{D}$  then
5      $A \leftarrow \text{analyzeConflict}(\mathcal{D}, \rho, C)$  ;
6     if  $A = \perp$  then output UNSATISFIABLE and exit;
7     else
8        $\perp$  add  $A$  to  $\mathcal{D}$  and backjump by shrinking  $\rho$  ;
9   else if exists clause  $C \in \mathcal{D}$  unit propagating  $x$  to  $b \in \{0, 1\}$  under  $\rho$  then
10    add propagated assignment  $x \stackrel{D}{=} b$  to  $\rho$  ;
11   else if time to restart then  $\rho \leftarrow \emptyset$  ;
12   else if time for clause database reduction then
13    erase (roughly) half of learned clauses in  $\mathcal{D} \setminus F$  from  $\mathcal{D}$ 
14   else if all variables assigned then output SATISFIABLE and exit;
15   else
16    use decision scheme to choose assignment  $x \stackrel{d}{=} b$  to add to  $\rho$  ;

```

Conflict Analysis Pseudocode

analyzeConflict($\mathcal{D}, \rho, C_{\text{confl}}$)

```

1  $C_{\text{learn}} \leftarrow C_{\text{confl}} ;$ 
2 while  $C_{\text{learn}}$  not UIP clause and  $C_{\text{learn}} \neq \perp$  do
3    $\ell \leftarrow$  literal assigned last on trail  $\rho$ ;
4   if  $\ell$  propagated and  $\bar{\ell}$  occurs in  $C_{\text{learn}}$  then
5      $C_{\text{reason}} \leftarrow \text{reason}(\ell, \rho, \mathcal{D});$ 
6      $C_{\text{learn}} \leftarrow \text{resolve}(C_{\text{learn}}, C_{\text{reason}});$ 
7    $\rho \leftarrow \rho \setminus \{\ell\};$ 
8 return  $C_{\text{learn}};$ 

```

State-of-the-art SAT solvers: What About the Recipe?

List of ingredients again (not exhaustive):

- Variable decisions & propagations
- Clause learning
- Restarts
- Clause database reduction

State-of-the-art SAT solvers: What About the Recipe?

List of ingredients again (not exhaustive):

- Variable decisions & propagations
- Clause learning
- Restarts
- Clause database reduction

Some natural questions:

- How best to combine these ingredients into a recipe?
- When and why does this recipe work?

State-of-the-art SAT solvers: What About the Recipe?

List of ingredients again (not exhaustive):

- Variable decisions & propagations
- Clause learning
- Restarts
- Clause database reduction

Some natural questions:

- How best to combine these ingredients into a recipe?
- When and why does this recipe work?

Why SAT solvers actually work so well
is a poorly understood question

Lots of research to comprehend this better
(Among other places in the MIAO group)



SAT Solver Analysis and the Resolution Proof System

How to make **rigorous** analysis of SAT solver performance?

Many intricate, hard-to-understand heuristics

So focus instead on **underlying method of reasoning**

SAT Solver Analysis and the Resolution Proof System

How to make **rigorous** analysis of SAT solver performance?

Many intricate, hard-to-understand heuristics

So focus instead on **underlying method of reasoning**

Resolution proof system

- Start with clauses of CNF formula (**axioms**)
- Derive new clauses by **resolution rule**

$$\frac{C_1 \vee x \quad C_2 \vee \bar{x}}{C_1 \vee C_2}$$

Resolution Proofs by Contradiction

Resolution rule:

$$\frac{C_1 \vee x \quad C_2 \vee \bar{x}}{C_1 \vee C_2}$$

Observation

If F is a satisfiable CNF formula and D is derived from clauses $D_1, D_2 \in F$ by the resolution rule, then $F \wedge D$ is satisfiable.

Resolution Proofs by Contradiction

Resolution rule:

$$\frac{C_1 \vee x \quad C_2 \vee \bar{x}}{C_1 \vee C_2}$$

Observation

If F is a satisfiable CNF formula and D is derived from clauses $D_1, D_2 \in F$ by the resolution rule, then $F \wedge D$ is satisfiable.

So can prove F **unsatisfiable** by deriving the unsatisfiable empty clause (denoted \perp) from F by resolution

Resolution Proofs by Contradiction

Resolution rule:

$$\frac{C_1 \vee x \quad C_2 \vee \bar{x}}{C_1 \vee C_2}$$

Observation

If F is a satisfiable CNF formula and D is derived from clauses $D_1, D_2 \in F$ by the resolution rule, then $F \wedge D$ is satisfiable.

So can prove F **unsatisfiable** by deriving the unsatisfiable empty clause (denoted \perp) from F by resolution

Such proof by contradiction also called **resolution refutation**


DPLL and Resolution Proofs

A DPLL execution is essentially a resolution proof

DPLL and Resolution Proofs

A DPLL execution is essentially a resolution proof


Look at our example again



DPLL and Resolution Proofs

A DPLL execution is essentially a resolution proof

Look at our example again




and apply resolution rule $\frac{C_1 \vee x \quad C_2 \vee \bar{x}}{C_1 \vee C_2}$ bottom-up

DPLL and Resolution Proofs

A DPLL execution is essentially a resolution proof

Look at our example again




and apply resolution rule $\frac{C_1 \vee x \quad C_2 \vee \bar{x}}{C_1 \vee C_2}$ bottom-up

DPLL and Resolution Proofs

A DPLL execution is essentially a resolution proof

Look at our example again




and apply resolution rule $\frac{C_1 \vee x \quad C_2 \vee \bar{x}}{C_1 \vee C_2}$ bottom-up

DPLL and Resolution Proofs

A DPLL execution is essentially a resolution proof

Look at our example again




and apply resolution rule $\frac{C_1 \vee x \quad C_2 \vee \bar{x}}{C_1 \vee C_2}$ bottom-up

DPLL and Resolution Proofs

A DPLL execution is essentially a resolution proof

Look at our example again




and **apply resolution rule** $\frac{C_1 \vee x \quad C_2 \vee \bar{x}}{C_1 \vee C_2}$ **bottom-up**

DPLL and Resolution Proofs

A DPLL execution is essentially a resolution proof

Look at our example again




and apply resolution rule $\frac{C_1 \vee x \quad C_2 \vee \bar{x}}{C_1 \vee C_2}$ bottom-up

DPLL and Resolution Proofs

A DPLL execution is essentially a resolution proof

Look at our example again




and apply resolution rule $\frac{C_1 \vee x \quad C_2 \vee \bar{x}}{C_1 \vee C_2}$ bottom-up

DPLL and Resolution Proofs

A DPLL execution is essentially a resolution proof

Look at our example again



and apply resolution rule $\frac{C_1 \vee x \quad C_2 \vee \bar{x}}{C_1 \vee C_2}$ bottom-up

DPLL Running Time and Tree-Like Resolution Proof Size

- Can extract resolution proof from any DPLL execution

DPLL Running Time and Tree-Like Resolution Proof Size

- Can extract resolution proof from any DPLL execution
- Requires an argument, of course, but not too hard to show

DPLL Running Time and Tree-Like Resolution Proof Size

- Can extract resolution proof from any DPLL execution
- Requires an argument, of course, but not too hard to show
- Such proof is **tree-like** — every derived clause **used only once** (to use a clause twice, we have to derive it twice from scratch)

DPLL Running Time and Tree-Like Resolution Proof Size

- Can extract resolution proof from any DPLL execution
- Requires an argument, of course, but not too hard to show
- Such proof is **tree-like** — every derived clause **used only once** (to use a clause twice, we have to derive it twice from scratch)
- Hence, **lower bounds** on **tree-like proof size** in resolution \Rightarrow lower bounds on **DPLL running time**

DPLL Running Time and Tree-Like Resolution Proof Size


- Can extract resolution proof from any DPLL execution
- Requires an argument, of course, but not too hard to show
- Such proof is **tree-like** — every derived clause **used only once** (to use a clause twice, we have to derive it twice from scratch)
- Hence, **lower bounds** on **tree-like proof size** in resolution \Rightarrow lower bounds on **DPLL running time**
- Conflict-driven clause learning adds “shortcut edges” in tree, but still yields resolution proof

CDCL and Resolution Proofs

Obtain resolution proof. . .


CDCL and Resolution Proofs

Obtain resolution proof from our example CDCL execution...




CDCL and Resolution Proofs

Obtain resolution proof from our example CDCL execution by stringing together conflict analyses:



CDCL and Resolution Proofs

Obtain resolution proof from our example CDCL execution by stringing together conflict analyses:



CDCL Running Time and General Resolution Proof Size

- Can extract general resolution proof (DAG-like, not tree-like) from CDCL execution

CDCL Running Time and General Resolution Proof Size

- Can extract general resolution proof (DAG-like, not tree-like) from CDCL execution
- Again requires an argument, but you have seen enough in this lecture to be able to fill in the required details. . .

CDCL Running Time and General Resolution Proof Size

- Can extract general resolution proof (DAG-like, not tree-like) from CDCL execution
- Again requires an argument, but you have seen enough in this lecture to be able to fill in the required details. . .
- This holds even for CDCL solvers with sophisticated heuristics and optimizations that we have not discussed*

CDCL Running Time and General Resolution Proof Size

- Can extract general resolution proof (DAG-like, not tree-like) from CDCL execution
- Again requires an argument, but you have seen enough in this lecture to be able to fill in the required details. . .
- This holds even for CDCL solvers with sophisticated heuristics and optimizations that we have not discussed*
- Hence, **lower bounds on resolution proof size \Rightarrow lower bounds on CDCL running time**

CDCL Running Time and General Resolution Proof Size

- Can extract general resolution proof (DAG-like, not tree-like) from CDCL execution
- Again requires an argument, but you have seen enough in this lecture to be able to fill in the required details. . .
- This holds even for CDCL solvers with sophisticated heuristics and optimizations that we have not discussed*
- Hence, **lower bounds on resolution proof size** \Rightarrow lower bounds on **CDCL running time**
- Lower (and upper) bounds for different methods of reasoning about propositional logic formulas studied in **proof complexity**

CDCL Running Time and General Resolution Proof Size

- Can extract general resolution proof (DAG-like, not tree-like) from CDCL execution
- Again requires an argument, but you have seen enough in this lecture to be able to fill in the required details. . .
- This holds even for CDCL solvers with sophisticated heuristics and optimizations that we have not discussed*
- Hence, **lower bounds on resolution proof size** \Rightarrow lower bounds on **CDCL running time**
- Lower (and upper) bounds for different methods of reasoning about propositional logic formulas studied in **proof complexity**

(*) Except for some **preprocessing techniques**, which is an important omission, but this gets complicated and we don't have time to go into details. . .

Current State of Affairs in SAT Solving

- State-of-the-art CDCL solvers often perform amazingly well
(“SAT is easy in practice”)

Current State of Affairs in SAT Solving

- State-of-the-art CDCL solvers often perform amazingly well (“SAT is easy in practice”)
- Very poor theoretical understanding:
 - Why do heuristics work?
 - Why are applied instances easy?

Current State of Affairs in SAT Solving

- State-of-the-art CDCL solvers often perform amazingly well (“SAT is easy in practice”)
- Very poor theoretical understanding:
 - Why do heuristics work?
 - Why are applied instances easy?
- Paradox: resolution quite weak proof system; many strong proof complexity lower bounds for (seemingly) “obvious” formulas (e.g., [Hak85, Urq87, BW01])

Current State of Affairs in SAT Solving

- State-of-the-art CDCL solvers often perform amazingly well (“SAT is easy in practice”)
- Very poor theoretical understanding:
 - Why do heuristics work?
 - Why are applied instances easy?
- Paradox: resolution quite weak proof system; many strong proof complexity lower bounds for (seemingly) “obvious” formulas (e.g., [Hak85, Urq87, BW01])
- See Chapter 7 on *Proof Complexity and SAT Solving* in the *Handbook of Satisfiability* for more details [BN21]

Theoretical Lower Bounds and Practical Reality

- If resolution so weak, how can CDCL SAT solvers be so good?
- One answer: “tricky” formulas don’t show up too often in practice
- Another area of intense research: Try to describe **what properties of “real-life” formulas make them easy or hard**

Theoretical Lower Bounds and Practical Reality

- If resolution so weak, how can CDCL SAT solvers be so good?
- One answer: “tricky” formulas don’t show up too often in practice
- Another area of intense research: Try to describe **what properties of “real-life” formulas make them easy or hard**
- But sometimes we would like to be able to solve also “tricky” formulas
- Can we go beyond resolution?

Theoretical Lower Bounds and Practical Reality

- If resolution so weak, how can CDCL SAT solvers be so good?
- One answer: “tricky” formulas don’t show up too often in practice
- Another area of intense research: Try to describe **what properties of “real-life” formulas make them easy or hard**
- But sometimes we would like to be able to solve also “tricky” formulas
- Can we go beyond resolution?
- Explore **stronger methods of reasoning!**
- Algorithms based on such methods could potentially lead to **exponential speed-ups** *[stay tuned for next lecture. . .]*

So... Is There a Smarter Way Than Brute-Force?

In theory, probably no...

- COLOURING, CLIQUE, SAT, and 1000s other problems are “all the same” — efficient algorithm for one can solve all (the problems are all **NP-complete**)
- Widely believed impossible to construct algorithms that are always (a) efficient and (b) correct (even in **worst case**)
- Settling this question is one of **Millennium Prize Problems**: Are there efficient algorithms for NP-complete problems?

So... Is There a Smarter Way Than Brute-Force?

In theory, probably no...

- COLOURING, CLIQUE, SAT, and 1000s other problems are “all the same” — efficient algorithm for one can solve all (the problems are all **NP-complete**)
- Widely believed impossible to construct algorithms that are always (a) efficient and (b) correct (even in **worst case**)
- Settling this question is one of **Millennium Prize Problems**: Are there efficient algorithms for NP-complete problems?

In practice, definitely yes!

- Real-world problems are usually not “worst-case” but highly structured
- Fairly simple (but clever) methods work amazingly well amazingly often (though we don't really understand why)

So... Is There a Smarter Way Than Brute-Force?

In theory, probably no...

- COLOURING, CLIQUE, SAT, and 1000s other problems are “all the same” — efficient algorithm for one can solve all (the problems are all **NP-complete**)
- Widely believed impossible to construct algorithms that are always (a) efficient and (b) correct (even in **worst case**)
- Settling this question is one of **Millennium Prize Problems**: Are there efficient algorithms for NP-complete problems?

In practice, definitely yes!

- Real-world problems are usually not “worst-case” but highly structured
- Fairly simple (but clever) methods work amazingly well amazingly often (though we don't really understand why)

Stark disconnect between theory and practice...

Research Goals in the MIAO Group (1/2)

Strengthen the mathematical analysis of algorithmic methods

- Study methods of reasoning powerful enough to capture state-of-the-art algorithms used in practice
- Prove theorems about their power and limitations
- E.g., resolution proof system captures CDCL reasoning

Research Goals in the MIAO Group (1/2)

Strengthen the mathematical analysis of algorithmic methods

- Study methods of reasoning powerful enough to capture state-of-the-art algorithms used in practice
- Prove theorems about their power and limitations
- E.g., resolution proof system captures CDCL reasoning

Construct stronger algorithms for combinatorial problems

- Use insights into stronger mathematical methods of reasoning to build algorithms for SAT and other combinatorial problems
- Aiming for exponential speed-ups over state of the art
- E.g., use cutting planes to build pseudo-Boolean solvers

Research Goals in the MIAO Group (2/2)

Improve understanding of efficient computation in practice

- Use computational complexity theory to study “real-world” (not worst-case) problems
- Combine theoretical study and empirical experiments
- E.g., take “crafted formulas” with provable theoretical properties and investigate correlation with practical solver performance

Research Goals in the MIAO Group (2/2)

Improve understanding of efficient computation in practice

- Use computational complexity theory to study “real-world” (not worst-case) problems
- Combine theoretical study and empirical experiments
- E.g., take “crafted formulas” with provable theoretical properties and investigate correlation with practical solver performance

Certify correctness for modern combinatorial solvers

- In many combinatorial optimization paradigms, state-of-the-art solvers are known to be buggy
- Develop methods to make solvers output not just answer but machine-verifiable proof of correctness of this answer


Some References for Further Reading

Handbook of Satisfiability (Especially chapter 7 😊)



[BHvMW21]

Proof Complexity by Jan Krajíček



[Kra19]

And survey papers, slides, and videos at www.jakobnordstrom.se

Take-Home Message

- Modern SAT solvers, although based on old and simple DPLL method, can be enormously efficient in practice
- SAT solving more of an art form than a science — theoretical understanding lagging far behind
- Can use proof complexity to analyze potential and limitations of SAT solvers
- And to get inspirations for algorithms based on stronger methods of reasoning
- Lots of challenging work for PhD students and postdocs (we're hiring!)

Take-Home Message

- Modern SAT solvers, although based on old and simple DPLL method, can be enormously efficient in practice
- SAT solving more of an art form than a science — theoretical understanding lagging far behind
- Can use proof complexity to analyze potential and limitations of SAT solvers
- And to get inspirations for algorithms based on stronger methods of reasoning
- Lots of challenging work for PhD students and postdocs (we're hiring!)

Thanks for listening!

References I

- [AS09] Gilles Audemard and Laurent Simon. Predicting learnt clauses quality in modern SAT solvers. In *Proceedings of the 21st International Joint Conference on Artificial Intelligence (IJCAI '09)*, pages 399–404, July 2009.
- [AS12] Gilles Audemard and Laurent Simon. Refining restarts strategies for SAT and UNSAT. In *Proceedings of the 18th International Conference on Principles and Practice of Constraint Programming (CP '12)*, volume 7514 of *Lecture Notes in Computer Science*, pages 118–126. Springer, October 2012.
- [BHvMW21] Armin Biere, Marijn J. H. Heule, Hans van Maaren, and Toby Walsh, editors. *Handbook of Satisfiability*, volume 336 of *Frontiers in Artificial Intelligence and Applications*. IOS Press, 2nd edition, February 2021.
- [BN21] Samuel R. Buss and Jakob Nordström. Proof complexity and SAT solving. In Biere et al. [BHvMW21], chapter 7, pages 233–350.
- [BW01] Eli Ben-Sasson and Avi Wigderson. Short proofs are narrow—resolution made simple. *Journal of the ACM*, 48(2):149–169, March 2001. Preliminary version in *STOC '99*.

References II

- [Coo71] Stephen A. Cook. The complexity of theorem-proving procedures. In *Proceedings of the 3rd Annual ACM Symposium on Theory of Computing (STOC '71)*, pages 151–158, May 1971.
- [DLL62] Martin Davis, George Logemann, and Donald Loveland. A machine program for theorem proving. *Communications of the ACM*, 5(7):394–397, July 1962.
- [DP60] Martin Davis and Hilary Putnam. A computing procedure for quantification theory. *Journal of the ACM*, 7(3):201–215, 1960.
- [EGG⁺18] Jan Elffers, Jesús Giráldez-Cru, Stephan Gocht, Jakob Nordström, and Laurent Simon. Seeking practical CDCL insights from theoretical SAT benchmarks. In *Proceedings of the 27th International Joint Conference on Artificial Intelligence (IJCAI '18)*, pages 1300–1308, July 2018.
- [Hak85] Armin Haken. The intractability of resolution. *Theoretical Computer Science*, 39(2-3):297–308, August 1985.

References III

- [KN20] Janne I. Kokkala and Jakob Nordström. Using resolution proofs to analyse CDCL solvers. In *Proceedings of the 26th International Conference on Principles and Practice of Constraint Programming (CP '20)*, volume 12333 of *Lecture Notes in Computer Science*, pages 427–444. Springer, September 2020.
- [Kra19] Jan Krajíček. *Proof Complexity*, volume 170 of *Encyclopedia of Mathematics and Its Applications*. Cambridge University Press, March 2019.
- [Lev73] Leonid A. Levin. Universal sequential search problems. *Problemy peredachi informatsii*, 9(3):115–116, 1973. In Russian. Available at <http://mi.mathnet.ru/ppi914>.
- [MMZ⁺01] Matthew W. Moskewicz, Conor F. Madigan, Ying Zhao, Lintao Zhang, and Sharad Malik. Chaff: Engineering an efficient SAT solver. In *Proceedings of the 38th Design Automation Conference (DAC '01)*, pages 530–535, June 2001.
- [MS99] João P. Marques-Silva and Karem A. Sakallah. GRASP: A search algorithm for propositional satisfiability. *IEEE Transactions on Computers*, 48(5):506–521, May 1999. Preliminary version in *ICCAD '96*.

References IV

- [PD07] Knot Pipatsrisawat and Adnan Darwiche. A lightweight component caching scheme for satisfiability solvers. In *Proceedings of the 10th International Conference on Theory and Applications of Satisfiability Testing (SAT '07)*, volume 4501 of *Lecture Notes in Computer Science*, pages 294–299. Springer, May 2007.
- [Urq87] Alasdair Urquhart. Hard examples for resolution. *Journal of the ACM*, 34(1):209–219, January 1987.