

Minimum Spanning Tree Problem


Input: A connected undirected graph $G = (V, E)$ with weight function $w : E \rightarrow \mathbb{R}$.

For simplicity, assume that all edge weights are distinct. (the algorithms will still work but the analysis is more difficult)

Output: A spanning tree T (a tree that connects all the vertices) of minimum weight:

$$w(T) = \sum_{(u,v) \in T} w(u,v)$$

Example: MST



How do we find the minimum spanning tree of a particular graph?

Useful theorem:

Theorem.

Let T be the MST of $G = (V, E)$, and let $A \subseteq V$. Suppose that $(u, v) \in E$ is the least-weight edge connecting A to $V \setminus A$. Then, $(u, v) \in T$.

(Proof skipped: see page 626 for additional details)

Remember, “A locally optimal choice is globally optimal” is the hallmark of a **greedy algorithm**.




From this theorem, create a greedy algorithm to compute the MST. Roughly the idea is that we can repeatedly choose the least-weight edge that connects a new vertex to our tree.

Prim's Algorithm




Idea: Maintain $V \setminus A$ as a priority queue Q . Key each vertex in Q with the weight of the least-weight edge connecting it to a vertex in A .

```
1:  $Q = V$ 
2: Set  $key[v] = \infty$  for all  $v \in V$ 
3: Set  $key[s] = 0$  for some arbitrary  $s \in V$ 
4: while  $Q$  is not empty do
5:    $u = ExtractMin(Q)$ 
6:   for each  $v \in Adj[u]$  do
7:     if  $v \in Q$  and  $w(u, v) < key[v]$  then
8:        $key[v] = w(u, v)$  //Decreases key in priority queue  $Q$ 
9:        $\pi[v] = u$ 
10:    end if
11:  end for
12: end while
```




Prim's Example: (1)



Prim's Example: (2)



Prim's Example: (3)



Prim's Algorithm Runtime

```

1:  $Q = V$ 
2: Set  $key[v] = \infty$  for all  $v \in V$ 
3: Set  $key[s] = 0$  for some arbitrary  $s \in V$ 
4: while  $Q$  is not empty do
5:    $u = ExtractMin(Q)$ 
6:   for each  $v \in Adj[u]$  do
7:     if  $v \in Q$  and  $w(u, v) < key[v]$  then
8:        $key[v] = w(u, v)$  //Decreases key in priority queue  $Q$ 
9:        $\pi[v] = u$ 
10:    end if
11:  end for
12: end while

```

Q	$T_{EXTRACT-MIN}$	$T_{DECREASE-KEY}$	Total Runtime
array			
binary heap			
Fibonacci heap (not covered)			

Kruskal's Algorithm

Another greedy algorithm for computing a MST is Kruskal's.

Idea: Repeatedly pick edge with smallest weight as long as it does not form a cycle.

- The algorithm creates a set of trees (a forest)
- During the algorithm the added edges merge the trees together, such that in the end only one tree remains