

Machine Learning Project

Classification of news articles

Jakob Sahlström
jasa5691@student.uu.se

Anders Lindström
anli6945@student.uu.se

Jesper Durebrandt
jedu6357@student.uu.se

Friday 25th April, 2014

Abstract

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Etiam lobortis facilisis sem. Nullam nec mi et neque pharetra sollicitudin. Praesent imperdiet mi nec ante. Donec ullamcorper, felis non sodales commodo, lectus velit ultrices augue, a dignissim nibh lectus placerat pede. Vivamus nunc nunc, molestie ut, ultricies vel, semper in, velit. Ut porttitor. Praesent in sapien. Lorem ipsum dolor sit amet, consectetur adipiscing elit. Duis fringilla tristique neque. Sed interdum libero ut metus. Pellentesque placerat. Nam rutrum augue a leo. Morbi sed elit sit amet ante lobortis sollicitudin. Praesent blandit blandit mauris. Praesent lectus tellus, aliquet aliquam, luctus a, egestas a, turpis. Mauris lacinia lorem sit amet ipsum. Nunc quis urna dictum turpis accumsan semper.

1 Introduction

Describe the problem Related work here maybe?
Introduction and stuff

2 Theory

2.1 Naive Bayes classifier

Let c be the class and $A = a_1, \dots, a_n$ be the attributes of a document. Then with Bayes Theorem

$$p(c|A) = \frac{p(A|c)p(c)}{p(A)}, \quad (1)$$

the attributes A is classified as class C if and only if

$$f_b(A) = \frac{p(c|A)}{p(\neg c|A)} \geq 1, \quad (2)$$

where $f_b(A)$ is called a *Bayesian* classifier. Assuming all attributes are independent given the class,

$$p(A|c) = p(a_1, \dots, a_n|c) = \prod_{i=1}^n p(a_i|c)$$

the final classifier can be written as

$$f_{nb}(A) = \frac{p(c)}{p(\neg c)} \prod_{i=1}^n \frac{p(a_i|c)}{p(a_i|\neg c)} \quad (3)$$

where f_{nb} is called the *Naive Bayesian* classifier.

Two models that uses the Naive Bayes assumption are the *multi-variate Bernoulli* model and the *multinomial* model. The main difference is that in the Bernoulli model the attributes are binary, indicating if a word from a vocabulary has occurred at least once or not. In the multinomial model the frequency of words are taken into account.

2.2 Support Vector Machine Classifier

Support vector machine classifiers (SVM's) classifies data belonging to two classes by finding the hyperplane with the widest margin that separates the classes. The data vectors that restrict the margin of the hyperplane are referred to as support vectors. This results in a maximization problem, where the objective function describes the width of the margin. This is solved using quadratic programming. An advantage with this approach is that the maximization problem is convex, meaning that the maximum found is guaranteed to be the global maximum. This requires, however, that the classes are linearly separable.

3 Method

Method and stuff

4 Results

Result and stuff

5 Related work

5.1 Naive Bayes Classifier

Naive Bayes models are widely used because of its simplicity and efficiency. A. McCallum and K. Nigam compares the two most common models, the multi-variate Bernoulli and the multinomial model, in the realm of document classification. They are explained in detailed both theoretically and empirically and in general the multinomial model outperforms the Bernoulli model [5].

5.2 Support Vector Machine Classifier

Support vector machine classifiers performs well on data that is linearly separable and is guaranteed to find the optimal hyperplane that separates the data. They can however only separate data into two classes, but if combined they are able to perform multi-class classification. A simple approach is to use k SVMs to solve a k -class classification problem. The SVMs may also be combined in a more sophisticated fashion, so that less than k SVMs can be used. Both methods are investigated in [3].

6 Conclusions & Future work

Conclusion and stuff

References

- [1] R. Berwick. An Idiots guide to Support vector machines, 2003.
- [2] V. Tampakas M. Ikonomakis, S. Kotsiantis. Text Classification Using Machine Learning Techniques, 2005.
- [3] Eddy Mayoraz and Ethem Alpaydin. Support Vector Machines for Multi-class Classification, 1999.
- [4] Andrew McCallum and Kamal Nigam. A comparison of event models for Naive Bayes text classification, 1998.
- [5] Harry Zhang. The Optimality of Naive Bayes, 2004.