

main__ex1

April 7, 2021

```
[1]: ###  
    # python  
    from enum import IntEnum, auto  
    from typing import Dict, Any, List, Optional  
    from dataclasses import dataclass  
  
    # lib  
    import numpy as np  
    import matplotlib.pyplot as plt  
    from scipy.special import erfinv, erf  
  
    # custom lib  
    import jx_lib  
  
    ### E1  
    OUT_DIR_E1="output/E1"  
    jx_lib.create_all_folders(DIR=OUT_DIR_E1)  
  
    @dataclass  
    class GMM:  
        pi: float  
        mu: List[float]  
        sigma: List[float]
```

```
[2]: GMM_Model_E1q1 = GMM(pi=0.5, mu=[1, -1], sigma=[0.5, 0.5])
```

0.1 E1 - Q1: X_i Histogram

- See histograms below:

```
[3]: def GMMsample(  
    gmm: GMM,  
    n = 1000,  
    ) -> "nparray":  
    # Generate data pool:  
    Pool1 = np.random.normal(loc=gmm.mu[0], scale=gmm.sigma[0], size=n * 10)  
    Pool2 = np.random.normal(loc=gmm.mu[1], scale=gmm.sigma[1], size=n * 10)
```

```

# Mix down-sample
U = np.random.uniform(0, 1, size=n)
X = np.array([Pool1[i] if Ui < gmm.pi else Pool2[i] for i, Ui in
→enumerate(U)])
return X

```


```

[4]: X = GMMsample(gmm=GMM_Model_E1q1, n=1000)

jx_lib.output_hist(
    data_dict = {"X": X},
    figsize = (12,6), bin_size = 50, OUT_DIR = OUT_DIR_E1, tag = "q1"
)

```

[4]:



0.2 E1 - Q2: U_i Distribution

- Final Formulation:

$$U_i = \Phi^{-1}(F(X_i))$$

where:

$$\Phi^{-1}(F) = \sqrt{2} \operatorname{erf}^{-1}(1 - 2F)$$


$$F(X_i) = \frac{1}{2} \left(\frac{1}{2} [1 + \operatorname{erf}(\frac{X_i - \mu_1}{\sigma_1 \sqrt{2}})] + \frac{1}{2} [1 + \operatorname{erf}(\frac{X_i - \mu_2}{\sigma_2 \sqrt{2}})] \right)$$

- See code and histograms below.
- By inspection, the distribution should be Gaussian approximately.

```
[5]: # %% E1q2
def GMMinv(
    X,
    gmm,
) -> "nparray":
    # CDF of GMM in q1:
    norm_cdf = lambda x, mu=0, sigma=1 : 0.5 * ( 1 + erf((x - mu) / (sigma * np.
    ↪sqrt(2))))
    CDF_gmm = lambda x: 0.5 * np.sum([norm_cdf(x, mu, sigma) for mu, sigma in ↪
    ↪zip(gmm.mu, gmm.sigma)], axis=0)
    F = CDF_gmm(x=X)
    # Inv. CDF of std. normal:
    U = - np.sqrt(2) * erfinv(1 - 2 * F) # EQUIVALENT: U = norm.ppf(F)
    return U
```

```
[6]: U = GMMinv(X=X, gmm=GMM_Model_E1q1)

jx_lib.output_hist(
    data_dict = {"U": U},
    figsize = (12,6), bin_size = 50, OUT_DIR = OUT_DIR_E1, tag = "q2"
)
```



0.3 E1 - Q3 : Binary Search

- See scripts below.
- See the function T plot with input $z \in [-5, 5]$ below.

```

[7]: # %% E1q3
def BinarySearch(
    F: "function",
    u: float, # \in (0,1)
    lb      = -100,
    ub      = 100,
    maxiter = 100,
    tol     = 1e-10
):
    while F(lb) > u:
        ub = lb
        lb = lb / 2
    while F(ub) < u:
        lb = ub
        ub = ub * 2
    for i in range(maxiter):
        x = (lb + ub)/2
        t = F(x)

        if t > u:
            ub = x
        else:
            lb = x

        if abs(t-u) <= tol:
            break

    return x

def computeT(
    gmm,
):
    norm_cdf = lambda x, mu=0, sigma=1 : 0.5 * ( 1 + erf((x - mu) / (sigma * np.
    ↪sqrt(2))))
    CDF_gmm = lambda x: 0.5 * np.sum([norm_cdf(x, mu, sigma) for mu, sigma in_
    ↪zip(gmm.mu, gmm.sigma)], axis=0)
    # CDF_gmm = lambda x: gmm.pi * norm.cdf(x, gmm.mu[0], gmm.sigma[0]) + (1 -_
    ↪gmm.pi) * norm.cdf(x, gmm.mu[1], gmm.sigma[1])
    T_z = lambda z: BinarySearch(F=CDF_gmm, u=norm_cdf(z))
    return T_z

```

```

[8]: T_z = computeT(gmm=GMM_Model_E1q1)

# plot T_z:
z_bnd = [-5, 5]
step = 0.1
z_num = np.arange(min(z_bnd), max(z_bnd) + step, step=step)


```

```

T_num = np.vectorize(T_z)(z_num)
jx_lib.output_plot(
    data_dict={"T function":{"x":z_num, "y":T_num}},
    Ylabel="T", Xlabel="z", OUT_DIR=OUT_DIR_E1, tag="T(z)"
)

```

[8]:



0.4 E1 - Q4 : PushForward

- See histogram of generated \tilde{X}_i below:
- Script is presented below:
- Resultant Histogram is similar to Ex1.1 (as second comparison histogram shown)

```

[9]: # %% E1q4
def PushForward(
    Z: List[float],
    gmm: GMM,
) -> List[float]:
    # grab T_z:
    T_z = computeT(gmm=gmm)
    Xi_hat = np.vectorize(T_z)(Z)
    return Xi_hat

```


```

[10]: Zi = np.random.normal(0, 1, size=1000)
Xi_hat = PushForward(Z=Zi, gmm=GMM_Model_E1q1)

```


```
jx_lib.output_hist(
    data_dict = {"Xi_hat": Xi_hat},
    figsize = (12,6), bin_size = 50, OUT_DIR = OUT_DIR_E1, tag = "q4"
)
```

[10]:



```
[11]: jx_lib.output_hist(
    data_dict = {"X": X, "Xi_hat": Xi_hat},
    figsize = (12,6), bin_size = 50, OUT_DIR = OUT_DIR_E1, tag = "q4-compare"
)
```


[11]:



0.5 E1 - Q5 : GMMinv as Ex1.2


- Histogram is as displayed below:
- It is in a form of gaussian distribution by inspection

```
[12]: # %% E1q5
U_hat = GMMinv(X=Xi_hat, gmm=GMM_Model_E1q1)
jx_lib.output_hist(
    data_dict = {"U_hat": U_hat},
    figsize = (12,6), bin_size = 50, OUT_DIR = OUT_DIR_E1, tag = "q5"
)
```



```
[13]: jx_lib.output_hist(
    data_dict = {"U": U, "U_hat": U_hat},
    figsize = (12,6), bin_size = 50, OUT_DIR = OUT_DIR_E1, tag = "q5-compare"
)
```

[13]:



0.6 (Optional, 0pt) E1 - Q6 : T as a 2-layer NN