

3300 Wax Resin Ribbon

General purpose Thermal Transfer Ribbon

Zebra's 3300 Wax Resin Ribbon is a general-purpose thermal transfer ribbon is a versatile solution engineered for a wide array of labeling needs. Its key benefits include the ability to print on all label substrates, from rough papers to synthetics, ensuring maximum flexibility. The ribbon is designed for high-speed printing environments, capable of reaching speeds up to 16 inches per second (400 mm/s). Furthermore, it operates at low energy settings, which not only reduces power consumption but also helps to preserve and extend the life of the printer's printhead, leading to lower operational costs over time.



The 3300 Wax Resin ribbon is suitable for an extensive range of applications, making it an ideal choice for industries such as pharmaceuticals (drug labels), food and beverage (food information labels), retail, and manufacturing. Its use cases extend to outdoor product labels, horticultural tags, building materials, clothing tags, and even automotive interior labels. The product meets numerous international standards and approvals, including REACH/SVHC, EU and US FDA food contact regulations, RoHS for heavy metals, California Proposition 65, and UL 969, ensuring it is safe and compliant for a global market. For best results, it should be stored between 5-35°C (40-95°F) with 20-80% relative humidity.

The ribbon is constructed with precision for optimal performance. It demonstrates strong resistance to abrasion and can withstand heat up to 100°C (212°F), making it durable for various conditions, although it has lower resistance to solvents.

Zebra 3300 Wax Resin Ribbon

For more information, please visit www.zebra.com/supplies

Specifications

Technical Specifications	
Color	Black
Ink Formulation	Wax/Resin
Base Film	Polyester Base
Film Caliper	4.5µm
Total Caliper: XX microns +/- 10%	< 9µm
Ink Melting Point	75°C (167°F)
Scanning Capabilities	IR and Visible Light
Optical Density	2.1 ODR
Heat Resistance	100°C (212°F)
Product Performance and Suitability	
Recommended storage conditions (before use)	5-35°C (40-95°F) with 20-80% relative humidity
Regulatory and compliance	
REACH / SVHC 1907/2006/EC EU Food Contact 1935/2004/EC US Food Contact FDA RoHS / Heavy Metals 2011/65/EU California Proposition 65 Halogens IEC 61249-2-21:2003 UL 969	
Stocked Sizes Available for Zebra Printers	
Essential-range, Mid-range and high-performance thermal printers, other legacy Zebra printers. Different widths/lengths are available on request subject to minimum order quantities and lead times.	
Material Testing in End Application	
The information contained in this document is to be used for guidance only and is not intended for use in setting specifications. All purchasers of Zebra products shall be solely responsible for independently determining if the product conforms to all requirements of their unique application. All products should be pre-tested to ensure they meet all intended requirements of specific end-use applications.	

*Specifications are subject to change without notice.

Markets and Applications

- Industries:**
- Pharmaceuticals (drug labels)
 - Food and Beverage (food information labels)
 - Retail
 - Manufacturing

- Use Cases:**
- Outdoor product labels
 - Horticultural tags
 - Building materials
 - Clothing tags
 - Automotive interior labels