



Z-Perform 1000D Removable

Direct thermal paper label with a removable adhesive

The Z-Perform 1000D Removable is a highly adaptable and dependable label solution crafted for various indoor applications where clean removability and exceptional performance are required. As a direct thermal paper label, it eliminates the need for ribbons, streamlining operations and delivering convenience and efficiency. Its matte finish, cold temperature capability, and BPA-free face stock reflect a thoughtful design that meets the demands of modern labelling while emphasizing safety and regulatory compliance.



When used in appropriate settings, the Z-Perform 1000D Removable delivers outstanding results. It provides high-contrast print quality, producing sharp, black images when paired with recommended Zebra printers. Its adhesive is formulated to balance strong adhesion with effortless removability, offering reliable performance on packaging materials, shelving, and other surfaces.

Designed specifically for indoor use, this label offers a versatile and efficient solution for businesses across industries. Whether for retail, food packaging, or general labelling applications, the Z-Perform 1000D Removable ensures seamless operations while maintaining exceptional safety and quality standards. With its combination of adaptability, compliance, and ease of use, it remains an indispensable choice for businesses seeking reliable, high-performance labels.

Engineered for temporary labelling needs, the removable adhesive provides strong adhesion to a wide range of surfaces while ensuring residue-free removal. This makes it particularly well-suited for applications such as retail labelling, food packaging, and other general-purpose uses. The label's ISEGA approval, along with its compliance with European food regulations (EC 1935/2004, EU 10/2011) and FDA 175.105 standards, further highlights its suitability for direct contact with dry and non-fatty foodstuffs, ensuring it meets stringent safety requirements.

While this label excels in controlled indoor environments, it is not recommended for conditions involving prolonged exposure to sunlight, extreme heat, or PVC surfaces, as these factors may affect its performance.

Z-Perform 1000D Removable

For more information, please visit www.zebra.com/barcodesupplies.

Specifications

Material Construction	
Facestock	Matte white uncoated thermal imaging paper 66 microns
Adhesive	Removable rubber adhesive 13 microns
Liner	60gsm glassine liner 47 microns
Total Thickness (+/- 10%)	126 microns
Environment	Indoor Use

Temperature Performance	
Minimum Application Temperature ¹	41°F/ 5°C
Service Temperature Range ²	14°F to 158°F/-10°C to 70°C

Recommended Printers and Ribbons	
Printers	Direct Thermal (No Ribbon Required)
Ribbons	N/A

Regulatory and Compliance	
Adhesive complies with European food regulations EC 1935/2004, EU 10/2011 and FDA 175.105 for direct contact with dry and non-fatty foodstuffs	

Additional Information	
Recommended Storage Conditions	6 months duration when stored at 20°C at 50% RH
Expected Life Span in Application	Indoor use, for up to 1 year
Sample Part Number	SAMPLE40762

Material Test in End Application	
The information contained in this document is to be used for guidance only and is not intended for use in setting specifications. All purchasers of Zebra products shall be solely responsible for independently determining if the product conforms to all requirements of their unique application.	

Footnotes	
1. When the label is applied, the environment and surface should be above this temperature.	
2. Following correct application and appropriate dwell time (usually 24hrs) the media will withstand this temperature range.	

Markets and Applications

- Indoor general purpose labelling and food labelling
- Labelling of most packaging materials
- Removable shelf-edge labelling, product and price labelling in retail
- Product Identification
- Work in progress labelling
- Removable labels for boxes, pallets, shelves or tote bins