Assignment 2 - John Akujobi

Owner	John Akujobi
Type	Homework
Created time	@February 3, 2024 5:44 PM
Status	In progress

CSC 317 Spring 2024 | Assignment #2 | Due: 2-12-24

From the textbook (ARM edition) do the following problems that start on page 175.

Assignments are to be submitted to D2L by 2:00pm on the due date.

Exercise 2.1 (5 points)

For the following C statement, write the corresponding LEGv8 assembly code. Assume that the C variables f, g, and h, have already been placed in registers X0, X1, and X2 respectively. Use a minimal number of LEGv8 assembly instructions.

`f = g + (h - 5);`

```
; f = X0
; g = X1
; h = X2
SUBI X3, X2, #5    ; Subtract 5 from h(X2) and put result in ter
ADDI X0, X1, X3; Add temp to g(X1) and put result in f(X0)
```

---

2. Exercise 2.2 (5 points)

Write a single C statement that corresponds to the two LEGv8 assembly instructions below.

`ADD f, g, h`

`ADD f, i, f`

```
// f = g + h
// f = f + i
// f = g + h + i

f = g + h + i;
```

---

3. Exercise 2.3 (5 points)

For the following C statement, write the corresponding LEGv8 assembly code. Assume that the variables f, g, h, i, and j are assigned to registers X0, X1, X2, X3, & X4, respectively.

Assume that the base address of the arrays A and B are in registers X6 and X7, respectively.

`B [8] = A [i – j];`

```
; f = X0
; g = X1
; h = X2
; i = X3
; j = X4
; A [0] = X6
; B [0] = X7
; B [8] = 8 * 8 = 64 Offset
;
```

---

4. Exercise 2.11 (all parts) (12 points)

Assume that registers X0 and X1 hold the values 0×8000000000000000 and 0×D000000000000000, respectively.

2.11.1

What is the value of X9 for the following assembly code?

`ADD X9, X0, X1`

> X9 = 0x5000000000000000

```
Decimal
8+13=21
21 = 15 hex

  0x8000000000000000
+ 0xD000000000000000
----------------------
 0x15000000000000000

ARM registers can't store more than 64 bits, so, the 1 in from w
leaving behind 0x5000000000000000
```

2.11.2

Is the result in X9 the desired result, or has there been overflow?

> There was overflow

```
0x15000000000000000 was the desired result
But because it exceeded the space for ARM registers, we had to c
leaving 0x15000000000000000
```

2.11.3

For the contents of registers X0 and X1 as specified above, what is the value of X9 for the following assembly code?

`SUB X9, X0, X1`

> X9 = 0x0B

```
8 - 13 (we have to borrow 1h or 16)
24 - 13 = 11 = B
0x18 = 0xD = 0xB

  0x8000000000000000 = X0
- 0xD000000000000000 = X1
--------------------
  0x0B00000000000000
--------------------
```

2.11.4

Is the result in X9 the desired result, or has there been overflow?

```
There wasn't exactly an overflow.
But there was a wrap around
```

2.11.5

For the contents of registers X0 and X1 as specified above, what is the value of X9 for the following assembly code?

`ADD X9, X0, X1`

`ADD X9, X9, X0`

> X9 = 0xD

```
ADD X9, X0, X1
  0x8000000000000000 = X0
```

```
+ 0xD000000000000000 = X1
----------------------
 0x15000000000000000

X9 = 0x5000000000000000


_____________________________________
_____________________________________
ADD X9, X9, X0
  0x5000000000000000
+ 0x8000000000000000
----------------------
  0xD000000000000000

8h + 8h + 13h =
8 + 8 + 13 = 29 = 1D hex
```

2.11.6

Is the result in X9 the desired result, or has there been overflow?

```
The desired result is 0x1D
but X9 does not contain it because of overflow
```

---

5. Exercise 2.14 (5 points)

Provide the instruction type and hexadecimal representation of the following instruction:

`STUR X9, [X10, #32]`

> F8025200

```
STUR opcode is 1984ten
[X10, #32] means there is a 32 bit offset from X10
So the instruction wants to store the data from there into X9

x10, [x10, #16], [x10, #32]
That is, storing the third data from x10

Using D-format (opcode, op2, Rn, Rt, address)
opcode: 1984ten -> 0x7C0h -> 11111000000 in binary (11 bits)
op2: 00 in binary (2 bits)
Rn (X10): 1010 in binary (5 bits)
Rt (X9): 01001 in binary (5 bits)
address (#32): This needs to fit into 9 bits.
                        32 in decimal is 100000 in binary,
                        but we need to pad it to 9 bits: 001000(

= 11111000000 00 1010 01001 001000000

Splitting it into groups of 4
= 1111 1000 0000 0101 0010 0100 0000

= F8025200
```

6. Exercise 2.30 (18 points)

Implement the following C code in LEGv8 assembly. Hint:
Remember that the stack pointer must remain aligned on a multiple of 16.

```c
int fib (int n) {
if (n==0)
    return 0;
else if (n == 1)
```

```
    return 1;
else
    return fib(n-1) + fib(n-2);
}
```

```
fib:
    //Lets assume that n is in x0
    //since that is where arguements go to

    sub sp, sp, #16  // Allocate stack space
    // Save frame pointer and return address
    stp x29, x30, [sp, #16]
    add x29, sp, #16  // Update frame pointer

    //if (n == 0) {return 0;}
    cmp x0, #0      //check if n is 0
    beq end_if_zero //jump to return 0 if n is 0

    //else if (n == 1) { return 1;}
    cmp x0, #1      //check if n is 1
    beq end_if_one  //jump to return 1 if n is 1

    //fib(n - 1)
    mov x1, x0      //copy n to x1 for keeping
    sub x0, x0, #1  //n = n - 1
    bl fib          // call fib(n - 1)
    mov x19, x0     //store fib(n - 1) in x19

    //fib(n - 2)
    mov x0, x1      //copy n to x0
    sub x0, x0, #2  //subtract 2 from n
    bl fib          //call fib

    add x0, x19, x1 //add fib(n - 1) + fib(n - 2)
```

```
    b end           //jump to 'end'

end_if_zero:
    mov x0, #0      // If n is 0, return 0
    b end           // Branch to label 'end'

end_if_one:
    mov x0, #1      // If n is 1, return 1

end:
    // Restore frame pointer and return address
    ldp x29, x30, [sp, #16]
    add sp, sp, #16  // Deallocate stack space
    ret  // Return to caller function
```

I used the below compiler alongside to translate and understand part of it

Compiler Explorer

Compiler Explorer is an interactive online compiler which shows the assembly output of compiled C++, Rust, Go (and many more) code.

https://godbolt.org/