

Mobile App API Endpoints

Base path is mounted in `src/app.js` as:

- `/api/mobile` + routes from `src/routes/api/mobileAppRouter.js`

All endpoints that are authenticated require a JWT access token:

- `Authorization: Bearer <accessToken>`

Common response format

All handlers use `buildResponse()` from `src/utils/mobileResponse.js`.

Success

```
{
  "isSuccess": true,
  "key": "SOME_KEY",
  "message": "Human readable message",
  "paging": { "totalRecords": 0, "pageSize": 12, "pageNumber": 1, "firstPage": -1,
    "lastPage": -1, "previousPage": -1, "nextPage": -1, "totalPages": -1, "firstItem":
    -1, "lastItem": -1, "withPaging": true },
  "data": { /* endpoint-specific */ },
  "dataList": null
}
```

Error (example shape)

```
{
  "isSuccess": false,
  "key": "ERR_400",
  "message": "Error message",
  "paging": { "totalRecords": 0, "pageSize": 12, "pageNumber": 1, "firstPage": -1,
    "lastPage": -1, "previousPage": -1, "nextPage": -1, "totalPages": -1, "firstItem":
    -1, "lastItem": -1, "withPaging": true },
  "data": null,
  "dataList": null
}
```

Auth failure uses `key: "AUTH_UNAUTHORIZED"`.

1) Auth

1.1 Signup

- **POST** /api/mobile/auth/signup
- **Auth:** none

Request body

```
{
  "name": "string",
  "phone": "string|number",
  "password": "string"
}
```

Response body (200)

```
{
  "isSuccess": true,
  "key": "SIGNUP_SUCCESS",
  "message": "Signup successful",
  "paging": { ... },
  "data": { "success": true },
  "dataList": null
}
```

1.2 Login

- **POST** /api/mobile/auth/login
- **Auth:** none

Request body

```
{
  "phone": "string|number",
  "password": "string"
}
```

Response body (200)

```
{
  "isSuccess": true,
  "key": "LOGIN_SUCCESS",
  "message": "Login successful",
  "paging": { ... },
  "data": {
    "accessToken": "JWT_ACCESS_TOKEN",
    "refreshToken": "JWT_REFRESH_TOKEN",
    "user": {
```

```
    "id": "string",
    "name": "string",
    "phone": "string",
    "balance": 0
  }
},
"dataList": null
}
```

1.3 Profile

- **GET** /api/mobile/profile
- **Auth:** required
 - **Authorization:** Bearer <accessToken>

Request body: none

Response body (200)

```
{
  "isSuccess": true,
  "key": "PROFILE_SUCCESS",
  "message": "Profile fetched",
  "paging": { ... },
  "data": {
    "user": {
      "id": "string",
      "name": "string",
      "phone": "string"
    },
    "balance": 0
  },
  "dataList": null
}
```

2) Wallet

2.1 Add credit (top-up)

- **POST** /api/mobile/wallet/add-credit
- **Auth:** required
 - **Authorization:** Bearer <accessToken>

Request body

```
{
  "amount": 1000
}
```

```
}
```

Notes:

- **amount** is in **Syrian pounds**.
- Server converts to cents internally.

Response body (200)

```
{
  "isSuccess": true,
  "key": "ADD_CREDIT_SUCCESS",
  "message": "Credit added",
  "paging": { ... },
  "data": {
    "balance": 0
  },
  "dataList": null
}
```

2.2 Deduct credit for bus payment

- **POST** `/api/mobile/wallet/deduct`
- **Auth:** required
 - `Authorization: Bearer <accessToken>`

Request body

```
{
  "bussId": "string"
}
```

Response body (200)

```
{
  "isSuccess": true,
  "key": "DEDUCT_SUCCESS",
  "message": "Credit deducted",
  "paging": { ... },
  "data": {
    "balance": 0,
    "deductedAmount": 12345
  },
  "dataList": null
}
```

2.3 Wallet balance + transactions

- **GET** `/api/mobile/wallet/balance`
- **Auth:** required
 - `Authorization: Bearer <accessToken>`

Request body: none

Response body (200)

```
{
  "isSuccess": true,
  "key": "GET_BALANCE_SUCCESS",
  "message": "Balance fetched",
  "paging": { ... },
  "data": {
    "balance": 0
  },
  "dataList": [
    {
      "id": "transactionId",
      "type": "credit|debit",
      "amount": 10000,
      "bussId": null,
      "purpose": "string",
      "timestamp": "ISO date string"
    }
  ]
}
```

2.4 Deduct price (no auth)

- **GET** `/api/mobile/wallet/deduct-price`
- **Auth:** none

Request body: none

Response body (200)

```
{
  "isSuccess": true,
  "key": "DEDUCT_PRICE_SUCCESS",
  "message": "Deduct price fetched",
  "paging": { ... },
  "data": {
    "priceInPounds": 1
  },
}
```

```
"dataList": null
}
```

3) Routes

3.1 Get all companies routes

- **GET** `/api/mobile/routes`
- **Auth:** required
 - `Authorization: Bearer <accessToken>`

Request body: none

Response body (200)

```
{
  "isSuccess": true,
  "key": "GET_ALL_ROUTES_SUCCESS",
  "message": "Routes fetched",
  "paging": { ... },
  "data": null,
  "dataList": [
    { /* returned object(s) from listPublicRoutes() */ }
  ]
}
```

The exact fields inside each route item are defined in `listPublicRoutes()` (in `src/services/busService.js`).