### 2009

# Virginia Department of Transportation Daily Traffic Volume Estimates Including Vehicle Classification Estimates

where available

## Special Locality Report 142

Town of Blackstone

Information in this report is included in Report

**67** 

(Nottoway County)

Prepared By

Virginia Department of Transportation Traffic Engineering Division

In Cooperation With

U.S. Department of Transportation Federal Highway Administration

### Virginia Department of Transportation Traffic Engineering Division Traffic Monitoring Section

The Virginia Department of Transportation (VDOT) conducts a program where traffic count data are gathered from sensors in or along streets and highways and other sources. From these data, estimates of the average number of vehicles that traveled each segment of road are calculated. VDOT periodically publishes booklets listing these estimates.

One of these booklets, titled "Average Daily Traffic Volumes with Vehicle Classification Data, on Interstate, Arterial and Primary Routes" includes a list of each Interstate and Primary highway segment with the estimated Annual Average Daily Traffic (AADT) for that segment. AADT is the total annual traffic estimate divided by the number of days in the year. This booklet also includes information such as estimates of the percentage of the AADT made up by 6 different vehicle types, ranging from cars to double trailer trucks; estimated Annual Average Weekday Traffic (AAWDT), which is the number of vehicles estimated to have traveled the segment of highway during a 24 hour weekday averaged over the year; as well as Peak Hour and Peak Direction factors used by planners to formulate design criteria.

In addition to the Primary and Interstate publication, one hundred books are published periodically, one for each of 100 areas across the state defined by VDOT for record-keeping purposes. These books include traffic volume estimates for roads within the county, cities, and towns within the area. These books are titled "Daily Traffic Volumes Including Vehicle Classification Estimates, where available; Jurisdiction Report numbers 00 through 99".

Also available are a number of reports summarizing the average Vehicle Miles Traveled (VMT) in selected jurisdictions and other categories of highways. There are many different ways to present traffic volume summary information. Because the user determines the value of each presentation, the reports have been redesigned based on user requests and feedback. The people of the VDOT Traffic Engineering Division Traffic Monitoring Section who produce these books welcome requests for other helpful ways of presenting the summary information.

A compact disc (CD) is available that includes files in the Adobe® Portable Document Format (PDF) that can be displayed, searched, and printed using common desktop computer equipment. The CD includes the publications described above as well as a number of other reports, including specialized VMT summaries and smaller AADT reports for each city and town separately.

### **Publication Notes**

### Parallel Roads

For road inventory and management purposes, some roadways are counted separately by direction and have separately published traffic estimates for each direction of travel. Examples of such roadways are the interstate system and routes with separated facilities and (usually) one-way traffic facilities in urban areas. In these publications, they are referred to as parallel roads. As a convenience for the users of the publication, the listing for segments of roads with parallel segments are published with both the traffic estimates for their own direction of travel (e.g. I-95 Northbound) as well as the estimate of the total of all traffic on the same route including parallel roadways (all directions of I-95). The publication will have a "Combined Traffic Estimates for Parallel Roadways on this Route" or "Combined Traffic" identifiers for the combined direction of travel estimates.

Roadways such as I-395 with a North segment, a South segment and a separate Reversible lane segment will have the estimate for more than two parallel roadways included in the entire combined traffic estimate.

Some routes have very complicated paths through cities and towns. These parallel paths may be too complex to allow a relationship between nearby sections of the opposite direction on the same route. In this case, to indicate that the traffic estimates for such a road segment may not include all directions of traffic on that route, the line that would list the combined values will indicate "NA" for not available.

VDOT's traffic monitoring program includes more than 100,000 segments of roads and highways ranging from several mile sections of Interstate highways to very short sections of city streets. Due to problems experienced obtaining some traffic count data, and the level of quality necessary to maintain confidence in the data, no estimate is currently available for some segments of roadway. These segments are included in the publications indicating "NA" for not available. It is the intention of the VDOT Traffic Engineering Division Traffic Monitoring group to obtain the data necessary and to report traffic volume estimates on all road segments included in these publications.

Many of the road segments in this program are local secondary roads. The amount and detail of data collected on these roads are not as great as the data collected on higher volume roads. The vehicle classification, average weekday traffic volumes, and the theoretical design hour traffic volumes are not calculated for these roads. The publications indicate "NA" for the information that is not available.

This publication is based on a traffic monitoring program initiated in 1997. Because the data collection techniques and statistical evaluation processes are different than those used in previous years, comparison with previous publications may be misleading.

### Glossary of Terms:

Route: The Route Number assigned to this segment of roadway with the master inventory route number if this is an overlapping route, with official street or highway name if available.

Length: Length of the traffic segment in miles.

AADT: Annual Average Daily Traffic. The estimate of typical daily traffic on a road segment for all days of the week, Sunday through Saturday, over the period of one year.

### QA: Quality of AADT:

- A Average of Complete Continuous Count Data
- B Average of Selected Continuous Count Data
- F Factored Short Term Traffic Count Data
- G Factored Short Term Traffic Count Data with Growth Element
- H Historical Estimate
- M Manual Uncounted Estimate
- N AADT of Similar Neighboring Traffic Link
- O Provided By External Source
- R Raw Traffic Count, Unfactored

4Tire: Percentage of the traffic volume made up of motorcycles, passenger cars, vans and pickup trucks.

Bus: Percentage of the traffic volume made up of busses.

**2Axle Truck**: Percentage of the traffic volume made up of 2 axle single unit trucks (not including pickups and vans).

**3+Axle Truck**: Percentage of the traffic volume made up of single unit trucks with three or more axles.

1Trail Truck: Percentage of the traffic volume made up of units with a single trailer.

2Trail Truck: Percentage of the traffic volume made up of units with more than one trailer.

QC: Quality of Classification Data:

- A Average of Complete Continuous Count Data
- B Average of Selected Continuous Count Data
- C Short Term Classified Traffic Count Data
- F Factored Short Term Traffic Count Data
- H Historical Estimate
- M Mass Collective Average
- N Classification Estimates of Similar Neighboring Traffic Link

K Factor: The estimate of the portion of the traffic volume traveling during the peak hour or design hour.

QK: Quality of the K Factor estimate:

- A Factor based on 30th Highest Hour Observed During at least 250 days of Continuous Traffic Data
- B Factor based on other Hour Observed During Less than 250 days of Continuous Traffic Data
- F Factor based on Highest Hour Collected at in a 48 Hour Weekday Period
- M Factor based on Manual Estimate of design hour
- N Design Hour Factor (K Factor) of Similar Neighboring Traffic Link
- O Provided by External Source

Dir Factor: The estimate of the portion of the traffic volume traveling in the peak direction during the peak hour..

AAWDT: Average Annual Weekday Traffic. The estimate of typical traffic over the period of one year for the days between Monday through Thursday inclusive.

QW: Quality of AAWDT:

- A Average of Complete Continuous Count Data
- B Average of Selected Continuous Count Data
- F Factored Short Term Traffic Count Data
- G Factored Short Term Traffic Count Data with Growth Element
- M Manual Uncounted Estimate
- N AAWDT of Similar Neighboring Traffic Link
- O Provided by External Source

Year: Year for which the published values are appropriate. If the Quality of AADT (QA) is "R", the year is the year that the raw traffic count was collected, and if available,

### Route Shield Legend

### Route Systems

North 81	Interstate Route	Traffic volume data for Interstate Routes and some other routes are reported separately by direction, as well as combined.
29	US Route	
7	Virginia State Rou	te
(F241)	Frontage Road (F	precedes frontage route number)
(600)	Secondary Route	

### **Special Routes**

Bus	Bus - Business Route
29	Bypas - Bypass Route
	Truck - Truck Route
ALT	ALT - Alternate Route
(220)	Wve - Wve Route connector

- P Parallel Route; Southbound or Westbound direction lanes of a numbered route where they are on a different road facility than the other direction.
- The VDOT Maintainenance Jurisdiction number is displayed below the Secondary Route Number if the Maintenance Jurisdiction is different than the jurisdiction in the title of the report.

### Virginia Department of Transportation Traffic Engineering Division

### 2009 Annual Average Daily Traffic Volume Estimates By Section of Route Town of Blackstone

		-					Tru	ıck			K		Dir		
Route	Jurisdiction	Length AADT	QA	4Tire	Bus		3+Axle			QC	Factor	QK	Factor	AAWDT	Q۷
	From:	SCL Blackste	one												
40 South Main St	Town of Blackstone	0.18 <b>3300</b>	G	94%	1%	1%	1%	3%	0%	С	0.095	F	0.659	3600	G
$\smile$	To:	SR 46 Brunswi	ck Rd												
40 South Main St	Town of Blackstone	0.57 9700	G	96%	0%	1%	0%	3%	0%	С	0.100	F		10000	(
	To	Tenth St													
30 South Main St	Town of Blackstone	0.21 <b>9400</b>	G	96%	0%	1%	0%	3%	0%	С	0.099	F		10000	(
30 South Main St	TOWIT OF BIACKSTOFIE			30 /0	070	1 70	070	370	070	C	0.033	'		10000	
	To- From:	West Entrance													_
40) South Main St	Town of Blackstone	0.47 <b>7600</b>	G	95%	1%	1%	1%	3%	0%	С	0.095	F		8100	(
	To:	Bus US 460 Chu													
40 (460) North Main St	Town of Blackstone	0.59 <b>Church St</b>	G	93%	1%	2%	1%	3%	0%	С	0.089	F		6600	(
	Town of Blackstone	Dinwiddie A		93%	1%	2%	170	3%	0%	C	0.069	Г		0000	
	From:	Bus US 460, North													
40 Dinwiddie Ave	Town of Blackstone	0.53 1800	G	92%	0%	1%	3%	4%	0%	С	0.115	F	0.573	2000	
40) 2	To:	ECL Blackst		0270	0,0		0,0	.,0	0,0		00	•	0.0.0		
	From	SCL Blacksto													_
46 Brunswick Rd	Town of Blackstone	0.15 <b>2000</b>	G	91%	1%	1%	1%	6%	0%	С	0.089	F	0.585	2200	(
Brunswick Rd	To:	SR 40 South M		3170	170		170	070	070	O	0.003	'	0.505	2200	`
	From														_
Bus Church St	Town of Blackstone	WCL Blackst 0.44 <b>3400</b>	G	94%	1%	1%	0%	3%	0%	С	0.099	F	0.521	3600	(
Church St	TOWIT OF BIACKSTOTIE	0.44 3400	<u> </u>	94%	170	1 70	0%	370	0%	C	0.099	Г	0.521	3000	,
Bus	To: From:	Amelia Av	e												_
Church St	Town of Blackstone	0.74 <b>4800</b>	G	95%	1%	1%	0%	3%	0%	С	0.1	F		5100	(
	To:	SR 40 South M	ain St												
Bus	From:	Elm St													
460 (40) North Main St	Town of Blackstone	0.59 <b>6100</b>	G	93%	1%	2%	1%	3%	0%	С	0.089	F		6600	(
$\sim$	To:	Dinwiddie A													
Bus	From:	SR 40 Dinwide								_		_			
North Main St	Town of Blackstone	0.14 <b>5300</b>	G	94%	1%	1%	1%	3%	0%	С	0.097	F		5600	(
Due .	To. From:	Division S	t												
Bus 460 North Main St	Town of Blackstone	0.37 <b>5200</b>	G	93%	1%	2%	1%	3%	0%	F	0.098	F	0.518	5600	(
460) 140/11/11/11/11/15	TOWIT OF DIACKSTOFIE			3J /0	1 /0	Z /0	1 /0	3/0	0 /0	'	0.030	'	0.010	3000	`
Bus	To: From:	Barco Rd													
North Main St	Town of Blackstone	0.56 <b>3500</b>	G	93%	1%	1%	1%	3%	0%	С	0.097	F	0.541	3800	(
	То:	ECL Blackst				i i				-					

6/12/2010 7

### Virginia Department of Transportation Traffic Engineering Division 2009 Annual Average Daily Traffic Volume Estimates By Section of Route Town of Blackstone

						I OWIT OI	Blackst	one								
Route	Length	AADT	QA	4Tire	Bus		Tru 3+Axle		2Trail	QC	K Factor	QK	Dir Factor	AAWDT	QW	Year
Town of Blackstone		From:	1			De	ad End				i					
1103	0.32	110	R				au Enu				NA			NA		08/28/200
67		To			142	-9 Tenth S	t; WCL Bl	lackstone								
		From:				Notte	oway Ave									
1 Amelia Ave	0.21	1200	G	98%	1%	1%	0%	0%	0%	С	0.109	F	0.506	1300	G	2009
<u> </u>		To: From:					urch St									
1 Amelia Ave	0.21	650	G	99%	0%	0%	ourth St 0%	0%	0%	С	0.118	F	0.663	690	G	2009
1) /	0.2.	To:					urch St	0,0	0,0			•	0.000			2000
		From:				Ch	urch St									
2 Brown St	0.24	3300	G	98%	1%	1%	0%	0%	0%	С	0.1	F		3600	G	2009
$\bigcup$		To	_			Notte	oway Ave									
2 Brown St	0.04	2300 From:	G	98%	1%	1%	0%	1%	0%	С	0.088	F	0.546	2400	G	2009
<u> </u>		To				D.	road St									
2 Brown St	0.33	1000 From:	G	97%	1%	1%	0%	0%	0%	С	0.096	F	0.586	1100	G	2009
2)		To:					ision St									
		From:				Beac	h Cliff Rd									
3 College Ave	0.55	270	G	98%	0%	2%	0%	0%	0%	С	0.148	F	0.5	290	G	2009
		To:	:			Te	enth St									
		From:				Br	own St									
4 Division St	0.06	860	G	96%	1%	3%	0%	1%	0%	С	0.1	F	0.654	920	G	2009
		To	<u></u>			Norti	h Main St									
		From:			,		Freeman S	St								
5 Fourth St	0.11	980	G	92%	3%	4%	0%	1%	0%	С	0.112	F	0.619	1000	G	2009
<u> </u>		To:	<u> </u>				elia Ave									
O		From:				JB-67-142					<b>_</b>					
6 S Freeman St	0.19	960 To:	G	98%	1%	1%	0%	0%	0%	F	0.116	F	0.655	1000	G	2009
			<u> </u>				rth Street									
Nottonio Aug	0.47	From:	<u> </u>	000/		Cole Harbo					0.400	_	0.50	0.40	_	2000
7 Nottoway Ave	0.47	590	G	96%	1%	1%	1%	1%	0%	С	0.106	F	0.52	640	G	2009
<u> </u>		From:	<u> </u>				ben Ave	407			<u> </u>	_				
7 Nottoway Ave	0.46	1100	G	97%	1%	1%	1%	1%	0%	С	0.105	F	0.570	1200	G	2009
							thouse Rd									
8 Ridge Rd	0.40	960	G	97%	1%		Blackstone	0%	0%	С	0.207	F	0.882	1000	G	2009
8 Ridge Rd	0.40	900 To:		9176	170	1% West F	0% Entrance R		0%		0.207	г	0.002	1000	G	2009
		From:					ad End	u								
9 Tenth St	0.81	100	G	99%	0%	1%	0%	0%	0%	F	0.162	F	0.5	110	G	2009
g) romarot	0.01		.—					070				•	0.0		Ū	2000
9 Tenth St	0.22	880	G	99%	0%	1%	lege Ave 0%	0%	00/	С	0.124		0.55	040	G	2009
9 Tenth St	0.33	OOU To:		99%	0%		outh Main		0%		0.124	F	0.55	940	G	2009
		From:														
10) Barco Rd	0.20	1700	G	96%	0%	1%	e Rd Rt 60 0%	2%	0%	С	0.087	F	0.571	1900	G	2009
10) 24/00/14	0.20	To:	Ť			US 460 B			070	<u> </u>		•	0.07 1	1000	Ū	2000
		From:				Sout	h Main St									
591) West Entrance Rd	0.22	3000	G	98%	1%	1%	0%	0%	0%	С	0.118	F		3200	G	2009
		To					ester St									
591) West Entrance Rd	0.15	1600	G	98%	1%	0%	0%	0%	0%	С	0.133	F	0.577	1700	G	2009
331)		To:	Ē				Blackstone									
	,	From:	-				Blackston									
592) Courthouse Rd	0.83	510	G	99%	1%	0%	0%	0%	0%	С	0.125	F	0.514	540	G	2009
		To				Notte	oway Ave									
		From:				Cour	thouse Rd									
(592) Nottoway Ave	0.07	1700	G	98%	1%	0%	0%	0%	0%	С	0.102	F	0.671	1800	G	2009

6/12/2010 8

### Virginia Department of Transportation Traffic Engineering Division 2009 Annual Average Daily Traffic Volume Estimates By Section of Route Town of Blackstone

		445=		4.7.	_		Tru	ıck		- 00	K	014	Dir	A A)A/DT	0)4/	.,
Route	Length	AADI	QA	4Tire	Bus	2Axle	3+Axle	1Trail	2Trail	QC	Factor	QK	Factor	AAWDT	QW	Year
Town of Blackstone			-													
		From				F	ort Ave									
(592) Nottoway Ave	0.22	1800	G	98%	1%	0%	1%	0%	0%	С	0.101	F		1900	G	2009
		To From				В	rown St									
(592) Elm St	0.09	740	G	98%	1%	0%	1%	0%	0%	F	0.128	F	0.584	790	G	2009
		To				Bu	s US 460									
		From				Nott	oway Ave									
(1584) North West Ave	1.82	2900	G	94%	1%	1%	2%	3%	0%	С	0.094	F	0.551	3100	G	2009
		To		SCL Blackstone												
		From				Lune	nburg Ave									
8th St		440	G	97%	2%	1%	0%	0%	0%	С	0.124	F		440	G	2009
		To				SR 4	10 Main St									
		From				Cour	thhouse Rd									
Bird St		100	G								0.167	F	0.714	100	G	2009
		To				Tho	mas Lane									
-		From				West	Entrance R	d			Ī					
Lester St		450	G								0.146	F	0.557	450	G	2009
		To				Bir	ch Street									
		From					4th St				1					
Lunenburg Avenue		1000	G	99%	0%	1%	0%	0%	0%	С	0.108	F	0.518	1000	G	2009
		To				BUS US	460 Churc	h St								

6/12/2010 9