2010

Virginia Department of Transportation Daily Traffic Volume Estimates Including Vehicle Classification Estimates

where available

Special Locality Report 301

Town of South Hill

Information in this report is included in Report

58

(Mecklenburg County)

Prepared By

Virginia Department of Transportation Traffic Engineering Division

In Cooperation With

U.S. Department of Transportation Federal Highway Administration

Virginia Department of Transportation Traffic Engineering Division Traffic Monitoring Section

The Virginia Department of Transportation (VDOT) conducts a program where traffic count data are gathered from sensors in or along streets and highways and other sources. From these data, estimates of the average number of vehicles that traveled each segment of road are calculated. VDOT periodically publishes booklets listing these estimates.

One of these booklets, titled "Average Daily Traffic Volumes with Vehicle Classification Data, on Interstate, Arterial and Primary Routes" includes a list of each Interstate and Primary highway segment with the estimated Annual Average Daily Traffic (AADT) for that segment. AADT is the total annual traffic estimate divided by the number of days in the year. This booklet also includes information such as estimates of the percentage of the AADT made up by 6 different vehicle types, ranging from cars to double trailer trucks; estimated Annual Average Weekday Traffic (AAWDT), which is the number of vehicles estimated to have traveled the segment of highway during a 24 hour weekday averaged over the year; as well as Peak Hour and Peak Direction factors used by planners to formulate design criteria.

In addition to the Primary and Interstate publication, one hundred books are published periodically, one for each of 100 areas across the state defined by VDOT for record-keeping purposes. These books include traffic volume estimates for roads within the county, cities, and towns within the area. These books are titled "Daily Traffic Volumes Including Vehicle Classification Estimates, where available; Jurisdiction Report numbers 00 through 99".

Also available are a number of reports summarizing the average Vehicle Miles Traveled (VMT) in selected jurisdictions and other categories of highways. There are many different ways to present traffic volume summary information. Because the user determines the value of each presentation, the reports have been redesigned based on user requests and feedback. The people of the VDOT Traffic Engineering Division Traffic Monitoring Section who produce these books welcome requests for other helpful ways of presenting the summary information.

A compact disc (CD) is available that includes files in the Adobe® Portable Document Format (PDF) that can be displayed, searched, and printed using common desktop computer equipment. The CD includes the publications described above as well as a number of other reports, including specialized VMT summaries and smaller AADT reports for each city and town separately.

Publication Notes

Parallel Roads

For road inventory and management purposes, some roadways are counted separately by direction and have separately published traffic estimates for each direction of travel. Examples of such roadways are the interstate system and routes with separated facilities and (usually) one-way traffic facilities in urban areas. In these publications, they are referred to as parallel roads. As a convenience for the users of the publication, the listing for segments of roads with parallel segments are published with both the traffic estimates for their own direction of travel (e.g. I-95 Northbound) as well as the estimate of the total of all traffic on the same route including parallel roadways (all directions of I-95). The publication will have a "Combined Traffic Estimates for Parallel Roadways on this Route" or "Combined Traffic" identifiers for the combined direction of travel estimates.

Roadways such as I-395 with a North segment, a South segment and a separate Reversible lane segment will have the estimate for more than two parallel roadways included in the entire combined traffic estimate.

Some routes have very complicated paths through cities and towns. These parallel paths may be too complex to allow a relationship between nearby sections of the opposite direction on the same route. In this case, to indicate that the traffic estimates for such a road segment may not include all directions of traffic on that route, the line that would list the combined values will indicate "NA" for not available.

VDOT's traffic monitoring program includes more than 100,000 segments of roads and highways ranging from several mile sections of Interstate highways to very short sections of city streets. Due to problems experienced obtaining some traffic count data, and the level of quality necessary to maintain confidence in the data, no estimate is currently available for some segments of roadway. These segments are included in the publications indicating "NA" for not available. It is the intention of the VDOT Traffic Engineering Division Traffic Monitoring group to obtain the data necessary and to report traffic volume estimates on all road segments included in these publications.

Many of the road segments in this program are local secondary roads. The amount and detail of data collected on these roads are not as great as the data collected on higher volume roads. The vehicle classification, average weekday traffic volumes, and the theoretical design hour traffic volumes are not calculated for these roads. The publications indicate "NA" for the information that is not available.

This publication is based on a traffic monitoring program initiated in 1997. Because the data collection techniques and statistical evaluation processes are different than those used in previous years, comparison with previous publications may be misleading.

Glossary of Terms:

Route: The Route Number assigned to this segment of roadway with the master inventory route number if this is an overlapping route, with official street or highway name if available.

Length: Length of the traffic segment in miles.

AADT: Annual Average Daily Traffic. The estimate of typical daily traffic on a road segment for all days of the week, Sunday through Saturday, over the period of one year.

QA: Quality of AADT:

- A Average of Complete Continuous Count Data
- B Average of Selected Continuous Count Data
- F Factored Short Term Traffic Count Data
- G Factored Short Term Traffic Count Data with Growth Element
- H Historical Estimate
- M Manual Uncounted Estimate
- N AADT of Similar Neighboring Traffic Link
- O Provided By External Source
- R Raw Traffic Count, Unfactored

4Tire: Percentage of the traffic volume made up of motorcycles, passenger cars, vans and pickup trucks.

Bus: Percentage of the traffic volume made up of busses.

2Axle Truck: Percentage of the traffic volume made up of 2 axle single unit trucks (not including pickups and vans).

3+Axle Truck: Percentage of the traffic volume made up of single unit trucks with three or more axles.

1Trail Truck: Percentage of the traffic volume made up of units with a single trailer.

2Trail Truck: Percentage of the traffic volume made up of units with more than one trailer.

QC: Quality of Classification Data:

- A Average of Complete Continuous Count Data
- B Average of Selected Continuous Count Data
- C Short Term Classified Traffic Count Data
- F Factored Short Term Traffic Count Data
- H Historical Estimate
- M Mass Collective Average
- N Classification Estimates of Similar Neighboring Traffic Link

K Factor: The estimate of the portion of the traffic volume traveling during the peak hour or design hour.

QK: Quality of the K Factor estimate:

- A Factor based on 30th Highest Hour Observed During at least 250 days of Continuous Traffic Data
- B Factor based on other Hour Observed During Less than 250 days of Continuous Traffic Data
- F Factor based on Highest Hour Collected at in a 48 Hour Weekday Period
- M Factor based on Manual Estimate of design hour
- N Design Hour Factor (K Factor) of Similar Neighboring Traffic Link
- O Provided by External Source

Dir Factor: The estimate of the portion of the traffic volume traveling in the peak direction during the peak hour..

AAWDT: Average Annual Weekday Traffic. The estimate of typical traffic over the period of one year for the days between Monday through Thursday inclusive.

QW: Quality of AAWDT:

- A Average of Complete Continuous Count Data
- B Average of Selected Continuous Count Data
- F Factored Short Term Traffic Count Data
- G Factored Short Term Traffic Count Data with Growth Element
- M Manual Uncounted Estimate
- N AAWDT of Similar Neighboring Traffic Link
- O Provided by External Source

Year: Year for which the published values are appropriate. If the Quality of AADT (QA) is "R", the year is the year that the raw traffic count was collected, and if available,

Route Shield Legend

Route Systems

North 81	Interstate Route	Traffic volume data for Interstate Routes and some other routes are reported separately by direction, as well as combined.
29	US Route	
7	Virginia State Rou	te
(F241)	Frontage Road (F	precedes frontage route number)
(600)	Secondary Route	

Special Routes

Bus	Bus - Business Route	
{29}	Bypas - Bypass Route	
	Truck - Truck Route	
ALT	ALT - Alternate Route	
(220)	Wye - Wye Route connector	

- P Parallel Route; Southbound or Westbound direction lanes of a numbered route where they are on a different road facility than the other direction.
- The VDOT Maintainenance Jurisdiction number is displayed below the Secondary Route Number if the Maintenance Jurisdiction is different than the jurisdiction in the title of the report.

		Town of So	utirriiii				Tru	ıok			K		Dir		
Route	Jurisdiction	Length AAD	Γ QA	4Tire	Bus					QC	Factor	QK		AAWDT	QW
Due	From:	SCL South	11:11			ZAXIE	3+Axle	IIIali	ZITali		Factor		Factor		
Bus (1) (58) Danville St	Town of South Hill	1.89 5100		96%	0%	1%	1%	2%	0%	С	0.096	F	0.616	5400	F
1 58 Danville St	Town or South Till			30 /0	070	1 70	1 /0	2/0	070	C	0.030	•	0.010	3400	'
Bus	To: From:	Locust	St												
1 58 Danville St	Town of South Hill	0.28 7200	F	96%	0%	1%	1%	2%	0%	F	0.094	F	0.500	7700	F
\bigcirc	To:	Plank R	d												
Bus Bus Ct	From:			000/	40/	40/	40/	40/	00/	_	0.000	_	0.500	0.400	_
1 (58) Danville St	Town of South Hill	0.09 7900	F	96%	1%	1%	1%	1%	0%	С	0.089	F	0.502	8400	F
Bus	To: From:	Goodes Ferr	y Blvd												
1 58 Danville St	Town of South Hill	0.23 7300	F	95%	1%	2%	1%	1%	0%	С	0.092	F	0.508	7800	F
(1) (30)	To	Mecklenbur													
Bus	From:	Danville	St												
1 (58) Mecklenburg Ave	Town of South Hill	0.16 8300	F	96%	1%	1%	1%	2%	0%	С	0.091	F	0.5	8800	F
\bigcirc	To: From:	US 58 BUS; SR 4	7 Atlantic S	St											
1 Mecklenburg Ave	Town of South Hill	0.08 7000	F	96%	1%	1%	0%	2%	0%	С	0.1	F	0.547	7500	F
	75.	Windsor	St.												
1 Mecklenburg Ave	Town of South Hill	0.58 9100		97%	1%	1%	0%	1%	0%	С	0.092	F	0.521	9700	F
1) months in series				0.70	.,,		0,0	.,0	0,0	Ū	0.002	•	0.02	0.00	•
Marilla da	From:	E Ferrell		070/	007		00/	40/	00/		0.004	_	0.547	0500	
1 Mecklenburg Ave	Town of South Hill	2.26 6100		97%	0%	1%	0%	1%	0%	С	0.094	F	0.517	6500	F
		NCL South													
MA Atlantin Ot	From:	Mecklenbur		000/	40/	40/	40/	407	00/	_	0.000	_	0.540	0700	_
47) W Atlantic St	Town of South Hill	0.63 6500	F	93%	1%	1%	1%	4%	0%	С	0.090	F	0.540	6700	F
	To: From:	Thomas													
(47) W Atlantic St	Town of South Hill	0.23 5400	F	96%	0%	1%	1%	3%	0%	С	0.094	F	0.605	5600	F
<u> </u>	To- From:	Opie R	d												
47) W Atlantic St	Town of South Hill	0.39 6100	F	93%	1%	1%	1%	4%	0%	С	0.095	F	0.622	6200	F
	To:	WCL South	n Hill												
	From:	SCL South Hill; I	Maple Lane	e											
(58)	Town of South Hill (Maint: 58)	0.69 6400	F	80%	1%	1%	2%	16%	0%	С	0.085	F	0.619	6200	F
	To:	BUS US 58; Co	intry I and												
58 E Atlantic St	Town of South Hill (Maint: 58)	0.24 2100		83%	1%	1%	1%	14%	1%	F	0.084	F	0.559	21000	F
(38) 2 / tildrillo 31	To:	ECL South H		0070	170		170	1170	170	•	0.001	•	0.000	21000	•
Due	From:	SCL South													
Bus (58) (1) Danville St	Town of South Hill	1.89 5100		96%	0%	1%	1%	2%	0%	С	0.096	F	0.616	5400	F
(36) (1) 54.77	. Swit of Goddinin			0070	370	1 /3	. 70	-/0	J / 0	J	0.000	•	0.010	O-100	•
Bus	From:	Locust	St												
58 1 Danville St	Town of South Hill	0.28 7200	F	96%	0%	1%	1%	2%	0%	F	0.094	F	0.500	7700	F
$\overline{}$	Tax	Plank R	d												
Bus	From:									_		_			_
(58) (1) Danville St	Town of South Hill	0.09 7900		96%	1%	1%	1%	1%	0%	С	0.089	F	0.502	8400	F
~ ~	To:	Goodes Ferr	y Blvd												

	·						Tru	ıck			K		Dir		
Jurisdiction	n Length	AADT	QA	4Tire	Bus	2Axle	3+Axle	1Trail	2Trail	QC	Factor	QK	Factor	AAWDT	QW
From:															
Town of South		7300	F	95%	1%	2%	1%	1%	0%	С	0.092	F	0.508	7800	F
To:															
Town of South				060/	10/	10/	10/	20/	00/	C	0.001	_	0.5	9900	F
Town of South				90%	170	176	1 70	270	0%	C	0.091	Г	0.5	0000	Г
From:		US 1; SR 47													
Town of South	h Hill 0.48	9700	F	97%	0%	1%	0%	2%	0%	С	0.083	F	0.571	10000	F
To		Windsor St													
Town of South				070/	00/	10/	00/	10/	00/	C	0.006	_	0.51	12000	F
Town of South				97%	0%	1%	0%	170	0%	C	0.086	Г	0.51	13000	Г
Franci						L									
L.	S			70%	10/_	19/-	0%	17%	20/-	F	O 138	Δ		10000	Α
	,														A
Combined Trainic Estimates for 2 Farane	i Roduways of this Route.			1970	1 /0	1 /0	0 /6	17 /0	2/0	-	INA			21000	^
From:		US 58													
Town of South Hill ((Maint: 58) 2.53	11000	Α	79%	1%	1%	0%	17%	2%	F	0.136	Α		9400	Α
Combined Traffic Estimates for 2 Paralle	el Roadways on this Route:	21000	Α	79%	1%	1%	0%	17%	2%	F	0.129	Α	0.543	19000	Α
To:		US 1													
Town of South Hill /	(Maint: 59) 0.53	11000		70%	10/	10/	Ω9/	170/	20/	_	0 127	٨		9000	_
	,		-									А			F
Combined Trainic Estimates for 2 Paralle				79%	1%	1%	0%	17%	2%	Г	INA			18000	Г
From						1									
Town of South Hill (79%	1%	1%	0%	18%	2%	F	0 129	Δ		11000	Α
										F		,,			Α
- I	Trodaways of this route.			1370	1 /0		070	17 70	270	'	INA			21000	
From:		US 58													
Town of South Hill ((Maint: 58) 2.72	11000	Α	79%	1%	1%	0%	18%	2%	F	0.127	Α		9100	Α
Combined Traffic Estimates for 2 Paralle	el Roadways on this Route:	21000	Α	79%	1%	1%	0%	17%	2%	F	0.129	Α	0.543	19000	Α
To: France		US 1				$=$ \vdash									
Town of South Hill ((Maint: 58) 0.20	11000	F	70%	10/	19/	0%	180/	2%	E	0.126	Δ		0100	F
`	,									F		^			F
To:				1970	170	1 70	U70	1770	∠70	Г	INA			10000	Г
From:															
11011.			_												
Town of South	th Hill 0.38	3300	F	91%	1%	3%	1%	5%	0%	C.	0.093	F	0.617	3400	F
	Town of South Hill Combined Traffic Estimates for 2 Paralle Town of South Hill Combined Traffic Estimates for 2 Paralle Town of South Hill Combined Traffic Estimates for 2 Paralle Town of South Hill Combined Traffic Estimates for 2 Paralle Town of South Hill Combined Traffic Estimates for 2 Paralle Town of South Hill Combined Traffic Estimates for 2 Paralle Town of South Hill Combined Traffic Estimates for 2 Paralle Town of South Hill Combined Traffic Estimates for 2 Paralle Town of South Hill Combined Traffic Estimates for 2 Paralle Town of South Hill Combined Traffic Estimates for 2 Paralle Town of South Hill Combined Traffic Estimates for 2 Paralle Town of South Hill Combined Traffic Estimates for 2 Paralle	Town of South Hill	Town of South Hill	Town of South Hill 0.23 7300 F	Prome	Town of South Hill 0.23 7300 F 95% 1%	April	Length AADT QA 4Tire Bus 2Axle 3+Axle 3+A	Second S	Trial Goods Ferry Blot Frail Goods Ferry Blot Ferry Blot Frail Goods Ferry Blot Frail Goods Ferry Blot Frail Goods Ferry Blot Frail Goods Ferry Blot Ferry Blot Frail Goods Ferry Blot Frail Goods Ferry Blot Ferry Blot Frail Goods Ferry Blot Ferry	Combined Traffic Estimates for 2 Parallel Roadways on this Route State Sta	Second Combined Traffic Estimates for 2 Parallel Roadways on this Route: 25000 F 27900 F	Combined Traffic Estimates for 2 Parallel Roadways on this Route: 21000 R. 2Axid 31Axid 1Trail 2Trail Combined Traffic Estimates for 2 Parallel Roadways on this Route: 21000 R. 2Axid 3Axid 1Trail 2Trail Combined Traffic Estimates for 2 Parallel Roadways on this Route: 21000 R. 79% 1% 1% 2% 1% 1% 0% 0% 0% 0% 0% 0	Second S	March Marc

Route	Length	AADT	QA	4Tire	Bus				QC	K Factor	QK	Dir Factor	AAWDT	QW	Year
Town of South Hill		From	ŧ			Mai	n St			1					
1 Brunswick Ave	0.13	790	F							0.126	F	0.685	810	F	2010
		To	-			SR 47 A	lantic St								
		From													
(2) Charles St	0.28			98%	0%			0%	С	0.124	F	0.556	200	F	2010
			<u> </u>												
Danville St	0.21		<u> </u>	000/	10/			00/		0.126	_	0.570	1600	_	2010
3 Danville St	Carrier Carr					2010									
		From	:												
4 Dortch Lane	0.18	1400	F	99%	1%			0%	С	0.116	F	0.521	1500	F	2010
•															
		From	:			Danvi	lle St								
7 Lunenburg Ave	0.16	1000	F	98%	0%	1%	1% 0%	0%	С	0.099	F	0.532	1100	F	2010
		То	:			Atlan	tic St								
					_						_				
8 Main St	0.45	960	_F	98%	1%	1%	υ% 0%	0%	C	0.109	F	0.661	980	F	2010
<u> </u>										\exists	_				
8 Main St	0.69	3100	F	99%	0%			0%	С	0.1	F	0.548	3200	F	2010
		10	<u> </u>												
Monlo St	0.07			000/	00/			00/		0.005	_	0.527	2000	E	2010
9 Maple St	0.07			90%	0%			0%		0.095	Г	0.527	3000	Г	2010
		From	: :I							<u> </u>					
10) Pace Dr	0.51			98%	0%			0%	С	0.107	F	0.658	1000	F	2010
10) . 400 2.	0.01			0070	0,0			0,0			•	0.000		-	_0.0
	0.13 790 F														
11) Raleigh Ave	0.65	1000	F	98%	1%			0%	С	0.113	F	0.579	1100	F	2010
		То	-			Hig	h St			<u> </u>					
11) Raleigh Ave	0.86		F	99%	0%			0%	С	0.134	F	0.507	540	F	2010
		To				Charl	es St								
11) Raleigh Ave	0.04	290 From	F	99%	0%			0%	F	0.153	F	0.5	300	F	2010
		То	:			Forest	Lane								
		From				Plan	k Rd								
12) Thomas St	0.15			97%	1%			0%	С	0.119	F	0.621	1800	F	2010
<u> </u>		To				Atlan	tic St								
O 14/1 - 0											_			_	
13) Windsor St	0.49			99%	0%			0%	C	0.087	F	0.782	2700	F	2010
	0.85					US	58			NΙΔ			NΔ		
14)	0.00		:			301-8 N	Main St						INA		
		From								i					
15) Field Dr	0.09	340	G	98%	1%			0%	С	NA			370	G	2010
		To	:			Pace	e Dr								
		From	:			South F	Iill Ave								
16) Goods Ferry Rd	0.59	1200	G	97%	1%	1%	0% 1%	0%	С	NA			1300	G	2010
\smile		То				Danvi	lle St								
523) Goodes Ferry Blvd	0.42			97%	1%			0%	С	0.099	F	0.593	1400	F	2010
<u> </u>			:												
Courte Lill Ave	0.31	1000	F	98%	1%		0% 0%	0%	С	0.116	F	0.543	1000	F	2010
523) South Alli Ave									_						
523) South Hill Ave						T-1	4 C4								
523) South Hill Ave	0.22	From 1200	F	98%	1%	Firs	t St 0% 0%	0%	С	0.107	F	0.508	1200	F	2010

D(-	Leceth	AADT		47	D		Tru	ck		QC	K	014	Dir	A A \ A \ A \ D T	0)4/	V
Route	Length	AADI	QA	4Tire	Bus	2Axle	3+Axle	1Trail	2Trail	QC	Factor	QK	Factor	AAWDT	QW	Year
own of South Hill		From				Moole	lambuma Ari				-1					
529) Chaptico Rd	0.46	1900	F	98%	0%	1%	lenburg Ave 0%	1%	0%	F	0.095	F	0.589	1900	F	2010
529 Chaptico Ru	0.40	1900 To		90 /0	0 /0		Vista Circl		076	-	0.093		0.569	1900		2010
		From					a Vista Cir				-					
529) Chaptico Rd	0.59	1100	F	98%	0%	1%	0%	1%	0%	С	0.097	F	0.637	1200	F	2010
029)		To				NCL	South Hill									
		From				D:	nville St									
Plank Rd	0.38	1600	F	98%	0%	1%	0%	0%	0%	С	0.100	F	0.535	1700	F	2010
319) 1 10 1 10	0.00	То		0070	0,0		Opie St	0,0	0,0			•	0.000		•	2010
_		From					lank Rd									
Opie Rd	0.26	2600	F	96%	1%	1%	1%	1%	0%	С	0.095	F	0.613	2700	F	2010
		To				At	lantic St									
		From				Bus US	58 Atlantic	St								
520) McCraken St	0.19	4400	F	99%	0%	1%	0%	0%	0%	С	0.091	F	0.572	4500	F	2010
329		To				-	11: 0:				_					
Lombardy St	0.61	4100 From	F	99%	0%	0%	anklin St 0%	0%	0%	С	0.092	F	0.576	4200	F	2010
520 Lombardy St	0.01	4100 To	Ė	33 /0	0 70		Ferrell St	070	070		0.032	'	0.570	4200 1	•	2010
		From					nbardy St				+					
E Ferrell St	0.32	3900	F	99%	0%	1%	0%	0%	0%	С	0.093	F	0.574	4000	F	2010
320)		To					lenburg Av									
		From					en Hill Rd				i					
Forest Ln		610	F			GIC	ZII TIIII KQ				0.126	F	0.526	660	F	2010
. 5.551 =		To				Sto	ockley St					•	0.020	000	•	_0.0
		From					•									
High St		290	F			Ka	eigh Ave				0.135	F	0.705	310	F	2010
riigir St		290 To				р	aker St				0.133		0.703	310		2010
Halasaa Ot		From	ᆫ			Lor	nbardy St					_	0.500	400	_	0011
Holmes St		180	F								0.113	F	0.522	190	F	2010
		To	<u> </u>			В	enton St									
		From				US	58 Bypass									
Maple Lane		NA									NA			NA		
		To				N	Iain St									