2010

Virginia Department of Transportation Daily Traffic Volume Estimates Including Vehicle Classification Estimates

where available

Special Locality Report 169

Town of Bloxom

Information in this report is included in Report

01

(Accomack County)

Prepared By

Virginia Department of Transportation Traffic Engineering Division

In Cooperation With

U.S. Department of Transportation Federal Highway Administration

Virginia Department of Transportation Traffic Engineering Division Traffic Monitoring Section

The Virginia Department of Transportation (VDOT) conducts a program where traffic count data are gathered from sensors in or along streets and highways and other sources. From these data, estimates of the average number of vehicles that traveled each segment of road are calculated. VDOT periodically publishes booklets listing these estimates.

One of these booklets, titled "Average Daily Traffic Volumes with Vehicle Classification Data, on Interstate, Arterial and Primary Routes" includes a list of each Interstate and Primary highway segment with the estimated Annual Average Daily Traffic (AADT) for that segment. AADT is the total annual traffic estimate divided by the number of days in the year. This booklet also includes information such as estimates of the percentage of the AADT made up by 6 different vehicle types, ranging from cars to double trailer trucks; estimated Annual Average Weekday Traffic (AAWDT), which is the number of vehicles estimated to have traveled the segment of highway during a 24 hour weekday averaged over the year; as well as Peak Hour and Peak Direction factors used by planners to formulate design criteria.

In addition to the Primary and Interstate publication, one hundred books are published periodically, one for each of 100 areas across the state defined by VDOT for record-keeping purposes. These books include traffic volume estimates for roads within the county, cities, and towns within the area. These books are titled "Daily Traffic Volumes Including Vehicle Classification Estimates, where available; Jurisdiction Report numbers 00 through 99".

Also available are a number of reports summarizing the average Vehicle Miles Traveled (VMT) in selected jurisdictions and other categories of highways. There are many different ways to present traffic volume summary information. Because the user determines the value of each presentation, the reports have been redesigned based on user requests and feedback. The people of the VDOT Traffic Engineering Division Traffic Monitoring Section who produce these books welcome requests for other helpful ways of presenting the summary information.

A compact disc (CD) is available that includes files in the Adobe® Portable Document Format (PDF) that can be displayed, searched, and printed using common desktop computer equipment. The CD includes the publications described above as well as a number of other reports, including specialized VMT summaries and smaller AADT reports for each city and town separately.

Publication Notes

Parallel Roads

For road inventory and management purposes, some roadways are counted separately by direction and have separately published traffic estimates for each direction of travel. Examples of such roadways are the interstate system and routes with separated facilities and (usually) one-way traffic facilities in urban areas. In these publications, they are referred to as parallel roads. As a convenience for the users of the publication, the listing for segments of roads with parallel segments are published with both the traffic estimates for their own direction of travel (e.g. I-95 Northbound) as well as the estimate of the total of all traffic on the same route including parallel roadways (all directions of I-95). The publication will have a "Combined Traffic Estimates for Parallel Roadways on this Route" or "Combined Traffic" identifiers for the combined direction of travel estimates.

Roadways such as I-395 with a North segment, a South segment and a separate Reversible lane segment will have the estimate for more than two parallel roadways included in the entire combined traffic estimate.

Some routes have very complicated paths through cities and towns. These parallel paths may be too complex to allow a relationship between nearby sections of the opposite direction on the same route. In this case, to indicate that the traffic estimates for such a road segment may not include all directions of traffic on that route, the line that would list the combined values will indicate "NA" for not available.

VDOT's traffic monitoring program includes more than 100,000 segments of roads and highways ranging from several mile sections of Interstate highways to very short sections of city streets. Due to problems experienced obtaining some traffic count data, and the level of quality necessary to maintain confidence in the data, no estimate is currently available for some segments of roadway. These segments are included in the publications indicating "NA" for not available. It is the intention of the VDOT Traffic Engineering Division Traffic Monitoring group to obtain the data necessary and to report traffic volume estimates on all road segments included in these publications.

Many of the road segments in this program are local secondary roads. The amount and detail of data collected on these roads are not as great as the data collected on higher volume roads. The vehicle classification, average weekday traffic volumes, and the theoretical design hour traffic volumes are not calculated for these roads. The publications indicate "NA" for the information that is not available.

This publication is based on a traffic monitoring program initiated in 1997. Because the data collection techniques and statistical evaluation processes are different than those used in previous years, comparison with previous publications may be misleading.

Glossary of Terms:

Route: The Route Number assigned to this segment of roadway with the master inventory route number if this is an overlapping route, with official street or highway name if available.

Length: Length of the traffic segment in miles.

AADT: Annual Average Daily Traffic. The estimate of typical daily traffic on a road segment for all days of the week, Sunday through Saturday, over the period of one year.

QA: Quality of AADT:

- A Average of Complete Continuous Count Data
- B Average of Selected Continuous Count Data
- F Factored Short Term Traffic Count Data
- G Factored Short Term Traffic Count Data with Growth Element
- H Historical Estimate
- M Manual Uncounted Estimate
- N AADT of Similar Neighboring Traffic Link
- O Provided By External Source
- R Raw Traffic Count, Unfactored

4Tire: Percentage of the traffic volume made up of motorcycles, passenger cars, vans and pickup trucks.

Bus: Percentage of the traffic volume made up of busses.

2Axle Truck: Percentage of the traffic volume made up of 2 axle single unit trucks (not including pickups and vans).

3+Axle Truck: Percentage of the traffic volume made up of single unit trucks with three or more axles.

1Trail Truck: Percentage of the traffic volume made up of units with a single trailer.

2Trail Truck: Percentage of the traffic volume made up of units with more than one trailer.

QC: Quality of Classification Data:

- A Average of Complete Continuous Count Data
- B Average of Selected Continuous Count Data
- C Short Term Classified Traffic Count Data
- F Factored Short Term Traffic Count Data
- H Historical Estimate
- M Mass Collective Average
- N Classification Estimates of Similar Neighboring Traffic Link

K Factor: The estimate of the portion of the traffic volume traveling during the peak hour or design hour.

QK: Quality of the K Factor estimate:

- A Factor based on 30th Highest Hour Observed During at least 250 days of Continuous Traffic Data
- B Factor based on other Hour Observed During Less than 250 days of Continuous Traffic Data
- F Factor based on Highest Hour Collected at in a 48 Hour Weekday Period
- M Factor based on Manual Estimate of design hour
- N Design Hour Factor (K Factor) of Similar Neighboring Traffic Link
- O Provided by External Source

Dir Factor: The estimate of the portion of the traffic volume traveling in the peak direction during the peak hour..

AAWDT: Average Annual Weekday Traffic. The estimate of typical traffic over the period of one year for the days between Monday through Thursday inclusive.

QW: Quality of AAWDT:

- A Average of Complete Continuous Count Data
- B Average of Selected Continuous Count Data
- F Factored Short Term Traffic Count Data
- G Factored Short Term Traffic Count Data with Growth Element
- M Manual Uncounted Estimate
- N AAWDT of Similar Neighboring Traffic Link
- O Provided by External Source

Year: Year for which the published values are appropriate. If the Quality of AADT (QA) is "R", the year is the year that the raw traffic count was collected, and if available,

Route Shield Legend

Route Systems

North 81	Interstate Route	Traffic volume data for Interstate Routes and some other routes are reported separately by direction, as well as combined.
29	US Route	
7	Virginia State Rou	te
(F241)	Frontage Road (F	precedes frontage route number)
(600)	Secondary Route	

Special Routes

Bus	Bus - Business Route
29 }	Bypas - Bypass Route
	Truck - Truck Route
ALT	ALT - Alternate Route
(220)	Wye - Wye Route connector

- P Parallel Route; Southbound or Westbound direction lanes of a numbered route where they are on a different road facility than the other direction.
- The VDOT Maintainenance Jurisdiction number is displayed below the Secondary Route Number if the Maintenance Jurisdiction is different than the jurisdiction in the title of the report.

Virginia Department of Transportation Traffic Engineering Division 2010 Annual Average Daily Traffic Volume Estimates By Section of Route Town of Bloxom

Route	Jurisdiction	Length	AADT	QA	4Tire	Bus		Tru 3+Axle			QC	K Factor	QK	Dir Factor	AAWDT	QW
	From:	V	VCL Bloxo	m												
(187) Shoremain Dr	Town of Bloxom (Maint: 01)	0.45	510	N	97%	0%	1%	1%	1%	0%	N	0.108	Ν	0.615	550	Ν
	To: From:	SR 316 Bayside Dr														
(187) Shoremain Dr	Town of Bloxom (Maint: 01)	0.59	1600	G	97%	0%	1%	1%	1%	0%	F	0.107	F	0.559	1700	G
$\underline{\smile}$	To:	I	ECL Bloxor	n												
	From:	9	SCL Bloxon	n												
(316) Bayside Dr	Town of Bloxom (Maint: 01)	0.39	3000	N	97%	1%	1%	0%	1%	0%	Ν	0.092	Ν		3200	N
	To:	SR 1	87 Shorema	in Dr												

7/1/2011 7

Virginia Department of Transportation Traffic Engineering Division 2010 Annual Average Daily Traffic Volume Estimates By Section of Route Town of Bloxom

							I OI BIOXOI									
Route	Length	AADT	QA	4Tire	Bus		Tru 3+Axle			QC	K Factor	QK	Dir Factor	AAWDT	QW	Year
Town of Bloxom																
(681) Mason Rd	0.17	350	R			SR 187	Shoremain	Dr			 NA			NA		07/26/2005
(681) Mason Rd	0.17	330				an ai								INA		07/20/2000
(681) Mason Rd	0.02	300 From	R			SR 31	6 Hopeton R	ld			NA			NA		07/26/2005
(681) Mason Rd	0.02	To				SC	L Bloxom							14/ (0172072000
		From				NO	CL Bloxom									
684 Guards Shore Rd	0.07	360	N								NA			NA		07/26/2005
01)		To				01-779 N	Mears Station	ı Rd								
684) Mitchell Rd	0.32	630	R								NA			NA		07/12/200
UI)		To				01-687 E	Bethel Church	h Rd								
\bigcirc		From				SR 187	Shoremain :	Dr								
687 Bethel Church Rd	0.02	1200	R								NA			NA		07/12/200
0		To From				01-68	4 Mitchell R	.d			\Box					
687 Bethel Church Rd	0.20	270	R								NA			NA		07/12/200
		To					CL Bloxom									
O 14 00 00 00	2.00	From	<u> </u>	200/	201		187; SR 316		201			_	0.500	4500	_	0010
Mears Station Rd	0.39	1400 _{To}	G	96%	0%	1%	2% CL Bloxom	1%	0%	F	0.098	F	0.532	1500	G	2010
		From						D.:								
2501) Back St	0.32	210	R			SK 187	Shoremain	Dr			NA			NA		08/02/2005
(2501) Back St	0.02	To				01-684 (Guards Shore	e Rd			iii			10.		00/02/2000
		From					7 Shoremain				i					
(2502) Hinman St	0.08	80	R								NA			NA		08/02/2005
(2502) Hinman St		To				01-25	506 Liberty S	it.								
(2502) Hinman St	0.07	80	R			01-25	00 Liberty 5	1			NA			NA		08/02/2005
(2502) Hinman St		To				01.2	504 Hearn St									
(2502) Hinman St	0.07	60 From	R			01-2	304 Heath 31				NA			NA		08/02/2005
(2502) Hinman St		To				01-68	4 Mitchell R	.d								
		From				SR 187	7 Shoremain	Dr								
(2503) Marshall St	0.06	60	R								NA			NA		08/02/2005
01)		To				01-2	513 Pruitt St									
(2503) Marshall St	0.09	180 From	R								NA			NA		08/02/2005
01)		To				SR 31	16 Bayside D	r								
		From				SR 187	Shoremain	Dr								
(2504) Hearn St	0.11	60	R								NA			NA		08/09/2005
		To				01-25	02 Hinman S	St								
O B + 0:	0.40	From				I	Dead End									00/00/000
2505 Parks St	0.10	80	R								NA			NA		08/09/2005
<u> </u>		From					01-2508									
2505 Parks St	0.15	90	R			CD 107	7 Cl	D.			NA			NA		08/09/2005
							Shoremain									
(2506) Liberty St	0.08	40	R			01-25	02 Hinman S	St			 NA			NA		08/09/2005
(2506) Liberty St	0.00	To				SR 187	7 Shoremain	Dr						INA		00/03/2000
		From					01-2508									
2507) Bull St	0.15	170	R				01-2300				NA			NA		08/09/2005
(2507) Bull St		To				SR 187	Shoremain 3	Dr								
		From				I	Dead End						·			
2508	0.02	60	R								NA			NA		08/09/2005
UI)		To From				01-2	2507 Bull St				¬—					
2508	0.04	60 From	R								NA			NA		08/09/2005
UI		To				01-2	505 Parks St									
		From				Ι	Dead End									
(2509) Hall St	0.25	20	R		_	_			_		NA			NA		08/09/2005
		To				SR 187	Shoremain 3	Dr								

7/1/2011 8

Virginia Department of Transportation Traffic Engineering Division 2010 Annual Average Daily Traffic Volume Estimates By Section of Route Town of Bloxom

					TOWN OF BIONOTH								
Length	AADT	QA	4Tire	Bus			QC	K Factor	QK	Dir Factor	AAWDT	QW	Year
		_				2				. 4010.			
					SR 187 Shoremain Dr								
0.12	70	R						NA_			NA		08/09/2005
	Т).			01-2511 Circle Dr								
	From	1:			01-2510 Circle Dr								
0.07	30	R						NA			NA		08/09/2005
	T):			01-2512 Circle Dr								
	Fron	1:			SR 187 Shoremain Dr								
0.06	20	R						NA			NA		08/09/2005
	Fron	2			01-2513 Pruitt St								
0.06	30	R						NA			NA		08/09/2005
	T):			01-2511 Circle Dr								
	Fron	1:			01-2512 Circle Dr								
0.07	20	R						NA			NA		08/09/2005
	Т	·-			01-2503 Marshall St								
	From	r			01-684 Mitchell Rd								
0.06	220	R						NA			NA		1986
	T):			Bloxom High School								
	0.12 0.07 0.06 0.06	0.12 70 Tr Pron 0.07 30 Tr Pron 0.06 20 0.06 30 Tr Pron 0.07 20 Tr Fron 0.07 20 0.06 220	0.12 70 R Tro Prom	0.12 70 R Try From:	0.12 70 R Tro From: 0.07 30 R To From: 0.06 20 R 0.06 30 R To From: 0.07 20 R Tro From: 0.07 20 R Tro From: 0.08 R	Length AADT QA 4Tire Bus 2Axle 3+Axle 1Trail	Length AADT QA 4Tire Bus 2Axle 3+Axle 1Trail 2Trail	Length AADT QA 4Tire Bus 2Axle 3+Axle 1Trail 2Trail QC	Length AADT QA 4Tire Bus SR 187 Shoremain Dr	Length AADT QA 4Tire Bus	Length AADT QA 4Tire Bus	Length AADT QA 4Tire Bus 2Axle 3+Axle 1Trail 2Trail QC Factor QK Factor AAWDT	Length AADT QA 4Tire Bus

7/1/2011 9