2008

Virginia Department of Transportation Daily Traffic Volume Estimates Including Vehicle Classification Estimates

where available

Special Locality Report 316

Town of Urbanna

Information in this report is included in Report

59

(Middlesex County)

Prepared By

Virginia Department of Transportation Traffic Engineering Division

In Cooperation With

U.S. Department of Transportation Federal Highway Administration

Virginia Department of Transportation Traffic Engineering Division Traffic Monitoring Section

The Virginia Department of Transportation (VDOT) conducts a program where traffic count data are gathered from sensors in or along streets and highways and other sources. From these data, estimates of the average number of vehicles that traveled each segment of road are calculated. VDOT periodically publishes booklets listing these estimates.

One of these booklets, titled "Average Daily Traffic Volumes with Vehicle Classification Data, on Interstate, Arterial and Primary Routes" includes a list of each Interstate and Primary highway segment with the estimated Annual Average Daily Traffic (AADT) for that segment. AADT is the total annual traffic estimate divided by the number of days in the year. This booklet also includes information such as estimates of the percentage of the AADT made up by 6 different vehicle types, ranging from cars to double trailer trucks; estimated Annual Average Weekday Traffic (AAWDT), which is the number of vehicles estimated to have traveled the segment of highway during a 24 hour weekday averaged over the year; as well as Peak Hour and Peak Direction factors used by planners to formulate design criteria.

In addition to the Primary and Interstate publication, one hundred books are published periodically, one for each of 100 areas across the state defined by VDOT for record-keeping purposes. These books include traffic volume estimates for roads within the county, cities, and towns within the area. These books are titled "Daily Traffic Volumes Including Vehicle Classification Estimates, where available; Jurisdiction Report numbers 00 through 99".

Also available are a number of reports summarizing the average Vehicle Miles Traveled (VMT) in selected jurisdictions and other categories of highways. There are many different ways to present traffic volume summary information. Because the user determines the value of each presentation, the reports have been redesigned based on user requests and feedback. The people of the VDOT Traffic Engineering Division Traffic Monitoring Section who produce these books welcome requests for other helpful ways of presenting the summary information.

A compact disc (CD) is available that includes files in the Adobe® Portable Document Format (PDF) that can be displayed, searched, and printed using common desktop computer equipment. The CD includes the publications described above as well as a number of other reports, including specialized VMT summaries and smaller AADT reports for each city and town separately.

Publication Notes

Parallel Roads

For road inventory and management purposes, some roadways are counted separately by direction and have separately published traffic estimates for each direction of travel. Examples of such roadways are the interstate system and routes with separated facilities and (usually) one-way traffic facilities in urban areas. In these publications, they are referred to as parallel roads. As a convenience for the users of the publication, the listing for segments of roads with parallel segments are published with both the traffic estimates for their own direction of travel (e.g. I-95 Northbound) as well as the estimate of the total of all traffic on the same route including parallel roadways (all directions of I-95). The publication will have a "Combined Traffic Estimates for Parallel Roadways on this Route" or "Combined Traffic" identifiers for the combined direction of travel estimates.

Roadways such as I-395 with a North segment, a South segment and a separate Reversible lane segment will have the estimate for more than two parallel roadways included in the entire combined traffic estimate.

Some routes have very complicated paths through cities and towns. These parallel paths may be too complex to allow a relationship between nearby sections of the opposite direction on the same route. In this case, to indicate that the traffic estimates for such a road segment may not include all directions of traffic on that route, the line that would list the combined values will indicate "NA" for not available.

VDOT's traffic monitoring program includes more than 100,000 segments of roads and highways ranging from several mile sections of Interstate highways to very short sections of city streets. Due to problems experienced obtaining some traffic count data, and the level of quality necessary to maintain confidence in the data, no estimate is currently available for some segments of roadway. These segments are included in the publications indicating "NA" for not available. It is the intention of the VDOT Traffic Engineering Division Traffic Monitoring group to obtain the data necessary and to report traffic volume estimates on all road segments included in these publications.

Many of the road segments in this program are local secondary roads. The amount and detail of data collected on these roads are not as great as the data collected on higher volume roads. The vehicle classification, average weekday traffic volumes, and the theoretical design hour traffic volumes are not calculated for these roads. The publications indicate "NA" for the information that is not available.

This publication is based on a traffic monitoring program initiated in 1997. Because the data collection techniques and statistical evaluation processes are different than those used in previous years, comparison with previous publications may be misleading.

Glossary of Terms:

Route: The Route Number assigned to this segment of roadway with the master inventory route number if this is an overlapping route, with official street or highway name if available.

Length: Length of the traffic segment in miles.

AADT: Annual Average Daily Traffic. The estimate of typical daily traffic on a road segment for all days of the week, Sunday through Saturday, over the period of one year.

QA: Quality of AADT:

- A Average of Complete Continuous Count Data
- B Average of Selected Continuous Count Data
- F Factored Short Term Traffic Count Data
- G Factored Short Term Traffic Count Data with Growth Element
- H Historical Estimate
- M Manual Uncounted Estimate
- N AADT of Similar Neighboring Traffic Link
- O Provided By External Source
- R Raw Traffic Count, Unfactored

4Tire: Percentage of the traffic volume made up of motorcycles, passenger cars, vans and pickup trucks.

Bus: Percentage of the traffic volume made up of busses.

2Axle Truck: Percentage of the traffic volume made up of 2 axle single unit trucks (not including pickups and vans).

3+Axle Truck: Percentage of the traffic volume made up of single unit trucks with three or more axles.

1Trail Truck: Percentage of the traffic volume made up of units with a single trailer.

2Trail Truck: Percentage of the traffic volume made up of units with more than one trailer.

QC: Quality of Classification Data:

- A Average of Complete Continuous Count Data
- B Average of Selected Continuous Count Data
- C Short Term Classified Traffic Count Data
- F Factored Short Term Traffic Count Data
- H Historical Estimate
- M Mass Collective Average
- N Classification Estimates of Similar Neighboring Traffic Link

K Factor: The estimate of the portion of the traffic volume traveling during the peak hour or design hour.

QK: Quality of the K Factor estimate:

- A Factor based on 30th Highest Hour Observed During at least 250 days of Continuous Traffic Data
- B Factor based on other Hour Observed During Less than 250 days of Continuous Traffic Data
- F Factor based on Highest Hour Collected at in a 48 Hour Weekday Period
- M Factor based on Manual Estimate of design hour
- N Design Hour Factor (K Factor) of Similar Neighboring Traffic Link
- O Provided by External Source

Dir Factor: The estimate of the portion of the traffic volume traveling in the peak direction during the peak hour..

AAWDT: Average Annual Weekday Traffic. The estimate of typical traffic over the period of one year for the days between Monday through Thursday inclusive.

QW: Quality of AAWDT:

- A Average of Complete Continuous Count Data
- B Average of Selected Continuous Count Data
- F Factored Short Term Traffic Count Data
- G Factored Short Term Traffic Count Data with Growth Element
- M Manual Uncounted Estimate
- N AAWDT of Similar Neighboring Traffic Link
- O Provided by External Source

Year: Year for which the published values are appropriate. If the Quality of AADT (QA) is "R", the year is the year that the raw traffic count was collected, and if available,

Route Shield Legend

Route Systems

North 81	Interstate Route	Traffic volume data for Interstate Routes and some other routes are reported separately by direction, as well as combined.								
29	US Route									
7	Virginia State Rou	te								
(F241)	Frontage Road (F precedes frontage route number)									
(600)	Secondary Route									

Special Routes

Bus	Bus - Business Route
29	Bypas - Bypass Route
	Truck - Truck Route
ALT	ALT - Alternate Route
(220)	Wve - Wve Route connector

- P Parallel Route; Southbound or Westbound direction lanes of a numbered route where they are on a different road facility than the other direction.
- The VDOT Maintainenance Jurisdiction number is displayed below the Secondary Route Number if the Maintenance Jurisdiction is different than the jurisdiction in the title of the report.

Virginia Department of Transportation Traffic Engineering Division

2008 Annual Average Daily Traffic Volume Estimates By Section of Route Town of Urbanna

Route	Jurisdiction	Length	AADT	QA	4Tire	Bus		Tru 3+Axle			QC	K Factor	QK	Dir Factor	AAWDT	QW
<u> </u>	From:	Е	CL Urbanna	a												
(227)	Town of Urbanna (Maint: 59)	0.63	3700	N	97%	1%	1%	0%	1%	0%	Ν	0.098	Ν	0.565	3800	N
$\overline{}$	To:	W	CL Urbann	a												

6/26/2009

Virginia Department of Transportation Traffic Engineering Division 2008 Annual Average Daily Traffic Volume Estimates By Section of Route Town of Urbanna

						I OWII	oi Oibai	IIIa								
Route	Length	AADT	QA	4Tire	Bus		Tru 3+Axle			QC	K Factor	QK	Dir Factor	AAWDT	QW	Year
Town of Urbanna		Fron	ı								-					
Rappahannock Ave	0.33	830	G	99%	0%	1%	SR 227 0%	0%	0%	С	0.103	F	0.523	850	G	2008
(1001) Rappahannock Ave	0.14	490 From	G	98%	1%	1%	6 Marston A	0%	0%	F	0.122	F	0.648	500	G	2008
(1001) Rappahannock Ave	0.18	200 From	G	98%	1%	1%	07 Taylor A 0% 014 Kent S	0%	0%	С	0.136	F	0.567	210	G	2008
(1002) Virginia St	0.23	From 380	R			Γ	Dead End 27; 59-100				NA			NA		05/19/2003
1003	0.12	From 900	R				59-1009 SR 227				NA			NA		05/19/2003
(1004) Wattling St	0.05	From 140	R				Dead End SR 227				NA			NA		05/19/2003
(1005) Cross St	0.25	760	G	99%	1%	0%	SR 227 0%	0%	0%	С	0.108	F	0.595	770	G	2008
(1005) Cross St	0.15	430 From	G	99%	1%	0%	6 Marston A	0%	0%	F	0.114	F	0.636	440	G	2008
(1005) Cross St	0.09	230 From	R				07 Taylor A				NA			NA		05/19/2003
(1005) Cross St	0.06	100 To	R				13 West Av				NA			NA		05/19/2003
(1006) Marston Ave	0.10	300	G	99%	0%	0%	appahanno	1%	0%	С	0.122	F	0.625	310	G	2008
(1006) Marston Ave	0.14	100 From	R				05 Cross Str Dead End	eet			NA			NA		05/19/2003
Taylor Ave	0.10	70	R				appahanno	ck Ave			NA			NA		05/19/2003
(1007) Taylor Ave	0.07	220 From	R				2 Chandler				NA			NA		05/19/2003
(1008) Colorado Ave	0.13	From 80	R			59-1001 R	appahanno	ck Ave			NA			NA		05/19/2003
(1009)	0.04	1000 To	R			:	59-1003 SR 227				NA			NA		05/19/2003
(1010) Grace Ave	0.05	480	R				SR 227	g.			NA			NA		05/19/2003
(1010) Grace Ave	0.06	370 From	R				25 Hilliard				NA			NA		05/19/2003
(1010) Grace Ave	0.08	230 From	R				019 Park S 20 Bonner				NA			NA		05/19/2003
(1012) 59	0.30	260	R			П	Dead End Of Cross Str				NA			NA		05/19/2003
(1013) West Ave	0.17	From	R			59-1001 R	appahanno	ck Ave			NA_			NA		05/19/2003
(1997)		To				59-1	014 Kent S	t								

6/26/2009 8

Virginia Department of Transportation Traffic Engineering Division 2008 Annual Average Daily Traffic Volume Estimates By Section of Route Town of Urbanna

							or Orbai								
Route	Length	AADT	QA	4Tire	Bus			uck 1Trail	QC	K Factor	QK	Dir Factor	AAWDT	QW	Year
Town of Urbanna		From:	1		-	0 1001 B	1	-1- A		-1					
Kent St	0.19	100	R		5	9-1001 K	appahanno	ock Ave		NA			NA		05/19/200
1014 Kent St	0.10	To-	<u> </u>			59-10	13 West A	ve		—			INA		00/10/200
		From:	I				SR 227			-					
1015	0.11	160	R				3K 221			NA			NA		05/19/200
1015	• • • • • • • • • • • • • • • • • • • •	To:				EC	L Urbanna	1		Ti.					
		From:					SR 227			i					
Upton Lane	0.04	510	R							NA			NA		05/19/200
59		To:				D	ead End								
		From:				D	ead End								
Obert St	0.13	140	R							NA			NA		05/19/200
59		To:			5	9-1001 R	appahanno	ock Ave							
		From:				59-10	21 Linden	St							
Park St	0.12	100	R							NA			NA		05/19/200
59		To:			5	9-1001 R	appahanno	ock Ave							
		From:				D	ead End								
Bonner St	0.05	70	R							NA			NA		05/19/20
		To				59-10	21 Linden	St		\neg —					
Bonner St	0.12	170 From:	R			57 10.	21 Emach			NA			NA		05/19/20
		To:			5	9-1001 R	appahanno	ock Ave							
		From:	- 			59-10	019 Park S	St		Ť					
Linden St	0.14	70	R							NA		NA		05/19/20	
59		To:				D	ead End								
		From:				D	ead End								
1022 Chandler Ave	0.04	30	R							NA			NA		05/19/200
59		To:				59-100	7 Taylor A	Ave							
1022) Chandler Ave	0.05	110 From:	R			37-100	77 Taylor 2	110		NA			NA		05/19/200
Chandler Ave		To:				D	ead End								
		From:				D	ead End								
1025) Hilliard St	0.06	40	R							NA			NA		05/18/200
1559		To:				59-101	10 Grace A	Ave							
		From:			5	9-1001 R	appahanno	ock Ave							
Red Cedar Lane	0.06	40	R				FF			NA			NA		05/18/200
59		To:				Cı	ul-de-Sac								
		From:			5	9-1001 R	appahanno	ock Ave							
Parkview Lane	0.06	90	R				••			NA			NA		05/18/200
59/		To:				Cı	ul-de-Sac								
<u></u>		From:			5	9-1001 R	appahanno	ock Ave	 						
1028	0.12	140	R							NA			NA		05/19/200
59		To:				Cı	ul-de-Sac								

6/26/2009 9