### 2008

# Virginia Department of Transportation Daily Traffic Volume Estimates Including Vehicle Classification Estimates

where available

## Special Locality Report 235

Town of Herndon

Information in this report is included in Report

**29** 

(Fairfax County)

Prepared By

Virginia Department of Transportation Traffic Engineering Division

In Cooperation With

U.S. Department of Transportation Federal Highway Administration

### Virginia Department of Transportation Traffic Engineering Division Traffic Monitoring Section

The Virginia Department of Transportation (VDOT) conducts a program where traffic count data are gathered from sensors in or along streets and highways and other sources. From these data, estimates of the average number of vehicles that traveled each segment of road are calculated. VDOT periodically publishes booklets listing these estimates.

One of these booklets, titled "Average Daily Traffic Volumes with Vehicle Classification Data, on Interstate, Arterial and Primary Routes" includes a list of each Interstate and Primary highway segment with the estimated Annual Average Daily Traffic (AADT) for that segment. AADT is the total annual traffic estimate divided by the number of days in the year. This booklet also includes information such as estimates of the percentage of the AADT made up by 6 different vehicle types, ranging from cars to double trailer trucks; estimated Annual Average Weekday Traffic (AAWDT), which is the number of vehicles estimated to have traveled the segment of highway during a 24 hour weekday averaged over the year; as well as Peak Hour and Peak Direction factors used by planners to formulate design criteria.

In addition to the Primary and Interstate publication, one hundred books are published periodically, one for each of 100 areas across the state defined by VDOT for record-keeping purposes. These books include traffic volume estimates for roads within the county, cities, and towns within the area. These books are titled "Daily Traffic Volumes Including Vehicle Classification Estimates, where available; Jurisdiction Report numbers 00 through 99".

Also available are a number of reports summarizing the average Vehicle Miles Traveled (VMT) in selected jurisdictions and other categories of highways. There are many different ways to present traffic volume summary information. Because the user determines the value of each presentation, the reports have been redesigned based on user requests and feedback. The people of the VDOT Traffic Engineering Division Traffic Monitoring Section who produce these books welcome requests for other helpful ways of presenting the summary information.

A compact disc (CD) is available that includes files in the Adobe® Portable Document Format (PDF) that can be displayed, searched, and printed using common desktop computer equipment. The CD includes the publications described above as well as a number of other reports, including specialized VMT summaries and smaller AADT reports for each city and town separately.

### **Publication Notes**

### Parallel Roads

For road inventory and management purposes, some roadways are counted separately by direction and have separately published traffic estimates for each direction of travel. Examples of such roadways are the interstate system and routes with separated facilities and (usually) one-way traffic facilities in urban areas. In these publications, they are referred to as parallel roads. As a convenience for the users of the publication, the listing for segments of roads with parallel segments are published with both the traffic estimates for their own direction of travel (e.g. I-95 Northbound) as well as the estimate of the total of all traffic on the same route including parallel roadways (all directions of I-95). The publication will have a "Combined Traffic Estimates for Parallel Roadways on this Route" or "Combined Traffic" identifiers for the combined direction of travel estimates.

Roadways such as I-395 with a North segment, a South segment and a separate Reversible lane segment will have the estimate for more than two parallel roadways included in the entire combined traffic estimate.

Some routes have very complicated paths through cities and towns. These parallel paths may be too complex to allow a relationship between nearby sections of the opposite direction on the same route. In this case, to indicate that the traffic estimates for such a road segment may not include all directions of traffic on that route, the line that would list the combined values will indicate "NA" for not available.

VDOT's traffic monitoring program includes more than 100,000 segments of roads and highways ranging from several mile sections of Interstate highways to very short sections of city streets. Due to problems experienced obtaining some traffic count data, and the level of quality necessary to maintain confidence in the data, no estimate is currently available for some segments of roadway. These segments are included in the publications indicating "NA" for not available. It is the intention of the VDOT Traffic Engineering Division Traffic Monitoring group to obtain the data necessary and to report traffic volume estimates on all road segments included in these publications.

Many of the road segments in this program are local secondary roads. The amount and detail of data collected on these roads are not as great as the data collected on higher volume roads. The vehicle classification, average weekday traffic volumes, and the theoretical design hour traffic volumes are not calculated for these roads. The publications indicate "NA" for the information that is not available.

This publication is based on a traffic monitoring program initiated in 1997. Because the data collection techniques and statistical evaluation processes are different than those used in previous years, comparison with previous publications may be misleading.

### Glossary of Terms:

Route: The Route Number assigned to this segment of roadway with the master inventory route number if this is an overlapping route, with official street or highway name if available.

Length: Length of the traffic segment in miles.

AADT: Annual Average Daily Traffic. The estimate of typical daily traffic on a road segment for all days of the week, Sunday through Saturday, over the period of one year.

### QA: Quality of AADT:

- A Average of Complete Continuous Count Data
- B Average of Selected Continuous Count Data
- F Factored Short Term Traffic Count Data
- G Factored Short Term Traffic Count Data with Growth Element
- H Historical Estimate
- M Manual Uncounted Estimate
- N AADT of Similar Neighboring Traffic Link
- O Provided By External Source
- R Raw Traffic Count, Unfactored

4Tire: Percentage of the traffic volume made up of motorcycles, passenger cars, vans and pickup trucks.

Bus: Percentage of the traffic volume made up of busses.

**2Axle Truck**: Percentage of the traffic volume made up of 2 axle single unit trucks (not including pickups and vans).

**3+Axle Truck**: Percentage of the traffic volume made up of single unit trucks with three or more axles.

1Trail Truck: Percentage of the traffic volume made up of units with a single trailer.

2Trail Truck: Percentage of the traffic volume made up of units with more than one trailer.

QC: Quality of Classification Data:

- A Average of Complete Continuous Count Data
- B Average of Selected Continuous Count Data
- C Short Term Classified Traffic Count Data
- F Factored Short Term Traffic Count Data
- H Historical Estimate
- M Mass Collective Average
- N Classification Estimates of Similar Neighboring Traffic Link

K Factor: The estimate of the portion of the traffic volume traveling during the peak hour or design hour.

QK: Quality of the K Factor estimate:

- A Factor based on 30th Highest Hour Observed During at least 250 days of Continuous Traffic Data
- B Factor based on other Hour Observed During Less than 250 days of Continuous Traffic Data
- F Factor based on Highest Hour Collected at in a 48 Hour Weekday Period
- M Factor based on Manual Estimate of design hour
- N Design Hour Factor (K Factor) of Similar Neighboring Traffic Link
- O Provided by External Source

Dir Factor: The estimate of the portion of the traffic volume traveling in the peak direction during the peak hour..

AAWDT: Average Annual Weekday Traffic. The estimate of typical traffic over the period of one year for the days between Monday through Thursday inclusive.

QW: Quality of AAWDT:

- A Average of Complete Continuous Count Data
- B Average of Selected Continuous Count Data
- F Factored Short Term Traffic Count Data
- G Factored Short Term Traffic Count Data with Growth Element
- M Manual Uncounted Estimate
- N AAWDT of Similar Neighboring Traffic Link
- O Provided by External Source

Year: Year for which the published values are appropriate. If the Quality of AADT (QA) is "R", the year is the year that the raw traffic count was collected, and if available,

### Route Shield Legend

### Route Systems

North 81	Interstate Route	Traffic volume data for Interstate Routes and some other routes are reported separately by direction, as well as combined.							
29	US Route								
7	Virginia State Rou	te							
(F241)	Frontage Road (F precedes frontage route number)								
(600)	Secondary Route								

### **Special Routes**

Bus	Bus - Business Route
29	Bypas - Bypass Route
	Truck - Truck Route
ALT	ALT - Alternate Route
(220)	Wve - Wve Route connector

- P Parallel Route; Southbound or Westbound direction lanes of a numbered route where they are on a different road facility than the other direction.
- The VDOT Maintainenance Jurisdiction number is displayed below the Secondary Route Number if the Maintenance Jurisdiction is different than the jurisdiction in the title of the report.

### Virginia Department of Transportation Traffic Engineering Division

### 2008 Annual Average Daily Traffic Volume Estimates By Section of Route Town of Herndon

							Tru	ck			K		Dir	
Route	Jurisdiction	Length A	ADT QA	4Tire	Bus	2Axle	3+Axle	1Trail	2Trail	QC	Factor	QK	AAWD7	T Q\
	From:	SCL Herndon, 29	9-657 Centreville	e Rd										
228 Elden St	Town of Herndon	0.24 <b>43</b>	3000 G	98%	1%	1%	0%	0%	0%	F	NA		47000	G
<u> </u>	To- Promi	Hernd	lon Pkwy											
228 Elden St	Town of Herndon	0.16 <b>22</b>	2000 F	99%	0%	1%	0%	0%	0%	F	0.085	F	24000	F
	To	Alah	oama Dr											
228 Elden St	Town of Herndon		0000 F	99%	0%	1%	0%	0%	0%	F	NA		22000	F
220)	Tod													
228 Elden St	From: Town of Herndon		ling Rd 6000 F	99%	0%	1%	0%	0%	0%	С	0.079	F	18000	F
228 Elder ot	Town of Heridan			3370	070	170	070	070	070	O	0.075	'	10000	
Elder Ot	To T		nter St	000/	00/	40/	00/	00/	00/		0.075	_	20000	
Elden St	Town of Herndon	0.09 18	3000 F	99%	0%	1%	0%	0%	0%	F	0.075	F	20000	F
	To: From:		ring St											
Elden St	Town of Herndon		3000 F	99%	0%	1%	0%	0%	0%	F	0.078	F	20000	F
	To: From:		6 Monroe St 66 Elden St											
228 Monroe St	Town of Herndon		500 F	98%	1%	1%	0%	0%	0%	F	0.092	F	7000	ı
220) (11011100 01	- Tomi of Horizon				1,70		070	070	070	•	0.002	•	7000	
Monroo St	Town of Herndon		ne St <b>F</b>	98%	1%	1%	0%	0%	0%	С	0.102	F	6000	
Monroe St	To:		rk Ave	90%	170	170	0%	070	0%	C	0.102	Г	6000	
	From:		nroe St											
Park Ave	Town of Herndon	0.19 6	900 F	98%	1%	1%	0%	0%	0%	F	0.094	F	7500	
	To	Gr	ant St											
Park Ave	Town of Herndon		400 F	98%	1%	1%	0%	0%	0%	F	0.089	F	8000	ı
226)1 4117110	To:		sville Rd	3070	170	<del></del>	070	070	070	•	0.000	•	0000	
_	From:		rk Ave											
228 Dranesville Rd	Town of Herndon	0.08 8	100 N	98%	1%	1%	0%	0%	0%	Ν	NA		8800	I
<u> </u>	To	Worc	hester St											
Dranesville Rd	Town of Herndon	0.26 8	100 F	98%	1%	1%	0%	0%	0%	С	NA		8800	
	To:	Harnd	lon Pkwy											
Dranesville Rd	From: Town of Herndon		6000 F	99%	0%	1%	0%	0%	0%	F	NA		18000	
28) 21 an 100 villo 1 tu	To:		Herndon	0070	070		070	070	070	•			10000	
ant	From:		Herndon											
ast 67 Dulles Toll Rd	Town of Herndon (Maint: 29)		2000 G	98%	0%	0%	0%	0%	0%	F	0.117	F	62000	(
67 Dalics Toll Na	Combined Traffic Estimates for 2 Parallel Roadwa			98%	0%	1%	0%	1%	0%	F	NA	'	118000	
	To:		Herndon	30 /0	0 /0	1/0	0 70	1 /0	0 /0	'	1 1/7		110000	, (
loot	From:		Herndon			<del>- 1</del>								
/est 267)Dulles Toll Rd	Town of Herndon (Maint: 29)		7000 G	98%	0%	1%	0%	1%	0%	F	0.109	F	56000	(
201   Duiles Foil Nu	Combined Traffic Estimates for 2 Parallel Roadwa			98%	0%	1%	0%	1%	0%	F	NA	•	118000	
	Combined France Estimates for 2 Farallel Roadway	ECL	,,,,,,	JU /0	U /0	1 /0	U /0	1 /0	U /0	Г	INA		110000	, (

6/26/2009

### Virginia Department of Transportation Traffic Engineering Division 2008 Annual Average Daily Traffic Volume Estimates By Section of Route Town of Herndon

						TOWIT	ог пени	IOI I								
Route	Length	AADT	QA	4Tire	Bus	2Axle	Tru 3+Axle		2Trail	QC	K Factor	QK	Dir Factor	AAWDT	QW	Year
Town of Herndon		From									-					
0606	0.28	320	R			Hern	don Schoo	l			NA			NA		1991
9606		To				Hern	don Schoo	1								
		From				SCI	L Herndon									
(6631) Van Buren St	0.25	20000	F	99%	1%	0%	0%	0%	0%	F	0.104	F		22000	F	2008
$\bigcirc$		To From				Herr	ndon Pkwy				$\neg$					
(6631) Van Buren St	0.23	8100	F	99%	1%	0%	0%	0%	0%	F	0.1	F		8800	F	2008
$\overline{}$		To From				Ala	abama Dr				$\Box$					
6631) Van Buren St	0.27	8600	F	99%	1%	0%	0%	0%	0%	С	0.098	F		9400	F	2008
		To From				S	pring St									
6631) Van Buren St	0.25	11000	F	99%	1%	0%	0%	0%	0%	F	0.095	F		12000	F	2008
$\bigcirc$		To From				C	Coral Rd				$\Box$					
6631) Van Buren St	0.20	7900	F	99%	1%	0%	0%	0%	0%	F	NA			8600	F	2008
$\bigcirc$		To				Е	Elden St									
$\bigcirc$		From					Buren St									
6654 Spring St	0.41	11000	F	99%	0%	0%	0%	0%	0%	С	0.102	F		12000	F	2008
<u> </u>		From					ictory Dr				$\Box$					
(6654) Spring St	0.22	13000	F	99%	0%	0%	0%	0%	0%	F	0.098	F		14000	F	2008
		To From				Herr	ndon Pkwy									
(6654) Spring St	0.19	34000	F	99%	0%	0%	0%	0%	0%	F	0.093	F		37000	F	2008
<u> </u>		To				SCI	L Herndon									
O 2: 11 - 5.1		From	<u> </u>				L Herndon					_			_	
6656 Sterling Rd	0.24	32000	F	99%	0%	1%	0%	0%	0%	F	0.085	F		35000	F	2008
<u> </u>		To From					ndon Pkwy									
6656 Sterling Rd	0.19	10000	F	99%	0%	1%	0%	0%	0%	F	NA			11000	F	2008
<u> </u>		To From					wood Place									
6656 Sterling Rd	0.32	10000	F	99%	0%	1%	0%	0%	0%	С	NA			11000	F	2008
<u> </u>		To From					elers Place	;								
6656 Sterling Rd	0.18	14000	F	99%	0%	1%	0%	0%	0%	F	NA			15000	F	2008
		To			9		28 Elden S onroe St; E									
6656) Elden St	0.72	20000	F	99%	0%	1%	0%	0%	0%	F	0.080	F		22000	F	2008
0000)		То														
6656) Elden St	0.30	32000	F	99%	0%	1%	ndon Pkwy 0%	0%	0%	F	0.083	F		35000	F	2008
6656) ZIGGIT GT	0.00	To		3370	070		L Herndon	070	070	•	0.000	•		00000	•	2000
		From				235-665	56 Sterling	Rd								
(6658) Herndon Pkwy	1.02	20000	F	98%	0%	1%	1%	0%	0%	С	0.092	F		22000	F	2008
$\bigcup$		To				SR 2:	28 Elden S	t								
(6658) Herndon Pkwy	0.48	13000 From	F	98%	1%	1%	1%	0%	0%	С	0.097	F		14000	F	2008
		To				Cam	npbell Way				<u> </u>					
(6658) Herndon Pkwy	0.23	12000	F	98%	1%	1%	1%	0%	0%	F	0.099	F		13000	F	2008
<u> </u>		To					1 Van Bure									
(6658) Herndon Pkwy	0.95	16000	F	98%	1%	1%	1%	0%	0%	F	0.104	F		18000	F	2008
		To		- / -			554 Spring									
<u> </u>		From				S	pring St					_				
6658 Herndon Pkwy	0.61	13000	F	98%	1%	1%	1%	0%	0%	F	0.090	F		14000	F	2008
		To					Elden St									
Horndon Dlaws	4 40	From	<u> </u>	000/	00/		Elden St	00/	00/		0.105	_		11000	_	2000
6660 Herndon Pkwy	1.42	9700	F 	99%	0%	1%	0%	0%	0%	С	0.105	F		11000	F	2008
O Hamada a Bi	4.00	From	<u> </u>	0001	001		Dranesville		001			_		0000		
(6660) Herndon Pkwy	1.32	8900	F	98%	0%	1%	1%	0%	0%	С	0.101	F		9600	F	2008
<u> </u>		From	L_				3 Crestviev									
(6660) Herndon Pkwy	0.38	13000	F	98%	0%	1%	1%	0%	0%	F	0.1	F		15000	F	2008
$\sim$		To				235-665	56 Sterling	Rd								

6/26/2009 8

### Virginia Department of Transportation Traffic Engineering Division 2008 Annual Average Daily Traffic Volume Estimates By Section of Route Town of Herndon

Length	AADT	QA	4Tire	Bus					QC	K Factor	QK	Dir Factor	AAWDT	QW	Year
					271/10	OTTINIC	TTTGII	ZIIGII		i dotoi		1 40101			
	From				Herr	ndon Pkwy									
0.40	12000	F	99%	1%	0%	0%	0%	0%	С	0.103	F		13000	F	2008
	To				NCI	L Herndon									
	From:				Eld	len Street									
	4800	G								NA		4	4800	G	2008
	To:				Vi	ne Street									
					P	ark Ave									
	4800	F								0.09	F		4800	F	2008
	To:				Hernd	lon Parkwa	y								
	From				15	st Street									
	1200	F								0.116	F	0.622	1200	F	2008
	To:				2n	d Street									
	From:				Ala	ıbama Dr									
	220	F								0.172	F	0.632	220	F	2008
	To				A	spen Dr								F G F	
	From				South of	f Spring Str	reet								
	920	F								0.119	F	0.515	920	F	2008
	To:				Enc	d of Road									
		0.40 12000 To  From: 4800 To  From: 1200 To  From: 220 To:	0.40 12000 F Try    From:	0.40 12000 F 99%  Try  From:  4800 G  Te:  From:  4800 F  To:  From:  1200 F  To:  From:  220 F  From:  From:	From:    12000   F   99%   1%	Length   AADT   QA   4Tire   Bus   2Axle	AADT	Company   Comp	AADT	Rength   AADT   QA   4Tire   Bus   2Axle   3+Axle   1Trail   2Trail   2Trail   2Trail   2 Trail   2 Trai	Rength   R	Length   AADT   QA   4Tire   Bus	Radd	AADT	AADT

6/26/2009 9