### 2008

# Virginia Department of Transportation Daily Traffic Volume Estimates Including Vehicle Classification Estimates

where available

# Special Locality Report 324

Town of Weber City

Information in this report is included in Report

84

(Scott County)

Prepared By

Virginia Department of Transportation Traffic Engineering Division

In Cooperation With

U.S. Department of Transportation Federal Highway Administration

### Virginia Department of Transportation Traffic Engineering Division Traffic Monitoring Section

The Virginia Department of Transportation (VDOT) conducts a program where traffic count data are gathered from sensors in or along streets and highways and other sources. From these data, estimates of the average number of vehicles that traveled each segment of road are calculated. VDOT periodically publishes booklets listing these estimates.

One of these booklets, titled "Average Daily Traffic Volumes with Vehicle Classification Data, on Interstate, Arterial and Primary Routes" includes a list of each Interstate and Primary highway segment with the estimated Annual Average Daily Traffic (AADT) for that segment. AADT is the total annual traffic estimate divided by the number of days in the year. This booklet also includes information such as estimates of the percentage of the AADT made up by 6 different vehicle types, ranging from cars to double trailer trucks; estimated Annual Average Weekday Traffic (AAWDT), which is the number of vehicles estimated to have traveled the segment of highway during a 24 hour weekday averaged over the year; as well as Peak Hour and Peak Direction factors used by planners to formulate design criteria.

In addition to the Primary and Interstate publication, one hundred books are published periodically, one for each of 100 areas across the state defined by VDOT for record-keeping purposes. These books include traffic volume estimates for roads within the county, cities, and towns within the area. These books are titled "Daily Traffic Volumes Including Vehicle Classification Estimates, where available; Jurisdiction Report numbers 00 through 99".

Also available are a number of reports summarizing the average Vehicle Miles Traveled (VMT) in selected jurisdictions and other categories of highways. There are many different ways to present traffic volume summary information. Because the user determines the value of each presentation, the reports have been redesigned based on user requests and feedback. The people of the VDOT Traffic Engineering Division Traffic Monitoring Section who produce these books welcome requests for other helpful ways of presenting the summary information.

A compact disc (CD) is available that includes files in the Adobe® Portable Document Format (PDF) that can be displayed, searched, and printed using common desktop computer equipment. The CD includes the publications described above as well as a number of other reports, including specialized VMT summaries and smaller AADT reports for each city and town separately.

#### **Publication Notes**

#### Parallel Roads

For road inventory and management purposes, some roadways are counted separately by direction and have separately published traffic estimates for each direction of travel. Examples of such roadways are the interstate system and routes with separated facilities and (usually) one-way traffic facilities in urban areas. In these publications, they are referred to as parallel roads. As a convenience for the users of the publication, the listing for segments of roads with parallel segments are published with both the traffic estimates for their own direction of travel (e.g. I-95 Northbound) as well as the estimate of the total of all traffic on the same route including parallel roadways (all directions of I-95). The publication will have a "Combined Traffic Estimates for Parallel Roadways on this Route" or "Combined Traffic" identifiers for the combined direction of travel estimates.

Roadways such as I-395 with a North segment, a South segment and a separate Reversible lane segment will have the estimate for more than two parallel roadways included in the entire combined traffic estimate.

Some routes have very complicated paths through cities and towns. These parallel paths may be too complex to allow a relationship between nearby sections of the opposite direction on the same route. In this case, to indicate that the traffic estimates for such a road segment may not include all directions of traffic on that route, the line that would list the combined values will indicate "NA" for not available.

VDOT's traffic monitoring program includes more than 100,000 segments of roads and highways ranging from several mile sections of Interstate highways to very short sections of city streets. Due to problems experienced obtaining some traffic count data, and the level of quality necessary to maintain confidence in the data, no estimate is currently available for some segments of roadway. These segments are included in the publications indicating "NA" for not available. It is the intention of the VDOT Traffic Engineering Division Traffic Monitoring group to obtain the data necessary and to report traffic volume estimates on all road segments included in these publications.

Many of the road segments in this program are local secondary roads. The amount and detail of data collected on these roads are not as great as the data collected on higher volume roads. The vehicle classification, average weekday traffic volumes, and the theoretical design hour traffic volumes are not calculated for these roads. The publications indicate "NA" for the information that is not available.

This publication is based on a traffic monitoring program initiated in 1997. Because the data collection techniques and statistical evaluation processes are different than those used in previous years, comparison with previous publications may be misleading.

#### Glossary of Terms:

Route: The Route Number assigned to this segment of roadway with the master inventory route number if this is an overlapping route, with official street or highway name if available.

Length: Length of the traffic segment in miles.

AADT: Annual Average Daily Traffic. The estimate of typical daily traffic on a road segment for all days of the week, Sunday through Saturday, over the period of one year.

#### QA: Quality of AADT:

- A Average of Complete Continuous Count Data
- B Average of Selected Continuous Count Data
- F Factored Short Term Traffic Count Data
- G Factored Short Term Traffic Count Data with Growth Element
- H Historical Estimate
- M Manual Uncounted Estimate
- N AADT of Similar Neighboring Traffic Link
- O Provided By External Source
- R Raw Traffic Count, Unfactored

4Tire: Percentage of the traffic volume made up of motorcycles, passenger cars, vans and pickup trucks.

Bus: Percentage of the traffic volume made up of busses.

**2Axle Truck**: Percentage of the traffic volume made up of 2 axle single unit trucks (not including pickups and vans).

**3+Axle Truck**: Percentage of the traffic volume made up of single unit trucks with three or more axles.

1Trail Truck: Percentage of the traffic volume made up of units with a single trailer.

2Trail Truck: Percentage of the traffic volume made up of units with more than one trailer.

QC: Quality of Classification Data:

- A Average of Complete Continuous Count Data
- B Average of Selected Continuous Count Data
- C Short Term Classified Traffic Count Data
- F Factored Short Term Traffic Count Data
- H Historical Estimate
- M Mass Collective Average
- N Classification Estimates of Similar Neighboring Traffic Link

K Factor: The estimate of the portion of the traffic volume traveling during the peak hour or design hour.

QK: Quality of the K Factor estimate:

- A Factor based on 30th Highest Hour Observed During at least 250 days of Continuous Traffic Data
- B Factor based on other Hour Observed During Less than 250 days of Continuous Traffic Data
- F Factor based on Highest Hour Collected at in a 48 Hour Weekday Period
- M Factor based on Manual Estimate of design hour
- N Design Hour Factor (K Factor) of Similar Neighboring Traffic Link
- O Provided by External Source

Dir Factor: The estimate of the portion of the traffic volume traveling in the peak direction during the peak hour..

AAWDT: Average Annual Weekday Traffic. The estimate of typical traffic over the period of one year for the days between Monday through Thursday inclusive.

QW: Quality of AAWDT:

- A Average of Complete Continuous Count Data
- B Average of Selected Continuous Count Data
- F Factored Short Term Traffic Count Data
- G Factored Short Term Traffic Count Data with Growth Element
- M Manual Uncounted Estimate
- N AAWDT of Similar Neighboring Traffic Link
- O Provided by External Source

Year: Year for which the published values are appropriate. If the Quality of AADT (QA) is "R", the year is the year that the raw traffic count was collected, and if available,

### Route Shield Legend

#### Route Systems

North 81	Interstate Route	Traffic volume data for Interstate Routes and some other routes are reported separately by direction, as well as combined.
29	US Route	
7	Virginia State Rou	te
(F241)	Frontage Road (F	precedes frontage route number)
(600)	Secondary Route	

#### **Special Routes**

Bus	Bus - Business Route
29	Bypas - Bypass Route
	Truck - Truck Route
ALT	ALT - Alternate Route
(220)	Wye - Wye Route connector

- P Parallel Route; Southbound or Westbound direction lanes of a numbered route where they are on a different road facility than the other direction.
- The VDOT Maintainenance Jurisdiction number is displayed below the Secondary Route Number if the Maintenance Jurisdiction is different than the jurisdiction in the title of the report.

#### Virginia Department of Transportation Traffic Engineering Division

### 2008 Annual Average Daily Traffic Volume Estimates By Section of Route Town of Weber City

Route	Jurisdiction	Length	AADT	QA	4Tire	Bus		Tru 3+Axle			QC	K Factor	QK	Dir Factor	AAWDT	QW
	From:	S	CL Weber C	ity												
(23)	Town of Weber City (Maint: 84)	0.51	24000	G	92%	0%	1%	1%	6%	0%	F	0.082	F	0.587	24000	G
	To	84-	514 N Yuma	ı Rd												
23	Town of Weber City (Maint: 84)	0.77	24000	G	92%	0%	1%	1%	6%	0%	F	0.081	F	0.554	24000	G
	To: From:		84-808													
(23)	Town of Weber City (Maint: 84)	0.70	24000	G	92%	0%	1%	1%	6%	0%	F	0.081	F	0.55	24000	G
$\bigcirc$	To:	US 58, US	421; NCL	Weber C	ity											
-	From:	US 23	; NCL Web	er City												
(58) (421) Hilton Rd	Town of Weber City (Maint: 84)	0.30	11000	Ğ	97%	0%	1%	1%	1%	0%	F	0.09	F	0.501	12000	G
	То:	To: ECL Weber City														
	From:	1	JS 23, US 5	8			Ī									
(421) (58) Hilton Rd	Town of Weber City (Maint: 84)	0.30	11000	G	97%	0%	1%	1%	1%	0%	F	0.09	F	0.501	12000	G
	To:	C	L Weber Ci	ty												

# Virginia Department of Transportation Traffic Engineering Division 2008 Annual Average Daily Traffic Volume Estimates By Section of Route Town of Weber City

						Town of Weber									
Route	Length	AADT	QA	4Tire	Bus	Tri 2Axle 3+Axle			QC	K Factor	QK	Dir Factor	AAWDT	QW	Year
Town of Weber City															
614)	0.07	4700	G	98%	0%	WCL Weber Ci 1% 1%	0%	0%	F	0.088	N	0.6	5100	G	2008
(614)		Tr				84-739									
614) Yuma Rd	0.10	4900		98%	0%	84-739 Charleston 1% 1%	Rd 0%	0%	С	0.095	_	0.601	E200	_	2009
(614) Yuma Rd	0.18	4900 To		96%	0%	1% 1% US 23 NORTH		0%	C	0.085	F	0.601	5300	G	2008
$\widehat{}$		Fron	n:			US 23 SOUTH									
614	0.13	<b>220</b>	R			ECL Walan Ca				NA			NA		02/03/2004
		Fron				ECL Weber Cit	.y								
720	0.19	300	R			84-1112				NA			NA		02/10/2004
730		To	00			84-1127									
$\bigcirc$	0.44	From				84-1127 Blanton	Dr						NΙΔ		02/40/200
730	0.41	<b>260</b>	R			84-735				NA			NA		02/10/2004
		Fron	1:			WCL Weber Ci	fx								
731	0.15	220	R			WEL WEBEI EI	ıy			NA			NA		02/10/2004
841)		To	_			0.15 ME of WC	Τ.								
(731)	0.40	270 From	R			0.13 1112 01 11 0				NA			NA		02/10/2004
(84)		To	00			84-1114 Chapel	St								
		Fron				Dead End									
735	0.25	360	R							NA			NA		02/10/2004
		Ton Fron	1:			US 23									
735	0.14	200	R							NA			NA		02/10/2004
<u> </u>		To	):			84-1111 Ventor									
$\bigcirc$	0.13	170	R			0.13 MS 84-73	5			NA			NA		02/10/200/
736	0.13	170								INA			INA		02/10/2004
<del>(200</del> )	0.06	40 From	R			84-735				NA			NA		02/10/2004
736	0.00	<b>40</b>				Dead End							INA		02/10/2004
		Fron	1:			84-735									
(7 <u>3</u> 7)	0.04	40	R			0.755				NA			NA		02/10/2004
· RA		To	00			Dead End									
		Fron				84-614									
(7 <u>3</u> 8)	0.19	370	R			24.50				NA			NA		02/10/2004
						84-739									
<del>(200</del> )	0.39	From <b>80</b>	" R			84-614				NA			NA		02/10/2004
(739)	0.53	To				Dead End							INA		02/10/2004
		Fron	n:			84-739									
(740) R4	0.07	120	R							NA			NA		02/10/2004
84		To	:			84-738									
$\bigcirc$		Fron	n:			US 23 SOUTH	I								
744	0.66	820	R			LIG 22 NODEL	Y			NA			NA		02/10/2004
		Fron	<u> </u>			US 23 NORTH	1								
745	0.10	190	R			US 23				NA			NA		02/10/2004
745	0.10	Tr				84-1116 Greenwoo	d Dr						14/1		02/10/200-
		From	1.			84-808 Shady Elm	Lane								
807 Shady Elm Lane	0.10	90	R							NA			NA		08/06/2007
04/		Te	o:			84-744									
<u> </u>		From	h.			84-807 Shady Elm	Lane								
808 Shady Elm Lane	0.08	90	R			****				NA			NA		08/06/2007
		To	1			US 23	~								
(1101) Winfield St	0.06	430	R			84-1102 Roland	St			NA			NA		08/06/2007
(1101) Winfield St	0.06	43U	_			SR 23				INA			INA		00/00/2007

# Virginia Department of Transportation Traffic Engineering Division 2008 Annual Average Daily Traffic Volume Estimates By Section of Route Town of Weber City

						Town of Weber									
Route	Length	AADT	QA	4Tire	Bus	Tru 2Axle 3+Axle		(	C I	K actor	QK	Dir Factor	AAWDT	QW	Year
Town of Weber City		From	.1							-					
(1102) Roland St	0.12	120	R			84-1103 Locust 5	St			 NA			NA		08/06/200
(1102) Roland St		To				Dead End									
		From	:			84-1104 Highland	1 St								
Locust St	0.07	130 To	R			04 1100 P 1 1	G.			NA			NA		08/06/200
		From	<u> </u> 			84-1102 Roland	St			<u> </u>					
(1104) Highland St	0.04	30	R			Dead End				 NA			NA		08/06/200
(1104) Highland St	0.0 .	То	:			84-1103 Locust S	St			<u> </u>					00,00,200
		From	:			Dead End									
North Highland St	0.03	30	R							NA			NA		08/06/200
		To				84-1103 Locust S									
Clares Ct	0.47	From	ᆫ			US 23 SOUTH	<u>{</u>						NIA		00/00/000
Clonce St	0.17	650	R							NA —			NA		08/06/200
Church Ct	0.00	From	<u> </u>			84-1120 Church	St						NIA		00/00/000
Church St	0.66	190 To	R			US 23 NORTH	<u> </u>			NA T			NA		08/06/200
		From	! :I			84-744				1					
(1111) Ventor Dr	0.17	430	R			64-744				NA			NA		08/06/200
(1111) Ventor Dr		To	:			Dead End									
		From	:			SR 23									
1112 McNut St	0.11	520	R							NA			NA		08/06/200
04		To				84-1113 Wilmeth	ı St								
( ) M/I	2.22	From	Ļ			84-1115 Click S	St								00/00/000
Wilmeth St	0.06	130 To	R			84-1112 McNut	C+			NA			NA		08/06/200
		From	:1				St .			<del> </del>					
(1114) Chapel St	0.24	1000	R			SR 23				J NA			NA		08/06/200
Chapel St	0.2	То				84-1112 McNut	St			i.					00/00/200
		From	:			84-1114 Chapel	St								
Click St	0.09	450	R			•				NA			NA		08/06/200
84)		To				NCL Weber Cit	ty			]					
O		From				Dead End									
(1116) Greenwood Dr	0.13	190 To	R			04.745				NA			NA		08/06/200
		From	] .i			84-745				1					
Johnson St	0.14	180	R			84-744				NA			NA		08/06/200
1117) COMINSON ST	0.14	То	r <u>`</u>			Dead End				Τ΄.			14/1		00/00/200
		From	:			84-744									
1118 Baltic Dr	0.10	220	R							NA			NA		08/06/200
84		To				Dead End									
		From				84-1106 S, Church	h St								
Tulip Poplar St	0.17	50	R							NA			NA		08/06/200
_		From				0.17 MN 84-110	)6			]_					
Tulip Poplar St	0.11	100 To	R			04.410637.61	1.0			NA			NA		08/06/200
			] 			84-1106 N, Church	h St			<u> </u>					
(1120) Church St	0.14	From <b>500</b>	R			US 23				 NA			NA		08/06/200
(1120) Church St	0.14	To			84	4-1106 Church St; Cl	lonce St			Ï			14/7		35,00,200
		From	1			US 23				i					
(1121) Spring Dr	0.11	290	R			0.5.25				NA			NA		08/06/200
Spring Dr		То				ECL Weber Cit	y								
		From	:			Dead End									
(1124) Wilhelm Ave	0.10	20	R							NA			NA		08/06/200
<u> </u>		To				US 23									

# Virginia Department of Transportation Traffic Engineering Division 2008 Annual Average Daily Traffic Volume Estimates By Section of Route Town of Weber City

Route	Length	AADT	QA	4Tire	Bus	2Axle 3+Axle		QC	K Factor	QK	Dir Factor	AAWDT	QW	Year
Town of Weber City														
		From				Dead End			<u> </u>					
(1125)	0.03	47	R						<u>N</u> A			NA		08/13/2007
(194)		To				84-739								
		From				Dead End								
(1126)	0.50	180	R						NA			NA		08/06/2007
(1126) 84		To				84-744								
		From				84-730								
1127 Blanton Dr	0.02	250	R						NA			NA		08/06/2007
84		To				US 23								
		From				84-744								
9762 84	0.06	330	R		•		•	•	NA			NA		10/31/2007
84		To				84-744								