

Glossary

Term	Definition
.png	An image file extension for Portable Network Graphics. This type of file is required for proper use of the drop-shadow CSS filter function.
.woff	A web font format developed by Mozilla. Files with the .woff extension can be used to style webpages.
@keyframes	A CSS rule specifying characteristics of a CSS animation.
3D Transformations	Three-dimensional effects on elements, including but not limited to rotate, translate, and scale.
Absolute Positioning	A technique for positioning elements in relation to their parent containers.
addEventListener()	A method that fires a function or block of code when a specified event occurs.
AJAX	Asynchronous JavaScript and XML (AJAX) is the concept of using the XMLHttpRequest object to retrieve and process data without disrupting what has been loaded on a webpage.
Animation	The method of creating a sequence of movement on a screen.
Animation-iteration-count	A CSS property specifying the number of iterations for a CSS animation.
Animation-name	A CSS property specifying the name of an animation, linking it to an @keyframes rule set.
Anonymous Function	A function without a name that can only be called by the variable where it is stored.
API	Application Programming Interface (API) is used to program graphical user interface (GUI) elements; includes a set of routines, protocols, and tools for building apps.
App Cache	Application (App) Cache selectively saves files listed in a text file called a cache manifest.
App State	A state that begins when a web browser sends the first request for a webpage to a web server and closes when the browser is closed.
Application	An application (app) is a program designed specifically for users.
Application Life Cycle	The complete process of planning, designing, writing, testing, packaging, validating, and deploying an app.
Background-image	A CSS property that adds a background image to an element.
Background-size	A CSS property specifying the size of background images.
Background-size: auto	A CSS property-value for the background-size property specifying that an image is displayed at its original size.
Backticks	A backtick (`) is a symbol used to initialize template strings in JavaScript. It should not be confused with single quotes.
beginPath()	A built-in canvas method that begins a path or resets a current path.
Block	A CSS property-value for the display property specifying that an element will take up the entire width of its parent container.
Blur	A CSS filter function specifying a blur value for an image.
Bootstrap	A CSS framework known for creating responsive web designs that work well across mobile devices.
Border-box	A CSS property-value for the box-sizing property specifying that an element's border is contained within its overall size.
Border-radius	A CSS property that rounds the corners of an element's border.
Box-Shadow	A CSS property that adds a shadow effect to the outside frame of an element.
Box-sizing	A CSS property specifying how the web browser calculates an element's height and width regarding its border.
Breakpoints	A designated stopping point in a program allowing a developer to analyze an application during execution.

Term	Definition
Bubbling	A term used to describe the order that events execute when multiple elements have been programmed to handle the same event. Specifically, inner events are handled first before bubbling outwards through the DOM.
Bug	An issue with an application that causes it to vary from the developer's expectations and/or user experience.
Cache	The act of storing resources on a client machine with the intent of faster load times.
Callbacks	Executable code, usually in the form of a function, that is passed into a function as an argument.
Canvas	An HTML element used to render graphics to a webpage.
Canvas Tag	An HTML tag used to create a canvas element.
Cascading	A term used to describe the order by which events execute when multiple elements have been programmed to handle the same event. Specifically, outer events are handled before cascading inwards through the DOM.
Class, in JavaScript	A template that is used to create JavaScript objects.
clearRect()	A built-in canvas method that clears a designated rectangle within an HTML canvas.
Code Execution	The phase where a script is executed one line at a time. This phase runs separately from the memory allocation phase.
Color Stop Position	Stopping points used to render a smooth color transition throughout a gradient.
Column-gap	A CSS property specifying the space between columns.
Comment	A line of code that is ignored by a program. Comments are typically used to organize and explain code blocks.
Console	A section within the Developer Tools displaying error messages that allow developers to interact with and manipulate the current webpage using JavaScript.
Constructor Function	A function that is used to create an object.
Contain	A CSS property-value for the background-size property specifying that an entire image will be visible inside a container.
Content-box	A CSS property-value for the box-sizing property specifying that an element's border is not contained within its overall size.
Cover	A CSS property-value for the background-size property specifying that an image will resize to cover an entire container.
createObjectURL()	A method used to return an object URL as a string.
Cross-Site Scripting	A cyberattack where malicious code is inserted into a webpage to access data.
CSS	Cascading Style Sheets (CSS) is a style sheet language used to add design and positioning properties to HTML elements on a webpage.
CSS Animations	A collection of CSS properties and rule sets allowing developers to animate HTML elements without JavaScript.
CSS Filter Function	A value that is added to the CSS Filter Property. For example, grayscale(); blur(); drop-shadow();.
CSS Filters	A CSS property specifying effects on an image, including blur, grayscale, and sepia.
CSS Framework	A library with predefined CSS classes intended to make web design more simple and consistent.
CSS Grid	A CSS module capable of creating flexible two-dimensional page layouts.
CSS Properties	Property/value combinations used to transform, style, and enhance text and graphics.
CSS Reset	A boilerplate set of CSS rules at the top of a stylesheet designed to address inconsistencies across web browsers.
CSS Rule Set	The combination of a CSS selector, CSS properties, and property values.
Database	An organized collection of data, often featuring tables, queries, and reports.
Datalist	An HTML tag that creates a drop-down menu for an input field. Users are not confined to the options in a datalist.
Debugger	A keyword that can be added to HTML code to designate a breakpoint or stopping point.

Term	Definition
Degrees	Degrees (deg) is a unit of measure used to define an angle.
Deployment	The process of initializing software support or integrating updated software into a current system.
Developer Tools	A collection of tools in a web browser used to analyze web applications.
Display	A CSS property-value combination specifying that an element should be removed from the flow of a page and not displayed.
Display: flex	A CSS property-value combination that enables a container to function as a flexbox.
Display: none	A CSS property-value combination specifying that an element be removed from the flow of a page and not displayed.
DOM	A Document Object Model (DOM) is a standard structure for an HTML document. JavaScript can be used to modify all elements of the DOM.
Downtime	The length of time a system is shut down due to maintenance or technical issues.
Drop-shadow	A CSS filter function that adds a shadow to the shape of an image rather than its natural rectangular border.
Dynamic Content	Content that changes in real-time based on a user and their actions.
Empty String	A string with no characters. In JavaScript, a variable set to an empty string can be manipulated as a string.
Equals Operator	A single equal sign specifying the value of a variable or property. A double equal sign checks for equality and returns a Boolean value.
Eric Meyer's CSS Reset	A popular CSS reset for addressing inconsistencies between web browsers.
ES6	A major update to JavaScript in 2015 that added significant new features.
Event	An action that occurs throughout the lifecycle of a program initiated by either an end-user or the program itself.
Event Listener	A built-in JavaScript method used to execute code when a specific action is taken on a specific element.
Event Object	A JavaScript object that is created as a result of a successful event listener.
Extend	A JavaScript keyword used along with the class keyword to create a new class by inheriting another class.
Extension	Specific functionality that can be added onto a larger existing program, such as a web browser or code editor.
External Files	Files from outside the current project or folder.
feGaussianBlur	An SVG filter that blurs an element.
Fetch API	Modern technique used by web browsers to make HTTP requests.
Fieldset	An HTML tag that groups HTML form elements and places a box around those elements.
FileReader Object	A built-in object that is used by a web browser to read files asynchronously.
fillRect()	A built-in canvas method that draws a filled rectangle onto an HTML canvas.
Filter Attribute	An attribute added to an SVG element that links the element to a predefined SVG filter.
Flex	A CSS property that is shorthand for the flex-grow, flex-shrink, and flex-basis properties.
Flex-basis	A CSS property specifying the initial size of a flex item along the flex container main axis.
Flexbox	A CSS module capable of creating flexible one-dimensional page layouts.
Flex-direction	A CSS property specifying how a flexbox will display multiple items.
Flex-flow	A CSS property specifying whether items will wrap inside of a flex container.
Flex-grow	A CSS property specifying how a flex item will grow inside of a flex container.
Flex-shrink	A CSS property specifying the how a flex item will shrink inside of a flex container.
Flex-wrap	A CSS property that is shorthand for the flex-direction and flex-wrap properties.
Float	A CSS property used to remove an element from the natural flow of a webpage and shift that element to the left or right.

Term	Definition
Font-family	A CSS property specifying the font for an element.
Font-style	A CSS property that is used to display an italic font style.
Font-weight	A CSS property that is used to display a bold or thin font style.
For-each Loop	A programming logic component where a code block is run once for every element in an array or list.
Forms	A section of a webpage designed to accept input from users.
Fractional Units	Fractional (fr) units are relative CSS units that size elements based on adjacent fractional values.
Gap	A CSS property that is shorthand for the row-gap and column-gap properties.
Geolocation API	Web browser functionality that enables programs to request and then use an end-user's location.
GetCurrentPosition()	A method available to a Geolocation Object that retrieves the location of a device.
Git	Software used to track changes to a collection of files.
GitHub	A code hosting platform for collaboration and version control.
Global Variable	A variable that can be accessed from all sections of a program.
Google Fonts	An online font library featuring free and open-source font families. Fonts are accessed through the Google Fonts API.
Gradient	A smooth transition from one color to another.
Graphic Elements	Visual elements that make up a webpage.
Grayscale	A CSS filter function that gradually converts an image to a colorless version.
Grid Gap	Space between rows and columns in a grid container.
Grid Line	A reference to the individual lines that divide the rows and columns of a grid. Lines are 1-based.
Grid-area	A CSS property specifying a variable name for an element. This value is used to organize a grid layout within the grid-template property.
Grid-Based Layouts	Webpage layouts based on several columns that make up 100% of the page width.
Grid-column	A CSS property that is shorthand for the grid-column-start and grid-column-end properties.
Grid-template	A CSS property specifying how predefined grid-areas should be arranged in a grid container.
Grid-template-columns	A CSS property specifying how CSS Grids display columns.
Grid-template-rows	A CSS property specifying how CSS Grids display rows.
Grid-view	A grid-view divides webpages up into several columns (usually 12) that enable a developer to control page layout using predefined CSS classes based on those columns.
Hexadecimal	A base-16 number type representing numbers with digits from 0 through 9 and letters from A through F.
Hidden	A CSS property-value for the overflow property specifying that a browser should hide content that overflows an element.
HTML Attribute	A characteristic of an HTML element that can be customized statically or dynamically.
HTML Element	An element defined by HTML tags, used as part of a webpage.
html()	A jQuery function specifying the inner HTML of an element.
HTMLCollection	A collection of HTML elements similar to an array.
If/else statement	A JavaScript statement that evaluates an expression and different blocks of code based on whether the expression is true or false.
Image Tag	An HTML tag used to define an image on a webpage.
Inheritance	The programming concept where a newly defined class can assume the properties and methods of a previously defined class.
Initial-scale	A CSS viewport meta tag property specifying that a webpage should not zoom during the initial loading process.
Injection Attack	A category of cyberattack where the attacker inputs malicious code into a form or database, causing an application to function differently.

Term	Definition
Inline	A CSS property-value for the display property specifying that an element can display alongside other inline elements.
Inline XML	XML code that is written directly into an HTML file rather than imported using a filename.
Inline-block	A CSS property-value for the display property specifying that an element can display inline with other elements while also accepting width and height values.
InnerHTML	The property of an HTML element that contains the characters between the opening and closing tag of the element.
Input Validation	The act of ensuring input data matches an expected format.
Instantiation	The creation of an object based on a template or class.
Internal Stylesheet	A CSS stylesheet that is added to the head section of an HTML document.
JavaScript	A scripting language used to create dynamic web content.
JavaScript Functions	Reusable JavaScript code that performs actions on data.
jQuery	A JavaScript library designed to make JavaScript easier to write while requiring less code.
JSON	JavaScript Object Notation (JSON) is an open-standard file format that uses human-readable text to transmit data consisting of key/value pairs.
JSON String	A JavaScript string that can be parsed into a JavaScript object.
JSON.parse()	A built-in JavaScript method that takes a JSON string as a parameter and returns a JavaScript object.
Justify-content	A CSS property specifying how CSS Flexbox spaces items inside of a flex container.
Key/Value Pairs	A technique where data can be stored and retrieved using a unique key.
Keyframes	Specific points throughout a CSS animation.
Legend	An HTML tag specifying a title for a form or fieldset.
Letter-spacing	A CSS property that is used to specify the horizontal space between characters in a word.
Linear Gradient	A smooth transition from one color to another along a straight axis.
LineTo()	A built-in canvas method that designates a new point and draws a straight line from the previous point on the canvas to the new point.
Local Storage	Browser-enabled storage that provides the ability to store key/value pairs. Local storage is constant unless explicitly cleared or deleted.
Logic Errors	An error in the flow of an application that typically does not cause an error message.
Loops	A programming logic component where an action or group of actions is run either a set number of times or until a condition is met.
Lorem Ipsum	Placeholder text frequently used in design layouts.
Malicious Attack	An attack designed to disrupt operations and steal sensitive information.
Margin	A CSS property specifying space around the outside of elements.
Max-length	An HTML attribute specifying the maximum number of characters allowed in an input tag or textarea tag.
MDN Web Docs	An open-source collection of documentation for web development.
Media Queries	A CSS3 technique that evaluates an expression to ensure that appropriate classes are applied to elements (normally based on screen size), with the main goal being responsive web design.
Meta Tag	An HTML tag that specifies the overall characteristics of an HTML page. Meta tags are placed inside the head section of an HTML page.
Meter	An HTML tag that creates a visual of a measurement or fractional value.
Method	In programming, an action that takes place, such as changing a property's attribute.
Microsoft Edge	Popular modern-day web browser.
Mouse Event	An event that returns an event object containing properties that describe the state of the mouse.
Mouseout (event)	A JavaScript event that fires when the mouse pointer leaves an element.
Mouseover (event)	A JavaScript event that fires when the mouse pointer hovers on an element.
MoveTo()	A built-in canvas method used to move to a specified point on a canvas without drawing a line.

Term	Definition
OffsetX	A property of a Mouse Event that describes the x-coordinate of the pointer related to the target element.
OffsetY	A property of a Mouse Event that describes the y-coordinate of the pointer related to the target element.
OOP	Object-Oriented Programmed (OOP) is a style of programming that is designed around objects and their properties that can contain data and code.
Opacity	A CSS property that specifies the transparency level for an element. Opacity can also be used to style an image using the CSS filter property along with the Opacity CSS Filter Function.
Output	An HTML tag that displays the results of a calculation or script.
Overflow	A CSS property specifying how a browser should react when content overflows within an element.
Pattern Attribute	An HTML attribute that can validate an input field using regular expressions.
Photoshop	A photo editing and graphic design tool used to create and edit graphics and digital images.
Pixel	A pixel (px) is a unit of measure used to define the smallest unit in a graphic display or digital image.
Pixelation	The effect of adjusting an image such that the human eye easily sees individual pixels.
Preview on Web Server	An extension for Visual Studio Code used to render a real-time preview of a webpage to a browser.
Properties	In JavaScript, named or numbered values that make up a JavaScript object.
Radial Gradient	A smooth transition from one color to another in a circle or oval shape.
ReadyState	A property of a request that describes the current loading state of a request.
Readystatechange	A JavaScript event that fires when there is a change to the readyState of a request.
Referenced XML	XML code that is imported into a file using a hyperlink or file location.
Regular Expressions	A sequence of characters used to describe a string pattern. That pattern is then used to search and replace strings or portions of strings.
Relative Positioning	A technique for positioning elements in relation to their natural position within a webpage's flow.
Render	The act of drawing content to a browser window.
Required	An HTML attribute used to throw an error during form submission if a form field is empty.
ResponseText	A property of the XMLHttpRequest object that receives text from a successful server request.
ResponseXML	A property of the XMLHttpRequest object that receives XML data from a server request.
Responsive Web Design	A design concept that uses various techniques to ensure that a webpage has an optimal design for various screens and devices.
Responsive Width	A characteristic of an HTML element specifying that an element's width is calculated based on the size of the browser window or parent container.
Reusable Code	Code that is written once and used in more than one instance.
Rotate	1: A built-in canvas method that rotates a canvas on the (0,0) point by a certain number of degrees. This method will only affect canvas elements drawn after this method is called. 2: A CSS property value that rotates an element by a specified degree value when used in conjunction with the transform property.
Row-gap	A CSS property specifying the space between rows for a grid.
Runtime	The period of time when a program is actively running.
Sandbox	An isolated environment used to test software.
Saturate	A CSS filter function that over-saturates an image.
Scale	A CSS property value that, when used in conjunction with the transform property, scales the size of an element either up or down.
Scroll	A CSS property-value for the overflow property specifying that a browser should add a scroll bar if content overflows an element.
Send()	A built-in method of the XMLHttpRequest object that sends a request to a server.

Term	Definition
Sepia	A CSS filter function that gradually converts an image to a brownish-red color, usually associated with old-style photographs.
Session State	An ASP.NET state that allows a specific user to store data on a web server and call that data anytime during a session.
Session Storage	Browser-enabled storage that provides the ability to store key/value pairs. Session storage is deleted when the browser tab is closed.
Skew	A CSS property value that, when used in conjunction with the transform property, tilts an image.
SQL Injection	A cyberattack where malicious code is inserted into a database with the intent of reading or modifying data.
String Literal	Also referred to as Template Strings, these strings are declared in JavaScript using backticks and allow the developer to inject expressions and JavaScript (interpolation).
Stroke()	A built-in canvas method that draws a line after two points have been designated using the moveTo method and lineTo method.
StrokeRect()	A built-in canvas method that draws an unfilled rectangle to an HTML canvas.
StrokeStyle	An HTML property used to set the color for the outline of a path.
Style Attribute	An attribute added to an HTML element that is used to set styles for an element.
SVG	A scalable vector graphic (SVG) is a two-dimensional graphic created by XML-style markup.
SVG Element	A container that defines a new coordinate system within an SVG document.
SVG Tag	An HTML tag that contains an SVG element.
Syntax Error	An error in an application's source code, most commonly a spelling error or punctuation error. These errors are typically underlined with a red squiggly line in most code editors.
Tailwind CSS	A CSS framework, made unique by its almost exclusive use of class names to design elements.
Target Element	The element that triggers a given event.
Textarea	An HTML tag that creates a large input field for users.
textContent	The property of an HTML element that returns a string containing the text from each child of that element.
Text-Shadow	A CSS property that adds a shadow effect to text.
This	A JavaScript keyword generally used to refer to an object itself, although use cases vary.
ToFixed()	A JavaScript function that formats a type Number to a set number of decimal places.
Transformations	Two-dimensional or three-dimensional effects on elements using CSS, including but not limited to rotate, scale, skew, and translate.
Transition	A CSS property that is used to specify the transitioning property and duration of the transition.
Transition-delay	A CSS property that is used to delay a previously defined transition.
Transition-timing-function	A CSS property that is used to specify the speed throughout a transition.
Translate	A built-in canvas method that designates a new position on the canvas as (0,0).
Type	An HTML attribute specifying the type for an HTML input tag.
UI	A user interface (UI) is the way that a user and a computer system interact.
UseCapture	The third parameter for the addEventListener method that takes a Boolean value, specifying whether or not events for an element are set to bubble or cascade.
User-Initiated Event	An event that fires due to the actions of an end-user.
Variable	A container that holds data, with the intent that the program will use the data many times.
Viewheight	Viewheight (vh) is a CSS unit of measurement specifying the height of an element relative to the viewport's height.
Viewport	Viewport is typically used in the context of a meta tag, where it specifies that the content width is set equal to the device width.
Viewwidth	Viewwidth (vw) is a CSS unit of measurement specifying the width of an element relative to the viewport's width.

Term	Definition
Visual Studio Code	A free, open-source integrated development environment created by Microsoft.
Web Server	Software that distributes and displays web content in a browser by accepting HTTP requests.
Web-Safe Fonts	Fonts that are readily available on almost any device or browser. These fonts are used alongside imported fonts, ensuring that at least one declared font is available.
Width	A CSS property specifying a width for a given element.
Window Event	An event that returns an event object containing properties that describe the state of the browser window.
XML	Extensible Markup Language (XML) is a markup language, similar to HTML, designed to store and transport data.
XMLHttpRequest Object	A built-in JavaScript object that manages the full lifecycle of a request to an API or web server.