

puremacro: macroeconometrics and quantitative macroeconomics on the core scientific-Python stack

Jorge Alonso Ortiz ¹

¹ Instituto Tecnológico Autónomo de México (ITAM), Mexico City, Mexico 

DOI: [10.xxxxxx/draft](https://doi.org/10.xxxxxx/draft)

Software

- [Review](#) 
- [Repository](#) 
- [Archive](#) 

Editor: [Open Journals](#) 

Reviewers:

- [@openjournals](#)

Submitted: 01 January 1970

Published: unpublished

License

Authors of papers retain copyright
and release the work under a
Creative Commons Attribution 4.0
International License ([CC BY 4.0](#))

Summary

puremacro is a Python library for empirical macroeconomics and for solving quantitative macroeconomic models. It gives researchers, instructors and students one consistent interface to the field's standard methods, and a way to check the library's numbers on the machine that produces them.

On the empirical side it covers vector autoregressions (VARs) with recursive, long-run, sign, sign-zero, narrative and external-instrument identification ([Antolín-Díaz & Rubio-Ramírez, 2018](#); [Blanchard & Quah, 1989](#); [Mertens & Ravn, 2013](#); [Rubio-Ramírez et al., 2010](#); [Sims, 1980](#); [Stock & Watson, 2018](#); [Uhlig, 2005](#)); factor-augmented VARs ([Bernanke et al., 2005](#)); local projections ([Jordà, 2005](#)); ARCH, GARCH and GARCH-MIDAS volatility models ([Bollerslev, 1986](#); [Engle, 1982](#); [Engle et al., 2013](#)); autocorrelation-robust and weak-instrument-robust inference ([Anderson & Rubin, 1949](#); [Montiel Olea & Pflueger, 2013](#); [Newey & West, 1987](#)); dynamic panels ([Arellano & Bond, 1991](#)); difference-in-differences and synthetic control ([Abadie et al., 2010](#); [Arkhangelsky et al., 2021](#)); mixed-frequency nowcasting ([Bańbura & Modugno, 2014](#); [Giannone et al., 2008](#)); and text-based uncertainty indices ([Baker et al., 2016](#)). On the modelling side it solves dynamic programs by value-function iteration and endogenous grids ([Carroll, 2006](#); [Iskhakov et al., 2017](#)); heterogeneous-agent economies, including sequence-space HANK models ([Aiyagari, 1994](#); [Auclert et al., 2021](#); [Young, 2010](#)); continuous-time models ([Achdou et al., 2022](#)); projection methods on Chebyshev, finite-element and Smolyak grids ([Judd, 1992](#); [Krueger & Kubler, 2004](#); [McGrattan, 1996](#); [Smolyak, 1963](#)); linear rational-expectations (DSGE) models; quantitative spatial and trade models ([Allen & Arkolakis, 2014](#); [Caliendo & Parro, 2015](#)); and climate-economy models ([Golosov et al., 2014](#); [Nordhaus, 2018](#)).

Its estimators and solvers are written against NumPy ([Harris et al., 2020](#)), SciPy ([Virtanen et al., 2020](#)), pandas ([McKinney, 2010](#)) and Matplotlib ([Hunter, 2007](#)) alone, and the package contains no compiled code of its own. The same code therefore also runs in a web browser under Pyodide ([The Pyodide development team, 2021](#)), which ships those libraries compiled to WebAssembly.

Statement of need

An applied macroeconomist's toolkit typically spans several ecosystems: reduced-form time series and panel econometrics from Python's statsmodels ([Seabold & Perktold, 2010](#)), arch ([Sheppard, 2025a](#)) and linearmodels ([Sheppard, 2025b](#)); structural identification from MATLAB toolboxes or R packages such as vars and lpirfs ([Adämmer, 2019](#); [Pfaff, 2008](#)); DSGE analysis in Dynare ([Adjemian et al., 2024](#)), which runs under MATLAB or GNU Octave; and heterogeneous-agent models in Python codes accelerated with Numba ([Auclert et al., 2021](#); [Batista et al., 2024](#); [Carroll et al., 2018](#)). Each tool is good at what it does, but combining them means several installations, often several languages, sometimes a commercial licence, and conventions that change from package to package. The cost is highest in teaching, where installation

42 problems consume class time and students' machines (managed laptops, low-end hardware,
43 tablets) may not support the full stack.

44 puremacro is written for that audience: instructors, students and applied researchers in
45 macroeconomics. It puts common estimators and models behind one set of conventions (shared
46 arguments such as lags, horizon and ci, and immutable result objects with plotting and table
47 export), keeps the dependencies of its numerical code to four ubiquitous libraries, and ships
48 the evidence needed to trust its output: galleries of checks that users can run themselves.

49 State of the field

50 statsmodels, arch and linearmodels are the reference Python implementations of reduced-form
51 time series, conditional volatility and panel and instrumental-variable estimation. puremacro
52 does not aim to replace them; it uses them as test oracles (see *Software design*). They do not,
53 however, implement the identification schemes that define structural macroeconometrics (sign,
54 sign-zero, narrative and external-instrument restrictions), nor do they solve heterogeneous-agent
55 or general-equilibrium models. For models, widely used tools are Dynare, the sequence-space
56 Jacobian toolkit, HARK and QuantEcon.py. In their domains they are more mature than
57 puremacro and, for large heterogeneous-agent problems, faster: puremacro trades speed for
58 portability.

59 That portability can be stated precisely. As of September 2026 the Pyodide distribution
60 includes NumPy, SciPy, pandas, Matplotlib and statsmodels, but not arch, linearmodels or
61 Numba; arch and linearmodels publish no pure-Python wheels that a browser could install
62 at run time; and HARK and QuantEcon.py declare Numba as a required dependency, while
63 the sequence-space Jacobian toolkit uses it in its core modules. In a browser, the volatility,
64 panel-IV and heterogeneous-agent layers of the usual stack are therefore unavailable, and
65 Dynare needs a different language runtime altogether.

66 This also answers the build-versus-contribute question. Individual estimators could be
67 contributed to existing packages, and some would be welcome there. What cannot be
68 contributed is the property that makes the collection usable on a constrained machine: one
69 import surface whose numerical code depends on nothing beyond four core libraries. That is
70 an invariant of the whole library, enforced by tests, not a feature that can be added to another
71 project's dependency graph.

72 Software design

73 **An import invariant.** Library modules import NumPy, SciPy, pandas and Matplotlib (plus
74 requests, in the data layer) at module scope; anything else, from Parquet support to optional
75 accelerators, is optional and imported only when available. Two tests enforce the rule against
76 the packages most likely to leak in. The first imports each of the 530 library modules (examples,
77 teaching helpers, text-scraping sources and optional Numba kernels are excluded) and fails
78 if statsmodels, linearmodels, arch or the scraping packages bs4, pdfplumber and pypdf have
79 entered sys.modules. The second repeats the sweep in a subprocess in which those packages
80 cannot be imported, so a module that would break on a machine without them fails in
81 continuous integration (CI) on a machine that has them. The wheel is pure Python, and its
82 base install adds only requests to the four core libraries; the Parquet and Excel engines are an
83 optional extra.

84 **Oracles that do not ship.** The packages forbidden at run time are the test suite's references.
85 Scripts in the repository run statsmodels, arch, linearmodels and esda once on fixed inputs
86 and store their outputs as package data, so the validation gallery can compare against them
87 without importing them; an opt-in test marker recomputes the stored outputs with the installed

88 packages to detect drift. The reference implementations thus certify the library without
89 becoming its dependencies, which is what lets breadth and portability coexist.

90 **Degrading rather than failing.** Where an external tool does better, puremacro uses it if present:
91 seasonal adjustment calls X-13ARIMA-SEATS through statsmodels when both are installed
92 and otherwise falls back to a native X-11. A runtime module detects the host (CPython
93 or Pyodide), the device class and the four capabilities that differ away from a workstation
94 (sockets, Parquet, threads and a writable filesystem), and offers opt-in adaptations such as a
95 browser fetch transport. A few dynamic-programming and projection solvers have optional
96 Numba kernels and experimental MLX and CuPy paths; NumPy remains the reference path
97 and the one tested in CI.

98 **Costs.** Writing everything in vectorised NumPy makes large heterogeneous-agent problems
99 slower than in JIT-compiled toolkits, and derivatives that other libraries obtain by automatic
100 differentiation must be coded by hand. The browser is a best-effort target rather than a
101 supported one: Parquet and Excel files need engines that not every Pyodide distribution
102 provides. Under Pyodide 314.0.5 in Node.js the full validation gallery passes, and an opt-in
103 release gate installs the package as the playground does and runs a 31-test smoke subset of
104 the suite.

105 **Scale.** Version 3.3.0 comprises about 730 modules and 220,000 lines of Python, exercised by
106 about 12,700 tests that CI runs on Linux, macOS and Windows under Python 3.11–3.13. Before
107 a release is tagged, a script checks the suite against a recorded baseline, the import invariant,
108 a snapshot of the public API that must be regenerated deliberately when the interface changes,
109 and that the version string agrees across the package metadata, changelog and citation file.

110 Verification

111 The validation gallery, `puremacro.validation.scorecard()`, runs 107 checks across 15
112 subsystems in under a minute, with none of the oracle packages installed; all pass (Figure 1).
113 The checks differ in strength, and each records its reference. Nineteen compare against an
114 external reference: stored outputs of statsmodels, arch, linearmodels and esda, SciPy results
115 computed at run time, or a published table. Agreement with independent implementations
116 is typically at machine precision (median relative difference of order 10^{-15}); the exception is
117 GARCH, whose estimates differ from arch's by up to 0.35% because the two packages use
118 different optimisers. Twenty-nine checks compare against analytical results, and 59 test internal
119 consistency, such as agreement between alternative algorithms and recovery of parameters
120 from simulated data.

121 A separate replication gallery, `puremacro.replication.scorecard()`, reproduces published
122 estimates of the return to schooling (Card, 1995), a textbook logit of married women's labour-
123 force participation on Mroz's (1987) data, and the output effect of tax changes (Romer &
124 Romer, 2010), as well as two qualitative predictions of incomplete-markets models (Aiyagari,
125 1994; Huggett, 1993): precautionary saving holds the interest rate below the rate of time
126 preference, and the rate falls as income risk rises. Most model solvers (sequence-space,
127 continuous-time, spatial, trade and climate) are covered by unit tests but not yet by gallery
128 checks.




Figure 1: The validation gallery of puremacro 3.3.0: 107 checks in 15 subsystems, by kind of reference; all pass. *External reference*: stored outputs of statsmodels, arch, linearmodels or esda, SciPy computed at run time, or a published table. *Analytical result*: a closed form, or an effect planted in simulated data. *Internal consistency*: agreement between alternative algorithms, identities that correct output must satisfy, or recovery of parameters from simulated data. Regenerate with python paper/make_scorecard_fig.py.

Research impact statement

puremacro is young (public since July 2026) and has not yet been used in published research or by other packages. Its significance is near-term, and rests on evidence a reviewer can check.

Teaching. The library was written for, and is used in, the author's course *Macroeconomía Avanzada* at ITAM, whose Fall 2026 edition builds its computational material on it. The course's 22 Spanish lesson notebooks are in the repository (notebooks/course), and 20 of them call puremacro directly.

Reproducible material. The repository contains 58 bilingual (English/Spanish) pairs of worked-example notebooks; all but one of them, with the lesson notebooks, are also published as a JupyterLite ([JupyterLite contributors, 2021](https://jupyterlite.github.io/puremacro/)) site that runs them in the browser.

Community readiness. The package is released on PyPI under the MIT licence, with documentation at <https://jalonso1979.github.io/puremacro/>, contribution guidelines, and CI on three operating systems.

AI usage disclosure

Generative AI was used extensively in writing puremacro, its documentation and this paper. Anthropic's Claude models, used through the Claude Code agent (Claude Opus 5, Claude Fable 5 and Claude Fable 5.1), generated or co-wrote much of the code, tests, documentation and notebooks: 109 of the 211 commits in the public repository carry a Claude co-author trailer. Google's Jules coding agent contributed 20 pull requests (refactoring, performance and test improvements), each reviewed and merged by the author. Claude also drafted and revised this paper, including checking its claims against the code and its references against Crossref.

The author set the scope and made the core design decisions (the import invariant, validation against stored outputs of reference implementations, and the shared interface conventions) and reviewed, edited and validated all AI-assisted output before it was merged. Correctness does

not rest on that review alone: it is checked by the test suite, the validation and replication galleries, and CI.

Acknowledgements

The author thanks the scientific-Python and Pyodide communities, whose work makes a browser-capable macroeconomics library possible.

References

- Abadie, A., Diamond, A., & Hainmueller, J. (2010). Synthetic control methods for comparative case studies: Estimating the effect of California's tobacco control program. *Journal of the American Statistical Association*, 105(490), 493–505. <https://doi.org/10.1198/jasa.2009.ap08746>
- Achdou, Y., Han, J., Lasry, J.-M., Lions, P.-L., & Moll, B. (2022). Income and wealth distribution in macroeconomics: A continuous-time approach. *The Review of Economic Studies*, 89(1), 45–86. <https://doi.org/10.1093/restud/rdab002>
- Adämmmer, P. (2019). Ipirfs: An R package to estimate impulse response functions by local projections. *The R Journal*, 11(2). <https://doi.org/10.32614/RJ-2019-052>
- Adjemian, S., Juillard, M., Karamé, F., Mutschler, W., Pfeifer, J., Ratto, M., Rion, N., & Villemot, S. (2024). *Dynare: Reference manual, version 6* (Dynare Working Papers No. 80). CEPREMAP. <https://ideas.repec.org/p/cpm/dynare/080.html>
- Aiyagari, S. R. (1994). Uninsured idiosyncratic risk and aggregate saving. *The Quarterly Journal of Economics*, 109(3), 659–684. <https://doi.org/10.2307/2118417>
- Allen, T., & Arkolakis, C. (2014). Trade and the topography of the spatial economy. *The Quarterly Journal of Economics*, 129(3), 1085–1140. <https://doi.org/10.1093/qje/qju016>
- Anderson, T. W., & Rubin, H. (1949). Estimation of the parameters of a single equation in a complete system of stochastic equations. *The Annals of Mathematical Statistics*, 20(1), 46–63. <https://doi.org/10.1214/aoms/1177730090>
- Antolín-Díaz, J., & Rubio-Ramírez, J. F. (2018). Narrative sign restrictions for SVARs. *American Economic Review*, 108(10), 2802–2829. <https://doi.org/10.1257/aer.20161852>
- Arellano, M., & Bond, S. (1991). Some tests of specification for panel data: Monte Carlo evidence and an application to employment equations. *The Review of Economic Studies*, 58(2), 277–297. <https://doi.org/10.2307/2297968>
- Arkhangelsky, D., Athey, S., Hirshberg, D. A., Imbens, G. W., & Wager, S. (2021). Synthetic difference-in-differences. *American Economic Review*, 111(12), 4088–4118. <https://doi.org/10.1257/aer.20190159>
- Auclert, A., Bardóczy, B., Rognlie, M., & Straub, L. (2021). Using the sequence-space Jacobian to solve and estimate heterogeneous-agent models. *Econometrica*, 89(5), 2375–2408. <https://doi.org/10.3982/ECTA17434>
- Baker, S. R., Bloom, N., & Davis, S. J. (2016). Measuring economic policy uncertainty. *The Quarterly Journal of Economics*, 131(4), 1593–1636. <https://doi.org/10.1093/qje/qjw024>
- Bañbura, M., & Modugno, M. (2014). Maximum likelihood estimation of factor models on datasets with arbitrary pattern of missing data. *Journal of Applied Econometrics*, 29(1), 133–160. <https://doi.org/10.1002/jae.2306>
- Batista, Q., Coleman, C., Furusawa, Y., Hu, S., Lunagariya, S., Lyon, S., McKay, M., Oyama, D., Sargent, T. J., Shi, Z., Stachurski, J., Winant, P., Watkins, N., Yang, Z., & Zhang,

- 196 H. (2024). QuantEcon.py: A community based Python library for quantitative economics.
197 *Journal of Open Source Software*, 9(93), 5585. <https://doi.org/10.21105/joss.05585>
- 198 Bernanke, B. S., Boivin, J., & Eliasziw, P. (2005). Measuring the effects of monetary policy:
199 A factor-augmented vector autoregressive (FAVAR) approach. *The Quarterly Journal of*
200 *Economics*, 120(1), 387–422. <https://doi.org/10.1162/0033553053327452>
- 201 Blanchard, O. J., & Quah, D. (1989). The dynamic effects of aggregate demand and supply
202 disturbances. *The American Economic Review*, 79(4), 655–673.
- 203 Bollerslev, T. (1986). Generalized autoregressive conditional heteroskedasticity. *Journal of*
204 *Econometrics*, 31(3), 307–327. [https://doi.org/10.1016/0304-4076\(86\)90063-1](https://doi.org/10.1016/0304-4076(86)90063-1)
- 205 Caliendo, L., & Parro, F. (2015). Estimates of the trade and welfare effects of NAFTA. *The*
206 *Review of Economic Studies*, 82(1), 1–44. <https://doi.org/10.1093/restud/rdu035>
- 207 Card, D. (1995). Using geographic variation in college proximity to estimate the return to
208 schooling. In L. N. Christofides, E. K. Grant, & R. Swidinsky (Eds.), *Aspects of labour*
209 *market behaviour: Essays in honour of John Vanderkamp* (pp. 201–222). University of
210 Toronto Press.
- 211 Carroll, C. D. (2006). The method of endogenous gridpoints for solving dynamic stochastic
212 optimization problems. *Economics Letters*, 91(3), 312–320. <https://doi.org/10.1016/j.econlet.2005.09.013>
- 213
- 214 Carroll, C. D., Kaufman, A. M., Kazil, J. L., Palmer, N. M., & White, M. N. (2018). The
215 Econ-ARK and HARK: Open source tools for computational economics. *Proceedings of the*
216 *17th Python in Science Conference*, 25–30. <https://doi.org/10.25080/Majora-4af1f417-004>
- 217 Engle, R. F. (1982). Autoregressive conditional heteroscedasticity with estimates of the variance
218 of United Kingdom inflation. *Econometrica*, 50(4), 987–1007. <https://doi.org/10.2307/1912773>
- 219
- 220 Engle, R. F., Ghysels, E., & Sohn, B. (2013). Stock market volatility and macroeconomic
221 fundamentals. *The Review of Economics and Statistics*, 95(3), 776–797. https://doi.org/10.1162/REST_a_00300
- 222
- 223 Giannone, D., Reichlin, L., & Small, D. (2008). Nowcasting: The real-time informational
224 content of macroeconomic data. *Journal of Monetary Economics*, 55(4), 665–676. <https://doi.org/10.1016/j.jmoneco.2008.05.010>
- 225
- 226 Golosov, M., Hassler, J., Krusell, P., & Tsyvinski, A. (2014). Optimal taxes on fossil fuel in
227 general equilibrium. *Econometrica*, 82(1), 41–88. <https://doi.org/10.3982/ECTA10217>
- 228 Harris, C. R., Millman, K. J., van der Walt, S. J., Gommers, R., Virtanen, P., Cournapeau,
229 D., Wieser, E., Taylor, J., Berg, S., Smith, N. J., Kern, R., Picus, M., Hoyer, S., van
230 Kerkwijk, M. H., Brett, M., Haldane, A., Fernández del Río, J., Wiebe, M., Peterson, P.,
231 ... Oliphant, T. E. (2020). Array programming with NumPy. *Nature*, 585(7825), 357–362.
232 <https://doi.org/10.1038/s41586-020-2649-2>
- 233 Huggett, M. (1993). The risk-free rate in heterogeneous-agent incomplete-insurance economies.
234 *Journal of Economic Dynamics and Control*, 17(5–6), 953–969. [https://doi.org/10.1016/0165-1889\(93\)90024-M](https://doi.org/10.1016/0165-1889(93)90024-M)
- 235
- 236 Hunter, J. D. (2007). Matplotlib: A 2D graphics environment. *Computing in Science &*
237 *Engineering*, 9(3), 90–95. <https://doi.org/10.1109/MCSE.2007.55>
- 238 Iskhakov, F., Jørgensen, T. H., Rust, J., & Schjerning, B. (2017). The endogenous grid
239 method for discrete-continuous dynamic choice models with (or without) taste shocks.
240 *Quantitative Economics*, 8(2), 317–365. <https://doi.org/10.3982/QE643>
- 241 Jordà, Ò. (2005). Estimation and inference of impulse responses by local projections. *The*
242 *American Economic Review*, 95(1), 161–182. <https://doi.org/10.1257/0002828053828518>

- 243 Judd, K. L. (1992). Projection methods for solving aggregate growth models. *Journal of*
244 *Economic Theory*, 58(2), 410–452. [https://doi.org/10.1016/0022-0531\(92\)90061-L](https://doi.org/10.1016/0022-0531(92)90061-L)
- 245 JupyterLite contributors. (2021). *JupyterLite: Jupyter running entirely in the browser*.
246 <https://github.com/jupyterlite/jupyterlite>.
- 247 Krueger, D., & Kubler, F. (2004). Computing equilibrium in OLG models with stochastic
248 production. *Journal of Economic Dynamics and Control*, 28(7), 1411–1436. [https://doi.org/10.1016/S0165-1889\(03\)00111-8](https://doi.org/10.1016/S0165-1889(03)00111-8)
- 249
- 250 McGrattan, E. R. (1996). Solving the stochastic growth model with a finite element method.
251 *Journal of Economic Dynamics and Control*, 20(1–3), 19–42. [https://doi.org/10.1016/0165-1889\(94\)00842-0](https://doi.org/10.1016/0165-1889(94)00842-0)
- 252
- 253 McKinney, W. (2010). Data structures for statistical computing in Python. *Proceedings of the*
254 *9th Python in Science Conference*, 56–61. <https://doi.org/10.25080/Majora-92bf1922-00a>
- 255 Mertens, K., & Ravn, M. O. (2013). The dynamic effects of personal and corporate income
256 tax changes in the United States. *American Economic Review*, 103(4), 1212–1247.
257 <https://doi.org/10.1257/aer.103.4.1212>
- 258 Montiel Olea, J. L., & Pflueger, C. (2013). A robust test for weak instruments. *Journal of*
259 *Business & Economic Statistics*, 31(3), 358–369. <https://doi.org/10.1080/00401706.2013.806694>
- 260
- 261 Mroz, T. A. (1987). The sensitivity of an empirical model of married women's hours of
262 work to economic and statistical assumptions. *Econometrica*, 55(4), 765–799. <https://doi.org/10.2307/1911029>
- 263
- 264 Newey, W. K., & West, K. D. (1987). A simple, positive semi-definite, heteroskedasticity
265 and autocorrelation consistent covariance matrix. *Econometrica*, 55(3), 703–708. <https://doi.org/10.2307/1913610>
- 266
- 267 Nordhaus, W. (2018). Projections and uncertainties about climate change in an era of
268 minimal climate policies. *American Economic Journal: Economic Policy*, 10(3), 333–360.
269 <https://doi.org/10.1257/pol.20170046>
- 270 Pfaff, B. (2008). VAR, SVAR and SVEC models: Implementation within R package vars.
271 *Journal of Statistical Software*, 27(4). <https://doi.org/10.18637/jss.v027.i04>
- 272 Romer, C. D., & Romer, D. H. (2010). The macroeconomic effects of tax changes: Estimates
273 based on a new measure of fiscal shocks. *American Economic Review*, 100(3), 763–801.
274 <https://doi.org/10.1257/aer.100.3.763>
- 275 Rubio-Ramírez, J. F., Waggoner, D. F., & Zha, T. (2010). Structural vector autoregressions:
276 Theory of identification and algorithms for inference. *The Review of Economic Studies*,
277 77(2), 665–696. <https://doi.org/10.1111/j.1467-937X.2009.00578.x>
- 278 Seabold, S., & Perktold, J. (2010). Statsmodels: Econometric and statistical modeling
279 with Python. *Proceedings of the 9th Python in Science Conference*, 92–96. <https://doi.org/10.25080/Majora-92bf1922-011>
- 280
- 281 Sheppard, K. (2025a). *bashtage/arch*. Zenodo. <https://doi.org/10.5281/zenodo.593254>
- 282 Sheppard, K. (2025b). *bashtage/linearmodels*. Zenodo. <https://doi.org/10.5281/zenodo.2591973>
- 283
- 284 Sims, C. A. (1980). Macroeconomics and reality. *Econometrica*, 48(1), 1–48. <https://doi.org/10.2307/1912017>
- 285
- 286 Smolyak, S. A. (1963). Quadrature and interpolation formulas for tensor products of certain
287 classes of functions. *Soviet Mathematics Doklady*, 4, 240–243.
- 288 Stock, J. H., & Watson, M. W. (2018). Identification and estimation of dynamic causal effects

- 289 in macroeconomics using external instruments. *The Economic Journal*, 128(610), 917–948.
290 <https://doi.org/10.1111/ecoj.12593>
- 291 The Pyodide development team. (2021). *pyodide/pyodide*. Zenodo. [https://doi.org/10.5281/](https://doi.org/10.5281/zenodo.5156931)
292 [zenodo.5156931](https://doi.org/10.5281/zenodo.5156931)
- 293 Uhlig, H. (2005). What are the effects of monetary policy on output? Results from an
294 agnostic identification procedure. *Journal of Monetary Economics*, 52(2), 381–419. <https://doi.org/10.1016/j.jmoneco.2004.05.007>
295
- 296 Virtanen, P., Gommers, R., Oliphant, T. E., Haberland, M., Reddy, T., Cournapeau, D.,
297 Burovski, E., Peterson, P., Weckesser, W., Bright, J., van der Walt, S. J., Brett, M.,
298 Wilson, J., Millman, K. J., Mayorov, N., Nelson, A. R. J., Jones, E., Kern, R., Larson, E., ...
299 SciPy 1.0 Contributors. (2020). SciPy 1.0: Fundamental algorithms for scientific computing
300 in Python. *Nature Methods*, 17(3), 261–272. <https://doi.org/10.1038/s41592-019-0686-2>
- 301 Young, E. R. (2010). Solving the incomplete markets model with aggregate uncertainty
302 using the Krusell–Smith algorithm and non-stochastic simulations. *Journal of Economic*
303 *Dynamics and Control*, 34(1), 36–41. <https://doi.org/10.1016/j.jedc.2008.11.010>

DRAFT