

W207— Applied Machine Learning

Cornelia Paulik, PhD

School of Information

UC Berkeley

Feedforward NN

Announcements

- Midterm exam: next week

Consists of a total of 37 questions to be completed within a 90-minute timeframe. Covers week 1-6 material.

The questions are divided as follows:

- 4 open-ended questions,
- 33 multiple-choice questions

- Final project: **baseline presentation** in two weeks

Last week

- Evaluation metrics for classification tasks
- Dealing with class imbalance
- Multiclass Logistic Regression (extend the **wine** dataset to 3 classes)

Last week

- Evaluation metrics for classification tasks
- Dealing with class imbalance
- Multiclass Logistic Regression (extend the **wine** dataset to 3 classes)



Input: Today is a great day.

Translation (in Romanian): Astazi e o zi frumoasa.

How do you
evaluate model performance?

Last week

- Evaluation metrics for classification tasks
- Dealing with class imbalance
- Multiclass Logistic Regression (extend the **wine** dataset to 3 classes)



Input: Today is a great day.

Translation (in Romanian): Astazi e o zi frumoasa.

Translation (in Romanian): Este o zi frumoasa astazi.

How do you
evaluate model performance?

Today's learning objectives

- General concepts: Feedforward Neural Networks (FFNN)
- Training, validation, and test datasets
- Application: Detect **Diabetic Retinopathy** using image data

Neural Networks

Shallow networks (no hidden layers) can only capture linear decision boundaries

Neural Networks

Shallow networks (no hidden layers) can only capture linear decision boundaries

What if **CT scans** data?





Image source: <https://www.medicalnewstoday.com/articles/153201#what-is-a-CT-scan>

Neural Networks

Shallow networks (no hidden layers) can only capture linear decision boundaries

What if **video** data?

Surgery



Hospital patient monitoring



Psychology



Image source: <https://web.stanford.edu/class/biods220/lectures/lecture5.pdf>

Neural Networks

Shallow networks (no hidden layers) can only capture linear decision boundaries

What if **audio** data? (e.g., speech recognition)




Image source: <https://cbmm.mit.edu/research/projects-thrust/theoretical-frameworks-intelligence/invariant-representation-learning>


Neural Networks

Shallow networks (no hidden layers) can only capture linear decision boundaries

What if **CT scans** data?

What if **video** data?

What if **audio** data? (e.g., speech recognition)



unstructured
data

Neural Networks

Shallow networks (no hidden layers) can only capture linear decision boundaries


What if CT scans data?

What if video data?

What if audio data? (e.g., speech recognition)

unstructured
data

Deep NN



a = activation function

Neural Networks

ML real world problems: we don't know how large the network should be a priori!

Small network



underfit



Network cannot
learn the
underlying
structure of
complex datasets

Very large network



overfit



Network
memorizes training
data

Neural Networks

ML real world problems: we don't know how large the network should be a priori!

Small network



underfit



Network cannot
learn the
underlying
structure of
complex datasets

Solution: build a network with a relatively higher capacity (slightly higher than necessary) to do well on training

Very large network



overfit



Network
memorizes training
data

Neural Networks

ML real world problems: we don't know how large the network should be a priori!

Small network

underfit

Network cannot learn the underlying structure of complex datasets

Solution: build a network with a relatively higher capacity (slightly higher than necessary) to do well on training

Prevent overfitting by applying one or more **regularization schemes**


dropout in NN
L1, L2 for others

Very large network

overfit

Network memorizes training data

Training, validation, and test datasets



Other splits: 60/20/20 is also popular.

Training, validation, and test datasets

All training (80%)

Test (20%)




Use only for final
evaluation

Done with hyperparameter selection using the validation set?

Common to **merge training and validation sets** to train a final model using chosen hyperparameters.

K-fold cross validation




All training (80%)




Test (20%)

Small labeled dataset? Very common in healthcare... K-fold cross validation (can be computationally expensive!) may be worthwhile.

K-fold cross validation




use different fold for validation






⋮

Small labeled dataset? Very common in healthcare... K-fold cross validation may be worthwhile.

K-fold cross validation



use different fold for validation




- Train model K times with a **different fold as the validation set**
- each time; then average the validation set results.

OK to apply same concept to test-time evaluation.

Smart approach: allows more data to be used for each training of the model, without compromising validation results

Application: detect **diabetic retinopathy**



Typical fundus images: (a) Normal; (b) Mild DR; (c) Moderate DR; (d) Severe DR; (e) Proliferic DR; (f) Macular edema.

Image source: <https://www.sciencedirect.com/science/article/pii/S0010482513002862#f0005>