Here's a **simple, repeatable daily routine (10–15 mins)** to lock these into muscle memory:

Remember

Shortcut	Shortcut
→ search a class	→ move back & forward
→ run something	
==========	==========
→ generate constructor	→ fix/import something
→ comment/uncomment	→ duplicate lines
→ move lines	→ delete lines
→ rename variable	
==========	==========
→ optimize imports	→ reformat code
→ select project panel	

🔁 Daily Routine (do this every coding session)

1. 🔥 Warm-up (2 mins)

force yourself to use shortcuts only:

- ⇧ ⇧ → search a class
- ⌥ ⌘ ← / → → move back & forward
- ⇧ ^ R → run something

2. ✍️ Editing drill (5 mins)

repeat every day:

- ⌘ N → generate constructor
- ⌥ ⏎ → fix/import something
- ⌘ / → comment/uncomment
- ⌘ D → duplicate lines
- ⇧ ⌥ ↑/↓ → move lines
- ⌘ ⌫ → delete lines
- ⌥ ⌘ R (rename) → rename variable

3. 🧼 Cleanup habit (2 mins)

- ^ ⌥ O → optimize imports
- ⌥ ⌘ L → reformat code **automatic at the end of every change**

No Mouse

- ⌘ 1 ↑/↓ → select project panel

4. 🧠 “One new shortcut focus” (2–3 mins)

Pick **1 shortcut per day** and overuse it:

Example:

- Day 1 → ⌥ ⏎ (use it constantly)
- Day 2 → ⌘ N
- Day 3 → ⌘ ⌥ ← / →

5. 🚫 Constraint rule (all day)

Force this rule while coding:

> “If I know a shortcut exists → I must use it”

No mouse fallback.

⚡ Memory hack (important)

Group them mentally:

- **Navigation** → ⇧⇧, ⌥⌘← →
- **Editing** → ⌘D, ⌘⌫, ⇧⌥
- **Fixing** → ⌥⏎
- **Cleanup** → ^⌥O, ⌥⌘L
- **Run** → ⇧^R

👉 Brain remembers **clusters, not lists**

⏱️ Timeline (realistic)

- Day 1–2 → feels slow
- Day 3–5 → starts automatic
- Week 2 → you stop thinking

If you want, I can turn this into a **1-page printable cheat sheet (visual layout for TDD sessions)**.