ARCHIPELAGO LIGHTING GROUP

DATASHEET

CONSTANT · MID-POWER · FACTORY / FIELD INSTALL

# EM15-PMB/120AC

MPN · BLD-PM15T-YYY

⚠ INFERRED SPECS — PENDING VERIFICATION

## 120 VAC Output Emergency Driver — Mid-Power

15W emergency LED driver with 120 VAC output for legacy fluorescent-replacement and AC-driven LED fixtures. Universal 100–347 VAC input. Compatible with all constANT-listed fixture series. Specify /CL adder for SILVAIR-networked Title 24 NLC compliance and auto-test.

### KEY FEATURES

- Universal 100–347 VAC input — one driver, every building voltage
- Operating range 32°F to 122°F
- Constant brightness for 90 min — no dimming as battery drains
- Self-protecting battery — overcharge / over-discharge / short-circuit
- Test switch with red LED status indicator
- /CL constANTLink option — SILVAIR networked auto-test
- 5-year limited warranty on driver and battery
- CSA C22.2 No.141 + CEC Title 20 compliant

### PERFORMANCE

| | |
|---|---|
| Emergency Output Power | 15 W |
| Emergency Runtime | 90 min |
| Output Type | AC constant |
| Recharge Time | 24 hours |
| Battery Type | LiFePO4 |
| Battery Charging Current | 0–250 mA |

### ELECTRICAL

| | |
|---|---|
| Input Voltage | 100–347 VAC |
| Input Frequency | 50 / 60 Hz |
| Input Current | 100 mA max |
| Input Power | 8.0 W max |
| Output Voltage | 120 VAC |
| Output Power | 15 W max |

### INSTALLATION

| | |
|---|---|
| Mounting Type | Surface mount |
| Test Switch | Test switch with indicator light |
| Wire Type | UL 2464, 24 AWG, 300 V, 80°C |
| Wire Length | 550 mm (21.65") |
| Installation | Factory or field |
| Power Factor | >0.50 |

### CONSTRUCTION

| | |
|---|---|
| Max. Application | 150 W or 4 A |
| Operating Temperature | 32°F to 122°F |
| Storage Temperature | 158°F max |
| Location Rating | Dry, damp |
| Battery Cycles | 500 full cycles |
| Warranty | 5-year limited |

### COMPLIANCE

| | |
|---|---|
| Safety Listings | UL 924 · CSA C22.2 No.141 |
| Energy Compliance | CEC Title 20 |
| Installation Li... | UL listed for factory & field install |
| Compatibility | All constANT-listed fixture series |

### COMPATIBILITY · CONSTANT APPLICATION QUICK GUIDE

lamparARCH · luxoARCH · planoARCH · tubularCH

See full Application Quick Guide for sensor & controller pairings.

### ORDERING INFORMATION

| | |
|---|---|
| EM15-PMB/120AC | Standard 15 W driver |
| EM15-PMB/120AC/CL | With constANTLink: SILVAIR networked auto-test |
| Vendor MPN | BLD-PM15T-YYY (BillDa) |

**15W** OUTPUT POWER

**90 min** EGRESS RUNTIME

**100–347V** UNIVERSAL INPUT

**/CL Ready** NLC ADDER

**AC Output** 120 VAC

**UL 924** LISTED

**Archipelago Lighting Group** · 4615 State Street, Montclair, CA 91763

+1 (866) 912-3200 · sales@archipelagolighting.com · archipelagolighting.com