ARCHIPELAGO LIGHTING GROUP

DATASHEET

CONSTANT · MID-POWER · FACTORY / FIELD INSTALL

EM20-CMB/260DC

MPN · BLD-CM20H-480800-20W

ArcticGuard Cold-Pack Emergency LED Driver — High-Voltage Mid-Power

20W constant-power emergency LED driver with cold-rated LiFePO4 battery. Drives 90–260 VDC LED arrays at constant power. Universal 100–347 VAC input. Specify /AG adder for cold-pack operating range. Compatible with lamparARCH and luxoARCH fixture families.

KEY FEATURES

- Universal 100–347 VAC input — one driver, every building voltage
- Test switch with red LED status indicator
- ArcticGuard cold-pack option — −4°F to 140°F operating range
- UL 924 listed for code-compliant emergency egress
- Constant brightness for 90 min — no dimming as battery drains
- 5-year limited warranty on driver and battery
- Self-protecting battery — overcharge / over-discharge / short-circuit
- CSA C22.2 No.141 + CEC Title 20 compliant

PERFORMANCE

Emergency Output Power	20 W
Emergency Runtime	90 min
Output Type	Constant power
Recharge Time	24 hours
Battery Type	LiFePO4 6.4V 3000mAh
Battery Charging Current	0–250 mA

ELECTRICAL

Input Voltage	100–347 VAC
Input Frequency	50 / 60 Hz
Input Current	100 mA max
Input Power	7 W max
Output Voltage	DC 36–150 V
Output Current	410–800 mA

INSTALLATION

Mounting Type	Surface mount
Test Switch	Test switch with indicator light
Wire Type	UL 2464, 24 AWG, 300 V, 80°C
Wire Length	550 mm (21.65")
Installation	Factory or field
Power Factor	>0.50

CONSTRUCTION

Max. Application	200 W or 4 A
Operating Temperature	32°F to 122°F (140°F /AG)
Storage Temperature	158°F max
Location Rating	Dry, damp, extreme temp
Battery Cycles	500 full cycles
Warranty	5-year limited

COMPLIANCE

Safety Listings	UL 924 · CSA C22.2 No.141
Energy Compliance	CEC Title 20
Installation Li...	UL listed for factory & field install
Compatibility	lamparARCH, luxoARCH

COMPATIBILITY · CONSTANT APPLICATION QUICK GUIDE

lamparARCH | luxoARCH

See full Application Quick Guide for sensor & controller pairings.

ORDERING INFORMATION

EM20-CMB/260DC	Standard 20 W driver
EM20-CMB/260DC/AG	With ArcticGuard cold-pack: −4°F operating
Vendor MPN	BLD-CM20H-480800-20W (BillDa)

20W OUTPUT POWER	**90 min** EGRESS RUNTIME
100–347V UNIVERSAL INPUT	**/AG Ready** COLD-PACK ADDER
LiFePO4 BATTERY	**UL 924** LISTED

Archipelago Lighting Group · 4615 State Street, Montclair, CA 91763

+1 (866) 912-3200 · sales@archipelagolighting.com · archipelagolighting.com