ARCHIPELAGO LIGHTING GROUP

DATASHEET



— CONSTANT · HIGH-POWER · FACTORY / FIELD INSTALL

EM25-HMB/170DC

MPN · BLD-HM25D-YYY

⚠ INFERRED SPECS — PENDING VERIFICATION

High-Voltage Emergency LED Driver — High-Output Mid-Power

25W constant-power emergency LED driver for 170 VDC LED arrays. Universal 100–347 VAC input. Compatible with all constANT-listed fixture series. Field-installable by certified electrician.

KEY FEATURES

- Universal 100–347 VAC input — one driver, every building voltage
- Operating range 32°F to 122°F
- Constant brightness for 90 min — no dimming as battery drains
- Self-protecting battery — overcharge / over-discharge / short-circuit
- Test switch with red LED status indicator
- UL 924 listed for code-compliant emergency egress
- 5-year limited warranty on driver and battery
- CSA C22.2 No.141 + CEC Title 20 compliant

PERFORMANCE

Emergency Output Power	25 W
Emergency Runtime	90 min
Output Type	Constant power
Recharge Time	24 hours
Battery Type	LiFePO4
Battery Charging Current	0–250 mA

ELECTRICAL

Input Voltage	100–347 VAC
Input Frequency	50 / 60 Hz
Input Current	150 mA max
Input Power	10 W max
Output Voltage	DC 170 V
Output Power	25 W max

INSTALLATION

Mounting Type	Surface mount
Test Switch	Test switch with indicator light
Wire Type	UL 2464, 24 AWG, 300 V, 80°C
Wire Length	550 mm (21.65")
Installation	Factory or field
Power Factor	>0.50

CONSTRUCTION

Max. Application	250 W or 4 A
Operating Temperature	32°F to 122°F
Storage Temperature	158°F max
Location Rating	Dry, damp
Battery Cycles	500 full cycles
Warranty	5-year limited

COMPLIANCE

Safety Listings	UL 924 · CSA C22.2 No.141
Energy Compliance	CEC Title 20
Installation Li...	UL listed for factory & field install
Compatibility	All constANT-listed fixture series

COMPATIBILITY · CONSTANT APPLICATION QUICK GUIDE

lamparARCH · luxoARCH · planoARCH · tubularCH

See full Application Quick Guide for sensor & controller pairings.

ORDERING INFORMATION

EM25-HMB/170DC	Standard 25 W driver
Vendor MPN	BLD-HM25D-YYY (BillDa)

25W OUTPUT POWER

90 min EGRESS RUNTIME

100-347V UNIVERSAL INPUT

32° to 122°F OPERATING RANGE

All Series COMPATIBLE

UL 924 LISTED

Archipelago Lighting Group · 4615 State Street, Montclair, CA 91763

+1 (866) 912-3200 · sales@archipelagolighting.com · archipelagolighting.com