ARCHIPELAGO LIGHTING GROUP

DATASHEET

CONSTANT · HIGH-POWER · FACTORY / FIELD INSTALL

# EM60-GMB/170DC

MPN · BLD-GM60X-YYY

## G-Series High-Power Emergency LED Driver

60W constant-power internal emergency LED driver. Mounts inside high-bay LED fixtures. Universal 100–347 VAC input. Drives 170 VDC LED arrays for 90 minutes during outage.

### KEY FEATURES

- Universal 100–347 VAC input — one driver, every building voltage
- Operating range 32°F to 122°F
- Constant brightness for 90 min — no dimming as battery drains
- Self-protecting battery — overcharge / over-discharge / short-circuit
- Test switch with red LED status indicator
- UL 924 listed for code-compliant emergency egress
- 5-year limited warranty on driver and battery
- CSA C22.2 No.141 + CEC Title 20 compliant

### PERFORMANCE

| | |
|---|---|
| Emergency Output Power | 60 W |
| Emergency Runtime | 90 min |
| Output Type | Constant power |
| Recharge Time | 24 hours |
| Battery Type | LiFePO4 6.4V 3000mAh |
| Battery Charging Current | 0–250 mA |

### ELECTRICAL

| | |
|---|---|
| Input Voltage | 100–347 VAC |
| Input Frequency | 50 / 60 Hz |
| Input Current | 200 mA max |
| Input Power | 15 W max |
| Output Voltage | DC 170 V |
| Output Current | ≤460 mA |

### INSTALLATION

| | |
|---|---|
| Mounting Type | Internal (fixture-integrated) |
| Test Switch | Test switch with indicator light |
| Wire Type | UL 2464, 24 AWG, 300 V, 80°C |
| Wire Length | 550 mm (21.65") |
| Installation | Factory or field |
| Power Factor | >0.50 |

### CONSTRUCTION

| | |
|---|---|
| Battery Information | LiFePO4 6.4V 3000mAh |
| Max. Application | 600 W |
| Operating Temperature | 32°F to 122°F |
| Storage Temperature | 158°F max |
| Location Rating | Dry, damp |
| Warranty | 5-year limited |

### COMPLIANCE

| | |
|---|---|
| Safety Listings | UL 924 · CSA C22.2 No.141 |
| Energy Compliance | CEC Title 20 |
| Installation Li... | UL listed for factory & field install |
| Compatibility | lampar RCH high-bay series |

### COMPATIBILITY · CONSTANT APPLICATION QUICK GUIDE

lampar RCH

See full Application Quick Guide for sensor & controller pairings.

### ORDERING INFORMATION

| | |
|---|---|
| EM60-GMB/170DC | Standard 60 W driver |
| Vendor MPN | BLD-GM60X-YYY (BillDa) |

| | |
|---|---|
| **60W** OUTPUT POWER | **90 min** EGRESS RUNTIME |
| **100–347V** UNIVERSAL INPUT | **32° to 122°F** OPERATING RANGE |
| **Internal** MOUNT TYPE | **UL 924** LISTED |