ARCHIPELAGO LIGHTING GROUP

DATASHEET

PIR DETECTION	**8FT** MAX HEIGHT
IP20 IP RATING	**12-24Vdc** INPUT VOLTAGE
UL CERTIFICATION	**by ⒶCS** PLATFORM

ⒶCS BY ALG APP
Scan to download on the App Store

CONTRⒶLS · BY ⒶCS

MSP-SRI/903P1/ACS

Occupancy Sensor | Indoor | PIR | ⒶCS | 1-Pin

Indoor fixture-integrated PIR sensor for ⒶCS networked platform. BLE SigMesh connectivity with 1-pin audio jack. Low-voltage 12-24Vdc input. DLC NLC qualified.

TECHNICAL SPECIFICATIONS

Detection Technology	**Passive Infrared (PIR)**
Input Voltage	**12-24Vdc**
Max Mounting Height	**8FT (2.4m)**
Detection Range	**Standard**
Network	**BLE SigMesh**
Mesh Capacity	**Up to 500 nodes**
DLC NLC	**Qualified**
IP Rating	**IP20**
Certification	**UL Listed**
Connector	**1-Pin Audio Jack**
Commissioning	**ⒶCS by ALG App (iOS)**
Operating Temp	**-20°C to +50°C**
Finish	**White**
Application	**Fixture**

FEATURES

- BLE SigMesh networked
- ⒶCS by ALG app commissioning
- 12-24Vdc low voltage
- Cloud energy analytics
- OTA firmware updates
- DLC NLC qualified
- 1-pin audio jack plug-and-play
- 500 node mesh capacity
- Zone scheduling
- Fixture-integrated design

COMPATIBLE LUMINAIRE FAMILIES

All ALG luminaire families

ORDERING INFORMATION

SKU	MSP-SRI/903P1/ACS
UPC	—
Case Quantity	—
Case Dimensions	—
Case Weight	—
Brand	**contrⒶLS**
Platform	**by ⒶCS**
Manufacturer	**Archipelago Lighting Group**