ARCHIPELAGO LIGHTING GROUP

DATASHEET

PIR DETECTION	**40FT** MAX HEIGHT
IP65 IP RATING	**12-24Vdc** INPUT VOLTAGE
UL CERTIFICATION	**by ⒶCS** PLATFORM

ⒶCS BY ALG APP
Scan to download on the App Store

CONTRⒶLS · BY ⒶCS

MSP-SRO/903PX/ACS

Occupancy Sensor | Outdoor | PIR | ⒶCS

Outdoor-rated PIR sensor for ⒶCS networked platform. IP65 protection with BLE SigMesh connectivity. Adapter for 1-pin or 3-pin connection. DLC NLC qualified.

TECHNICAL SPECIFICATIONS

Detection Technology	Passive Infrared (PIR)
Input Voltage	12-24Vdc
Max Mounting Height	40FT (12m)
Detection Range	Extended
Network	BLE SigMesh
Mesh Capacity	Up to 500 nodes
DLC NLC	Qualified
IP Rating	IP65
Certification	UL Listed
Connector	Adapter: 1 or 3-Pin
Commissioning	ⒶCS by ALG App (iOS)
Operating Temp	-30°C to +60°C
Finish	White
Application	Fixture

FEATURES

- IP65 outdoor rated
- DLC NLC qualified
- Dual adapter (1-pin / 3-pin)
- Weather-resistant housing
- Zone scheduling
- BLE SigMesh networked
- ⒶCS by ALG app commissioning
- 40FT detection range
- Cloud energy analytics
- Utility rebate eligible

COMPATIBLE LUMINAIRE FAMILIES

All ALG luminaire families

ORDERING INFORMATION

SKU	MSP-SRO/903PX/ACS
UPC	—
Case Quantity	—
Case Dimensions	—
Case Weight	—
Brand	contrⒶLS
Platform	by ⒶCS
Manufacturer	Archipelago Lighting Group