ARCHIPELAGO LIGHTING GROUP

DATASHEET

Microwave DETECTION	**8FT** MAX HEIGHT
IP20 IP RATING	**10-15Vdc** INPUT VOLTAGE
UL CERTIFICATION	**Bi-Level** PLATFORM

CONTRⒶLS · BI-LEVEL

MSM-MTO/7D/BLS

Occupancy Sensor | Indoor | Microwave | Euro DIP

Compact Euro-style microwave sensor with DIP switch configuration. Low-profile design for surface-mount and recessed applications. 8FT max height for low-ceiling commercial spaces.

TECHNICAL SPECIFICATIONS

Detection Technology	5.8GHz Microwave	IP Rating	IP20
Input Voltage	10-15Vdc	Certification	UL Listed
Max Mounting Height	8FT (2.4m)	Connector	Wire-In
Detection Range	Adjustable via DIP	Commissioning	DIP Switch
Hold Time	5s – 30min	Operating Temp	-20°C to +50°C
Daylight Harvesting	Yes	Finish	White
Stand-by Dimming	10% – 100%	DLC / NLC	No (Standalone)

FEATURES

- Compact Euro-style form factor
- 5.8GHz microwave detection
- 8FT low-ceiling optimized
- Adjustable stand-by dimming
- Low-voltage driver compatible
- DIP switch configuration
- Low-profile surface mount
- Built-in daylight harvesting
- Maintenance-free design
- Discrete ceiling integration

COMPATIBLE LUMINAIRE FAMILIES

planoⒶRCH (Troffers & Panels) | selectⒶRCH (Strips & Wraps)

ORDERING INFORMATION

SKU	MSM-MTO/7D/BLS
UPC	—
Case Quantity	—
Case Dimensions	—
Case Weight	—
Brand	contrⒶLS
Platform	Bi-Level
Manufacturer	Archipelago Lighting Group