ARCHIPELAGO LIGHTING GROUP

DATASHEET

CONTRⒶLS · BI-LEVEL

MSP-HTO/07P3/BLS

Occupancy Sensor | Outdoor | PIR | 3-Pin

Outdoor-rated PIR occupancy sensor with IP65 protection and 3-pin connector. 39FT detection range for covered parking and building perimeter applications.

PIR DETECTION	39FT MAX HEIGHT
IP65 IP RATING	10-15Vdc INPUT VOLTAGE
UL CERTIFICATION	Bi-Level PLATFORM

TECHNICAL SPECIFICATIONS

Detection Technology	Passive Infrared (PIR)	IP Rating	IP65
Input Voltage	10-15Vdc	Certification	UL Listed
Max Mounting Height	39FT (12m)	Connector	3-Pin Outdoor
Detection Range	Adjustable via IR	Commissioning	IR Remote
Hold Time	5s – 30min	Operating Temp	-30°C to +60°C
Daylight Harvesting	Yes	Finish	White
Stand-by Dimming	10% – 100%	DLC / NLC	No (Standalone)

FEATURES

- IP65 outdoor rated
- 39FT detection range
- IR remote commissioning
- Built-in daylight harvesting
- Perimeter lighting control
- Passive infrared detection
- 3-pin outdoor connector
- Weather-resistant housing
- Covered parking applications
- Walk-through test mode

COMPATIBLE LUMINAIRE FAMILIES

lamparⒶRCH (UFO High Bay) | LLHB/Tiny-I (Linear High Bay) | LV3P (Vapor Tight)

COMPATIBLE REMOTES

RM-HT/03S · 3-Button | RM-HT/05S · 5-Button Dimming | RM-HT/06S · LCD Full Config

ORDERING INFORMATION

SKU	MSP-HTO/07P3/BLS
UPC	819313022988
Case Quantity	—
Case Dimensions	—
Case Weight	—
Brand	contrⒶLS
Platform	Bi-Level
Manufacturer	Archipelago Lighting Group