ARCHIPELAGO LIGHTING GROUP

DATASHEET

BLE Mesh COMMUNICATION	**13FT** MAX HEIGHT
IP20 IP RATING	**12-24Vdc** INPUT VOLTAGE
UL CERTIFICATION	**SILVAIR** PLATFORM

— CONTRⒶLS · BY SILVAIR

MSM-HTI/08P1/NLC

Occupancy Sensor | Indoor | NLC | Silvair | Microwave | 1-Pin

Indoor microwave sensor for Silvair enterprise NLC platform. BLE mesh connectivity with Silvair app commissioning. Icarus-III form factor with 1-pin audio jack. Unlimited network scalability.

TECHNICAL SPECIFICATIONS

Detection Technology	5.8GHz Microwave	IP Rating	IP20
Input Voltage	12-24Vdc	Certification	UL Listed
Max Mounting Height	13FT (4m)	Connector	1-Pin Audio Jack
Network	Bluetooth Mesh (Silvair)	Commissioning	Silvair App
Scalability	Unlimited nodes	Operating Temp	-20°C to +50°C
DLC NLC	Qualified	Finish	White
BMS Integration	Open APIs	Application	Fixture

FEATURES

- Silvair-certified BLE mesh
- 5.8GHz microwave detection
- BMS integration via APIs
- Granular zone control
- 1-pin audio jack connection
- Unlimited network scalability
- Enterprise NLC platform
- Silvair app commissioning
- Daylight harvesting
- Third-party BMS compatible

COMPATIBLE LUMINAIRE FAMILIES

All ALG luminaire families

ORDERING INFORMATION

SKU	MSM-HTI/08P1/NLC
UPC	—
Case Quantity	—
Case Dimensions	—
Case Weight	—
Brand	contrⒶLS
Platform	by SILVAIR
Manufacturer	Archipelago Lighting Group