ARCHIPELAGO LIGHTING GROUP

DATASHEET

CONSTANT · LOW-POWER · FACTORY / FIELD INSTALL

EM08-HMB/170DC

MPN · BLD-HM08D-YYY

High-Voltage Emergency LED Driver

8W constant-power emergency LED driver for 170 VDC LED arrays. Universal 100–347 VAC input. Compatible with all constANT-listed fixture series. Specify /XD adder for 120-minute extended runtime where AHJ requires it.

KEY FEATURES

- Universal 100–347 VAC input — one driver, every building voltage
- Operating range 32°F to 122°F
- Constant brightness for 90 min · 120 min (/XD) — no dimming as battery drains
- Self-protecting battery — overcharge / over-discharge / short-circuit
- /XD Extended Discharge option — 120 min runtime for AHJ requirements
- UL 924 listed for code-compliant emergency egress
- 5-year limited warranty on driver and battery
- CSA C22.2 No.141 + CEC Title 20 compliant

PERFORMANCE

Emergency Output Power	8 W
Emergency Runtime	90 min · 120 min (/XD)
Output Type	Constant power
Recharge Time	≥24 hours (initial)
Battery Type	Cold-rated Li-ion
Battery Charging Current	≤250 mA

ELECTRICAL

Input Voltage	100–347 VAC
Input Frequency	50 / 60 Hz
Input Current	100 mA max
Input Power	8 W max
Output Voltage	DC 170 V
Output Power	8 W

INSTALLATION

Mounting Type	Surface mount
Test Switch	Test switch with indicator light
Wire Type	UL 2464, 24 AWG, 300 V, 80°C
Wire Length	Per OEM label
Installation	Factory or field
Mounting Centers	7.0" driver · 6.2" battery

CONSTRUCTION

Driver Dimensions	7.4" × 1.5" × 1.14"
Battery Case Dimensions	6.5" × 1.61" × 0.98"
Operating Temperature	32°F to 122°F
Location Rating	Dry, damp
IP Rating	Per host fixture
Warranty	5-year limited

COMPLIANCE

Safety Listings	UL 924 · CSA C22.2 No.141
Energy Compliance	CEC Title 20
Installation Li...	UL listed for factory & field install
Compatibi...	constANT Application Quick Guide

COMPATIBILITY · CONSTANT APPLICATION QUICK GUIDE

lamparARCH · luxoARCH · planoARCH · tubulARCH

See full Application Quick Guide for sensor & controller pairings.

ORDERING INFORMATION

EM08-HMB/170DC	Standard 8 W driver
EM08-HMB/170DC/XD	With Extended Discharge: 120-minute runtime
Vendor MPN	BLD-HM08D-YYY (BillDa)

8W OUTPUT POWER

90/120 min STANDARD / /XD

100–347V UNIVERSAL INPUT

32° to 122°F OPERATING RANGE

All Series COMPATIBLE

UL 924 LISTED

Archipelago Lighting Group · 4615 State Street, Montclair, CA 91763

+1 (866) 912-3200 · sales@archipelagolighting.com · archipelagolighting.com