ARCHIPELAGO LIGHTING GROUP

DATASHEET

Microwave DETECTION	**13FT** MAX HEIGHT
IP20 IP RATING	**10-15Vdc** INPUT VOLTAGE
UL CERTIFICATION	**Bi-Level** PLATFORM

CONTRⒶLS · BI-LEVEL

MSM-HTI/08P1/BLS

Indoor fixture-integrated microwave occupancy sensor with IR remote commissioning. Designed for high-bay and mid-bay commercial applications. Plug-and-play 1-pin audio jack connection with automatic high/low power switching.

TECHNICAL SPECIFICATIONS

Detection Technology	5.8GHz Microwave	IP Rating	IP20
Input Voltage	10-15Vdc	Certification	UL Listed
Max Mounting Height	13FT (4m)	Connector	1-Pin Audio Jack
Detection Range	Adjustable via IR	Commissioning	IR Remote
Hold Time	5s – 30min	Operating Temp	-20°C to +50°C
Daylight Harvesting	Yes (10-2000 Lux)	Finish	White
Stand-by Dimming	10% – 100%	DLC / NLC	No (Standalone)

FEATURES

- 5.8GHz microwave through-lens detection
- IR remote commissioning (RM-HT series)
- Built-in daylight harvesting sensor
- Plug-and-play 1-pin connection
- No wiring required (sensor-to-driver)
- Automatic high/low power switching
- Adjustable sensitivity and hold time
- Stand-by dimming level adjustable
- Compact fixture-integrated design
- Walk-through test mode

COMPATIBLE LUMINAIRE FAMILIES

lamparⒶRCH (UFO High Bay) · planoⒶRCH (Troffers & Panels) · selectⒶRCH (Strips & Wraps) · LLHB/Tiny-I (Linear High Bay) · LV3P (Vapor Tight)

COMPATIBLE REMOTES

RM-HT/03S · 3-Button · RM-HT/05S · 5-Button Dimming · RM-HT/06S · LCD Full Config

ORDERING INFORMATION

SKU	MSM-HTI/08P1/BLS
UPC	819313024340
Case Quantity	50 pcs
Case Dimensions	15.75 × 11.81 × 9.84 in
Case Weight	9.26 lb
Brand	contrⒶLS
Platform	Bi-Level
Manufacturer	Archipelago Lighting Group